02036-8107

## **SAFETY DATA SHEET**

2716

#### Section 1. Identification

Product name : MINWAX® WOOD FINISH®

Dark Walnut

Product code : 2716

Other means of identification

: Not available.

· Not available

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

**Manufacturer** : MINWAX Company

101 W. Prospect Ave Cleveland, Ohio 44115

Emergency telephone number of the company

US/Canada: (800) 424-9300

Mexico: CHEMTREC México 800-681-9531. Available 24 hours and 365 days per year

Product Information
Telephone Number

: US/Canada: (800) 523-9299

Mexico: 800-717-3123 / 55-5333-1501

Transportation Emergency Telephone Number

: US / Canada: (800) 424-9300

Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

### Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 3 CARCINOGENICITY - Category 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -

Category 3

SPEČIFÍC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

ASPIRATION HAZARD - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 58.4%

(oral), 58.4% (dermal), 58.4% (inhalation)

**GHS label elements** 

Hazard pictograms







Signal word

: Danger

**Hazard statements** 

: Flammable liquid and vapor.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure.

#### **Precautionary statements**

Date of issue/Date of revision: 10/4/2024Date of previous issue: 9/24/2024Version: 34.011/162716MINWAX® WOOD FINISH®<br/>Item Numbers: 02036-8107, 的操作器<br/>Page 1 of 16

#### Section 2. Hazards identification

#### General

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

#### **Prevention**

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

#### Response

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

#### **Storage**

: Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep

#### Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

## Supplemental label elements

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

## Hazards not otherwise classified

: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

## Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available

#### **CAS** number/other identifiers

Ingredient name	% by weight	CAS number
Light Aliphatic Hydrocarbon	≥25 - ≤50	64742-47-8
Heavy Naphthenic Petroleum Oil	≥10 - ≤25	64742-52-5
Light Aliphatic Hydrocarbon	≥10 - ≤25	64742-47-8
Med. Aliphatic Hydrocarbon Solvent	≤5	64742-88-7
Light Aromatic Hydrocarbons	<1	64742-95-6
trimethylbenzene	<1	25551-13-7
Mineral Spirits (Odorless)	<1	64742-48-9
1,3,5-Trimethylbenzene	≤0.3	108-67-8
1,2,4-Trimethylbenzene	≤0.3	95-63-6
Carbon Black	≤0.3	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision	: 10/4/2024	Date of previous issue	: 9/24/2024	Version	: 34.01	2/16
2716 MINWAX® WOOD FI Item Numbers: 02036-8107, 1993 R Walnut	NISH®			SHW-85	NA-GHS-US	age 2 of 16

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact : Immedia

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open

airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing

before reuse. Clean shoes thoroughly before reuse.

Ingestion : Get medical attention immediately. Call a poison center or physician. Wash out mouth

with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar,

tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact**: No known significant effects or critical hazards.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

Skin contact : No known significant effects or critical hazards.

**Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and

enters airways.

#### Over-exposure signs/symptoms

Eye contact : No specific data.

**Inhalation** : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact : No specific data.

Ingestion : Adverse symptoms may include the following:

nausea or vomiting

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Date of issue/Date of revision: 10/4/2024Date of previous issue: 9/24/2024Version: 34.013/1627 16MINWAX® WOOD FINISH®<br/>Item Numbers: 02036-8107, 內容學學學和如此SHW-85-NA-GHS-US<br/>Page 3 of 16

### Section 4. First aid measures

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing media

: Do not use water jet.

Specific hazards arising from the chemical

: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters Remark

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

: Flammable liquid.

#### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

 Date of issue/Date of revision
 : 10/4/2024
 Date of previous issue
 : 9/24/2024
 Version
 : 34.01
 4/16

 2716
 MINWAX® WOOD FINISH® ltem Numbers: 02036-8107. 图34-84 Walnut
 SHW-85-NA-GHS-US Page 4 of 16

#### Section 6. Accidental release measures

#### Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS#	Exposure limits
Light Aliphatic Hydrocarbon	64742-47-8	ACGIH TLV (United States, 1/2024). [Kerosene] Absorbed through skin. TWA: 200 mg/m³, (as total hydrocarbon vapor) 8 hours.
Heavy Naphthenic Petroleum Oil	64742-52-5	ACGIH TLV (United States, 1/2024). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction
Date of issue/Date of revision : 10/4/2024	Date of previous issue	• 9/24/2024 Version : 34 01 5/16

Date of issue/Date of revision : 10/4/2024 Date of previous issue : 9/24/2024 Version : 34.01 5/16
2716 MINWAX® WOOD FINISH® SHW-85-NA-GHS-US Page 5 of 16

•	•	
		OSHA PEL (United States, 5/2018). [Oil mist, mineral]
		TWA: 5 mg/m <sup>3</sup> 8 hours.
		NIOSH REL (United States, 10/2020). [OIL
		MIST MINERAL]
		TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist
Light Aliphatic Hydrocarbon	64742-47-8	ACGIH TLV (United States, 1/2024).
		[Kerosene] Absorbed through skin.
		TWA: 200 mg/m³, (as total hydrocarbon
		vapor) 8 hours.
Med. Aliphatic Hydrocarbon Solvent	64742-88-7	OSHA PEL (United States, 5/2018).
mean / impriante r r y an estante en estre en e	0 2 00 .	[Naphtha (Coal tar)]
		TWA: 100 ppm 8 hours.
		TWA: 400 mg/m <sup>3</sup> 8 hours.
Light Aromatic Hydrocarbons	64742-95-6	None.
trimethylbenzene	25551-13-7	ACGIH TLV (United States, 1/2024).
united lyiberizone	20001 10 7	[trimethyl benzene, isomers]
		TWA: 10 ppm 8 hours.
Mineral Spirits (Odorless)	64742-48-9	ACGIH TLV (United States, 1/2024).
Willerar Spirits (Odoriess)	04742-40-9	[Kerosene] Absorbed through skin.
		TWA: 200 mg/m³, (as total hydrocarbon
		vapor) 8 hours.
1,3,5-Trimethylbenzene	108-67-8	ACGIH TLV (United States, 1/2024).
1,3,5-Tillletriyiberizerle	100-07-0	[trimethyl benzene, isomers]
		TWA: 10 ppm 8 hours.
		NIOSH REL (United States, 10/2020).
		TWA: 25 ppm 10 hours.
		TWA: 23 ppm 10 hours.  TWA: 125 mg/m³ 10 hours.
1.2.4 Trim athydhanzana	95-63-6	
1,2,4-Trimethylbenzene	95-63-6	NIOSH REL (United States, 10/2020).
		TWA: 25 ppm 10 hours.
		TWA: 125 mg/m³ 10 hours.
		ACGIH TLV (United States, 1/2024).
O auto au Blanda	4000 00 4	TWA: 10 ppm 8 hours.
Carbon Black	1333-86-4	ACGIH TLV (United States, 1/2024).
		TWA: 3 mg/m³ 8 hours. Form: Inhalable
		fraction
		NIOSH REL (United States, 10/2020).
		TWA: 3.5 mg/m³ 10 hours.
		OSHA PEL (United States, 5/2018).
		TWA: 3.5 mg/m³ 8 hours.

#### Occupational exposure limits (Canada)

Ingredient name	CAS#	Exposure limits
Petroleum refining, hydrotreated light distillate	64742-47-8	CA British Columbia Provincial (Canada, 8/2023). [Kerosene/Jet fuels] Absorbed through skin. Notes: Application restricted to conditions in which there are negligible aerosol exposures.  TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.  CA Alberta Provincial (Canada, 3/2023). [Kerosene/Jet fuels] Absorbed through skin.  OEL: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.

Date of issue/Date of revision : 10/4/2024 Date of previous issue : 9/24/2024 Version : 34.01 6/16
2716 MINWAX® WOOD FINISH®
Item Numbers: 02036-8107, 1934-8 Walnut SHW-85-NA-GHS-US
Page 6 of 16

Petroleum refining, hydrotreated light distillate	64742-47-8	CA Ontario Provincial (Canada, 6/2019). Absorbed through skin.  TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.  CA Quebec Provincial (Canada, 2/2024).  [kerosene] Absorbed through skin.  TWAEV: 200 mg/m³ 8 hours.  CA British Columbia Provincial (Canada,
		8/2023). [Kerosene/Jet fuels] Absorbed through skin. Notes: Application restricted to conditions in which there are negligible aerosol exposures.  TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.  CA Alberta Provincial (Canada, 3/2023). [Kerosene/Jet fuels] Absorbed through skin.  OEL: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.  CA Ontario Provincial (Canada, 6/2019). Absorbed through skin.  TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.  CA Quebec Provincial (Canada, 2/2024). [kerosene] Absorbed through skin.  TWAEV: 200 mg/m³ 8 hours.
Medium aliphatic solvent naphtha (petroleum) C9-C12	64742-88-7	CA Ontario Provincial (Canada, 6/2019). [Mineral Spirits] TWA: 525 mg/m³ 8 hours.
Petroleum refining, hydrotreated light distillate	64742-48-9	CA British Columbia Provincial (Canada, 8/2023). [Kerosene/Jet fuels] Absorbed through skin. Notes: Application restricted to conditions in which there are negligible aerosol exposures.  TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.  CA Alberta Provincial (Canada, 3/2023). [Kerosene/Jet fuels] Absorbed through skin.  OEL: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.  CA Ontario Provincial (Canada, 6/2019). Absorbed through skin.  TWA: 200 mg/m³, (as total hydrocarbon vapour) 8 hours.  CA Quebec Provincial (Canada, 2/2024). [kerosene] Absorbed through skin.  TWAEV: 200 mg/m³ 8 hours.
Carbon black	1333-86-4	CA British Columbia Provincial (Canada, 8/2023).  TWA: 3 mg/m³ 8 hours. Form: Inhalable CA Ontario Provincial (Canada, 6/2019).  TWA: 3 mg/m³ 8 hours. Form: Inhalable particulate matter.  CA Quebec Provincial (Canada, 2/2024).  TWAEV: 3 mg/m³ 8 hours. Form: inhalable aerosol fraction
Date of issue/Date of revision : 10/4/2024 Date of pre	evious issue	: 9/24/2024 <b>Version</b> : 34.01 7/16

2716 MINWAX® WOOD FINISH® SHW-85-NA-GHS-US Page 7 of 1

CA Alberta Provincial (Canada, 3/2023).
OEL: 3.5 mg/m <sup>3</sup> 8 hours.
CA Saskatchewan Provincial (Canada,
4/2021).
STEL: 7 mg/m³ 15 minutes.
TWA: 3.5 mg/m <sup>3</sup> 8 hours.

#### Occupational exposure limits (Mexico)

	CAS#	Exposure limits
Light Aliphatic Hydrocarbon		ACGIH TLV (United States, 1/2024). [Kerosene] Absorbed through skin. TWA: 200 mg/m³, (as total hydrocarbon vapor) 8 hours.
Light Aliphatic Hydrocarbon		ACGIH TLV (United States, 1/2024). [Kerosene] Absorbed through skin. TWA: 200 mg/m³, (as total hydrocarbon vapor) 8 hours.

#### **Biological exposure indices (United States)**

No exposure indices known.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

## Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

## Environmental exposure controls

: This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

#### **Skin protection**

Date of issue/Date of revision: 10/4/2024Date of previous issue: 9/24/2024Version: 34.018/162716MINWAX® WOOD FINISH®<br/>Item Numbers: 02036-8107, 的操作機和utSHW-85-NA-GHS-US<br/>Page 8 of 16

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**Appearance** 

Physical state
Color
Brown.

Odor
Not available.
Not available.

Ph
Not applicable.
Not applicable.
Not available.
Not applicable.
Not available.
148°C (298.4°F)

Flash point

: Closed cup: 41°C (105.8°F) [Pensky-Martens Closed Cup]

Evaporation rate : 1 (butyl acetate = 1)
Flammability : Flammable liquid.
Lower and upper explosion
limit/flammability limit : Lower: 0.6%
Upper: 6%

Vapor pressure

: 0.17 kPa (1.27 mm Hg)

Relative vapor density : 5 [Air = 1]
Relative density : 0.85
Solubility(ies) :

MediaResultcold waterNot soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Kinematic (40°C (104°F)): <20.5 mm²/s (<20.5 cSt)

Molecular weight : Not applicable.

 Date of issue/Date of revision
 : 10/4/2024
 Date of previous issue
 : 9/24/2024
 Version
 : 34.01
 9/16

 2716
 MINWAX® WOOD FINISH® ltem Numbers: 02036-8107, 的操作器和ut
 SHW-85-NA-GHS-US Page 9 of 16

## Section 9. Physical and chemical properties

Heat of combustion : 30.753 kJ/g

## Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Incompatible materials

: Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
, ,	LD50 Oral	Rat	>5000 mg/kg	-
Oil	I D50 01	Det	0.400 //	
Light Aromatic Hydrocarbons	LD50 Oral	Rat	8400 mg/kg	-
trimethylbenzene	LD50 Oral	Rat	8970 mg/kg	4 5
1,3,5-Trimethylbenzene	LC50 Inhalation Vapor	Rat	24000 mg/m³	4 hours
1017: "	LD50 Oral	Rat	5000 mg/kg	<b>5.</b>
1,2,4-Trimethylbenzene	LC50 Inhalation Vapor	Rat	18000 mg/m³	4 hours
	LD50 Oral	Rat	5 g/kg	-
Carbon Black	LD50 Oral	Rat	>15400 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Heavy Naphthenic Petroleum Oil	Skin - Severe irritant	Rabbit	-	500 mg	-
Light Aromatic Hydrocarbons	Eyes - Mild irritant	Rabbit	-	24 hours 100 uL	-
trimethylbenzene	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
1,3,5-Trimethylbenzene	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-

#### **Sensitization**

Not available.

#### **Mutagenicity**

Date of issue/Date of revision	: 10/4/2024	Date of previous issue	: 9/24/2024	Version	: 34.01	10/16
2716 MINWAX® WOOD I Item Numbers: 02036-8107, <b>四</b> 翰格 <b>(Walnut</b>	FINISH®			SHW-85	NA-GHS-U	age 10 of 16

## Section 11. Toxicological information

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Carbon Black	-	2B	-

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Light Aliphatic Hydrocarbon	Category 3	-	Narcotic effects
Light Aromatic Hydrocarbons	Category 3	-	Respiratory tract irritation
	Category 3		Narcotic effects
Mineral Spirits (Odorless)	Category 3	-	Narcotic effects
1,3,5-Trimethylbenzene	Category 3	-	Respiratory tract irritation
1,2,4-Trimethylbenzene	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Med. Aliphatic Hydrocarbon Solvent	Category 1	-	-

#### **Aspiration hazard**

Name	Result
Light Aliphatic Hydrocarbon	ASPIRATION HAZARD - Category 1
Light Aliphatic Hydrocarbon	ASPIRATION HAZARD - Category 1
Med. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1
Light Aromatic Hydrocarbons	ASPIRATION HAZARD - Category 1
trimethylbenzene	ASPIRATION HAZARD - Category 1
Mineral Spirits (Odorless)	ASPIRATION HAZARD - Category 1
1,3,5-Trimethylbenzene	ASPIRATION HAZARD - Category 1
1,2,4-Trimethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely

routes of exposure

: Not available.

#### Potential acute health effects

Eye contact

: No known significant effects or critical hazards.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

**Skin contact**: No known significant effects or critical hazards.

Ingestion : Can cause central nervous system (CNS) depression. May be fatal if swallowed and

enters airways.

Date of issue/Date of revision: 10/4/2024Date of previous issue: 9/24/2024Version: 34.0111/162716MINWAX® WOOD FINISH®<br/>Item Numbers: 02036-8107. 的操作器InutSHW-85-NA-GHS-US<br/>Page 11 of 16

## Section 11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

**Inhalation**: Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact : No specific data.

**Ingestion** : Adverse symptoms may include the following:

nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate

effects

: Not available.

Potential delayed effects

Long term exposure

: Not available.

Long term exposure

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Causes damage to organs through prolonged or repeated exposure.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

Not available.

## Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Light Aliphatic Hydrocarbon	Acute LC50 2200 µg/l Fresh water	Fish - Lepomis macrochirus	4 days
Light Aliphatic Hydrocarbon	Acute LC50 2200 µg/l Fresh water	Fish - Lepomis macrochirus	4 days
trimethylbenzene	Acute LC50 5600 µg/l Marine water	Crustaceans - Palaemonetes	48 hours
Mineral Spirits (Odorless)	Acute LC50 2200 µg/l Fresh water	Fish - Lepomis macrochirus	4 days
1,3,5-Trimethylbenzene	Acute LC50 13000 μg/l Marine water	Crustaceans - Cancer magister - Zoea	48 hours
	Acute LC50 12520 µg/l Fresh water	Fish - Carassius auratus	96 hours
	Chronic NOEC 0.4 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	21 days
Date of issue/Date of revision	: 10/4/2024 Date of previous issue	: 9/24/2024 <b>Version</b> : 3	4.01 12/

 Date of issue/Date of revision
 : 10/4/2024
 Date of previous issue
 : 9/24/2024
 Version
 : 34.01
 12/16

 2716
 MINWAX® WOOD FINISH® ltem Numbers: 02036-8107, 图编表 Walnut
 SHW-85-NA-GHS-US Page 12 of 16

Section 12. Ecological information				
1,2,4-Trimethylbenzene	Acute LC50 4910 μg/l Marine water	Crustaceans - Elasmopus pectenicrus - Adult	48 hours	
	Acute LC50 7720 μg/l Fresh water	Fish - Pimephales promelas	96 hours	

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Light Aromatic Hydrocarbons	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Light Aromatic Hydrocarbons	-	10 to 2500	High
1,3,5-Trimethylbenzene	-	161	Low
1,2,4-Trimethylbenzene	-	243	Low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### **Disposal methods**

: This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **Section 14. Transport information**

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT. Marine pollutant (Light Aliphatic Hydrocarbon, Med. Aliphatic Hydrocarbon Solvent)
1		1	1		1

2716 MINWAX® WOOD FINISH® Item Numbers: 02036-8107, 图编操机 Walnut

SHW-85-NA-GHS-US Page 13 of 16

Transport hazard class(es)	3	3	3	3	3
	PLANMABLE LIDERS				¥2
Packing group	III	III	III	III	III
Environmental hazards	No.	No.	No.	Yes. The environmentally hazardous substance mark is not required.	Yes.
Additional information	This product may be re-classified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids are not regulated as hazardous materials.	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).	-	The environmentally hazardous substance mark may appear if required by other transportation regulations.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤ kg.  Emergency schedules F-E, SE
	ERG No.	ERG No.	ERG No.		
	128	128	128		

Special precautions for user :

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according : Not available. to IMO instruments

**Proper shipping name** : Not available.

## Section 15. Regulatory information

**U.S. Federal regulations** 

: TSCA 5(a)2 final significant new use rules: Chlorodiazocarboxylate

List name **Chemical name** Notes United States - TSCA 5(a) 40 CFR 721.10414 Chlorodiazocarboxylate

2 - Final significant new

use rules

**SARA 313** 

Date of issue/Date of revision : 10/4/2024 Date of previous issue : 9/24/2024 Version: 34.01 14/16 SHW-85-NA-GHS-US Page 14 of 16 2716 MINWAX® WOOD FINISH® Item Numbers: 02036-8107, 1993 Walnut

## Section 15. Regulatory information

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

#### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

#### International regulations

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists : Australia inventory (AIIC): Not determined.

China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Taiwan Chemical Substances Inventory (TCSI): Not determined.

Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

### Section 16. Other information

**Hazardous Material Information System (U.S.A.)** 



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
CARCINOGENICITY - Category 2	On basis of test data Calculation method Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 ASPIRATION HAZARD - Category 1	Calculation method Calculation method

#### **History**

Date of printing : 10/4/2024

Date of issue/Date of : 10/4/2024

revision

Date of previous issue : 9/24/2024 Version : 34.01

Date of issue/Date of revision : 10/4/2024 Date of previous issue : 9/24/2024 Version : 34.01 15/16
2716 MINWAX® WOOD FINISH® tem Numbers: 02036-8107, 內容性學學和如此

## Section 16. Other information

Key to abbreviations

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not availableSGG = Segregation Group

UN = United Nations

Indicates information that has changed from previously issued version.

#### **Notice to reader**

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date of revision : 10/4/2024 Date of previous issue : 9/24/2024 Version : 34.01 16/16 SHW-85-NA-GHS-US Page 16 of 16 2716 MINWAX® WOOD FINISH® Item Numbers: 02036-8107, 四級報告 Walnut