

02224-3010



edding Permanent Marker Refill Ink (red, blue) contained in: edding T 25, MTK 25, 3000, 3300, 800, 850, No. 1, 0,5; edding Permanent Marker Ink (violet, light blue) contained in: edding T 25, 3000, 3300; edding Permanent Marker Ink (grey, ochre, steelblue, carmine red, magenta) contained in: edding 3000, 3300, 0,5

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Date of issue: 24 July 2019 Revision date: 24 July 2019 Version: 1.0.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : edding Permanent Marker Refill Ink (red, blue) contained in: edding T 25, MTK 25, 3000, 3300, 800, 850, No. 1, 0,5; edding Permanent Marker Ink (violet, light blue) contained in: edding T 25, 3000, 3300; edding Permanent Marker Ink (grey, ochre, steelblue, carmine red, magenta) contained in: edding 3000, 3300, 0,5

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Ink

1.3. Supplier

edding International GmbH
Bookkoppel 7
22926 Ahrensburg
Germany
T: +49 (0) 4102-808-0
sdb_info@umco.de

c/o MBCA/edding
2100 Ponce De Leon Blvd Ph 5
Coral Gables, FL 33134
USA
T: +1 (305) 851-5631

1.4. Emergency telephone number

Emergency number : +1 (305) 851-5631 (9AM-5PM ET)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 3 Flammable liquid and vapor
Specific target organ toxicity (single exposure) Category 3 May cause drowsiness or dizziness

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : Flammable liquid and vapor
May cause drowsiness or dizziness

Precautionary statements (GHS US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.

edding Permanent Marker Refill Ink (red, blue) contained in: edding T 25, MTK 25, 3000, 3300, 800, 850, No. 1, 0,5; edding Permanent Marker Ink (violet, light blue) contained in: edding T 25, 3000, 3300; edding Permanent Marker Ink (grey, ochre, steelblue, carmine red, magenta) contained in: edding 3000, 3300, 0,5
Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 If inhaled: Remove person to fresh air and keep comfortable for breathing
 Call a poison center or doctor if you feel unwell
 In case of fire: Use media other than water to extinguish.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
1-methoxy-2-propanol, monopropylene glycol methyl ether	(CAS-No.) 107-98-2	75 - 90	Flam. Liq. 3, H226 STOT SE 3, H336
Ethyl alcohol	(CAS-No.) 64-17-5	0 - < 10	Flam. Liq. 2, H225 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Obtain medical attention if breathing difficulty persists.

First-aid measures after skin contact : Wash off with soap and plenty of water. Obtain medical attention if irritation persists.

First-aid measures after eye contact : Rinse with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

First-aid measures after ingestion : Rinse mouth. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Not expected to present a significant skin hazard under anticipated conditions of normal use.

Symptoms/effects after eye contact : Not expected to present a significant eye contact hazard under anticipated conditions of normal use.

Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Alcohol-resistant foam. dry extinguishing powder. Carbon dioxide (CO2).

Unsuitable extinguishing media : Do not use water jet.

24 July 2019

EN (English US)

2/10

Item Numbers: 02224-3010, 02224-5010

Page 2 of 10

edding Permanent Marker Refill Ink (red, blue) contained in: edding T 25, MTK 25, 3000, 3300, 800, 850, No. 1, 0,5; edding Permanent Marker Ink (violet, light blue) contained in: edding T 25, 3000, 3300; edding Permanent Marker Ink (grey, ochre, steelblue, carmine red, magenta) contained in: edding 3000, 3300, 0,5
Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor. On combustion, forms: carbon oxides (CO and CO₂).
 Explosion hazard : No direct explosion hazard.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Evacuate personnel to a safe area. Exercise caution when fighting any chemical fire.
 Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : For further information refer to section 8: "Exposure controls/personal protection".
 Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : For further information refer to section 8: "Exposure controls/personal protection".
 Emergency procedures : Ventilate area. Eliminate all ignition sources if safe to do so.

6.2. Environmental precautions

Do not discharge into drains or the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : No special decontamination procedures needed. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Collect spillage.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure adequate ventilation. Do not breathe vapors. Take precautionary measures against static discharge. Keep away from open flames, hot surfaces and sources of ignition.
 Hygiene measures : Use good personal hygiene practices. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Wash contaminated clothing prior to re-use.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Store tightly closed in a dry, cool and well-ventilated place.
 Incompatible materials : Acids. alkalis. Oxidizing agent.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)		
ACGIH	Local name	1-Methoxy-2-propanol
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
ACGIH	Remark (ACGIH)	Eye irr; CNS impair; A4 (Not classifiable as a Human Carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories)

edding Permanent Marker Refill Ink (red, blue) contained in: edding T 25, MTK 25, 3000, 3300, 800, 850, No. 1, 0,5; edding Permanent Marker Ink (violet, light blue) contained in: edding T 25, 3000, 3300; edding Permanent Marker Ink (grey, ochre, steelblue, carmine red, magenta) contained in: edding 3000, 3300, 0,5

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)		
NIOSH	NIOSH REL (TWA) (mg/m ³)	360 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	540 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
Ethyl alcohol (64-17-5)		
ACGIH	Local name	Ethanol
ACGIH	ACGIH STEL (ppm)	1000 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Impermeable protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Long sleeved protective clothing

Respiratory protection:

An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Opaque.
Color	: Various
Odor	: Characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available

edding Permanent Marker Refill Ink (red, blue) contained in: edding T 25, MTK 25, 3000, 3300, 800, 850, No. 1, 0,5; edding Permanent Marker Ink (violet, light blue) contained in: edding T 25, 3000, 3300; edding Permanent Marker Ink (grey, ochre, steelblue, carmine red, magenta) contained in: edding 3000, 3300, 0,5
Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Boiling point	: 110 - 112 °C (230 - 233.6 °F)
Flash point	: 28 - 31 °C (86 - 87.8 °F)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Vapor pressure at 50 °C	: < 110 kPa
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.944 - 0.97 g/cm ³
Solubility	: Soluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Acids. alkalis. Oxidizing agent.

10.6. Hazardous decomposition products

On combustion, forms: carbon oxides (CO and CO₂). Hydrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
LD50 oral rat	5000 mg/kg
LD50 dermal rabbit	13 g/kg
LC50 inhalation rat (mg/l)	> 6 mg/l/4h
LC50 inhalation rat (ppm)	> 7559 ppm (Exposure time: 6 h)

edding Permanent Marker Refill Ink (red, blue) contained in: edding T 25, MTK 25, 3000, 3300, 800, 850, No. 1, 0,5; edding Permanent Marker Ink (violet, light blue) contained in: edding T 25, 3000, 3300; edding Permanent Marker Ink (grey, ochre, steelblue, carmine red, magenta) contained in: edding 3000, 3300, 0,5
Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethyl alcohol (64-17-5)	
LD50 oral rat	7060 mg/kg
LC50 inhalation rat (mg/l)	124.7 mg/l/4h

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitization	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness.

Specific target organ toxicity – repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Viscosity, kinematic	: No data available
Likely routes of exposure	: Skin and eye contact. Ingestion. Inhalation.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : This material has not been tested for environmental effects.

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
LC50 fish 1	20.8 g/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23300 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Ethyl alcohol (64-17-5)	
LC50 fish 1	12.0 - 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
LC50 other aquatic organisms 1	5012 mg/l 48 hours- daphnia
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
ErC50 (algae)	275 mg/l
ErC50 (other aquatic plants)	4432 mg/l
NOEC (acute)	9.6 mg/l Daphnia magna

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

edding Permanent Marker Refill Ink (red, blue) contained in: edding T 25, MTK 25, 3000, 3300, 800, 850, No. 1, 0,5; edding Permanent Marker Ink (violet, light blue) contained in: edding T 25, 3000, 3300; edding Permanent Marker Ink (grey, ochre, steelblue, carmine red, magenta) contained in: edding 3000, 3300, 0,5

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
BCF fish 1	< 2
Log Pow	-0.437
Ethyl alcohol (64-17-5)	
Log Pow	-0.32

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Recycle or dispose of in compliance with current legislation.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1263 Paint related material (1-methoxy-2-propanol, monopropylene glycol methyl ether), 3, III
UN-No.(DOT)	: UN1263
Proper Shipping Name (DOT)	: Paint related material 1-methoxy-2-propanol, monopropylene glycol methyl ether
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: III - Minor Danger
Hazard labels (DOT)	: 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 173
DOT Packaging Bulk (49 CFR 173.xxx)	: 242

edding Permanent Marker Refill Ink (red, blue) contained in: edding T 25, MTK 25, 3000, 3300, 800, 850, No. 1, 0,5; edding Permanent Marker Ink (violet, light blue) contained in: edding T 25, 3000, 3300; edding Permanent Marker Ink (grey, ochre, steelblue, carmine red, magenta) contained in: edding 3000, 3300, 0,5
Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	<p>: 367 - For the purposes of documentation and package marking: a. The proper shipping name "Paint related material" may be used for consignments of packages containing "Paint" and "Paint related material" in the same package; b. The proper shipping name "Paint related material, corrosive, flammable" may be used for consignments of packages containing "Paint, corrosive, flammable" and "Paint related material, corrosive, flammable" in the same package; c. The proper shipping name "Paint related material, flammable, corrosive" may be used for consignments of packages containing "Paint, flammable, corrosive" and "Paint related material, flammable, corrosive" in the same package; and d. The proper shipping name "Printing ink related material" may be used for consignments of packages containing "Printing ink" and "Printing ink related material" in the same package.</p> <p>B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.</p> <p>B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.</p> <p>B131 - When transported by highway, rail, or cargo vessel, waste Paint and Paint related material (UN1263; PG II and PG III), when in plastic or metal inner packagings of not more than 26.5 L (7 gallons), are excepted from the marking requirements in §172.301(a) and (c) and the labeling requirements in §172.400(a), when further packed in the following specification and non-specification bulk outer packagings and under the following conditions:</p> <p>a. Primary receptacles must conform to the general packaging requirements of subpart B of part 173 of this subchapter and may not leak. If they do leak, they must be overpacked in packagings conforming to the specification requirements of part 178 of this subchapter or in salvage packagings conforming to the requirements in §173.12 of this subchapter.</p> <p>b. Primary receptacles must be further packed in non-specification bulk outer packagings such as cubic yard boxes, plastic rigid-wall bulk containers, dump trailers, and roll-off containers. Bulk outer packagings must be liquid tight through design or by the use of lining materials.</p> <p>c. Primary receptacles may also be further packed in specification bulk outer packagings. Authorized specification bulk outer packagings are UN11G fiberboard intermediate bulk containers (IBC) and UN13H4 woven plastic, coated and with liner flexible intermediate bulk containers (FIBCs) meeting the Packing Group II performance level and lined with a plastic liner of at least 6 mil thickness.</p> <p>d. All inner packagings placed inside bulk outer packagings must be blocked and braced to prevent movement during transportation that could cause the container to open or fall over. Specification IBCs and FIBCs are to be secured to a pallet.</p> <p>IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).</p> <p>T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)</p> <p>TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.</p> <p>TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.</p>
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 128

24 July 2019

EN (English US)

8/10

Item Numbers: 02224-3010, 02224-5010

Page 8 of 10

edding Permanent Marker Refill Ink (red, blue) contained in: edding T 25, MTK 25, 3000, 3300, 800, 850, No. 1, 0,5; edding Permanent Marker Ink (violet, light blue) contained in: edding T 25, 3000, 3300; edding Permanent Marker Ink (grey, ochre, steelblue, carmine red, magenta) contained in: edding 3000, 3300, 0,5
Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 1263 PAINT RELATED MATERIAL (1-methoxy-2-propanol; monopropylene glycol methyl ether), 3, III
 UN-No. (IMDG) : 1263
 Proper Shipping Name (IMDG) : PAINT RELATED MATERIAL
 Class (IMDG) : 3 - Flammable liquids
 Packing group (IMDG) : III - substances presenting low danger
 Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 1263 Paint (1-methoxy-2-propanol, monopropylene glycol methyl ether), 3, III
 UN-No. (IATA) : 1263
 Proper Shipping Name (IATA) : Paint
 Class (IATA) : 3 - Flammable Liquids
 Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Ethyl alcohol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)

Listed on the Canadian DSL (Domestic Substances List)

Ethyl alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Ethyl alcohol (64-17-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

edding Permanent Marker Refill Ink (red, blue) contained in: edding T 25, MTK 25, 3000, 3300, 800, 850, No. 1, 0,5; edding Permanent Marker Ink (violet, light blue) contained in: edding T 25, 3000, 3300; edding Permanent Marker Ink (grey, ochre, steelblue, carmine red, magenta) contained in: edding 3000, 3300, 0,5
Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Japanese ISHL (Industrial Safety and Health Law)
 Listed on the Korean ECL (Existing Chemicals List)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on INSQ (Mexican National Inventory of Chemical Substances)
 Listed on the TCSI (Taiwan Chemical Substance Inventory)

Ethyl alcohol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)
 Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Japanese ISHL (Industrial Safety and Health Law)
 Listed on the Korean ECL (Existing Chemicals List)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on INSQ (Mexican National Inventory of Chemical Substances)
 Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 21 May 2019
 Other information : Conforms to ASTM D-4236.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product