# MSDS for #02285 - KAKIMORI PISAFTENTY DATA SHEET

## 1. CHEMICAL PRODUCT AND IDENTIFICATION

Chemical product name: Pigment Ink 03 tototo Name of manufacturer: Turner Colour Works Ltd.

Address: 2-15-7 mitsuyakita yodogawa-ku, Osaka-fu, Japan

Name of section:

Phone number: +81-(0)6-6308-1216 +81-(0)6-6308-1216 Emergency call: Fax number: +81-(0)6-6305-3018 E-MAIL: kenkyuu@turner.co.jp Revised Date / Issued Data: November 24. 2022

Form No.: HK023E-01

#### 2. HAZARDS IDENTIFICATION

#### GHS Classifi

GHS Physical Hazards: Not applicable.

GHS Health and Environmental Hazards:

Serious eye damage/Eye irritation : category 2 Reproductive toxicity: category 2 Specific target organ systemic toxicity(single exposure) : category 2 Specific target organ systemic toxicity(repeated exposure) : category 2

hazard pictograms:





Signal word: Warning

Hazard statements:

Causes serious eye irritation. H319

May damage fertility or the unborn child . H360

H371 May cause damage to organs .

H373 May cause damage to organs through prolonged or repeated exposure.

## Precautionary statements:

Security precaution:

P201 Obtain special instructions before use.

Do not handle until all safety precautions have been read and P202

understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash hands thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face

P280 protection.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove P305+P351+P338

contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention. P308+P313

P337+P313 If eye irritation persists: Get medical advice/attention.

storage:

P403+P233 Store in a well ventilated place. Keep container P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Mixture: Mixture

General pro Aqueous pigment ink

Components:

	CAS No.	EINECS No.	%
ethylene glycol	107-21-1	203-473-3	1 - 3
2-(2-butoxyethoxy) ethanol	112-34-5	203-961-6	1 – 2
glycerine	56-81-5	200-289-5	5 - 10
propylene glycol	57-55-6	200-388-0	5 - 10
propan-2-ol	67-63-0	200-661-7	1 - 2
C.I. Pigment Violet 23	6358-30-1	228-767-9	< 1
C.I. Pigment Red 258	57301-22-1	_	1 - 2
Acylic Resin(Water soluble)	Registered	Polymer	1 – 5
Water	7732-18-5	231-791-2	70 – 80

## 4.FIRST - AID MEASURES

Eye contact: Immediately wash with plenty of clean running water for at least 15 minutes. If you

are wearing contact lenses and can easily remove them, remove them.

Thoroughly wash the back of the eyelids.

Seek medical attention if there is any change in appearance or irritation / pain.

Skin contact: Quickly wipe off the deposits with a cloth.

Remove all contaminated clothing..

Thoroughly wash off with plenty of water and soap or skin cleanser. Do not use solvent

or thinner.

Seek medical attention if you feel unwell if you have any changes in appearance or

irritation / pain.

Inhalation: If you feel sick after inhaling vapor, gas, etc., move it to a place with fresh air.

Rest in a posture that makes it easy to breathe. Contact your doctor if you feel

unwell.

Ingestion: If swallowed by mistake, rest and seek medical attention immediately.

Do not swallow vomit.

Do not force vomiting except as directed by your doctor.

## 5. FIRE - FIGHTING MEASURES

Specific hazards regarding with fire fighting measure:

Apply water from a safe distance to cool and project surrounding area.

Firefighters should wear proper protective equipment and self-breathing apparatus.

Suitable extinguishing media:

Water/Dry chemical powder/Carbon dioxide/Foam and dry sand.

Hazardous combustion products:

Carbon monoxide, smoke, fumes and oxides of carbon.

#### MSDS for #02285 - KAKIMORI PIGMENT INK

Personal precautions:

Wear proper protective equipment.

In case of insufficient ventilation, wear suitable respiratory equipment.

Shut off all sources of ignition. Avoid contact with skin and eyes.

Remove ignition sources and ventilate the area.

Evacuate personnel to safe area. Evacuate non-essential personnel.

### Environmental precautions:

Do not wash away into sewer, watercourse or river.

Prevent spills from entering a lot of outflow, watercourses or low areas.

In order to prevent a lot of outflow, it should with the ground etc.

#### Methods for cleaning up:

Take up spilled material with ashes or other absorbents.

After material is completely picked up, wash the spill site with soap and water

and ventilate the area.

Put all wastes in a plastic bag for disposal and seal it tightly.

Remove, clean, or dispose of contaminated clothing.

## 7. HANDLING AND STORAGE

Handling: Keep away from sources of ignition. - No smoking. Avoid contact with eyes.

Avoid contact with skin. Do not swallow. Do not breathe gas/fumes/vapor/spray.

Use only in well-ventilated areas. When using do not eat or drink. Wash hands before breaks and immediately after handling the product.

Storage: Keep out of the reach of children. Keep container in a well-ventilated place.

Keep away from food, drink and animal feeding stuffs.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Biological limit values

No biological limit allocated.

Components with workplace control parameters

ethylene glycol CAS-No. 107-21-1

IOELV Short-term value: 104mg/m3, 40ppm Long-term value: 52mg/m3, 20ppm

2-(2-butoxyethoxy) ethanol CAS-No. 112-34-5

IOELV Short-term value: 101.2mg/m3, 15ppm Long-term value: 67.5mg/m3, 10ppm

Exposure controls:

Occupational Provide adequate local exhaust ventilation to maintain worker exposure

exposure controls: below exposure limits.

Personal protective equipment:

Respiratory protection: In case of insufficient ventilation, wear suitable

respiratory equipment. Wear suitable gloves.

Hand protection: Wear suitable gloves.

Eye protection: Wear safety glasses with side shields.

Skin protection: Wear suitable protective clothing.

Environmental exposure Maintain levels below Community environmental protection

controls: thresholds.

General hygiene considerations: Handle in accordance with good industrial hygiene and

safety practice.

MSDS for #02285 - KAKIM Physical State	9. PHYSICAL AND CHEMI ORI PIGMENT INK		Page 4 of	
Color:		— <del>Liquid.</del> Red Pink		
Odor:		Faint alcohol odor		
pH:		8. 0 - 10. 5		
Boiling point / b	oiling range:	100°C (water)		
Melting point / melting range:		No information available.		
Flash point:		No information available.		
Flammability (solid, gas):		No information available.		
Explosive properties:		No information available.		
Oxidizing properties:		No information available.		
Vapor pressure:		No information available.		
Relative density	(of concentrat	1.0 - 1.1		
	water) (of concentrate):	Complete.		
Solubility (in	oil) (of concentrate):	Impossible		
Partition coeff	icient: n-octanol/water:	No information available.		
Viscosity (of con	centrate):	No information available.		
Miscibility:		No information available.		
Vapor density:		No information available.		
Evaporation rate:		No information available.		
Auto-ignition tem	perature:	No information available.		
Lower Flammabilit	y Limit:	No information available.		
Upper Flammabilit	y Limit:	No information available.		
	10. STABILITY AND	REACTIVITY		
tability:	j			
		if heated. Do not puncture. Do no		
onditions to avoid:	No dangerous reaction known under conditions of normal use.			

Conditions to avoid:

Materials to avoid: Acids. Bases. Oxidizers. Reducing agents.

Hazardous decomposition

products:

No information available.

## 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

o varaoo rorovant re	variate refevante for Grader routeron.				
ethylene glycol		107-21-1			
Oral	LD50	5840 mg/kg (rat)			
Dermal	LD50	9530 mg/kg (rbt)			
Glycerin		112-34-5			
0ral	LD50	12600 mg/kg (rat)			
propylene glycol		57-55-6			
Oral	LD50	20000 mg/kg (rat)			
Dermal	LD50	20800 mg/kg (rbt)			
2-(2-butoxyethoxy) e	112-34-5				
Oral	LD50	5660 mg/kg (rat)			
Dermal	LD50	4000  mg/kg (rbt)			
propan-2-ol		67-63-0			
Oral	LD50	5840 mg/kg (rat)			
Dermal	LD50	9530 mg/kg (rbt)			
	LC50/4h	30 mg/l (rat)			

#### MSDS for #02285 - KAKIMORI PIGMENT INK Page 5 of 5 further relevant information available. Persistence and degradability No further relevant information available. Behavior in environmental systems: No further relevant information available. Bioaccumulative potential: Mobility in soil: No further relevant information available. Additional ecological information: No further relevant information available. 13 DISPOSAL CONSIDERATIONS

Do not dump sewers, on the ground or into any of water. Consult an expert on the disposal of recovered material.

Be sure to mention name, catalog number quantity of the material.

Disposal must be made according to official regulations.

## 14. TRANSPORT INFORMATION

UN-Number ADR, AND, IMDG, IATA Void ADR, AND, IMDG, IATA UN-proper shipping name Void Transport hazard class(es) ADR, AND, IMDG, IATA Void ADR, AND, IATA Packing group Void

Environmental hazards: Marine pollutant: ethylene glycol

[7. HANDOLING AND STRAGE] Reference

Coarse handling, such as making a cargo reverse or throwing it, is not carried out.

## 15. REGULATORY INFORMATION

Regulatory information with regard to this substance in your country or in your region be examined by your own responsibility.

## 16.OTHER INFORMATION

#### Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.