

SAFETY DATA SHEET Burnt Umber Dry Pigment
REVISED: 01/25/2023

02959-8054



SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: Burnt Umber Dry Pigment
Product Description: Pigment, colorant
Intended Use: Fine art painting and decorative coatings

COMPANY

Company Name: Gamblin Artists Colors
Company Address: 323 SE Division Pl.
 Portland, OR 97202
 USA
Company Phone: 503-235-1945
Emergency Phone: Local Emergency Room



SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION: Carc. 1A H350
 STOT RE 1 H372

LABEL ELEMENTS:

Hazard symbol:



Signal word: Danger

Hazard statement: H350 - May cause cancer (Inhalation).
 H372 - Causes damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation).

Precautionary statements:

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P260 - Do not breathe dust.
 P270 - Do not eat, drink or smoke when using this product.
 P280 - Wear eye protection, protective clothing, protective gloves.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P314 - Get medical advice/attention if you feel unwell.
 P405 - Store locked up.
 P501 - Dispose of contents/container according to local, regional, national, and international regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC):

1

SAFETY DATA SHEET: Burnt Umber Dry Pigment
REVISED: 12/30/2015



Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CAS NUMBER/OTHER IDENTIFIERS

Name	CAS#	Concentration (%)	Classification (GHS-US)
Umber	12713-03-0	80-85	Not classified
Talc (No asbestos)	14807-96-6	5-7	Not classified
Magnesium carbonate	546-93-0	3-5	Not classified
Iron oxide black	12227-89-3	2-3	Not classified
Iron oxide red	1309-37-1	2-3	Not classified
Quartz, crystalline silica	14808-60-7	2.5-3.0	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372

SECTION 4: FIRST AID MEASURES

- Eyes:** Wash with clean water for at least 15 minutes. If irritation persists, get medical attention.
- Skin:** Flush contaminated skin with plenty of water.
- Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.
- Ingestion:** Do NOT induce vomiting. Rinse mouth. Call a doctor/physician if problems arise.
- Most important symptoms and effects, both acute and delayed:**
 May cause cancer. May cause respiratory irritation. May cause skin irritation. May cause eye irritation. Ingestion is not likely to be harmful or have adverse effects. Repeated exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis.
 Chronic Symptoms: May cause cancer.
- Indication of Any Immediate Medical Attention and Special Treatment Needed:**
 If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE FIGHTING MEASURES

FIRE FIGHTING

- Extinguishing Media:** Use extinguishing agent suitable for type of surrounding fire.
- Unsuitable Extinguishing Media:**
 Do not use a heavy water stream. Use of heavy stream of water may spread fire. Application of water stream to hot product may cause frothing and increase fire intensity.

SAFETY DATA SHEET: Burnt Umber Dry Pigment
REVISED: 12/30/2015



Special Hazards Arising From the Substance or Mixture

Not considered flammable but may burn at high temperatures.
 Product is not explosive. Hazardous reactions will not occur under normal conditions.

Special Fire Fighting Procedures:

Use protective equipment appropriate for surrounding materials. Do not enter fire area without proper protective equipment, including respiratory protection. Use water spray or fog for cooling exposed containers.

Other information: Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing dust

NON-EMERGENCY PERSONNEL

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

EMERGENCY RESPONDERS

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop spill if safe to do so. Eliminate ignition sources. Ventilate area.

ENVIRONMENTAL PRECAUTIONS

General Measures: Prevent entry to sewers and public waters.

METHODS FOR MATERIAL CONTAINMENT AND CLEAN-UP

For Containment: Contain and collect as any solid.

Methods for Clean-up: Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal.

ADDITIONAL

See Heading 8. Exposure controls and personal protection.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.
 Wash hands and other exposed areas with mild soap and water before eating, drinking

CONDITIONS FOR SAFE STORAGE

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place.
 Keep container closed when not in use.

Incompatible Products: Strong acids. Strong bases. Strong oxidizers.

SPECIFIC END USE(S) Wood stains, paint, and coatings.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

SAFETY DATA SHEET: Burnt Umber Dry Pigment
 REVISED: 12/30/2015



Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³
USA OSHA	OSHA PEL (STEL) (mg/m ³)	250 mppcf/%SiO ₂ +5, 10mg/m ³ /%SiO ₂ +2

Talc (14807-96-6)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	2 mg/m ³ (containing no Asbestos and <1% Quartz-respirable dust)
USA IDLH	US IDLH (mg/m ³)	1000 mg/m ³ (containing no asbestos and <1% quartz)

Magnesium carbonate (546-93-0)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)

Particulates not otherwise classified (PNOC) (RR-00072-6)		
USA ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ Respirable fraction 10 mg/m ³ Total Dust
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ Respirable fraction 15 mg/m ³ Total Dust

Iron oxide red (1309-37-1)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ TLV
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (respirable fraction, < 5% SiO ₂)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
USA IDLH	US IDLH (mg/m ³)	2500 mg/m ³

EXPOSURE CONTROLS

Appropriate Engineering Controls:

Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment:

Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.

Materials for Protective Clothing:

Chemically resistant materials and fabrics.

Hand Protection:

Wear chemically resistant protective gloves.

Eye Protection:

Chemical goggles or safety glasses.

Skin and Body Protection:

Wear suitable protective clothing.

Respiratory Protection:

Use a NIOSH-approved respirator or self-contained breathing apparatus

whenever exposure may exceed established Occupational Exposure Limits.

Environmental Exposure Controls:

Do not allow the product to be released into the environment.

Consumer Exposure Controls:

Do not eat, drink or smoke during use.

SAFETY DATA SHEET: Burnt Umber Dry Pigment
 REVISED: 12/30/2015



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

GENERAL INFORMATION

Physical State: Powder
Color: Dark brown
Odor: None
Odor Threshold: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Boiling Point: N/A
Melting Point: > 1000° C
Freezing Point: N/A
Vapor Pressure: N/A
Vapor Density: N/A
Relative Density: 3.6
Evaporation Rate: N/A
Solubility in Water: Insoluble in cold water and hot water
Solids by Weight: N/D
Tap Density 0.8 g/cm³
VOC Content: N/D
Molecular Weight: N/A
Viscosity: N/D
Decomposition Temp: N/D
pH: 7-8

SECTION 10: STABILITY AND REACTIVITY

INFORMATION ON STABILITY AND REACTIVITY

Stability: Material is stable under normal conditions
Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.
Materials to Avoid: Strong acids. Strong bases. Strong oxidizers.
Hazardous Decomposition or Bi-Products: Carbon oxides (CO, CO₂). Silicon oxides.
Possibility of Hazardous Reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

Acute Toxicity: Not classified
Quartz (14808-60-7) LD50 Oral Rat > 5000 mg/kg
 LD50 Dermal Rat > 5000 mg/kg
 IARC group 1
Skin Corrosion/Irritation: Not classified
Serious Eye Damage/Irritation: Not classified
Respiratory or Skin Sensitization: Not classified
Germ Cell Mutagenicity: Not classified

SAFETY DATA SHEET: Burnt Umber Dry Pigment
REVISED: 12/30/2015



Carcinogenicity: May cause cancer (Inhalation)
National Toxicity Program (NTP) Status: Known Human Carcinogens
Reproductive Toxicity: Not classified
Specific Target Organ Toxicity (Single Exposure): Not classified
Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation).
Aspiration Hazard: Not classified
Chronic Symptoms: May cause cancer.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS

Inhalation: Repeated exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis.
Ingestion: No adverse effects due to ingestion are expected
Skin: May cause skin irritation
Eye: May cause eye irritation

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION

Ecotoxicity: **Talc (14807-96-6)**
 LC50 Fish 1 > 100 g/l
 (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
Mobility: No information available

PERSISTENCE AND MOBILITY

Biodegradation: No information available
Bioaccumulative potential: No information available
Mobility in Soil: No additional information available
Other Information: Avoid release to the environment

SECTION 13: DISPOSAL CONSIDERATIONS

NOTE: Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at the time of disposal.

Waste Disposal: Dispose of in accordance with national, state, and local regulations.
 Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

LAND (DOT): Not regulated
SEA (IMDG): Not regulated
AIR (IATA): Not regulated

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

SARA Section 311/312 Hazard Classes

Delayed (chronic) health hazard
Quartz (14808-60-7) Listed on the United States TSCA (Toxic Substances Control Act) inventory
Umber (12713-03-0) Listed on the United States TSCA (Toxic Substances Control Act) inventory
Talc (14807-96-6) Listed on the United States TSCA (Toxic Substances Control Act) inventory
Iron oxide red (1309-37-1)

SAFETY DATA SHEET: Burnt Umber Dry Pigment
REVISED: 12/30/2015



Listed on the United States TSCA (Toxic Substances Control Act) inventory

Iron oxide black (12227-89-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Magnesium carbonate (546-93-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US STATE REGULATIONS

Quartz (14808-60-7)

California

Proposition 65 - Carcinogens List

WARNING: This product contains chemicals known to the State of California to cause cancer.

Massachusetts Right To Know List U.S.

New Jersey Right to Know Hazardous Substance List

Pennsylvania RTK (Right to Know) List

Iron Oxide Red (1309-37-1)

Massachusetts Right To Know List

New Jersey Right to Know Hazardous Substance List

Pennsylvania RTK (Right to Know) List

Talc (14807-96-6)

Massachusetts Right To Know List U.S.

New Jersey Right to Know Hazardous Substance List

Pennsylvania RTK (Right to Know) List

Magnesium Carbonate (546-93-0)

Massachusetts Right To Know List

New Jersey Right to Know Hazardous Substance List

Barium Sulfate (7727-43-7)

Massachusetts Right To Know List

New Jersey Right to Know Hazardous Substance List

Pennsylvania RTK (Right to Know) List

INTERNATIONAL REGULATIONS:

EINECS (EU)

All of the ingredients contained in this product are either listed or exempt. Those exemptions are in accordance with (EC) No. 1907/2006, Article 2(7)(b), for naturally occurring ores.

DSL (Canada) All components of this blend are listed, including those listed by way of a naturally occurring ore. CEPA, 1999, Section 2.2.1.4.

China (IECSC) All ingredients are listed

Japan (METI) All ingredients are either listed, or exempt as naturally occurring minerals.

Australia (AICS) All ingredients are listed

Philippines (PICCS) All ingredients are listed or exempt as naturally occurring substances.

New Zealand (NZIoC) All ingredients are listed.

SECTION 16: OTHER INFORMATION

GHS FULL TEXT PHRASES

SAFETY DATA SHEET: Burnt Umber Dry Pigment
REVISED: 12/30/2015



Carc. 1A	Carcinogenicity Category 1A
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure

HMIS III Rating: Health 1 1 Slight Hazard - Irritation or minor reversible injury possible

Fire 0 Minimal Hazard
 Reactivity 0 Minimal Hazard
 Personal Protection E (glasses, gloves, dust respirator)

N/D = Not determined, N/A = Not applicable

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Updates made in accordance with implementation of GHS requirements.

The information and recommendations contained herein are, to the best of Gamblin's knowledge and belief, accurate and reliable, but it is not warranted to be. You can contact Gamblin to ensure that this document is the most current available. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use and it is the user's responsibility to carefully read the product label and follow instructions for safe use of the product.