

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 5.1 (12/07/2023) - Page 1/14

Vitrail : matt medium - FDS022

**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

Product name : Vitrail : matt medium

Product code : FDS022.

See list of references in appendix.

UFI : 33X0-N087-100V-7HKW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paints & Varnishes for artists

1.3. Details of the supplier of the safety data sheet

Registered company name : PEBEO SAS.

Address : CS 10106 .13881.GEMENOS CEDEX.FRANCE.

Telephone : 33 (0) 4.42.32.08.08. Fax : 33 (0) 4.42.32.01.70.

reglementation@pebeo.com

www.pebeo.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.**Other emergency numbers**

United Kingdom : 0870 600 6266 Ireland : 01 809 25 66

SECTION 2 : HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture****In compliance with EC regulation No. 1272/2008 and its amendments.**

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Repeated exposure may cause skin dryness or cracking (EUH066).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS02



GHS07

Signal Word :

WARNING

Product identifiers :

EC 919-857-5

EC 919-857-5

603-064-00-3

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

HYDROCARBONS, C9-C11, ISOALKANES, CYCLICS, < 2% AROMATICS

1-METHOXY-2-PROPANOL

Hazard statements :

H226

Flammable liquid and vapour.

H336

May cause drowsiness or dizziness.

EUH066

Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 5.1 (12/07/2023) - Page 2/14

Vitrail : matt medium - FDS022

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P271 Use only outdoors or in a well-ventilated area.

Precautionary statements - Storage :

P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Precautionary statements - Disposal :

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	Classification (EC) 1272/2008	Note	%
CAS: 64742-48-9 EC: 919-857-5 REACH: 01-2119463258-33 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	[1]	25 \leq x % < 50
CAS: 64742-48-9 EC: 919-857-5 REACH: 01-2119463258-33 HYDROCARBONS, C9-C11, ISOALKANES, CYCLICS, < 2% AROMATICS	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	[1]	10 \leq x % < 25
INDEX: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1 1-METHOXY-2-PROPANOL	GHS02, GHS07 Wng Flam. Liq. 3, H226 STOT SE 3, H336	[1]	2.5 \leq x % < 10
CAS: 7631-86-9 EC: 231-545-4 REACH: 01-2119379499-16-0000 PIGMENT WHITE 27 C.I. 77811 SYNTHETIC AMORPHOUS SILICON DIOXIDE (NANO)		[1] [nano]	2.5 \leq x % < 10
EC: 918-481-9 REACH: 01-2119457273-39 HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS	GHS08 Dgr Asp. Tox. 1, H304		0 \leq x % < 2.5
CAS: 64216-15-5 EC: 264-731-9 CALCIUM 3,5,5-TRIMETHYLHEXANOATE	GHS07 Wng Acute Tox. 4, H302 Eye Irrit. 2, H319		0 \leq x % < 2.5

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 5.1 (12/07/2023) - Page 3/14

Vitrail : matt medium - FDS022

CAS: 22464-99-9 EC: 245-018-1 2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT	GHS08 Wng Repr. 2, H361d	[2]	0 <= x % < 2.5
---	--------------------------------	-----	----------------

Nanoform

Identification CAS: 7631-86-9 EC: 231-545-4 REACH: 01-2119379499-16-0000 PIGMENT WHITE 27 C.I. 77811 SYNTHETIC AMORPHOUS SILICON DIOXIDE (NANO)	Nanoform Name of nanoform(s): Silicon dioxide Shape and aspect ratio of particles: sphere Crystallinity: amorphous Surface functionalisation / treatment: no
---	---

Information on ingredients :

(Full text of H-phrases: see section 16)

[Nano] Nanoform.

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures**In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of non-conductive

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m ³ :	VME-ppm :	VLE-mg/m ³ :	VLE-ppm :	Notes :
107-98-2	375	100	568	150	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-98-2	100 ppm	150 ppm			

- South Africa / DOL RL (Department of Labour, Recommended limits, 1995) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-98-2	100 ppm 360 mg/m ³	300 ppm 1080 mg/m ³		Sk	
7631-86-9	6 mg/m ³				

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME :	VME :	Excess	Notes
107-98-2		100 ppm 370 mg/m ³		2(I)

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 5.1 (12/07/2023) - Page 6/14

Vitril : matt medium - FDS022

7631-86-9		4E mg/m ³				
- Australia (NOHSC: 3008, 1995) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
107-98-2	100 ppm 369 mg/m ³	150 ppm 553 mg/m ³		H		
7631-86-9	2 mg/m ³			A		
- Belgium (Royal decree of 11/05/2021) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
107-98-2	50 ppm 184 mg/m ³	100 ppm 369 mg/m ³		D		
- Canada / Alberta (Occupational health and safety code, 2009) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
107-98-2	100 ppm 369 mg/m ³	150 ppm 553 mg/m ³				
- Canada / British Colombia (2009) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
107-98-2	50 ppm	75 ppm				
- Canada / Quebec (Regulations on occupational health and safety) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
107-98-2	100 ppm 369 mg/m ³	150 ppm 553 mg/m ³				
- Denmark (2020) :						
Stof	TWA	VSTEL	Loftvaerdi	Anm		
107-98-2	50 ppm 185 mg/m ³			EH		
- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :						
CAS	VME-ppm :	VME-mg/m ³ :	VLE-ppm :	VLE-mg/m ³ :	Notes :	TMP No :
107-98-2	50	188	100	375	*	84
- Finland (HTP-värden 2018) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
107-98-2	100 ppm 370 mg/m ³	150 ppm 560 mg/m ³				
- Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT), 2019) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
107-98-2	100 ppm 375 mg/m ³	150 ppm 568 mg/m ³		via dermica. VLI		
- Hong-Kong (Code of practice on control of air impurities (Chemicals substances) in the workplace, 04/2002) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
107-98-2	100 ppm	150 ppm	-	-	-	
- Ireland (Code of practice for the Chemical Agents Regulations, 2021) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
107-98-2	100 ppm 375 mg/m ³	150 ppm 568 mg/m ³				
- Japan (JSOH, Recommendation of occupational exposure limits 2021-2022) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
7631-86-9	4 mg/m ³					
- Malaysia :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
107-98-2	100 ppm	150 ppm	-	-	-	
- Norway (Veiledning om administrative normer for forurensning i arbeidsatmosfære, 2019) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
107-98-2	50 ppm 180 mg/m ³			HE		

Vitrail : matt medium - FDS022

- New Zealand (Workplace Exposure standards, 11/2020, edition 12-1) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-98-2	100 ppm 369 mg/m ³	150 ppm 553 mg/m ³			

- Netherlands / MAC-waarde (10 december 2014) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-98-2	375 mg/m ³	563 mg/m ³		Huid	

- Poland (Dz. U. z 2018 r. poz. 917, 1000 i 1076) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64742-48-9	300 mg/m ³	900 mg/m ³			
64742-48-9	300 mg/m ³	900 mg/m ³			
107-98-2	180 mg/m ³	360 mg/m ³			

- Czech Republic (Regulation No. 361/2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-98-2	270 mg/m ³	550 mg/m ³		D	

- Slovakia (Regulation 300/2007, 471/2011 23/11/2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-98-2	100 ppm 375 mg/m ³	150 ppm 568 mg/m ³		K	

- Switzerland (Suva 2021) :

CAS	VME	VLE	Valeur plafond	Notations
64742-48-9	50 ppm 300 mg/m ³	100 ppm 600 mg/m ³		
64742-48-9	50 ppm 300 mg/m ³	100 ppm 600 mg/m ³		
107-98-2	100 ppm 360 mg/m ³	200 ppm 720 mg/m ³		
7631-86-9	4 ppm			

- Sweden (AFS 2018 :1) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-98-2	50 ppm 190 mg/m ³	150 ppm 568 mg/m ³		H	

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-98-2	100 ppm 375 mg/m ³	150 ppm 560 mg/m ³		Sk	

- USA / NIOSH REL (National Institute for Occupational Safety and Health, Recommended exposure limits) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-98-2	100 ppm	150 ppm	-	-	-

- USA / NIOSH IDLH (National Institute for Occupational Safety and Health, Immediately Dangerous to Life or Health Concentrations) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-98-2	100 ppm 360 mg/m ³	150 ppm 540 mg/m ³			
7631-86-9	6 mg/m ³				

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****Physical state**

Physical state :

Viscous liquid.

Colour

Unspecified

Odour

Odour threshold :

Not stated.

Melting point

Melting point/melting range :

Not relevant.

Freezing point

Freezing point / Freezing range :

Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range :

210 °C.

Flammability

Flammability (solid, gas) :

Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) :

Not stated.

Explosive properties, upper explosivity limit (%) :

Not stated.

Flash point

Flash Point :

28.60 °C.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 5.1 (12/07/2023) - Page 9/14

Vitrail : matt medium - FDS022**Auto-ignition temperature**

Self-ignition temperature : Not relevant.

Decomposition temperature

Decomposition point/decomposition range : Not relevant.

pH

pH : Not relevant.

pH (aqueous solution) : Not stated.

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Insoluble.

Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density and/or relative density

Density : 0.93

Relative vapour density

Vapour density : Not stated.

9.2. Other information

VOC (g/l) : 470.33

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

Formation of explosible dust/air mixtures

Characteristic of dust particles : Not stated.

Maximum pressure generated by the explosion : Not stated.

Deflagration index (Kst) : Not stated.

Minimum ignition energy : Not stated.

MEC/LEL: Not stated.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

11.1.1. Substances**Acute toxicity :**

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

Oral route : LD50 > 5000 mg/kg bodyweight/day
OECD Guideline 401 (Acute Oral Toxicity)
Species : Rat (recommended by the CLP)

Dermal route : LD50 > 5000 mg/kg bodyweight/day
OECD Guideline 402 (Acute Dermal Toxicity)
Species : Rabbit (recommended by the CLP)

Inhalation route (Vapours) : LC50 > 4951 mg/m³
OECD Guideline 403 (Acute Inhalation Toxicity)
Species : Rat (recommended by the CLP)

Carcinogenicity :

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

Carcinogenicity Test : Negative.
No carcinogenic effect.
OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicant :

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

No toxic effect for reproduction
OECD Guideline 414 (Prenatal Developmental Toxicity Study)
OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

Specific target organ systemic toxicity - repeated exposure :

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

Oral route : Duration of exposure : 90 days
C > 100 mg/kg body weight/day
Duration of exposure : 90 days
OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Species : Rat (recommended by CLP)

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 5.1 (12/07/2023) - Page 11/14

Vitrail : matt medium - FDS022

Inhalation route (Vapours) :

Duration of exposure : 90 days
 C > 1 mg/l/6hrs/day
 Duration of exposure : 90 days
 OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

11.1.2. Mixture

No toxicological data available for the mixture.

11.2. Information on other hazards**Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 7631-86-9 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

SECTION 12 : ECOLOGICAL INFORMATION**12.1. Toxicity****12.1.1. Substances**

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

Fish toxicity :

LC50 > 1000 mg/l
 Species : Oncorhynchus mykiss
 Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 1000 mg/l
 Species : Daphnia magna
 Duration of exposure : 48 h

Algae toxicity :

ECr50 > 1000 mg/l
 Species : Pseudokirchnerella subcapitata
 Duration of exposure : 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability**12.2.1. Substances**

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 5.1 (12/07/2023) - Page 12/14

Vitrail : matt medium - FDS022

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

20 01 27 * paint, inks, adhesives and resins containing dangerous substances

15 01 02 plastic packaging

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2020 [40-20] - ICAO/IATA 2023 [64]).

14.1. UN number or ID number

1263

14.2. UN proper shipping name

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

- Classification :



3

14.4. Packing group

III

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	30	5 L	163 367 650	E1	3	D/E

If Q <450l, see 2.2.3.1.5.1.

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	3	-	III	5 L	F-E. S-E	163 223 367 955	E1	Category A	-

if Q < 450 l see IMDG 2.3.2.5.

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	III	355	60 L	366	220 L	A3 A72 A192	E1
	3	-	III	Y344	10 L	-	-	A3 A72 A192	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

Container information:

The mixture is contained in packaging that does not exceed 125 ml.

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): <https://echa.europa.eu/substances-restricted-under-reach>.

Explosives precursors :

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

Particular provisions :

No data available.

Swiss ordinance on the incentive tax on volatile organic compounds :

107-98-2 1-méthoxypropane-2-ol (éther 1-méthylrique d'alpha-propylèneglycol)
34590-94-8 2-(3-méthoxypropoxy)propane-1-ol

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

CMR: Carcinogenic, mutagenic or reprotoxic.

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 5.1 (12/07/2023) - Page 14/14

Vitrail : matt medium - FDS022

IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.
WGK : Wassergefährdungsklasse (Water Hazard Class).
GHS02 : Flame
GHS07 : Exclamation mark
PBT: Persistent, bioaccumulable and toxic.
vPvB : Very persistent, very bioaccumulable.
SVHC : Substances of very high concern.

Reference	Désignation Référence
051002	MEDIUM MAT VITRAIL 45 ML
758413	VITRAIL COFFRET COLLECTION