Page 1

09412-XXXX

00000634	SAFETY DATA SHEE	
	Tri-Art Manufacturing Inc.	
TriA	4 Harvey Street	
	Kingston ON K7K 580	

K7K 5B9 y٤ Canada (613) 541-0299

SHEET

PRODUCT: **Tri-Art Low Viscosity Colours**

SECTION 01: IDENTIFICATION

Product identifier Initial supplier identifier Emergency telephone number and any	Tri-Art Low Viscosity Colours Tri-Art Manufacturing Inc. 4 Harvey Street Kingston, ON. K7K 5B9 Canada 1-888-541-0299 Tri-Art: (613) 541-0299 (9 am to 5 pm EST).	
restrictions	11-Art, (013) 541-0239 (9 am to 5 pm EST).	
Recommended use and restrictions Chemical family Note		
SECTION 02: HAZARD IDENTIFICATION		

Hazard Classification	Non-toxic - does not meet OSHA Hazard Communication classification criteria. Does not
	meet any hazard criteria defined by the Hazardous Products Regulations 2015.
Signal Word	Not hazardous.
Precautionary Statements	Avoid prolonged contact with skin. Avoid contact with eyes. Wash skin thoroughly after
	handling. Do not ingest this product and wash hands before consuming food.
Hazard Description	
·	irritating. Eye contact may cause mild transient irritation. If ingested, may cause irritation of
	mouth, throat, and stomach. Swallowing may cause irritation, nausea and vomiting.
	Ingestion of larger amounts may cause defects to the central nervous system (e.g.
	dizziness, headache).
Mixtures Statement	The product label has been evaluated in accordance with ASTM-4236.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %

* Titanium Dioxide and Carbon Black are ingredients in some colours 13463-67-7, 1333-86-4

SECTION 04: FIRST-AID MEASURES

SECTION 05: FIRE-FIGHTING MEASURES		
Additional Information	with your doctor. Treat symptomatically.	
Skin Contact	Wash off with soap and plenty of water. In the unlikely event that irritation occurs, consult	
Inhalation	Unintentional inhalation of this product should not pose any health risks.	
Ingestion	Do not induce vomiting. Never give anything by mouth if victim is unconscious. Consult a physician.	
Eye Contact	Immediately flush eyes with running water for at least 5 to 10 minutes. If irritation persists, seek prompt medical attention.	

Suitable and unsuitable extinguishing This product does not burn in its liquid form. Use extinguishing media suitable to the media surrounding fire. Carbon oxides in the event the dried paint is involved in a fire. Hazardous Combustion Products..... Special protective equipment and precautions for fire-fighters Specific hazards arising from the hazardous product None required for this product. Not flammable under normal conditions of use. This product is not sensitive to mechanical impact or static discharge.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions / protective	Spills on floors can create a slip hazard. Adequate precautions should be taken when
equipment	walking on spilled product.
Emergency Procedures	Keep children and all others away from spilled material.
Methods / Materials For Containment	Use suitable absorbent materials such as cloth, rags, sponges, or paper towels .

Item Numbers: 09412-1023, 09412-1603, 09412-2123, 09412-2543, 09412-3193, 09412-30412-30412-30412-30412-4013, 09412-4013, 09412-4043, 0941 5233, 09412-5963, 09412-6073, 09412-6513, 09412-9163, 09412-7803, 09412-7803, 09412-8053, 09412-8063, 09412-8073, 09412-8083, 09412-8073, 09412-8013, 09412-6913, 09412-9163, 0 09412-9273, 09412-9313, 09412-9533, 09412-9613

Page 2

0000634

SAFETY DATA SHEET

PRODUCT: Tri-Art Low Viscosity Colours

SECTION 06: ACCIDENTAL RELEASE MEASURES

Clean Up..... Contain and wipe up the spill with absorbent material or cloth. Rinse the cloth with water and repeat the process until surface is clean and dry of spilled material

SECTION 07: HANDLING AND STORAGE

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Keep away from extreme heat and flame. Keep containers tightly closed when not in use. Precautions for safe handling..... Store in a cool, dry, well ventilated area. Do not freeze. Recommended storage temperature: 0 - 30°C (32 - 86°F). Conditions for safe storage, including any incompatibilities **SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION** NIOSH ACGIH TLV OSHA PEL INGREDIENTS TWA STEL PEL STEL REL

Personal protective equipment: Clothing/Type
Eye/Type Gloves/Type
Engineering Controls

No personal protective equipment is necessary when handling or using this product. No special protective clothing is required to use this product. Take the necessary precautions to avoid liquid contact with eyes. No gloves are required to handle this product. No special ventilation requirements are necessary for this product.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Decomposition Temperature Not ava	I. us colors. vidour. tta available. tta available. tta available. tta available. 2.5. 1.40 (calcula 32° F. ble in water. 2.7 212°F. tr to water. lammable. oplicable. oplicable. oplicable. tta. vailable.
Viscosity	vailable.

SECTION 10: STABILITY AND REACTIVITY

(calculated). water.

Avoid extreme heat or freezing temperatures. Stable under the recommended storage and handling conditions prescribed. Reactivity..... Chemical stability..... Possibility of hazardous reactions..... Will not occur. Hazardous decomposition products...... Incompatible materials..... None known, refer to hazardous combustion products in Section 5. There are no known incompabilities. Note On Decomposition..... Not applicable.

SECTION 11: TOXICOLOGICAL INFORMATION

NGREDIENTS		LC50	LD50
Routes of Exposure:	generated during intende Ingestion of large amouni inhalation may cause irrit may result in little or no ir may cause mild transient	possible routes of exposure. Mists d use of this product. Do not take in is may be harmful. If product is hear ation to the nose, throat and respira ritation. Prolonged contact may be a irritation. May cause irritation of mo itation, nausea and vomiting.	nternally or ingest this product. ted or mists are formed, ntory tract. Direct skin contact more irritating. Eye contact

Item Numbers: 09412-1023, 09412-1063, 09412-2123, 09412-2543, 09412-3193, 0941 5233, 09412-5963, 09412-6073, 09412-6513, 09412-9163, 09412-7803, 09412-7803, 09412-8053, 09412-8053, 09412-8073, 09412-8083, 09412-8073, 09412-8013, 09412-8013, 09412-9103, 0 09412-9273, 09412-9313, 09412-9533, 09412-9613

0000634

SAFETY DATA SHEET

Page 3

PRODUCT: Tri-Art Low Viscosity Colours

SECTION 11: TOXICOLOGICAL INFORMATION

	Exposure Material	None known. Some colours contain carbon black, an IARC 2B carcinogen. However, the carbon black used in this product is in a non-respirable form and under normal conditions of use carbon black cannot become airborne. The carcinogenic effects of carbon black are therefore not applicable to this product. Some colours contain titanium dioxide, an IARC Group 2B carcinogen. However, the titanium dioxide used in this product is in a non respirable form and under normal conditions of use, Titanium dioxide cannot become airborne. The carcinogenic effects of titanium dioxide are therefore not applicable to this product.
Aggravated Medic	al Conditions	None are anticipated under normal use.
Note		Use of this product following our recommended instructions should not cause any health hazards, other than those indicated above

SECTION 12: ECOLOGICAL INFORMATION

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods	Empty containers should be recycled in accordance with local municipal recycling practices. Containers that are not empty should be brought to your local waste paint
Appropriate Disposal Considerations Properties Affect Disposal Sewage Disposal Comments	recycling facility Wherever possible unused paint should be brought to your local waste paint facility. None anticipated. Wherever possible, paint should not be washed down the sewer.

SECTION 14: TRANSPORT INFORMATION

UN Number UN Proper Name Transport Hazard Class	Not regulated.
Packaging Group	
Environmental Hazards	
Guidance On Transport In Bulk	Not regulated.
Guidance on transport by air (IATA)	
Any Special Precautions	Regulations. None known.

SECTION 15: REGULATORY INFORMATION

GHS Classification WHMIS 1988 Classification CEPA Status TSCA Inventory Status OSHA SARA TITLE III	The ingredients in this product appear on the DSL.
Section 302 - Extremely Hazardous Substances	None.
Section 311/312 - Hazard Categories SARA Section 313	This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.
EPA Hazardous Air Pollutants (HAPS) 40CFR63	None.
HS Code	
California Proposition 65	Carbon black is known by the state of California to cause cancer. However, Carbon black is listed when found in unbound, airborne particles of respirable size. Titanium dioxide is known by the state of California to cause cancer. However, Titanium dioxide is listed when found in unbound, airborne particles of respirable size.

Item Numbers: 09412-1023, 09412-1603, 09412-2123, 09412-2543, 09412-3193, 09412-313, 09

0000634

SAFETY DATA SHEET

Page 4

PRODUCT: Tri-Art Low Viscosity Colours

SECTION 16: OTHER INFORMATION

Prepared By Disclaimer	Tri-Art Manufacturing Inc www.tri-art.ca - email: support@tri-art.ca. This Safety Data Sheet was prepared by Tri-Art Manufacturing and obtained from supplier information. The information in the Safety Data Sheet is off ered for your consideration and guidance when exposed to this product. Tri-Art Manufacturing Inc. disclaims all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process. This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Tri-Art
Date of the latest revision of the safety data sheet	Manufacturing Inc. 2023-05-01

Item Numbers: 09412-1023, 09412-1603, 09412-2123, 09412-2543, 09412-3193, 09412-313,