SAFETY DATA SHEET

DATE: 24-Aug-2011 REVISION: 19-Apr-2018

1. PRODUCT INFORMATION

Product Name: ZIG POSTERMAN

Product Number: PMA-20, PMA-30, PMA-50, PMA-120, PMA-130, PMA-130S, PMA-150

Recommend Application: Ink

Company Information: Company Name: KURETAKE CO., LTD.

Address: 576 Minamikyobate-cho, 7-chome, Nara-shi, 630-8670

Division: Laboratory

Tel: +81. 742. 50. 2055 Emergency Tel: +81. 742. 50. 2055 Fax: +81. 742. 50. 2077

E-mail: kuretake@kuretake.co.jp

2. HAZARDS IDENTIFICATION

GHS Classification

Physical hazards Flammable liquid Out of Division

Health hazards Acute toxicity (Oral) Not Classification
Acute toxicity (Endermic) Not Classification
Acute toxicity (Inhale : Gas) Not Applicable

Acute toxicity (Inhale : Dust, Mist)
Skin corrosion / irritative
Serious eye damage / eye irritation
Sensitizing property of apparatus

Not Classification
Not Classification
Not Classification

respiratorius and skin

Generate cell mutagenicity
Carcinogen

Not Classification
Category2

Reproductive effect Category1A-1B(except black)

Specially Target Organ Single exposure Category1A-18(except black)

Category1A-18(except black)

Category1 (Central nervous system, Kidney, Heart

Systemic toxicology/ Fluorescence color)
Repeated exposure Category1 (Liver /except black, metallic colors)
Category1 (Central nervous system, Heart,

Respiratory organ/ Fluorescence color)
Category2(Central nervous system
/except black, metallic colors)

Attractant respiratory harmful effect Not Classification

Environmental hazards Acute aquatic toxicity Not Classification
Chronic aquatic toxicity Not Classification

Chronic aquatic toxicity

Hazardous to the ozone layer

Not Classificatio
Out of Division

Label element Pictogram



Signal words Danger

/ Systematic Toxicity

Hazardous Information

May cause genetic defects.

May damage fertility or the unborn child.

Hazard for the organ (Central nervous system, Kidney, Heart, Systemic toxicology)

Hazard for the organ (Liver, Central nervous system, Heart, Respiratory organ) by exposed long term.

[Measure for Safety]

Do not use this product until read all safety precaution and understand it. Before use, please get the operating instruction. Keep this product away from the ignition source such as fever, spark, open flame and high temperature. - NO SMOKING

To prevent from exposure, use personal protective equipment or ventilation. Wear protective gloves, glasses and face mask. Use this product in the well ventilated area or outside only.

[First Aid]

If a fire occur, fight a fire in the proper way.

Inhale: Remove the victim to the fresh air area and keep him guiet.

Swallow: Do not vomit by force. See a doctor.

Eye: Clean by water in a few minutes. Put off the contacts if possible.

Skin: Clean by a large of water with soap.

Skin or Hair: Put off the polluted clothes immediately.

Exposure: See a doctor.

If the irritate to the eyes continue, see a doctor. If feel bad, see a doctor.

[Storage]

Keep the container air-tight, store in the cool and well ventilated area and locked.

[Disposal]

For dispose the content and container, entrust to the special waste disposer authorized by the governor of prefectural and city governments.

Country / Community Information

3. COMPOSITION AND INGREDIENT INFORMATION

Single, Mixture: Mixture

Ingredient and content

Ingredient name	CAS No.	Concentration wt%
Ethyl alcohol	64-17-5	2.0 - 4.0
Carbon black(in four colors only)	1333-86-4	
	Black	9.0 - 10
	Brown	<0.5
	Slate Grey	<0.5
	Burnt Sienna	<0.5
Titanium dioxide(except black)	13463-67-7	7.5 - 15.5

4. FIRST AID

For Inhale Remove the victim to the fresh air area. If feel bad, see a doctor.

For Skin Put off the all polluted clothes immediately. Clean with the proper temp. and slow flowing water

for over 15 minutes. If have irritate the skin, see a doctor. Call a doctor if feel bad. Before re-use

the put off clothes, clean it up and remove the pollution.

For Eyes Put off the contacts if possible, and continue to clean. Clean the eyes carefully for a few minutes.

If the eyes get this product, clean the eye immediately and wash away completely. If the cleaning

eyes not enough, it may cause irreversible eye damage.

If irritate to the eyes continue, see a doctor.

For Swallow Call a doctor, if feel bad. Rinse the mouth out. Do not have the victim vomit.

Expected acute symptom and late symptom:

Sialorrhea, face flash, cough, dizzy, lethargy, headache, sore throat, deliquim animi barf, vomition

Most important sign and symptom:

Protect the person received first aid:

Rescuer must wear proper protective equipment according to the situation.

Special notandum for doctor:

Symptom will appear later, so that if the patient exposed excessively, it needs medical follow progress.

5. FIRE-FIGHTING MEASURE

Extinguishing Media: Small fire / Carbon dioxide, dry chemical extinguishing media, water spray, alcoholic resistance

fire foam.

Great Conflagration: Water spray, mist water, alcoholic resistance fire form.

Forbidden Extinguishing Media: Cylindrical pouring water.

Special Dangerous and Harmful Effect:

The irritative, toxicity and corrosive gas is generated by fire. The container will be burst by heating. If it is not dangerous, move the container from the fire area.

If it is impossible to move, cool the container and around by spraying water. After extinguishing

a fire, cool the container completely by large quantity of water.

Protect the Person Extinguish a Fire:

For fighting fire, wear compressed air open-circuit SBCA and protect equipment for chemical. Fight a fire from up wind.

6. ACCIDENTAL RELEASE MEASURES

Notandum for Human Body, Protective Equipment and Emergency Measure:

The worker must wear proper protector (refer to section 8) not to get the paint on the skin or into eyes. Do not touch the leakage material or walk into it. Keep the proper distance in all direction as the leakage area immediately. No unauthorized entry. If leakage but not occur a fire, wear the occlusive and impervious protect wear. Stay in the wind. Move away from the low ground.

Ventilate before enter the sealed area
3051, 21822-1000, 21322-2000, 21322-1001, 21322-1001, 21322-1000, 21322-1000, 21322-1001, 21322-3001, 21322-2001, 21322-2001, 21322-2001, 21322-3001, 21322-3001, 21322-3002, 21322-3002, 21322-3003, 21322-300

Notandum for Environment:

Prevent from influx into the drain ditch, sewer, basement and closed area.

Take notice not to affect the environment by discharge the paint into the river.

Collect Neutralization:

In small quantity case, absorb the leakage material by dry sand and nonflammable material or collect it in the sealed type container then dispose it. In small quantity case, collect the absorbed material by clean antistatic tools. In large quantity case, yard the leakage material by mound to prevent flow out and lead it into safety area then collect it. In large quantity case, water spray lower than the context of the cont

the steam temperature but it may not inhibit combustion at the sealed area.

Containment or Depurant and Equipment:

If it is not danger, stop the leakage. Ground all equipment which need for handle the leakage

material. Use steam retard foam for lower the steam concentration.

Precaution of Second Disaster:

Clear away all ignition source immediately(Do not smoking near around, forbid firework and flame) In case large steam generating, retard it by mist spray. Call related agency and ask the help.

Protect the Person Extinguish a Fire: None

7. HANDLING AND STORAGE

Handling Do the equipment measure described on the section 8 and wear protector.

Local exhaust ventilation, whole ventilation:

Do the local exhaust ventilation and whole ventilation described on section 8. Prevent leakage

the liquid and steam as possible.

Safe handling notandum:

This product irritate the eyes so that care not to get it into the eyes. This product may cause sleep or vertigo, irritate the apparatus respiratorius and damage organ parts so that do not touch, inhale and swallow it. Do not fall, drop, shock or drag the container. Clean hands well after use this product. Use this product outside or well ventilated area only. Avoid touching, refer to the section10 Keep away from high temperature materials spark and fire, and avoid touching oxidizer and organic peroxide.

Keep the container airtight and stock it in well ventilated place. Stock in the fulfilled and ventilated and cool place. Keep away from oxidant. Keep away from direct sunlight and fire. The inventory location must be fire-proof construction and the floor must be impermeable to prevent permeate

the basement and spill to outside. Lock up the container.

Dangerous goods if mixed:

Refer to the section 10.

Container material:

Use the container regulated by fire law and UN transportation law.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Install the eye washing devices and safety shower where handle or stock this product.

Protection Equipment

Storage

For apparatus respiratorius:

Wear proper respiratory protect equipment such as gas mask for organic gas

(if high concentration, wear air-supplied respirator).

For hands: Wear the gloves designated by manufacturer.

For eyes: Wear the eye protector designated by manufacturer.

For skin and Body: Wear protect boots, oil resistant apron (impermeable and antistatic) and protect clothes

(antistatic) designated by manufacturer.

Hygiene Measure

Check the protect equipment regularly with check sheet. Clean hands well after use this product

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form liquid Condition (20°C) Odor Odorless **Boiling** point Approx. 100°C Vapor pressure No data Density (20°C) 1.08-1.25 pH (against water base) No data Other No data Hazardous Information Flash point No data Ignition point No data

Ignition point No data
Explosion limit No data

No data
No data

Other Hazardous Information

Item Numbers: 21322-0000, 21322-1001, 21322-1002, 21322-1005, 21322-1009, 21322-1009, 21322-1101, 21322-1109, 21322-1009, 21322-1509, 21322-1509, 21322-2001, 21322-2005, 21322-2005, 21322-2001, 21322-3001, 21322-3001, 21322-3005, 2132

10. STABILITY AND REACTIVITY

Stability: Under usually storage condition, it is stable.

Hazardous Reactivity: Nothing Avoid Condition Nothing Avoid Touching Nothing

Hazardous Decomposition Product: Nothing

11. TOXICOLOGICAL INFORMATION

Harmful ingredient and exposure limit.

Name	Exposure	ACGIH (TLV)	IARC	OTHER
Ethyl alcohol	-	1000ppm	1	LD50(oral, rat) 6200 - 15000mg/kg
Carbon black	-	3.5 mg/m ³	2B	LD50(oral, rat) 15400mg/kg
Titanium dioxide	-	10mg/m ³	2B	LD50(oral, rat) >10000mg/kg

Other harmful information relevant to composition:

Harmful information for product:

No data

12. ECOLOGICAL INFORMATION

Acute Hazardous Aquatic Environment No data Inveteracy Hazardous Aquatic Environment No data

13. DISPOSAL CONSIDERATIONS

Residue Waste: For dispose, follow the related regulation and standard of local governments. Ask the licensed

industrial waste disposal company or local governments.

For Burning: Spray the incinerator with waste liquid directly or mix with flammable solvent in small quantity to burn.

Activated sludge process.

Polluted container and package: Clean the container and recycle or treat it in accordance with the related regulation or

local governments. If dispose the container, remove the content completely.

14. TRANSPORT INFORMATION

Common: Please follow the section7. Check if there are no leakage from container and take cargo without

falling, dropping and damage.

Land Transportation: In case of fall under the Fire Law, Industrial Safety and Health Law, Poisonous Material Control

Law follow each relevant mode of transportation.

Marine Transportation: Please follow the Law for Safety of Vessel.

Air Transportation: Please follow the Aviation Law and regulation of ICAO.

UN No. N/A Packing group N/A

15. REGULATORY INFORMATION

Regulatory information with regard to this substance in your country or region should be examined by your own responsibility.

16. OTHER INFORMATION

Main cited item

JPMA "Data Base for raw material MSDS"

JPMA "MSDS Guide Book [Mixture (for paint)]" 4th version

JPMA "MSDS Guide Book [Mixture (for paint)]" 4th version-addenda version

Solvent pocket book

Raw material manufacturer MSDS

DFGOT (1996) IUCLID (2000)

Regarding to the description content:

The description content of this data sheet is based on the documentation, information and data

that we can garner at the present moment so that it might be change depend on new information.

And it is recommend for usual handling so that in case of special handling, use it before take

safety measure that suitable for your application and usage.

The description content is information service and not certification.

N/A = Not Applicable