

SAFETY DATA SHEET

DATE: 24-Aug-2011

REVISION: 15-Nov-2023

Page 1 of 5

MSDS for #21322 - ZIG POSTERMAN MARKER

1. PRODUCT INFORMATION

Product Name: ZIG POSTERMAN

Product Number: PMA-20, PMA-30, PMA-50, PMA-120, PMA-130, PMA-130S, PMA-150

Recommend Application: Ink

Company Information: Company Name: KURETAKE CO., LTD.
 Address: 576 Minamikyobate-cho, 7-chome, Nara-shi, 630-8670
 Division: Laboratory
 Tel: +81. 742. 50. 2055
 Emergency Tel: +81. 742. 50. 2055
 Fax: +81. 742. 50. 2077
 E-mail: kuretake@kuretake.co.jp

2. HAZARDS IDENTIFICATION

GHS Classification

Physical hazards

Flammable liquid

Out of Division

Health hazards

Acute toxicity (Oral)
 Acute toxicity (Endermic)
 Acute toxicity (Inhale : Gas)
 Acute toxicity (Inhale : Dust, Mist)
 Skin corrosion / irritative
 Serious eye damage / eye irritation
 Sensitizing property of apparatus
 respiratorius and skin
 Generate cell mutagenicity
 Carcinogen
 Reproductive effect
 Single exposure

Not Classification
 Not Classification
 Not Applicable
 Not Classification
 Category 2 (metallic only)
 Category 2 (metallic only)
 Not Classification
 Not Classification
 Category1
 Category1A-1B (except black and metallic)
 Category1 (Central nervous system, Kidney, Heart,
 Systemic toxicology/ Fluorescence color)
 Category 1 (Central nervous system, Kidney, Heart,
 Respiratory organ / metallic)
 Category1 (Liver / except black and metallic)
 Category1 (Central nervous system,
 Heart, Respiratory organ/
 Fluorescence color and metallic)
 Category2 (Central nervous system
 /except black)
 Not Classification
 Not Classification
 Not Classification
 Out of Division

Specially Target Organ
/ Systematic Toxicity

Repeated exposure

Attractant respiratory harmful effect

Environmental hazards

Acute aquatic toxicity
 Chronic aquatic toxicity
 Hazardous to the ozone layer

Label element
Pictogram

Signal words

Danger

Hazardous Information

Causes skin irritation (metallic only)
 Causes eye irritation (metallic only)
 May cause cancer
 May damage fertility or the unborn child. (except black and metallic)
 Hazard for the organ (Central nervous system, Kidney, Heart, Systemic toxicology, Respiratory organ)
 (Fluorescence color and metallic)
 Hazard for the organ (Liver, Central nervous system, Heart, Respiratory organ) by exposed long term.
 (except black)

Do not use this product until read all safety precaution and understand it. Before use, please get the operating instruction. Keep this product away from the ignition source such as fever, spark, open flame and high temperature. - NO SMOKING

To prevent from exposure, use personal protective equipment or ventilation. Wear protective gloves, glasses and face mask. Use this product in the well ventilated area or outside only. Do not inhale the mist, vapor and spray. Keep the container air tight.

【First Aid】

If a fire occur, fight a fire in the proper way.
 Inhale: Remove the victim to the fresh air area and keep him quiet.
 Swallow: Do not vomit by force. See a doctor.
 Eye: Clean by water in a few minutes. Put off the contacts if possible.
 Skin: Clean by a large of water with soap.
 Skin or Hair: Put off the polluted clothes immediately.
 Exposure: See a doctor.
 If the irritate to the eyes continue, see a doctor. If feel bad, see a doctor.

【Storage】

Keep the container air-tight, store in the cool and well ventilated area and locked.

【Disposal】

For dispose the content and container, entrust to the special waste disposer authorized by the governor of prefectural and city governments.

Country / Community Information

3. COMPOSITION AND INGREDIENT INFORMATION

Single, Mixture:

Mixture

Ingredient and content

Ingredient name	CAS No.	Concentration wt%
Ethyl alcohol	64-17-5	2.0 - 4.0
Carbon black(in four colors only)	1333-86-4	
	Black	9.0 - 10
	Brown	<0.5
	Slate Grey	<0.5
	Burnt Sienna	<0.5
Titanium dioxide(except black and metallic)	13463-67-7	7.5 - 15.5
Aluminum flake (metallic only)	7429-90-5	≤10.3
Ethylene glycol	107-21-1	≤2.9
Propylene glycol mono methyl ether	107-98-2	≤4.7
Phosphoric acid	7664-38-2	≤0.2
Ammonium Hydroxide	1336-21-6	≤1.1

4. FIRST AID

For Inhale

Remove the victim to the fresh air area. If feel bad, see a doctor.

For Skin

Put off the all polluted clothes immediately. Clean with the proper temp. and slow flowing water for over 15 minutes. If have irritate the skin, see a doctor. Call a doctor if feel bad. Before re-use the put off clothes, clean it up and remove the pollution.

For Eyes

Put off the contacts if possible, and continue to clean. Clean the eyes carefully for a few minutes. If the eyes get this product, clean the eye immediately and wash away completely. If the cleaning eyes not enough, it may cause irreversible eye damage.
 If irritate to the eyes continue, see a doctor.

For Swallow

Call a doctor, if feel bad. Rinse the mouth out. Do not have the victim vomit.

Expected acute symptom and late symptom:

Sialorrhea, face flash, cough, dizzy, lethargy, headache, sore throat, deliquim animi barf, vomition

Most important sign and symptom:

Protect the person received first aid:

Rescuer must wear proper protective equipment according to the situation.

Special notandum for doctor:

Symptom will appear later, so that if the patient exposed excessively, it needs medical follow progress.

5. FIRE-FIGHTING MEASURE

Extinguishing Media:

Small fire / Carbon dioxide, dry chemical extinguishing media, water spray, alcoholic resistance fire foam.

Great Conflagration:

Water spray, mist water, alcoholic resistance fire form.

Forbidden Extinguishing Media:

Cylindrical pouring water.

Special Dangerous and Harmful Effect:

MSDS for #21322 - ZIG POSTERMAN MARKER

Page 3 of 5

The irritative, toxicity and corrosive gas is generated by fire. The container will be damaged by heating. It is not dangerous, move the container from the fire area.

If it is impossible to move, cool the container and around by spraying water. After extinguishing a fire, cool the container completely by large quantity of water.

Protect the Person Extinguish a Fire:

For fighting fire, wear compressed air open-circuit SBCA and protect equipment for chemical. Fight a fire from up wind.

6. ACCIDENTAL RELEASE MEASURES

Notandum for Human Body, Protective Equipment and Emergency Measure:

The worker must wear proper protector (refer to section 8) not to get the paint on the skin or into eyes. Do not touch the leakage material or walk into it. Keep the proper distance in all direction as the leakage area immediately. No unauthorized entry. If leakage but not occur a fire, wear the occlusive and impervious protect wear. Stay in the wind. Move away from the low ground. Ventilate before enter the sealed area.

Notandum for Environment:

Prevent from influx into the drain ditch, sewer, basement and closed area.
Take notice not to affect the environment by discharge the paint into the river.

Collect Neutralization:

In small quantity case, absorb the leakage material by dry sand and nonflammable material or collect it in the sealed type container then dispose it. In small quantity case, collect the absorbed material by clean antistatic tools. In large quantity case, yard the leakage material by mound to prevent flow out and lead it into safety area then collect it. In large quantity case, water spray lower the steam temperature but it may not inhibit combustion at the sealed area.

Containment or Depurant and Equipment:

If it is not danger, stop the leakage. Ground all equipment which need for handle the leakage material. Use steam retard foam for lower the steam concentration.

Precaution of Second Disaster:

Clear away all ignition source immediately (Do not smoking near around, forbid firework and flame)
In case large steam generating, retard it by mist spray. Call related agency and ask the help.

Protect the Person Extinguish a Fire: None

7. HANDLING AND STORAGE

Handling Do the equipment measure described on the section 8 and wear protector.

Local exhaust ventilation, whole ventilation:

Do the local exhaust ventilation and whole ventilation described on section 8. Prevent leakage the liquid and steam as possible.

Safe handling notandum:

This product irritate the eyes so that care not to get it into the eyes. This product may cause sleep or vertigo, irritate the apparatus respiratorius and damage organ parts so that do not touch, inhale and swallow it. Do not fall, drop, shock or drag the container. Clean hands well after use this product. Use this product outside or well ventilated area only. Avoid touching, refer to the section 10. Keep away from high temperature materials spark and fire, and avoid touching oxidizer and organic peroxide.

Storage

Keep the container airtight and stock it in well ventilated place. Stock in the fulfilled and ventilated and cool place. Keep away from oxidant. Keep away from direct sunlight and fire. The inventory location must be fire-proof construction and the floor must be impermeable to prevent permeate the basement and spill to outside. Lock up the container.

Dangerous goods if mixed:

Refer to the section 10.

Container material:

Use the container regulated by fire law and UN transportation law.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Install the eye washing devices and safety shower where handle or stock this product.

Protection Equipment

For apparatus respiratorius:

Wear proper respiratory protect equipment such as gas mask for organic gas (if high concentration, wear air-supplied respirator).

For hands:

Wear the gloves designated by manufacturer.

For eyes:

Wear the eye protector designated by manufacturer.

For skin and Body:

Wear protect boots, oil resistant apron (impermeable and antistatic) and protect clothes (antistatic) designated by manufacturer.

Hygiene Measure

Check the protect equipment regularly with check sheet. Clean hands well after use this product

MSDS for #21322 - ZIG POSTERMAN MARKER

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form	Condition (20°C)	liquid
	Odor	Odorless
	Boiling point	100°C
	Vapor pressure	No data
	Density (20°C)	1.08-1.25
	pH (against water base)	No data
	Other	No data
Hazardous Information	Flash point	No data
	Ignition point	No data
	Explosion limit	No data
Other Hazardous Information		No data

10. STABILITY AND REACTIVITY

Stability:	Under usually storage condition, it is stable.
Hazardous Reactivity:	Nothing
Avoid Condition	Nothing
Avoid Touching	Nothing
Hazardous Decomposition Product:	Nothing

11. TOXICOLOGICAL INFORMATION

Harmful ingredient and exposure limit.

Name	ACGIH (TLV)	IARC	OTHER
Ethyl alcohol	1000ppm	1	LD ₅₀ (oral, rat) 6200 - 15000mg/kg
Carbon black	3.5 mg/m ³	2B	LD ₅₀ (oral, rat) 15400mg/kg
Titanium dioxide	10mg/m ³	2B	LD ₅₀ (oral, rat) > 10000mg/kg
Aluminum flake	-	-	No data
Ethylene glycol	MAX 100mg/m ³ (aerosol)	-	LD ₅₀ (oral, rat) = 4700mg/kg
Propylene glycol mono methyl ether	100 ppm	-	LD ₅₀ (oral, rat) = 5000mg/kg
Phosphoric acid	1mg/m ³	-	LD ₅₀ (oral, rat) = 1530mg/kg LD ₅₀ (skin, rabbit) = 2740mg/kg
Ammonium Hydroxide	-	-	LD ₅₀ (oral, rat) = 350mg/kg

Other harmful information relevant to composition:

No data

Harmful information for product:

No data

12. ECOLOGICAL INFORMATION

Acute Hazardous Aquatic Environment
Inveteracy Hazardous Aquatic Environment

No data

No data

13. DISPOSAL CONSIDERATIONS

Residue Waste:	For dispose, follow the related regulation and standard of local governments. Ask the licensed industrial waste disposal company or local governments.
For Burning:	Spray the incinerator with waste liquid directly or mix with flammable solvent in small quantity to burn. Activated sludge process.
Polluted container and package:	Clean the container and recycle or treat it in accordance with the related regulation or local governments. If dispose the container, remove the content completely.

14. TRANSPORT INFORMATION

Common: Please follow the section 7. Check if there are no leakage from container and take cargo with care to avoid falling, dropping and damage.

MSDS for #21322 - ZIG POSTERMAN MARKER

Page 5 of 5

Land Transportation: In case of fall under the Fire Law, Industrial Safety and Health Law, Poisonous Material Control Law follow each relevant mode of transportation.

Marine Transportation:
IMDG Not classified as a dangerous goods under transport regulations

Air Transportation:
IATA/ICAO Not classified as a dangerous goods under transport regulations
UN No. Non-Regulated
Packing group Non-Regulated

The carbon black included in this product is not classified as a dangerous goods to UN3088 and UN1361, UN1362

CARBON NOT SUBJECT TO THE PROVISIONS OF THE IMDG CODE

The provisions of the IMDG Code do not apply to non-activated Carbon blacks of mineral origin and Carbons made by a steam activation process.

IMDG Code Special Provision 925, under Part 3, Chapter 3.3, of the Code states:

IMDG Code Special Provision	
925	<p>The provisions of this Code do not apply to:</p> <ul style="list-style-type: none"> - non-activated carbon blacks of mineral origin; - a consignment of carbon if it passes the tests for self-heating substances as reflected in the United Nations Manual of Tests and Criteria (see 33.3.1.3.3), and is accompanied by a certificate from a laboratory accredited by the competent authority, stating that the product to be loaded has been correctly sampled by trained staff from that laboratory and that the sample was correctly tested and has passed the test; and - carbons made by a steam activation process.

15. REGULATORY INFORMATION

Regulatory information with regard to this substance in your country or region should be examined by your own responsibility.

16. OTHER INFORMATION

Main cited item

JPMA "Data Base for raw material MSDS"
JPMA "MSDS Guide Book [Mixture (for paint)]" 4th version
JPMA "MSDS Guide Book [Mixture (for paint)]" 4th version-addenda version
Solvent pocket book
Raw material manufacturer MSDS
DFGOT (1996)
IUCLID (2000)

Regarding to the description content:

The description content of this data sheet is based on the documentation, information and data that we can garner at the present moment so that it might be change depend on new information. And it is recommend for usual handling so that in case of special handling, use it before take safety measure that suitable for your application and usage.

The description content is information service and not certification.

N/A = Not Applicable