

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_ash_c] 1/6

22192-2004



Safety Data Sheet

According to OSHA 29 CFR 1910.1200 HCS & Canada WHMIS



Revision Date : 09.01. 2020

SECTION 1: Identification

1.1. Product identifier

Product Name : Artline FURNITURE Marker

EK-95

Color : (Ash)



1.2. Recommended use of the chemical and restrictions on use

Recommended use : Permanent marker ink

1.3. Details of the supplier of the safety data sheet

Company Name : Shachihata Inc. (U.S.A.)

Address : 20775 S. Western Ave., Suite 105 Torrance, CA 90501 U.S.A.

Telephone : 1-800-541-9719

Fax : 1-800-541-7166

Contact (e-mail) : customerservice@xstamper.com

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300

(For Hazardous materials or dangerous goods incident, spill, leak, fire, exposure or accident)

SECTION 2: Hazard(s) identification

According to OSHA 29 CFR 1910.1200 HCS & Hazardous Product Regulation (WHMIS 2015)

2.1.1 Classification of the substance or mixture

Flammable liquids, Category 2

H225 : Highly flammable liquid and vapour

Serious eye damage, Category 1

H318 : Causes serious eye damage

Specific target organ toxicity ; single exposure, Category 3
(narcotic effects)

H336 : May cause drowsiness or dizziness

2.1.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statement : Highly flammable liquid and vapour
Causes serious eye damage
May cause drowsiness or dizziness

(H225)

(H318)

(H336)

Precautionary statement

【Prevention】

Keep out of reach of children.

(P102)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(P210)

Take precautionary measures against static discharge.

(P243)

Avoid breathing vapours.

(P261)

Use only outdoors or in a well-ventilated area.

(P271)

Wear eye protection.

(P280)

【Response】

In case of fire : Use dry chemical powder, foam or carbon dioxide to extinguish.

(P370+P378)

IF INHALED : Remove person to fresh air and keep comfortable for breathing.

(P304+P340)

IF IN EYES : Rinse cautiously with water for several minutes

(P305+P351+P338)

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_ash_c] 2/6

If eye irritation persists : Get medical advice and attention. (P337+P313)

Immediately call a POISON CENTER or physician. (P310)

IF ON SKIN (or hair) : Take off immediately all contaminated clothing. Rinse skin with water. (P303+P361+P353)

If skin irritation occurs : Get medical advice and attention. (P332+P313)

【Storage】

Store in a well-ventilated place. Keep container tightly closed. (P403+P233)

【Disposal】


Dispose of contents and container in accordance with local regulations. (P501)

2.1.3 Other hazards

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS2015).

2.3 Other information



SECTION 3: Composition/information on ingredients

Substance / Mixture : Mixture

Ingredients :

Chemical Name / Generic name	Composition weight %	CAS Registry No.	Classification (OSHA HCS 2012)	
			Hazard Class	Hazard statement
Ethanol	45 ~ 55	64-17-5	Flam. Liq. 2	H225
1-methoxypropan-2-ol	20 ~ 30	107-98-2	Flam. Liq. 3 STOT. SE. 3	H226 H336
Ethyl lactate	5 ~ 15	97-64-3	Flam. Liq. 3 Eye Dam. 1 STOT. SE. 3	H226 H318 H335
Synthetic resin	10 ~ 20	Confidential	none	none
Dyestuff	<1	Confidential	none	none
total	100			

SECTION 4: First-aid measures

4.1. Description of first aid measures

IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a doctor if symptoms persist.

IF ON SKIN : Remove / Take off immediately all contaminated clothing. Wash with soap and water. If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.

IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

IF SWALLOWED : After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach, and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient when not conscious. Receive the doctor's treatment (stomach pump) promptly.

Note to Physicians :

All treatments should be based on observed signs and symptoms of distress in the patient.

Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_ash_c] 3/6

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder, foam or carbon dioxide
 Unsuitable extinguishing media : Water jet

5.2. Special hazards arising from the substance or mixture

For initial stage extinction, carbon dioxide or dry chemical powder.
 When a fire extends, fire is extinguished by a large amount of water spray.
 Do not discharge extinguishing waters into the aquatic environment.

5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn.
 Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe area. Shut off all sources of ignition.
 No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

6.2. Environmental precautions

Do not throw the leakage thing directly into environment

6.3. Methods and material for containment and cleaning up

In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth, etc.), and then wipe off the waste well with waste cloth, and rag.
 In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.) and collect into empty container by scoop, suction equipment or the like.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling : Use with adequate ventilation.
 Avoid contact with skin, eyes and clothing.
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep containers tightly closed and store in a cool and dry place.
 areas and containers : Keep away from heat and flame, ignition source and sunlight.
 Keep out of the reach of children.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ACGIH (2019)

Ethanol	STEL	1,000 ppm
1-methoxypropan-2-ol	TWA	50 ppm

OSHA PEL

Ethanol	TWA	1,000 ppm
---------	-----	-----------

Canada Ontario Provincial

Ethanol	STEL	1,000 ppm
1-methoxypropan-2-ol	TWA	100 ppm

Canada Quebec Provincial

Ethanol	TWA	1,000 ppm
1-methoxypropan-2-ol	TWA	100 ppm

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_ash_c] 4/6

8.2. Exposure controls**Personal protective equipment**

- Respiratory Protection : Use with local exhaust ventilation, when in long use.
Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.
- Hand Protection : Avoid contact with hands. Wear safety gloves, if necessary.
- Eye Protection : Avoid contact with eyes. Wear safety glasses, if necessary.
- Skin Protection : Avoid skin contact. Wear personal protection apron, boots, if necessary.

Environmental exposure controls

- General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- Appearance : Ash color liquid
- Odor : Minor solvent odour
- pH : Not applicable
- Boiling point : 172.4°F (78°C) ~ 309°F (154°C)
- Flash point : 60.8°F (16°C) (closed cup)
- Relative Density (at 77°F, 25°C) : 0.85 ~ 0.95 (g/cm³)
- Solubility in Water : Insoluble

SECTION 10: Stability and reactivity**10.1. Reactivity**

No dangerous reaction known under conditions of normal use.

10.2. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.3. Chemical stability

The product is stable.

10.4. Conditions to Avoid

High temperature, Direct sunlight, Fire

10.5. Incompatible Materials

No data available

10.6. Hazardous decomposition products

CO, CO₂

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

- Acute toxicity : LD/LC50 values that are relevant for classification
- | | | | |
|------------------------|------|------------------------|--|
| [Ethanol] | | | |
| Oral-rat | LD50 | >5,000 mg/kg | |
| Inhalation-rat | LC50 | >20 mg/L/4h | |
| [1-methoxypropan-2-ol] | | | |
| Oral-rat | LD50 | >2,000 - <=5,000 mg/kg | |
| Dermal-rabbit | LD50 | >5,000 mg/kg | |
| Inhalation-rat | LC50 | >20 mg/L/4h | |
| [Ethyl lactate] | | | |
| Oral-rat | LD50 | >2,000 mg/kg | |
| Dermal-rabbit | LD50 | >5,000 mg/kg | |
- Serious eye damage : Category 1 Causes serious eye damage
- Specific target organ toxicity : Category 3 May cause drowsiness or dizziness
(single exposure)

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_ash_c] 5/6

Carcinogenicity : This product does not contain any component that is considered a human carcinogen by IARC, ACGIH, EPA, EU or NTP.

SECTION 12: Ecological information

- 12.1. Ecotoxicity : No data available
 12.2. Persistence and degradability : No data available
 12.3. Bioaccumulative potential : No data available
 12.4. Mobility in soil : No data available
 12.5. Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
 Disposal must be made according to official regulations.
 Comply with all Federal, State, and Local regulations regarding disposal.
 Do not allow product to reach ground, any water course or sewage system.

SECTION 14: Transport information

- 14.1. UN number (DOT, ADR, IMDG, IATA) : UN1210
 14.2. UN proper shipping name (DOT, ADR, IMDG, IATA) : PRINTING INK, flammable
 14.3. Transport hazard class(es) (DOT, ADR, IMDG, IATA) :
 · Class 3 (Flammable liquids.)
 · Label 3
 14.4. Packing group (DOT, ADR, IMDG, IATA) : II
 14.5. Environmental hazards Marine pollutant : N
 14.6. Special precautions for user EMS Number : F-E,S-D



☆☆

Artline FURNITURE Marker (EK-95) is not a hazardous material by the special provision.

Artline FURNITURE Marker (EK-95) (The amount of ink : less than 10ml)

UN number : UN3175
 UN proper shipping name : Solids containing Flammable Liquid. n.o.s.
 IATA Special Provision A46
 IMDG Code Special Provision 216
 ADG Special Provision 216

According to IATA Special Provision A46, and IMDG Code Special Provision 216, small inner packagings consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed onto a solid material are not subject to as a hazardous material/dangerous goods provided there is no free liquid in the packet or article.

SECTION 15: Regulatory information

< USA Information >

OSHA STATUS : This product is hazardous under 29 CFR 1910.1200.
 TSCA STATUS : All components on TSCA INVENTORY.
 TSCA Hazard Communication Program (40 CFR Part 721) (SNUR) : Not Applicable
 CERCLA REPORTABLE QUANTITY (40 CFR 117,302) : Not Applicable
 SARA TITLE III Section 313 (40 CFR 372) : Not Applicable
 California Proposition 65 : Not listed

< Canada Information >

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

Canada inventory : All components of this product are listed in the DSL/NDL Inventory.

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_ash_c] 6/6

SECTION 16: Other information, including date of preparation or last revision

Last Revision Date : 09.01. 2020

Preparation Date : 20.05. 2015



This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.

EU RoHS (Directive 2011/65/EU)
EU ELV (DIRECTIVE 2000/53/EC)

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_beech_c] 1/6



Safety Data Sheet

According to OSHA 29 CFR 1910.1200 HCS & Canada WHMIS



Revision Date : 09.01. 2020

SECTION 1: Identification

1.1. Product identifier

Product Name : Artline FURNITURE Marker

EK-95

Color : (Beech)



1.2. Recommended use of the chemical and restrictions on use

Recommended use : Permanent marker ink

1.3. Details of the supplier of the safety data sheet

Company Name : Shachihata Inc. (U.S.A.)

Address : 20775 S. Western Ave., Suite 105 Torrance, CA 90501 U.S.A.

Telephone : 1-800-541-9719

Fax : 1-800-541-7166

Contact (e-mail) : customerservice@xstamper.com

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300

(For Hazardous materials or dangerous goods incident, spill, leak, fire, exposure or accident)

SECTION 2: Hazard(s) identification

According to OSHA 29 CFR 1910.1200 HCS & Hazardous Product Regulation (WHMIS 2015)

2.1.1 Classification of the substance or mixture

Flammable liquids, Category 2

H225 : Highly flammable liquid and vapour

Serious eye damage, Category 1

H318 : Causes serious eye damage

Specific target organ toxicity ; single exposure, Category 3
(narcotic effects)

H336 : May cause drowsiness or dizziness

2.1.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statement : Highly flammable liquid and vapour
Causes serious eye damage
May cause drowsiness or dizziness

(H225)

(H318)

(H336)

Precautionary statement

【Prevention】

Keep out of reach of children.

(P102)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(P210)

Take precautionary measures against static discharge.

(P243)

Avoid breathing vapours.

(P261)

Use only outdoors or in a well-ventilated area.

(P271)

Wear eye protection.

(P280)

【Response】

In case of fire : Use dry chemical powder, foam or carbon dioxide to extinguish.

(P370+P378)

IF INHALED : Remove person to fresh air and keep comfortable for breathing.

(P304+P340)

IF IN EYES : Rinse cautiously with water for several minutes

(P305+P351+P338)

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_beech_c] 2/6

If eye irritation persists : Get medical advice and attention. (P337+P313)

Immediately call a POISON CENTER or physician. (P310)

IF ON SKIN (or hair) : Take off immediately all contaminated clothing. Rinse skin with water. (P303+P361+P353)

If skin irritation occurs : Get medical advice and attention. (P332+P313)

【Storage】

Store in a well-ventilated place. Keep container tightly closed. (P403+P233)

【Disposal】


Dispose of contents and container in accordance with local regulations. (P501)

2.1.3 Other hazards

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS2015).

2.3 Other information



SECTION 3: Composition/information on ingredients

Substance / Mixture : Mixture

Ingredients :

Chemical Name / Generic name	Composition weight %	CAS Registry No.	Classification (OSHA HCS 2012)	
			Hazard Class	Hazard statement
Ethanol	45 ~ 55	64-17-5	Flam. Liq. 2	H225
1-methoxypropan-2-ol	20 ~ 30	107-98-2	Flam. Liq. 3 STOT. SE. 3	H226 H336
Ethyl lactate	5 ~ 15	97-64-3	Flam. Liq. 3 Eye Dam. 1 STOT. SE. 3	H226 H318 H335
Synthetic resin	10 ~ 20	Confidential	none	none
Dyestuff	<1	Confidential	none	none
total	100			

SECTION 4: First-aid measures

4.1. Description of first aid measures

IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a doctor if symptoms persist.

IF ON SKIN : Remove / Take off immediately all contaminated clothing. Wash with soap and water. If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.

IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

IF SWALLOWED : After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach, and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient when not conscious. Receive the doctor's treatment (stomach pump) promptly.

Note to Physicians :

All treatments should be based on observed signs and symptoms of distress in the patient.

Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_beech_c] 3/6

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder, foam or carbon dioxide
 Unsuitable extinguishing media : Water jet

5.2. Special hazards arising from the substance or mixture

For initial stage extinction, carbon dioxide or dry chemical powder.
 When a fire extends, fire is extinguished by a large amount of water spray.
 Do not discharge extinguishing waters into the aquatic environment.

5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn.
 Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe area. Shut off all sources of ignition.
 No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

6.2. Environmental precautions

Do not throw the leakage thing directly into environment

6.3. Methods and material for containment and cleaning up

In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth, etc.), and then wipe off the waste well with waste cloth, and rag.
 In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.) and collect into empty container by scoop, suction equipment or the like.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling : Use with adequate ventilation.
 Avoid contact with skin, eyes and clothing.
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep containers tightly closed and store in a cool and dry place.
 areas and containers : Keep away from heat and flame, ignition source and sunlight.
 Keep out of the reach of children.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ACGIH (2019)

Ethanol	STEL	1,000 ppm
1-methoxypropan-2-ol	TWA	50 ppm

OSHA PEL

Ethanol	TWA	1,000 ppm
---------	-----	-----------

Canada Ontario Provincial

Ethanol	STEL	1,000 ppm
1-methoxypropan-2-ol	TWA	100 ppm

Canada Quebec Provincial

Ethanol	TWA	1,000 ppm
1-methoxypropan-2-ol	TWA	100 ppm

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_beech_c] 4/6

8.2. Exposure controls**Personal protective equipment**

- Respiratory Protection : Use with local exhaust ventilation, when in long use.
Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.
- Hand Protection : Avoid contact with hands. Wear safety gloves, if necessary.
- Eye Protection : Avoid contact with eyes. Wear safety glasses, if necessary.
- Skin Protection : Avoid skin contact. Wear personal protection apron, boots, if necessary.

Environmental exposure controls

- General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- Appearance : Beech color liquid
- Odor : Minor solvent odour
- pH : Not applicable
- Boiling point : 172.4°F (78°C) ~ 309°F (154°C)
- Flash point : 60.8°F (16°C) (closed cup)
- Relative Density (at 77°F, 25°C) : 0.85 ~ 0.95 (g/cm³)
- Solubility in Water : Insoluble

SECTION 10: Stability and reactivity**10.1. Reactivity**

No dangerous reaction known under conditions of normal use.

10.2. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.3. Chemical stability

The product is stable.

10.4. Conditions to Avoid

High temperature, Direct sunlight, Fire

10.5. Incompatible Materials

No data available

10.6. Hazardous decomposition products

CO, CO₂

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

- Acute toxicity : LD/LC50 values that are relevant for classification
- | | | | |
|-------------------------|------|------------------------|--|
| [Ethanol] | | | |
| Oral-rat | LD50 | >5,000 mg/kg | |
| Inhalation-rat | LC50 | >20 mg/L/4h | |
| [1-methoxypropan-2-ol] | | | |
| Oral-rat | LD50 | >2,000 - <=5,000 mg/kg | |
| Dermal-rabbit | LD50 | >5,000 mg/kg | |
| Inhalation-rat | LC50 | >20 mg/L/4h | |
| [Ethyl lactate] | | | |
| Oral-rat | LD50 | >2,000 mg/kg | |
| Dermal-rabbit | LD50 | >5,000 mg/kg | |
- Serious eye damage : Category 1 Causes serious eye damage
- Specific target organ toxicity : Category 3 May cause drowsiness or dizziness
(single exposure)

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_beech_c] 5/6

Carcinogenicity : This product does not contain any component that is considered a human carcinogen by IARC, ACGIH, EPA, EU or NTP.

SECTION 12: Ecological information

- 12.1. Ecotoxicity : No data available
 12.2. Persistence and degradability : No data available
 12.3. Bioaccumulative potential : No data available
 12.4. Mobility in soil : No data available
 12.5. Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
 Disposal must be made according to official regulations.
 Comply with all Federal, State, and Local regulations regarding disposal.
 Do not allow product to reach ground, any water course or sewage system.

SECTION 14: Transport information

- 14.1. UN number (DOT, ADR, IMDG, IATA) : UN1210
 14.2. UN proper shipping name (DOT, ADR, IMDG, IATA) : PRINTING INK, flammable
 14.3. Transport hazard class(es) (DOT, ADR, IMDG, IATA) :
 · Class 3 (Flammable liquids.)
 · Label 3
 14.4. Packing group (DOT, ADR, IMDG, IATA) : II
 14.5. Environmental hazards Marine pollutant : N
 14.6. Special precautions for user EMS Number : F-E,S-D



☆☆

Artline FURNITURE Marker (EK-95) is not a hazardous material by the special provision.

Artline FURNITURE Marker (EK-95) (The amount of ink : less than 10ml)

UN number : UN3175
 UN proper shipping name : Solids containing Flammable Liquid. n.o.s.
 IATA Special Provision A46
 IMDG Code Special Provision 216
 ADG Special Provision 216

According to IATA Special Provision A46, and IMDG Code Special Provision 216, small inner packagings consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed onto a solid material are not subject to as a hazardous material/dangerous goods provided there is no free liquid in the packet or article.

SECTION 15: Regulatory information

< USA Information >

OSHA STATUS : This product is hazardous under 29 CFR 1910.1200.
 TSCA STATUS : All components on TSCA INVENTORY.
 TSCA Hazard Communication Program (40 CFR Part 721) (SNUR) : Not Applicable
 CERCLA REPORTABLE QUANTITY (40 CFR 117,302) : Not Applicable
 SARA TITLE III Section 313 (40 CFR 372) : Not Applicable
 California Proposition 65 : Not listed

< Canada Information >

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

Canada inventory : All components of this product are listed in the DSL/NDL Inventory.

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_beech_c] 6/6

SECTION 16: Other information, including date of preparation or last revision

Last Revision Date : 09.01. 2020

Preparation Date : 20.05. 2015



This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.

EU RoHS (Directive 2011/65/EU)
EU ELV (DIRECTIVE 2000/53/EC)

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_birchbrown_c] 1/6



Safety Data Sheet

According to OSHA 29 CFR 1910.1200 HCS & Canada WHMIS



Revision Date : 09.01. 2020

SECTION 1: Identification

1.1. Product identifier

Product Name : Artline FURNITURE Marker

EK-95

Color : (Birchbrown)



1.2. Recommended use of the chemical and restrictions on use

Recommended use : Permanent marker ink

1.3. Details of the supplier of the safety data sheet

Company Name : Shachihata Inc. (U.S.A.)

Address : 20775 S. Western Ave., Suite 105 Torrance, CA 90501 U.S.A.

Telephone : 1-800-541-9719

Fax : 1-800-541-7166

Contact (e-mail) : customerservice@xstamper.com

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300

(For Hazardous materials or dangerous goods incident, spill, leak, fire, exposure or accident)

SECTION 2: Hazard(s) identification

According to OSHA 29 CFR 1910.1200 HCS & Hazardous Product Regulation (WHMIS 2015)

2.1.1 Classification of the substance or mixture

Flammable liquids, Category 2

H225 : Highly flammable liquid and vapour

Serious eye damage, Category 1

H318 : Causes serious eye damage

Specific target organ toxicity ; single exposure, Category 3
(narcotic effects)

H336 : May cause drowsiness or dizziness

2.1.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statement : Highly flammable liquid and vapour
Causes serious eye damage
May cause drowsiness or dizziness

(H225)

(H318)

(H336)

Precautionary statement

【Prevention】

Keep out of reach of children.

(P102)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(P210)

Take precautionary measures against static discharge.

(P243)

Avoid breathing vapours.

(P261)

Use only outdoors or in a well-ventilated area.

(P271)

Wear eye protection.

(P280)

【Response】

In case of fire : Use dry chemical powder, foam or carbon dioxide to extinguish.

(P370+P378)

IF INHALED : Remove person to fresh air and keep comfortable for breathing.

(P304+P340)

IF IN EYES : Rinse cautiously with water for several minutes

(P305+P351+P338)

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_birchbrown_c] 2/6

If eye irritation persists : Get medical advice and attention.

(P337+P313)

Immediately call a POISON CENTER or physician.

(P310)

IF ON SKIN (or hair) : Take off immediately all contaminated clothing. Rinse skin with water.

(P303+P361+P353)

If skin irritation occurs : Get medical advice and attention.

(P332+P313)

【Storage】

Store in a well-ventilated place. Keep container tightly closed.

(P403+P233)

【Disposal】

Dispose of contents and container in accordance with local regulations.


(P501)

2.1.3 Other hazards

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS2015).

2.3 Other information



SECTION 3: Composition/information on ingredients

Substance / Mixture : Mixture

Ingredients :

Chemical Name / Generic name	Composition weight %	CAS Registry No.	Classification (OSHA HCS 2012)	
			Hazard Class	Hazard statement
Ethanol	40 ~ 50	64-17-5	Flam. Liq. 2	H225
1-methoxypropan-2-ol	20 ~ 30	107-98-2	Flam. Liq. 3 STOT. SE. 3	H226 H336
Ethyl lactate	5 ~ 15	97-64-3	Flam. Liq. 3 Eye Dam. 1 STOT. SE. 3	H226 H318 H335
Synthetic resin	10 ~ 20	Confidential	none	none
Dyestuff	1 ~ 10	Confidential	none	none
total	100			

SECTION 4: First-aid measures

4.1. Description of first aid measures

IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a doctor if symptoms persist.

IF ON SKIN : Remove / Take off immediately all contaminated clothing. Wash with soap and water. If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.

IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

IF SWALLOWED : After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach, and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient when not conscious. Receive the doctor's treatment (stomach pump) promptly.

Note to Physicians :

All treatments should be based on observed signs and symptoms of distress in the patient.

Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_birchbrown_c] 3/6

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder, foam or carbon dioxide

Unsuitable extinguishing media : Water jet

5.2. Special hazards arising from the substance or mixture

For initial stage extinction, carbon dioxide or dry chemical powder.

When a fire extends, fire is extinguished by a large amount of water spray.

Do not discharge extinguishing waters into the aquatic environment.

5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn.

Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe area. Shut off all sources of ignition.

No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

6.2. Environmental precautions

Do not throw the leakage thing directly into environment

6.3. Methods and material for containment and cleaning up

In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth, etc.), and then wipe off the waste well with waste cloth, and rag.

In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.) and collect into empty container by scoop, suction equipment or the like.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling : Use with adequate ventilation.

Avoid contact with skin, eyes and clothing.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep containers tightly closed and store in a cool and dry place.

areas and containers Keep away from heat and flame, ignition source and sunlight.

Keep out of the reach of children.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ACGIH (2019)

Ethanol STEL 1,000 ppm

1-methoxypropan-2-ol TWA 50 ppm

OSHA PEL

Ethanol TWA 1,000 ppm

Canada Ontario Provincial

Ethanol STEL 1,000 ppm

1-methoxypropan-2-ol TWA 100 ppm

Canada Quebec Provincial

Ethanol TWA 1,000 ppm

1-methoxypropan-2-ol TWA 100 ppm

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_birchbrown_c] 4/6

8.2. Exposure controls**Personal protective equipment**

- Respiratory Protection : Use with local exhaust ventilation, when in long use.
Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.
- Hand Protection : Avoid contact with hands. Wear safety gloves, if necessary.
- Eye Protection : Avoid contact with eyes. Wear safety glasses, if necessary.
- Skin Protection : Avoid skin contact. Wear personal protection apron, boots, if necessary.

Environmental exposure controls

- General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- Appearance : Birchbrown color liquid
- Odor : Minor solvent odour
- pH : Not applicable
- Boiling point : 172.4°F (78°C) ~ 309°F (154°C)
- Flash point : 60.8°F (16°C) (closed cup)
- Relative Density (at 77°F, 25°C) : 0.85 ~ 0.95 (g/cm³)
- Solubility in Water : Insoluble

SECTION 10: Stability and reactivity**10.1. Reactivity**

No dangerous reaction known under conditions of normal use.

10.2. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.3. Chemical stability

The product is stable.

10.4. Conditions to Avoid

High temperature, Direct sunlight, Fire

10.5. Incompatible Materials

No data available

10.6. Hazardous decomposition products

CO, CO₂

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

- Acute toxicity : LD/LC50 values that are relevant for classification
- | | | | |
|-------------------------|------|------------------------|--|
| [Ethanol] | | | |
| Oral-rat | LD50 | >5,000 mg/kg | |
| Inhalation-rat | LC50 | >20 mg/L/4h | |
| [1-methoxypropan-2-ol] | | | |
| Oral-rat | LD50 | >2,000 - <=5,000 mg/kg | |
| Dermal-rabbit | LD50 | >5,000 mg/kg | |
| Inhalation-rat | LC50 | >20 mg/L/4h | |
| [Ethyl lactate] | | | |
| Oral-rat | LD50 | >2,000 mg/kg | |
| Dermal-rabbit | LD50 | >5,000 mg/kg | |
- Serious eye damage : Category 1 Causes serious eye damage
- Specific target organ toxicity : Category 3 May cause drowsiness or dizziness
(single exposure)

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_birchbrown_c] 5/6

Carcinogenicity : This product does not contain any component that is considered a human carcinogen by IARC, ACGIH, EPA, EU or NTP.

SECTION 12: Ecological information

- 12.1. Ecotoxicity : No data available
 12.2. Persistence and degradability : No data available
 12.3. Bioaccumulative potential : No data available
 12.4. Mobility in soil : No data available
 12.5. Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
 Disposal must be made according to official regulations.
 Comply with all Federal, State, and Local regulations regarding disposal.
 Do not allow product to reach ground, any water course or sewage system.

SECTION 14: Transport information

- 14.1. UN number (DOT, ADR, IMDG, IATA) : UN1210
 14.2. UN proper shipping name (DOT, ADR, IMDG, IATA) : PRINTING INK, flammable
 14.3. Transport hazard class(es) (DOT, ADR, IMDG, IATA) :
 · Class 3 (Flammable liquids.)
 · Label 3
 14.4. Packing group (DOT, ADR, IMDG, IATA) : II
 14.5. Environmental hazards Marine pollutant : N
 14.6. Special precautions for user EMS Number : F-E,S-D



☆☆

Artline FURNITURE Marker (EK-95) is not a hazardous material by the special provision.

Artline FURNITURE Marker (EK-95) (The amount of ink : less than 10ml)

UN number : UN3175
 UN proper shipping name : Solids containing Flammable Liquid. n.o.s.
 IATA Special Provision A46
 IMDG Code Special Provision 216
 ADG Special Provision 216

According to IATA Special Provision A46, and IMDG Code Special Provision 216, small inner packagings consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed onto a solid material are not subject to as a hazardous material/dangerous goods provided there is no free liquid in the packet or article.

SECTION 15: Regulatory information

< USA Information >

OSHA STATUS : This product is hazardous under 29 CFR 1910.1200.
 TSCA STATUS : All components on TSCA INVENTORY.
 TSCA Hazard Communication Program (40 CFR Part 721) (SNUR) : Not Applicable
 CERCLA REPORTABLE QUANTITY (40 CFR 117,302) : Not Applicable
 SARA TITLE III Section 313 (40 CFR 372) : Not Applicable
 California Proposition 65 : Not listed

< Canada Information >

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

Canada inventory : All components of this product are listed in the DSL/NDL Inventory.

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_birchbrown_c] 6/6

SECTION 16: Other information, including date of preparation or last revision

Last Revision Date : 09.01. 2020

Preparation Date : 20.05. 2015



EU RoHS (Directive 2011/65/EU)
EU ELV (DIRECTIVE 2000/53/EC)

This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_black_c] 1/6



Safety Data Sheet

According to OSHA 29 CFR 1910.1200 HCS & Canada WHMIS

Artline
Xstamper

Revision Date : 09.01. 2020

SECTION 1: Identification

1.1. Product identifier

Product Name : Artline FURNITURE Marker

EK-95 Color : (Black)



1.2. Recommended use of the chemical and restrictions on use

Recommended use : Permanent marker ink

1.3. Details of the supplier of the safety data sheet

Company Name : Shachihata Inc. (U.S.A.)

Address : 20775 S. Western Ave., Suite 105 Torrance, CA 90501 U.S.A.

Telephone : 1-800-541-9719

Fax : 1-800-541-7166

Contact (e-mail) : customerservice@xstamper.com

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300

(For Hazardous materials or dangerous goods incident, spill, leak, fire, exposure or accident)

SECTION 2: Hazard(s) identification

According to OSHA 29 CFR 1910.1200 HCS & Hazardous Product Regulation (WHMIS 2015)

2.1.1 Classification of the substance or mixture

Flammable liquids, Category 2

H225 : Highly flammable liquid and vapour

Serious eye damage, Category 1

H318 : Causes serious eye damage

Specific target organ toxicity ; single exposure, Category 3
(respiratory tract irritation, narcotic effects)

H335 : May cause respiratory irritation

H336 : May cause drowsiness or dizziness

2.1.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statement : Highly flammable liquid and vapour
Causes serious eye damage
May cause respiratory irritation
May cause drowsiness or dizziness

(H225)

(H318)

(H335)

(H336)

Precautionary statement

【Prevention】

Keep out of reach of children.

(P102)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(P210)

Take precautionary measures against static discharge.

(P243)

Avoid breathing vapours.

(P261)

Use only outdoors or in a well-ventilated area.

(P271)

Wear eye protection.

(P280)

【Response】

In case of fire : Use dry chemical powder, foam or carbon dioxide to extinguish.

(P370+P378)

IF INHALED : Remove person to fresh air and keep comfortable for breathing

(P304+P340)

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_black_c] 2/6

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists : Get medical advice and attention.

(P337+P313)

Immediately call a POISON CENTER or physician.

(P310)

IF ON SKIN (or hair) : Take off immediately all contaminated clothing. Rinse skin with water.

(P303+P361+P353)

If skin irritation occurs : Get medical advice and attention.

(P332+P313)

【Storage】

Store in a well-ventilated place. Keep container tightly closed.

(P403+P233)

【Disposal】


Dispose of contents and container in accordance with local regulations.

(P501)

2.1.3 Other hazards

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS2015).

2.3 Other information**SECTION 3: Composition/information on ingredients**

Substance / Mixture : Mixture

Ingredients :

Chemical Name / Generic name	Composition weight %	CAS Registry No.	Classification (OSHA HCS 2012)	
			Hazard Class	Hazard statement
Ethanol	25 ~ 35	64-17-5	Flam. Liq. 2	H225
1-methoxypropan-2-ol	20 ~ 25	107-98-2	Flam. Liq. 3 STOT. SE. 3	H226 H336
Ethyl lactate	20 ~ 25	97-64-3	Flam. Liq. 3 Eye Dam. 1 STOT. SE. 3	H226 H318 H335
Synthetic resin	5 ~ 15	Confidential	none	none
Dyestuff	10 ~ 20	Confidential	none	none
total	100			

★★ This ink contain chromium compounds,dyestuff (Trivalent chromium, not Hexavalent chromium).

SECTION 4: First-aid measures**4.1. Description of first aid measures**

IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a doctor if symptoms persist.

IF ON SKIN : Remove / Take off immediately all contaminated clothing. Wash with soap and water. If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.

IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

IF SWALLOWED : After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach, and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient when not conscious. Receive the doctor's treatment (stomach pump) promptly.

Note to Physicians :

All treatments should be based on observed signs and symptoms of distress in the patient.

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_black_c] 3/6

Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder, foam or carbon dioxide
 Unsuitable extinguishing media : Water jet

5.2. Special hazards arising from the substance or mixture

For initial stage extinction, carbon dioxide or dry chemical powder.
 When a fire extends, fire is extinguished by a large amount of water spray.
 Do not discharge extinguishing waters into the aquatic environment.

5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn.
 Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe area. Shut off all sources of ignition.
 No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

6.2. Environmental precautions

Do not throw the leakage thing directly into environment

6.3. Methods and material for containment and cleaning up

In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth, etc.), and then wipe off the waste well with waste cloth, and rag.
 In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.) and collect into empty container by scoop, suction equipment or the like.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling : Use with adequate ventilation.
 Avoid contact with skin, eyes and clothing.
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep containers tightly closed and store in a cool and dry place.
 areas and containers : Keep away from heat and flame, ignition source and sunlight.
 Keep out of the reach of children.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ACGIH (2019)

Ethanol	STEL	1,000 ppm
1-methoxypropan-2-ol	TWA	50 ppm

OSHA PEL

Ethanol	TWA	1,000 ppm
---------	-----	-----------

Canada Ontario Provincial

Ethanol	STEL	1,000 ppm
1-methoxypropan-2-ol	TWA	100 ppm

Canada Quebec Provincial

Ethanol	TWA	1,000 ppm
1-methoxypropan-2-ol	TWA	100 ppm

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_black_c] 4/6

8.2. Exposure controls**Personal protective equipment**

- Respiratory Protection : Use with local exhaust ventilation, when in long use.
Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.
- Hand Protection : Avoid contact with hands. Wear safety gloves, if necessary.
- Eye Protection : Avoid contact with eyes. Wear safety glasses, if necessary.
- Skin Protection : Avoid skin contact. Wear personal protection apron, boots, if necessary.

Environmental exposure controls

- General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- Appearance : Black liquid
- Odor : Minor solvent odour
- pH : Not applicable
- Boiling point : 172.4°F (78°C) ~ 309°F (154°C)
- Flash point : 66.2°F (19°C) (closed cup)
- Relative Density (at 77°F, 25°C) : 0.85 ~ 0.95 (g/cm³)
- Solubility in Water : Insoluble

SECTION 10: Stability and reactivity**10.1. Reactivity**

No dangerous reaction known under conditions of normal use.

10.2. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.3. Chemical stability

The product is stable.

10.4. Conditions to Avoid

High temperature, Direct sunlight, Fire

10.5. Incompatible Materials

No data available

10.6. Hazardous decomposition products

CO, CO₂

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

- Acute toxicity : LD/LC50 values that are relevant for classification
- | | | | |
|-------------------------|------|------------------------|--|
| [Ethanol] | | | |
| Oral-rat | LD50 | >5,000 mg/kg | |
| Inhalation-rat | LC50 | >20 mg/L/4h | |
| [1-methoxypropan-2-ol] | | | |
| Oral-rat | LD50 | >2,000 - <=5,000 mg/kg | |
| Dermal-rabbit | LD50 | >5,000 mg/kg | |
| Inhalation-rat | LC50 | >20 mg/L/4h | |
| [Ethyl lactate] | | | |
| Oral-rat | LD50 | >2,000 mg/kg | |
| Dermal-rabbit | LD50 | >5,000 mg/kg | |
- Serious eye damage : Category 1 Causes serious eye damage
- Specific target organ toxicity (single exposure) : Category 3 May cause respiratory irritation
May cause drowsiness or dizziness

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_black_c] 5/6

Carcinogenicity : This product does not contain any component that is considered a human carcinogen by IARC, ACGIH, EPA, EU or NTP.

SECTION 12: Ecological information

- 12.1. Ecotoxicity : No data available
 12.2. Persistence and degradability : No data available
 12.3. Bioaccumulative potential : No data available
 12.4. Mobility in soil : No data available
 12.5. Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
 Disposal must be made according to official regulations.
 Comply with all Federal, State, and Local regulations regarding disposal.
 Do not allow product to reach ground, any water course or sewage system.

SECTION 14: Transport information

- 14.1. UN number (DOT, ADR, IMDG, IATA) : UN1210
 14.2. UN proper shipping name (DOT, ADR, IMDG, IATA) : PRINTING INK, flammable
 14.3. Transport hazard class(es) (DOT, ADR, IMDG, IATA) :
 · Class 3 (Flammable liquids.)
 · Label 3
 14.4. Packing group (DOT, ADR, IMDG, IATA) : II
 14.5. Environmental hazards Marine pollutant : N
 14.6. Special precautions for user EMS Number : F-E,S-D



☆☆

Artline FURNITURE Marker (EK-95) is not a hazardous material by the special provision.

Artline FURNITURE Marker (EK-95) (The amount of ink : less than 10ml)

UN number : UN3175
 UN proper shipping name : Solids containing Flammable Liquid. n.o.s.
 IATA Special Provision A46
 IMDG Code Special Provision 216
 ADG Special Provision 216

According to IATA Special Provision A46, and IMDG Code Special Provision 216, small inner packagings consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed onto a solid material are not subject to as a hazardous material/dangerous goods provided there is no free liquid in the packet or article.

SECTION 15: Regulatory information

< USA Information >

OSHA STATUS : This product is hazardous under 29 CFR 1910.1200.
 TSCA STATUS : All components on TSCA INVENTORY.
 TSCA Hazard Communication Program (40 CFR Part 721) (SNUR) : Not Applicable
 CERCLA REPORTABLE QUANTITY (40 CFR 117,302) : Not Applicable
 SARA TITLE III Section 313 (40 CFR 372) : Not Applicable
 California Proposition 65 : Not listed

< Canada Information >

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

Canada inventory : All components of this product are listed in the DSL/NDL Inventory.

[ANSI Z400.1/Z129.1-2010][Shachihata Inc.] [EK-95_black_c] 6/6

SECTION 16: Other information, including date of preparation or last revision

Last Revision Date : 09.01. 2020

Preparation Date : 20.05. 2015

EU RoHS (Directive 2011/65/EU)
EU ELV (DIRECTIVE 2000/53/EC)

This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.