



23718-XXXX

Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive**SDS ID: SDS-25**

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Elmer's Extra-Strength Spray Adhesive

Synonyms

E456, 60456

Chemical Family

Adhesive.

Product Use

Adhesive.

Restrictions on Use

None known.

Details of the supplier of the safety data sheet

Newell Office Brands

Product of Newell Office Brands, Inc.

6655 Peachtree Dunwoody Rd. NE

Atlanta, GA 30328

www.elmers.com

Phone: 1.888.435.6377

Emergency Phone #: 1.888.516.2502

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Aerosols - Category 1

Gases Under Pressure - Compressed gas

Aspiration Hazard - Category 1

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2A

Specific Target Organ Toxicity - Single Exposure - Category 3

Hazardous to the Aquatic Environment - Acute - Category 2

Hazardous to the Aquatic Environment - Chronic - Category 2

GHS Label Elements**Symbol(s)****Signal Word**

Danger

Hazard Statement(s)

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways.

Causes skin irritation.



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive

SDS ID: SDS-25

Causes serious eye irritation.
May cause respiratory irritation. May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

Precautionary Statement(s)

Prevention

Keep away from heat/sparks/open flame/hot surfaces - No smoking.
Pressurized container: Do not pierce or burn, even after use.
Do not spray on an open flame or other ignition sources.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash thoroughly after handling.
Avoid release to the environment.

Response

Collect spillage.
IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists, get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash before reuse.
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
Do NOT induce vomiting.
Call a POISON CENTER or doctor if you feel unwell.
Specific treatment (see label).

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Statement(s) of Unknown Aquatic Toxicity

0% of the mixture consists of ingredient(s) of unknown acute aquatic toxicity.
0% of the mixture consists of ingredient(s) of unknown chronic aquatic toxicity.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
107-83-5	2-Methylpentane	20 - 40
96-14-0	3-Methylpentane	10 - 20
67-64-1	Acetone	10 - 20
75-37-6	1,1-Difluoroethane	2.5 - 10
75-83-2	Neohexane	2.5 - 10



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive

SDS ID: SDS-25

79-29-8	2,3-Dimethylbutane	2.5 - 10
106-97-8	Butane	2.5 - 10
115-10-6	Dimethyl ether	2.5 - 10
74-98-6	Propane	2.5 - 10
8050-26-8	Resin acids and Rosin acids, esters with pentaerythritol	2.5 - 10
No CAS Number	Other components below reportable levels	2.5 - 10

Section 4 - FIRST AID MEASURES

Description of Necessary Measures

Call a POISON CENTER or doctor/physician if you feel unwell.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Skin

Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

Ingestion

Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Aspiration into the lungs may result in pulmonary edema and pneumonitis.

Most Important Symptoms/Effects

Acute

May cause respiratory irritation, skin irritation, eye irritation. May cause drowsiness or dizziness.

Delayed

No information on significant adverse effects.

Note to Physicians

Mineral oil, vegetable oil, or petroleum jelly may help soften the bonding between skin surfaces.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

regular dry powder. alcohol resistant foam. water. carbon dioxide.

Unsuitable Extinguishing Media

None known.

Special Hazards Arising from the Chemical

Pressurized container: May burst if heated, releasing flammable gases.

Advice for firefighters



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive

SDS ID: SDS-25

Wear self-contained breathing apparatus with a full facepiece and protective clothing.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. In case of fire and/or explosion do not breathe fumes. Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Keep unnecessary people away, isolate hazard area and deny entry. Wear personal protective clothing and equipment, see Section 8. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and Materials for Containment and Cleaning Up

Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Ventilate closed spaces before entering. Eliminate all ignition sources if safe to do so. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Move containers away from spill to a safe area. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewers, basements, or confined areas.

Environmental Precautions

Avoid release to the environment. Avoid discharge into drains, surface water or groundwater. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Pressurized container: Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material. Do not eat, drink or smoke when using this product. Do not cut, puncture, or weld on or near this container. Ground any equipment used in handling. Do not reuse containers. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes and skin. Avoid prolonged exposure. Use only in well-ventilated areas. Do not empty into drains. Keep out of the reach of children.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Do not puncture container. Keep away from heat and ignition sources. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. This material can accumulate static charge by flow or agitation and can be ignited by static discharge. Keep away from incompatible materials. Keep out of reach of children.

Incompatible Materials

oxidizing agents.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

2-Methylpentane	107-83-5
ACGIH:	500 ppm TWA
	1000 ppm STEL



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive

SDS ID: SDS-25

NIOSH:	100 ppm TWA ; 350 mg/m3 TWA (related to Isohexane)
	510 ppm Ceiling 15 min ; 1800 mg/m3 Ceiling 15 min (related to Isohexane)
Mexico:	500 ppm TWA VLE-PPT (except n-Hexane) ; 1760 mg/m3 TWA VLE-PPT (except n-Hexane) (related to Hexane, branched and linear)
	1000 ppm STEL [PPT-CT] (except n-Hexane) ; 3500 mg/m3 STEL [PPT-CT] (except n-Hexane) (related to Hexane, branched and linear)
3-Methylpentane	96-14-0
ACGIH:	500 ppm TWA
	1000 ppm STEL
NIOSH:	100 ppm TWA ; 350 mg/m3 TWA (related to Isohexane)
	510 ppm Ceiling 15 min ; 1800 mg/m3 Ceiling 15 min (related to Isohexane)
Mexico:	500 ppm TWA VLE-PPT (except n-Hexane) ; 1760 mg/m3 TWA VLE-PPT (except n-Hexane) (related to Hexane, branched and linear)
	1000 ppm STEL [PPT-CT] (except n-Hexane) ; 3500 mg/m3 STEL [PPT-CT] (except n-Hexane) (related to Hexane, branched and linear)
Acetone	67-64-1
ACGIH:	250 ppm TWA
	500 ppm STEL
NIOSH:	250 ppm TWA ; 590 mg/m3 TWA
	2500 ppm IDLH (10% LEL)
Europe:	500 ppm TWA ; 1210 mg/m3 TWA
OSHA (US):	1000 ppm TWA ; 2400 mg/m3 TWA
Mexico:	1000 ppm TWA VLE-PPT ; 2400 mg/m3 TWA VLE-PPT
	1260 ppm STEL [PPT-CT] ; 3000 mg/m3 STEL [PPT-CT]
Neohexane	75-83-2
ACGIH:	500 ppm TWA
	1000 ppm STEL
NIOSH:	100 ppm TWA ; 350 mg/m3 TWA (related to Isohexane)
	510 ppm Ceiling 15 min ; 1800 mg/m3 Ceiling 15 min (related to Isohexane)



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive
SDS ID: SDS-25

Mexico:	500 ppm TWA VLE-PPT (except n-Hexane); 1760 mg/m3 TWA VLE-PPT (except n-Hexane) (related to Hexane, branched and linear)
	1000 ppm STEL [PPT-CT] (except n-Hexane); 3500 mg/m3 STEL [PPT-CT] (except n-Hexane) (related to Hexane, branched and linear)
2,3-Dimethylbutane	79-29-8
ACGIH:	500 ppm TWA
	1000 ppm STEL
NIOSH:	100 ppm TWA ; 350 mg/m3 TWA (related to Isohexane)
	510 ppm Ceiling 15 min ; 1800 mg/m3 Ceiling 15 min (related to Isohexane)
Mexico:	500 ppm TWA VLE-PPT (except n-Hexane); 1760 mg/m3 TWA VLE-PPT (except n-Hexane) (related to Hexane, branched and linear)
	1000 ppm STEL [PPT-CT] (except n-Hexane); 3500 mg/m3 STEL [PPT-CT] (except n-Hexane) (related to Hexane, branched and linear)
Butane	106-97-8
ACGIH:	1000 ppm STEL (explosion hazard)
NIOSH:	800 ppm TWA ; 1900 mg/m3 TWA
	1600 ppm IDLH (>10% LEL)
Mexico:	800 ppm TWA VLE-PPT ; 1900 mg/m3 TWA VLE-PPT
Dimethyl ether	115-10-6
Europe:	1000 ppm TWA ; 1920 mg/m3 TWA
Propane	74-98-6
ACGIH:	(See Appendix F: Minimal Oxygen Content, explosion hazard)
NIOSH:	1000 ppm TWA ; 1800 mg/m3 TWA
	2100 ppm IDLH (10% LEL)
OSHA (US):	1000 ppm TWA ; 1800 mg/m3 TWA

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)
Acetone (67-64-1)

25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

Engineering Controls

Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive

SDS ID: SDS-25

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear eye/face protection. Wear safety glasses with side shields. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate chemical resistant clothing.

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear protective gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Not available	Physical State	liquid
Odor	Not available	Color	Not available
Odor Threshold	Not available	pH	Not available
Melting Point	Not available	Boiling Point	Not available
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Not available	Flammability (solid, gas)	Not available
Autoignition Temperature	743 °F (395 °C estimated)	Flash Point	-156 °F (propane)
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	42 psig (propane)
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	0.714 (estimated)
Water Solubility	Not available	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	0.714 g/cm3
Physical Form	Aerosol	VOC	63.6 %
Volatility	80.5 % (estimated)	Molecular Weight	Not available
Heat of Combustion	42.03 kJ/g (estimated)		

Section 10 - STABILITY AND REACTIVITY

Reactivity



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive

SDS ID: SDS-25

No hazard expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid friction and static electricity.

Incompatible Materials

oxidizing agents.

Hazardous decomposition products

oxides of carbon, hydrocarbons.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May be fatal if swallowed and enters airways. Prolonged exposure can cause nausea, dizziness, headache, and narcotic effects. May cause respiratory irritation. May cause a narcotic effect.

Skin Contact

Causes skin irritation.

Eye Contact

Causes serious eye irritation.

Ingestion

May be fatal if swallowed and enters airways.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

2-Methylpentane (107-83-5)

Oral LD50 Rat 15000 mg/kg (related to Hexane, branched and linear)

3-Methylpentane (96-14-0)

Oral LD50 Rat 15000 mg/kg (related to Hexane, branched and linear)

Acetone (67-64-1)

Oral LD50 Rat 5800 mg/kg

Dermal LD50 Rabbit >15700 mg/kg

Inhalation LC50 Rat 50100 mg/m³ 8 h

Neohexane (75-83-2)

Oral LD50 Rat 15000 mg/kg (related to Hexane, branched and linear)

2,3-Dimethylbutane (79-29-8)

Oral LD50 Rat 15000 mg/kg (related to Hexane, branched and linear)

Butane (106-97-8)

Inhalation LC50 Rat 658 g/m³ 4 h

Dimethyl ether (115-10-6)

Inhalation LC50 Rat 164000 ppm 4 h

Propane (74-98-6)

Inhalation LC50 Rat 658 mg/L 4 h



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive

SDS ID: SDS-25

Resin acids and Rosin acids, esters with pentaerythritol (8050-26-8)

Oral LD50 Rat >2000 mg/kg (in corn oil ;no deaths occurred)

Product Toxicity Data

Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Inhalation - Vapor	> 20 mg/L
Oral	> 2000 mg/kg

Immediate Effects

May cause eye irritation, respiratory tract irritation, skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

Causes skin irritation, eye irritation, respiratory tract irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

Acetone	67-64-1
ACGIH:	A4 - Not Classifiable as a Human Carcinogen

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No data available

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

respiratory tract irritation.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

May be fatal if swallowed and enters airways.

Medical Conditions Aggravated by Exposure

No data available.



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive
SDS ID: SDS-25

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

Acetone	67-64-1
Fish:	LC50 96 h Oncorhynchus mykiss 4.74 - 6.33 mL/L; LC50 96 h Pimephales promelas 6210 - 8120 mg/L [static]; LC50 96 h Lepomis macrochirus 8300 mg/L
Invertebrate:	EC50 48 h Daphnia magna 10294 - 17704 mg/L [Static] EPA ; EC50 48 h Daphnia magna 12600 - 12700 mg/L IUCLID

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations. Do not puncture container.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14 - TRANSPORT INFORMATION

Component Marine Pollutants (IMDG)

This material contains one or more of the following chemicals required by IMDG to be identified as marine pollutants

3-Methylpentane	96-14-0
	IMDG regulated marine pollutant (UN1208) (related to Hexane, branched and linear)
Neohexane	75-83-2
	IMDG regulated marine pollutant (UN1208) (related to Hexane, branched and linear)
2,3-Dimethylbutane	79-29-8
	IMDG regulated marine pollutant (UN1208) (related to Hexane, branched and linear)

US DOT Information:

Shipping Name: AEROSOLS

Hazard Class: 2.1

UN/NA #: UN1950

Required Label(s): 2.1

Marine pollutant

Additional information: This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently. (Special provisions: N82; Packaging exceptions: 306.)

IATA Information:

Shipping Name: AEROSOLS, FLAMMABLE

Hazard Class: 2.1

UN#: UN1950



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive

SDS ID: SDS-25

Required Label(s): 2.1

Marine pollutant

Additional information: Special precautions for user: Read safety instructions, SDS and emergency procedures before handling. Packaging Exceptions: LTD QTY (Passenger and cargo aircraft: Allowed with restrictions; Cargo aircraft only: Allowed with restrictions.)

IMDG Information:

Shipping Name: AEROSOLS

Hazard Class: 2.1

UN#: UN1950

Required Label(s): 2.1

Marine pollutant

Additional information: Special precautions for user: Read safety instructions, SDS and emergency procedures before handling. Packaging Exceptions: LTD QTY (Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable.)

International Bulk Chemical Code

This material contains one or more of the following chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

2-Methylpentane	107-83-5
IBC Code:	Category Y (related to Hexane, branched and linear)
3-Methylpentane	96-14-0
IBC Code:	Category Y (related to Hexane, branched and linear)
Neohexane	75-83-2
IBC Code:	Category Y (related to Hexane, branched and linear)
2,3-Dimethylbutane	79-29-8
IBC Code:	Category Y (related to Hexane, branched and linear)

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Acetone	67-64-1
CERCLA:	5000 lb final RQ ; 2270 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C) 2016 reporting categories

Acute Health: Yes **Chronic Health:** No **Fire:** Yes **Pressure:** Yes **Reactivity:** No

SARA Section 311/312 (40 CFR 370 Subparts B and C) 2017 reporting categories

Flammable; Gas Under Pressure; Skin Corrosion/Irritation; Serious Eye Damage/Eye Irritation; Specific Target Organ Toxicity; Aspiration Hazard

U.S. State Regulations



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive

SDS ID: SDS-25

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
2-Methylpentane	107-83-5	Yes	Yes	Yes	Yes	Yes
3-Methylpentane	96-14-0	Yes	Yes	Yes	No	Yes
Acetone	67-64-1	Yes	Yes	Yes	Yes	Yes
1,1-Difluoroethane	75-37-6	No	Yes	No	Yes	No
Neohexane	75-83-2	Yes	Yes	Yes	Yes	Yes
2,3-Dimethylbutane	79-29-8	Yes	Yes	Yes	Yes	Yes
Butane	106-97-8	Yes	Yes	Yes	Yes	Yes
Dimethyl ether	115-10-6	No	Yes	Yes	Yes	Yes
Propane	74-98-6	No	Yes	Yes	Yes	Yes

Not listed under California Proposition 65

Canada Regulations

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

2-Methylpentane	107-83-5
	1 %
3-Methylpentane	96-14-0
	1 % (related to Hexane, branched and linear)
Acetone	67-64-1
	1 %
Neohexane	75-83-2
	1 %
2,3-Dimethylbutane	79-29-8
	1 %
Butane	106-97-8
	1 %



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive
SDS ID: SDS-25
Component Analysis - Inventory
2-Methylpentane (107-83-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

3-Methylpentane (96-14-0)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Acetone (67-64-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

1,1-Difluoroethane (75-37-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Neohexane (75-83-2)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

2,3-Dimethylbutane (79-29-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Butane (106-97-8)



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive
SDS ID: SDS-25

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Dimethyl ether (115-10-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Propane (74-98-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Resin acids and Rosin acids, esters with pentaerythritol (8050-26-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Other components below reportable levels ()

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
No	No	No	No	No	No	No	No	No	No	No	No	No	No

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 2 Fire: 4 Reactivity: 1

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

Summary of Changes

Updated SDS: 1/24/2017

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act;



Safety Data Sheet

Material Name: Elmer's Extra-Strength Spray Adhesive

SDS ID: SDS-25

CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL) , KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; NDSL - Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH - Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

Supplier gives no warranty whatsoever, including the warranties of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser shall determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental, consequential or any other damages arising out of the use or misuse of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights.