



Laguna Clay Co.

30402-1356

## Safety Data Sheet (SDS)

GHS - United States

### Section 1 - Identification

<b>Product Name</b>	<b>GEMD1002 EMD-1002 ALABASTER WHITE GLAZE</b>
<b>Common Names</b>	Glaze, Ceramic Glaze, Pottery Glaze, Dry glaze
<b>Company / Manufacturer</b>	Laguna Clay Co. 14400 Lomitas Ave. City of Industry, CA 91746 (626) 330-0631 fax (626) 333-7694
<b>Emergency Number</b>	911
<b>Product Use</b>	Non-exhaustive list: pottery manufacturing, glazing ceramic ware
<b>Restrictions on Use</b>	None applicable

### Section 2 - Hazardous Identification

**Contains Crystalline Silica  $\geq$ 1% Respirable**

**GHS label elements /  
Hazard pictograms**



**Signal Word:  
Danger**

**OSHA/HCS status**

Glaze mixture in dry form is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

**Classification of the  
substance or  
mixture**

Carcinogenicity (inhalation) - Category 1A and Specific organ toxicity (Repeated Exposure) (Respiratory tract through inhalation) - Category 1

**Hazard Statement**

(H350) Cancer Hazard. Contains quartz (crystalline silica) which may cause cancer. Risk of cancer depends upon duration and level of exposure to the dust. Not an acute hazard.  
(H332) Prolonged inhalation of dust may cause lung injury. Inhalation of high concentrations of dust may cause mechanical irritation and discomfort of the respiratory tract. Repeated exposure may have chronic effects.  
(H316 + H320 + H335) Can cause skin, respiratory, and eye irritation.

**Precautionary  
Statements**

(P261) Avoid breathing dust.  
(P280) Wear protective gloves, eye, and respiratory protection.

EMD-1002 ALABASTER WHITE GLAZE

info@lagunaclay.com (800) 452-4862

January 10, 2020  
Item Numbers: 30402-1356

En (English)

Page 1 of 7  
Page 1 of 7

Laguna Clay Co.

EMD-1002 ALABASTER WHITE GLAZE

GEMD1002

Safety Data Sheet (SDS)

GHS - United States

### Section 3 - Composition / Information on Ingredients

#### Substances/Mixtures

Mixture - A trade secret claim is made for this item.

Component	CAS #	Approx % by Wt.
FRIT	65997-18-4	>65%
Zirconium silicate	14940-68-2	5-10%
kaolin	1332-58-7	5-10%
Crystalline silica - quartz	14808-60-7	<5%
Barium Carbonate	513-77-9	<5%
Bentonite	1302-78-9	<2%
Barium Sulfate	7727-43-7	<2%
Strontium Carbonate	1633-05-2	<2%

### Section 4 - First Aid Measures

#### First-Aid Measures

<b>Eye Contact</b>	If eye contact occurs, rinse immediately with plenty of water. If irritation persists, seek medical attention.
<b>Skin Contact</b>	If irritation occurs, wash thoroughly with water. If it persists, seek medical attention.
<b>Inhalation</b>	Move victim to fresh air in well ventilated area. If coughing or irritation persists, seek medical attention.
<b>Ingestion</b>	Consult physician and/or obtain competent medical assistance.

#### Symptoms and Effects, both Acute and Delayed

<b>Eye Contact</b>	Prolonged contact with large amounts of dust may cause mechanical irritation.
<b>Skin Contact</b>	Prolonged contact with large amounts of dust may cause mechanical irritation.
<b>Inhalation</b>	Inhalation of high concentrations of dry glaze dust may cause mechanical irritation and discomfort. Long term exposure may cause chronic effects (see section 11).
<b>Ingestion</b>	Large quantities ingested may cause gastrointestinal irritation.
<b>Chronic Symptoms</b>	Repeated or prolonged exposure to respirable crystalline silica dust may cause lung damage in the form of silicosis. Symptoms will include shortness of breath, fever fatigue, loss of appetite, chest pain, dry non-productive cough.

EMD-1002 ALABASTER WHITE GLAZE

info@lagunaclay.com (800) 452-4862

January 10, 2020  
Item Numbers: 30402-1356

En (English)

Page 2 of 7  
Page 2 of 7

**Laguna Clay Co.**

Safety Data Sheet (SDS)

**EMD-1002 ALABASTER WHITE GLAZE****GEMD1002**

GHS - United States

**Section 5 - Fire Fighting Measures**

<b>General Fire Hazards</b>	Glaze mixture in dry or moist form is not flammable and does not support fire. The paper bags or plastic bags and cardboard boxes containing the mixture are flammable.
<b>Extinguishing Media</b>	Use appropriate extinguishing media for surrounding fire.
<b>Chemical hazards from fire</b>	Glaze mixture does not contain hazardous decomposition products.
<b>Protective actions and equipment for fire-fighters</b>	Glaze mixture and packaging can become slippery when wet. Fire-fighters should wear appropriate protective equipment.

**Section 6 - Accidental Release Measures**

<b>Clean-up Methods</b>	If appropriate, use gentle water spray to wet down and minimize dust generation.
<b>Personal Precautions and Personal Protective Equipment</b>	Wear appropriate protective equipment and clothing during clean-up. When dry sweeping use NIOSH approved respirators when dust levels exceed exposure limits.
<b>Environmental Precautions</b>	Please read Section 2 completely. If any environmental warnings such as; H411 or H412 are listed in Section 2, please use appropriate procedures when disposing of product and container. Do not put materials into waterways or stormdrains.
<b>Emergency procedures &amp; Methods of Containment</b>	There are no emergency procedures required for this mixture. Place dry glaze dust in a sealed container for re-use or proper disposal.

**Section 7 - Handling & Storage**

<b>Precautions for safe handling</b>	Read label before use. Do not eat, drink or smoke when using this product. Protect dry material from moisture until use. Do not allow liquid glaze to freeze. Use proper lifting techniques to avoid physical injury.
<b>Recommendations on the conditions for safe storage</b>	No special storage considerations. Do not store liquid glaze mixture below freezing point (< 0 °C or < 32°F).

**EMD-1002 ALABASTER WHITE GLAZE**

info@lagunaclay.com (800) 452-4862

January 10, 2020  
Item Numbers: 30402-1356

En (English)

Page 3 of 7  
Page 3 of 7

**Laguna Clay Co.**

Safety Data Sheet (SDS)

**EMD-1002 ALABASTER WHITE GLAZE****GEMD1002**

GHS - United States

**Section 8 - Exposure Counts / Personal Protection****Airborne Exposure Limits**

Hazardous Ingredient	Wt. % Approx.	CAS#	OSHA PEL* / ACGIH TLV*
FRIT	>65%	65997-18-4	/ 10mg/m3 STEL Zr
Zirconium Silicate	5-10%	14940-68-2	5mg/m3 / 5mg/m3
Kaolin	5-10%	1332-58-7	5mg/m3 / 2mg/m3 respirable
Crystalline Silica - quartz	<5%	14808-60-7	0.1mg/m3 / 0.025mg/m3 respirable
Barium Carbonate	<5%	513-77-9	0.5mg/m3 / 0.5mg/m3 respirable
Bentonite	<2%	1302-78-9	5mg/m3 / 3mg/m3 respirable
Barium Sulfate	<2%	7727-43-7	10PPM(STEL) / 10mg/m3 total dust
Strontium Carbonate	<2%	1633-05-2	none established

**Engineering Measures**

Glaze mixture in moist form poses no inhalation health risk. Once glaze mixture has dried, there may be dust generated by cleaning and working processes. In the event that dust is generated, use local exhaust ventilation or other engineering controls as required to maintain exposures below applicable occupational exposure limits (TLV).

**Personal Protective Equipment (PPE)**

**Respiratory** Dust is generated when working with dry glaze mixture. To minimize exposure to dust and/or crystalline silica, cutting or sanding dry glaze products should be conducted with sufficient ventilation. Respirable dust and quartz levels should be monitored regularly. Dust and quartz levels in excess of appropriate exposure limits should be reduced by feasible engineering controls, including (but not limited to) wet sanding, wet suppression, ventilation, and process enclosure. When such controls are not feasible, NIOSH/MSHA approved respirators must be worn in accordance with a respiratory protection program which meets OSHA requirements as set forth at 29 CFR 1910.134 and ANSI Z88.2-1080 "Practices for Respiratory Protection". In most cases, a disposable N-95 Particulate Respirator is sufficient.

**Eyes** Use of NIOSH/OSHA approved safety glasses with side shields is recommended. Face shields should also be used in excessively dusty conditions. Wear tight fitting dust goggles when excessively (visible) dusty conditions are present or are anticipated. NIOSH recommends that contact lenses not be worn when working with crystalline silica dust.

**Skin and Body** Protective Clothing is not essential. Use gloves and/or protective clothing if abrasion or allergic reactions are experienced.

**Section 9 - Physical & Chemical Properties**

<b>Appearance</b>	Lump/dry powder or colored liquid	<b>Evaporation Rate</b>	No data available
<b>Color</b>	Various colors	<b>Solubility in water at 100 C</b>	None
<b>Physical state</b>	Solid	<b>Decomposition temperature</b>	Not Applicable
<b>pH</b>	6 - 8	<b>Viscosity</b>	Not Applicable
<b>Odor</b>	Earthy odor	<b>Flashpoint</b>	Not Applicable
<b>Odor threshold</b>	Not Applicable	<b>Boiling Point</b>	Not Applicable
<b>Melting Point</b>	> 1200 °C (>2150°F)	<b>Flammability</b>	Not Applicable
<b>Freezing Point</b>	< 0 °C (<32°F)	<b>Vapor Pressure (mm HG)</b>	Not Applicable
<b>Relative density/Specific</b>		<b>Vapor Density</b>	Not Applicable
		<b>Partition coefficient</b>	Not Applicable

**Laguna Clay Co.**

Safety Data Sheet (SDS)

**EMD-1002 ALABASTER WHITE GLAZE****GEMD1002**

GHS - United States

**Section 10 - Stability & Reactivity**

<b>Reactivity</b>	No dangerous reactions are known under normal conditions of use
<b>Chemical Stability</b>	Stable at standard temperature and pressure. No stabilizers required to maintain chemical stability.
<b>Possibility of Hazardous Reactions and Conditions to Avoid</b>	None known
<b>Incompatibility / Hazardous decomposition products</b>	None known

**Section 11 - Toxicological Information**

**Primary Route of Exposure:** Skin, Eye Contact, Inhalation and Ingestion

**Specific Organ Toxicity - Single Exposure**

Target organs include ears, skin, respiratory system, and gastrointestinal tract.

**Specific Organ Toxicity - Repeated Exposure**

Causes damage to eyes, skin, respiratory system, and gastrointestinal tract through prolonged or repeated exposure.

**Acute Short-Term Exposure Effects**

May cause eye irritation, skin irritation, respiratory tract irritation, and gastrointestinal tract irritation. Inhalation of high concentrations of dry glaze dust may cause mechanical irritation and discomfort. Long term exposure may cause chronic effects.

**Chronic Long Term Exposure Effects**

Silica has been classified by OSHA as a human lung carcinogen. Repeated or prolonged exposure of respirable crystalline silica dust may cause lung damage in the form of silicosis.

Effects of silicosis include bronchitis/chronic obstructive pulmonary disorder, increased susceptibility to tuberculosis, scleroderma (a disease affecting skin, blood vessels, joints and skeletal muscles), and possible renal disease. Acute silicosis can be fatal.

**Related Symptoms**

Symptoms will include shortness of breath, fever, fatigue, loss of appetite, chest pain, dry non-productive cough.

**Medical Conditions Aggravated by Exposure:**

Individuals with pre-existing allergies, eye disorders, skin disorders, respiratory disorders and/or gastrointestinal

## OSHA, IARC, and NTP Carcinogen Classifications

Chemicals with Carcinogen Potential	CAS #	OSHA	IARC	NTP
Crystalline silica - quartz	14808-60-7	YES	YES - 1	YES

IARC - International Agency for Research on Cancer  
 1 = Carcinogenic to humans  
 2A = Probably carcinogenic to humans  
 2B = Possibly carcinogenic to humans

OSHA - Occupational Safety & Health Administration  
 NTP - National Toxicology Program

Laguna Clay Co.

EMD-1002 ALABASTER WHITE GLAZE

GEMD1002

Safety Data Sheet (SDS)

GHS - United States

## Section 12 - Ecological Information (non-mandatory)

<b>Ecotoxicity</b>	None Known
<b>Biochemical oxygen demand (BOD5)</b>	None Known
<b>Chemical oxygen demand (COD)</b>	None Known
<b>Products of Biodegradation</b>	None Known
<b>Toxicity of the products of Biodegradation</b>	None Known
<b>Bioaccumulation Potential</b>	None Known
<b>Potential to move from soil to groundwater</b>	None Known
<b>Other adverse effects</b>	None Known

## Section 13 - Disposal Configurations (non-mandatory)

<b>Personal Protection</b>	Refer to section 8 for proper PPE when disposing of waste material.
<b>Appropriate disposal containers</b>	Standard waste disposal containers - no special requirements.
<b>Appropriate disposal methods</b>	Disposal of this product should comply with the requirements of environmental protection and waste disposal legislation and any regional or local authority requirements.
<b>Physical and chemical properties that may affect disposal</b>	Glaze dust or waste should be placed in a sealed container or in a manner that reduces or eliminates the release of the product.
<b>Sewage disposal</b>	Do not dispose of into sinks or toilets. Never dispose of this product into a sewer system.
<b>Special precautions for landfills or incineration activities</b>	There are no special precautions for disposal in a landfill. This product is non-combustible and is not suitable for incineration.

## Section 14 - Transportation Information (non-mandatory)

Regulatory Information	UN Number	UN Proper Shipping Name	Transport Hazard Class	Packing Group Number	Bulk Transport Guidance	Special Precautions
<b>DOT Classification</b>	Not regulated	—	—	—	—	—
<b>TDG Classification</b>	Not regulated	—	—	—	—	—
<b>ADR/RID Class</b>	Not regulated	—	—	—	—	—
<b>IMDG Class</b>	Not regulated	—	—	—	—	—
<b>IATA-DGR Class</b>	Not regulated	—	—	—	—	—

EMD-1002 ALABASTER WHITE GLAZE

info@lagunaclay.com (800) 452-4862

January 10, 2020  
Item Numbers: 30402-1356

En (English)

Page 6 of 7  
Page 6 of 7

Laguna Clay Co.

**EMD-1002 ALABASTER WHITE GLAZE****GEMD1002**

Safety Data Sheet (SDS)

GHS - United States

**Section 15 - Regulatory Information (non-mandatory)****TSCA - Toxic Substances Control Act - EPA**

Quartz and other chemicals are listed in the TSCA Chemical Substance Inventory.

**California Prop. 65 WARNING**

This product contains a chemical known to the State of California to cause cancer. (Prop. 65 - California Health and Safety Code Section 2549 Et Seq).

**SARA/Title III (Emergency Planning & Community Right-to-Know Act)**

This mixture contains no substances at or above the reporting threshold under section 313, based on available data.

**Section 16 - Other Information (non-mandatory)****Definitions**

<b>ACGIH</b>	American Conference of Governmental Industrial Hygienists
<b>CAS</b>	Chemical Abstract Service
<b>CAL-OSHA</b>	California Occupational Safety & Health Administration
<b>IARC</b>	International Agency for Research on Cancer
<b>OSHA</b>	Occupational Safety & Health Administration
<b>MSHA</b>	Mine Safety and Health Administration
<b>NIOSH</b>	National Institute of Occupational Safety and Health
<b>NTP</b>	National Toxicology Program
<b>HCS</b>	Hazardous communication standard
<b>OSHA PEL</b>	OSHA permissible exposure limit
<b>STEL</b>	Short-term exposure limit
<b>TLV</b>	Threshold limit value

Three types of TLVs for chemical substances as defined by the **ACGIH** are:

<b>TLV-TWA</b>	Time weighted average - average exposure on the basis of an 8h/day, 40h/week work schedule.
<b>TLV-STEL</b>	Short-term exposure limit - spot exposure for a duration of 15 minutes, that cannot be repeated more than 4 times per day, with at least 60 minutes between exposure periods.
<b>TLV-C</b>	Ceiling limit - absolute exposure limit that should not be exceeded at any time.

This SDS is in compliance with The Globally Harmonized System of Classification and Labeling of Chemicals (GHS), and is subject to revision at any time without notice. Its current revision date is : 1/10/2020

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must

**EMD-1002 ALABASTER WHITE GLAZE****info@lagunaclay.com (800) 452-4862**January 10, 2020  
Item Numbers: 30402-1356

En (English)

Page 7 of 7  
Page 7 of 7