33213-2504



STANDARD CERAMIC SUPPLY COMPANY
P.O. Box 16240
Pittsburgh, PA 15242-0240

### **SAFETY DATA SHEET**

### **Section 1: IDENTIFICATION**

Name, address, telephone number and emergency telephone number of the manufacturer:

Standard Ceramic Supply Company
24 Chestnut Street / P.O. Box 16240
Carnegie, PA 15106-2028
Telephone / Emergency Telephone Number: 412-276-6333

Product Identifier used on the label: Standard Moist and Dry Clays 910 White, 910 Gray, and 910 Red

Recommended use of product: Ceramic ware

### **Section 2: HAZARDS IDENTIFICATION**



**GHS label elements / Hazard Pictograms** 

Clay mixture in dry form is considered hazardous by OSHA Hazard

Signal Word: Danger

Communication Standard (29 CFR 1910.1200)

Classification of the substance

Carcinogenicity (inhalation) – Category 1A and Specific organ toxicity (Repeated Exposure) (Respiratory tract through

inhalation) – Category 1

**Hazard Statement(s):** 

OSHA/HCS status

(H350) Cancer Hazard. Contains silica dust which can cause cancer. Risk of cancer depends upon duration and level of

exposure to the dust. Not an acute hazard.

(H332) Prolonged inhalation of dust may cause mechanical irritation and discomfort of respiratory tract. Repeated exposure

may have chronic effects.

(H316 + H320 + H335) Can cause skin, respiratory and eye

irritation.

Precautionary statement(s):

Not harmful in moist form. (Avoid breathing in dust)

Wear gloves, eye and respiratory protection when working with

dust form.



## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CAS NUMBER	% OF FORMULA
Kaolin/Clay	1332-58-7	0% - 65%
Acacia Gum	9000-01-05	Confidential
Borax	1303-96-4	Confidential

## **Section 4: FIRST-AID MEASURES**

### **DESCRIPTION OF FIRST-AID MEASURES**

Ingestion: Contact a physician immediately.

Inhalation: May cause irritation; remove from exposure.

Skin Contact: May cause irritation; rinse skin with soap and water.

Eye Contact: May cause irritation; flush eyes with water for at least 15 minutes. If irritation

continues afterwards, contact a physician.

### **Section 5: FIRE-FIGHTING MEASURES**

### **EXTINGUISHING MEDIA**

Suitable extinguishing media: None

# SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS

Protective equipment for firefighters: None

Special firefighting procedures: None

# Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and/or Emergency Procedures: None

**Environmental Precautions: None** 

Methods and Materials for Containment and Clean up: Clean up any wet spills or clay slop with a damp sponge. For dry spills, spray with water and use a damp sponge to clean up.

Page | 2



**Special Spill Response Procedures: None** 

### **Section 7: HANDLING AND STORAGE**

Precautions for Safe Handling and Use: None

**Conditions for Safe Storage: None** 

Incompatible Materials: None

### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**EXPOSURE LIMITS** 

Ingredients	OSHA PEL	ACGIH TLV
Kaolin/Clay	N/A	N/A
Acacia Gum	5mg/m3	5mg/m3
Borax	10mg/m3	5mg/m3

#### **EXPOSURE CONTROLS**

Ventilation and engineering measures: None

Respiratory protection: Use a NIOSH approved respirator.

Skin protection: Wear appropriate protective clothing such as overalls, smocks, and aprons.

Eye/face protection: None

Hygienic Practices: Food, beverages, and smoking materials should not be in work area. Employees should wash hands thoroughly before eating, drinking, or smoking.

# Section 9: PHYSICAL/CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):

Solid

Upper/lower flammability or explosive limits:

None

Odor:

None

Page | 3



Vapor pressure: N/A Odor threshold: Negligible Vapor density: N/A pH: N/A Relative density: N/A Freezing point: N/A Solubility(ies) N/A Initial boiling point and boiling range: N/A Flash Point: N/A **Evaporation rate:** N/A Flammability (solid gas) N/A Partition coefficient: n-octanol/water: None Auto-ignition temperature: N/A

### Section 10: STABILITY / REACTIVITY

Reactivity: N/A

Viscosity:

Chemical stability: Stable

**Decomposition temperature:** 

Possibility of hazardous reactions: None

Conditions to avoid: None

Incompatible materials: None

Hazardous decomposition products: N/A

## Section 11: TOXICOLGICAL INFORMATION

## INFORMATION ON LIKELY ROUTES OF EXPOSURE

Routes of Entry: Inhalation is the most important during excessive handling of clay.

None

N/A

POTENTIAL HEALTH EFFECTS, Signs and symptoms of short-term (acute) exposure

Page | 4

Page 4 of 6



Sign and symptoms inhalation: Coughing or irritation may occur.

Sign and symptoms ingestion: Sickness or irritation may occur.

Sign and symptoms skin: Redness or irritation may occur.

Sign and symptoms eyes: Redness or irritation may occur.

Potential chronic health effects: These mixtures contain silica, which can cause Silicosis through inhalation over an extended period of time. Overexposure to silica may also result in injury to the lungs.

Carcinogenicity: Silica (Quartz) is a human carcinogen.

Toxicological data: These products conform to 16 CFR 1500.14 (LHAMA) and ASTM-4236. They have been certified by an independent, 3<sup>rd</sup> party toxicologist to be NON-TOXIC.

# Section 12: ECOLOGICAL INFORMATION (non-mandatory)

**Eco toxicity: None** 

Persistence and degradability: Yes

Bioaccumulation potential: No

Mobility in soil: No

Other adverse environmental effects: None

# Section 13: DISPOSAL CONSIDERATIONS (non-mandatory)

Handling for Disposal: None

Methods of Disposal: None

# Section 14: TRANSPORT INFORMATION (non-mandatory)

**UN Shipping Name: N/A** 

**UN Number: N/A** 

**Environmental Hazard: None** 

Packing Group: None

Transportation Hazard Class: N/A

Page | 5



**Special Precautions: None** 

NOT DANGEROUS FOR TRANSPORT

## Section 15: REGULATORY INFORMATION (non-mandatory)

Silica (Quartz) is listed by California, Proposition 65, as a carcinogen.

Silica (Quartz) is listed on the IARC, OSHA, and NTP carcinogen list.

All ingredients are on U.S. TSCA Inventory.

All products listed in this SDS conform to ASTM-4236 standards. Materials have been evaluated under the provisions of 16 CFR 1500.14 of the Labeling of Hazardous Art Material Act. These products have been listed as non-toxic and non-flammable under proposed use conditions. No specific warning is required.

### **Section 16: OTHER INFORMATION**

This information is furnished with out warranty, representation, inducement or license or any kind, except that it is accurate to the best of knowledge of Standard Ceramic Supply Company or obtained from other references and sources believed to be accurate.

Standard Ceramic Supply Company does not assume any legal responsibility for use or reliance on our products. Customers are encouraged to conduct their own tests before using any product. Read all product labels prior to handling.

Preparation date: 05/22/2014