

**SAFETY DATA SHEET**

50993-1050

**1. Identification**

<b>Product identifier</b>	<b>IdeaPaint CREATE CLEAR THAT (Part A)</b>	
<b>Other means of identification</b>		
<b>Product code</b>	IdeaPaint CREATE CLEAR- THAT (Part A)	
<b>Recommended use</b>	Dry erase coating.	
<b>Recommended restrictions</b>	None known.	
<b>Manufacturer/Importer/Supplier/Distributor information</b>		
<b>Manufacturer/Supplier</b>	IdeaPaint 40 Broad Street, 1st Floor Boston, MA 02109	
<b>Telephone number</b>	617.714.1050	
<b>e-mail</b>	marty@ideapaint.com	
<b>Emergency</b>	+1.866.519.4752 (US, Canada, Mexico) +1-760-476-3962 (US, Canada, Mexico) Access Code: 333641	

**2. Hazard(s) identification**

<b>Physical hazards</b>	Flammable liquids	Category 4
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1
	Germ cell mutagenicity	Category 2
	Carcinogenicity	Category 2
	Reproductive toxicity	Category 1B
	Specific target organ toxicity, repeated exposure	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	
<b>Label elements</b>		



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Combustible liquid. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing genetic defects. Suspected of causing cancer. May damage fertility or the unborn child. May damage the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.
<b>Precautionary statement</b>	
<b>Prevention</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from flames and hot surfaces-No smoking. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

<b>Response</b>	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Take off contaminated clothing and wash before reuse. Collect spillage. In case of fire: Use water fog, foam, dry chemical powder, carbon dioxide (CO <sub>2</sub> ) to extinguish.
<b>Storage</b>	Store in a well-ventilated place. Keep cool. Store locked up.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	Components of the product may be absorbed into the body through the skin.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	CAS number	%
Siloxanes and silicones, di-me, methoxy ph polymers with ph silsesquioxanes, methoxy-terminated	68957-04-0	40-70
Epoxy resin, MW <= 700	30583-72-3	10-30
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	1-5
Dibutyltin di(acetate)	1067-33-0	1-5
Ethanol	64-17-5	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1
Xylene	1330-20-7	0.1-1
Silicon dioxide, crystalline silica-free	7631-86-9	0,3-<1

**Composition comments** All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects. Causes damage to organs through prolonged or repeated exposure.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	If exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

IdeaPaint CREATE CLEAR THAT (Part A)

909896 Version #: 02 Revision date: 17-November-2017 Issue date: 19-October-2017

Item Numbers: 50993-1050

SDS US

2 / 11  
Page 2 of 19

<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Combustible liquid. Material will burn in a fire.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist or vapor. Do not get this material in contact with eyes. Do not taste or swallow. Avoid contact with skin and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Persons susceptible to allergic reactions should not handle this product. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
<b>Conditions for safe storage, including any incompatibilities</b>	Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Dibutyltin di(acetate) (CAS 1067-33-0)	PEL	0.1 mg/m3
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3 1000 ppm
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3 100 ppm
Xylene (CAS 1330-20-7)	PEL	435 mg/m3 100 ppm
Additional components	Type	Value
Methanol (CAS 67-56-1)	PEL	260 mg/m3 200 ppm

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)	TWA	0.8 mg/m3
		20 mppcf

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Dibutyltin di(acetate) (CAS 1067-33-0)	STEL	0.2 mg/m3
Ethanol (CAS 64-17-5)	TWA	0.1 mg/m3
	STEL	1000 ppm
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

**Additional components**

Components	Type	Value
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Dibutyltin di(acetate) (CAS 1067-33-0)	TWA	0.1 mg/m3
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3
	TWA	125 ppm
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)	TWA	435 mg/m3
		100 ppm
Additional components	TWA	6 mg/m3
Methanol (CAS 67-56-1)	STEL	325 mg/m3
	TWA	250 ppm
		260 mg/m3
		200 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
Additional components	Value	Determinant	Specimen	Sampling Time
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

Dibutyltin di(acetate) (CAS 1067-33-0)  
Methanol (CAS 67-56-1)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

Dibutyltin di(acetate) (CAS 1067-33-0)

Skin designation applies.

IdeaPaint CREATE CLEAR THAT (Part A)

SDS US

909896 Version #: 02 Revision date: 17-November-2017 Issue date: 19-October-2017

4 / 11  
Page 4 of 19

Methanol (CAS 67-56-1)	Skin designation applies.
<b>US - Tennessee OELs: Skin designation</b>	
Dibutyltin di(acetate) (CAS 1067-33-0)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
<b>US ACGIH Threshold Limit Values: Skin designation</b>	
Dibutyltin di(acetate) (CAS 1067-33-0)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
<b>US. NIOSH: Pocket Guide to Chemical Hazards</b>	
Dibutyltin di(acetate) (CAS 1067-33-0)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
<b>Appropriate engineering controls</b>	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles). Wear face shield if there is risk of splashes.
<b>Skin protection</b>	
<b>Hand protection</b>	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
<b>Skin protection</b>	
<b>Other</b>	Wear appropriate chemical resistant clothing, including apron and sleeves. Full body suit and boots are recommended when handling large volumes or in emergency situations.
<b>Respiratory protection</b>	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Remove contaminated clothing. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Clear.

**Odor** Mild.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** Not available.

**Initial boiling point and boiling range** > 220 °F (> 104.44 °C)

**Flash point** > 190.0 °F (> 87.8 °C) Closed Cup

**Evaporation rate** 32 (Butyl Acetate = 1)

**Flammability (solid, gas)** Not applicable.

### Upper/lower flammability or explosive limits

**Flammability limit - lower (%)** Not available.

**Flammability limit - upper (%)** Not available.

**Explosive limit - lower (%)** Not available.

**Explosive limit - upper (%)** Not available.

**Vapor pressure** 0.2 hPa (20°C/68°F)

**Vapor density** Not available.

**Relative density** 1.13 (H<sub>2</sub>O=1)

IdeaPaint CREATE CLEAR THAT (Part A)

SDS US

909896 Version #: 02 Revision date: 17-November-2017 Issue date: 19-October-2017

Item Numbers: 50993-1050

5 / 11  
Page 5 of 19

<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Insoluble in water.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	> 572 °F (> 300 °C)
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.
<b>Pounds per gallon</b>	9.5 lbs/gal
<b>VOC</b>	< 25 g/l (wt%)

## 10. Stability and reactivity

<b>Reactivity</b>	Product reacts with curing agents for epoxy resin, such as amine and acid anhydrides. Product reacts violently with excess curing agents (in particular aliphatic amines), and generates heat.
<b>Chemical stability</b>	Product reacts with curing agents for epoxy resin, such as amine and acid anhydrides.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization may occur with excess of aliphatic amine curing agent.
<b>Conditions to avoid</b>	High temperatures. Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents. Strong bases (especially primary and secondary aliphatic amines).
<b>Hazardous decomposition products</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye damage.
<b>Ingestion</b>	Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Causes damage to organs through prolonged or repeated exposure.

### Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components	Species	Test Results
Ethanol (CAS 64-17-5)		
<b>Acute</b>		
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Mouse	39 g/m <sup>3</sup> , 4 Hours
<b>Oral</b>		
LD50	Rat	7000 - 11000 mg/kg
Ethylbenzene (CAS 100-41-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	15400 mg/kg
<b>Inhalation</b>		
LC50	Rat	17.4 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	3500 - 4700 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

IdeaPaint CREATE CLEAR THAT (Part A)

SDS US

909896 Version #: 02 Revision date: 17-November-2017 Issue date: 19-October-2017  
Item Numbers: 50993-1050

6 / 11  
Page 6 of 19

<b>Serious eye damage/eye irritation</b>	Causes serious eye damage.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	Suspected of causing genetic defects.
<b>Carcinogenicity</b>	Suspected of causing cancer.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)	3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
<b>NTP Report on Carcinogens</b>	
Not listed.	
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)</b>	
Not regulated.	
<b>Reproductive toxicity</b>	May damage fertility. May damage the unborn child.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not an aspiration hazard.
<b>Chronic effects</b>	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.
<b>Further information</b>	Symptoms may be delayed. Components of the product may be absorbed into the body through the skin.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
Ethanol (CAS 64-17-5)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	LC50	Ceriodaphnia dubia Daphnia magna
		5012 mg/l, 48 hours 454 mg/l, 11 days
Fish	LC50	Pimephales promelas
		13480 mg/l, 96 hours
<i>Chronic</i>		
Crustacea	NOEC	Ceriodaphnia dubia
		9.6 mg/l, 10 days
Ethylbenzene (CAS 100-41-4)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Daphnia magna
Fish	LC50	Oncorhynchus mykiss
		1.81 - 2.38 mg/l, 48 hours 4.2 mg/l, 96 hours
<i>Chronic</i>		
Crustacea	LC50	Ceriodaphnia dubia
		3.6 mg/l, 7 days
<b>Additional components</b>		
Methanol (CAS 67-56-1)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Daphnia magna
Fish	LC50	Bluegill (Lepomis macrochirus)
		> 10000 mg/l, 48 hours 15400 mg/l, 96 hours

**Persistence and degradability** The product is not expected to be readily biodegradable.

**Bioaccumulative potential** Has the potential to bioaccumulate.

**Partition coefficient n-octanol / water (log Kow)**

IdeaPaint CREATE CLEAR THAT (Part A)	1.7 QSAR-method, (20 °C)
Dibutyltin di(acetate) (CAS 1067-33-0)	1.27
Ethanol (CAS 64-17-5)	-0.31
Ethylbenzene (CAS 100-41-4)	3.15

**Mobility in soil** The product is not expected to adsorb to soil.

**Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.

**13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**US RCRA Hazardous Waste U List: Reference**

Methanol (CAS 67-56-1) U154

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. Transport information****DOT**

<b>UN number</b>	UN3082
<b>UN proper shipping name</b>	Environmentally hazardous substances, liquid, n.o.s. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Dibutyltin di(acetate))
<b>Transport hazard class(es)</b>	
Class	9
Subsidiary risk	-
Label(s)	9
<b>Packing group</b>	III
<b>Environmental hazards</b>	
Marine pollutant	Yes
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	8, 146, 335, IB3, T4, TP1, TP29
<b>Packaging exceptions</b>	155
<b>Packaging non bulk</b>	203
<b>Packaging bulk</b>	241

**IATA**

<b>UN number</b>	UN3082
<b>UN proper shipping name</b>	Environmentally hazardous substance, liquid, n.o.s. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Dibutyltin di(acetate))
<b>Transport hazard class(es)</b>	
Class	9
Subsidiary risk	-
Label(s)	9
<b>Packing group</b>	III
<b>Environmental hazards</b>	Yes
<b>ERG Code</b>	9L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**IMDG**

<b>UN number</b>	UN3082
<b>UN proper shipping name</b>	Environmentally hazardous substances, liquid, n.o.s. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Dibutyltin di(acetate))
<b>Transport hazard class(es)</b>	
Class	9



<b>Subsidiary risk</b>	-
<b>Label(s)</b>	9
<b>Packing group</b>	III
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	Yes
<b>EmS</b>	F-A, S-F
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not applicable.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Ethylbenzene (CAS 100-41-4)	Listed.
Methanol (CAS 67-56-1)	Listed.
Xylene (CAS 1330-20-7)	Listed.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Respiratory or skin sensitization  
Germ cell mutagenicity  
Carcinogenicity  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Ethylbenzene	100-41-4	0.1 - 1
Xylene	1330-20-7	0.1-1

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)  
Methanol (CAS 67-56-1)  
Xylene (CAS 1330-20-7)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

#### FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethanol (CAS 64-17-5) Low priority

**US state regulations** WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US. Massachusetts RTK - Substance List

Dibutyltin di(acetate) (CAS 1067-33-0)  
Ethanol (CAS 64-17-5)

Ethylbenzene (CAS 100-41-4)  
 Methanol (CAS 67-56-1)  
 Silicon dioxide, crystalline silica-free (CAS 7631-86-9)  
 Xylene (CAS 1330-20-7)

**US. New Jersey Worker and Community Right-to-Know Act**

Ethanol (CAS 64-17-5)  
 Ethylbenzene (CAS 100-41-4)  
 Methanol (CAS 67-56-1)  
 Silicon dioxide, crystalline silica-free (CAS 7631-86-9)  
 Xylene (CAS 1330-20-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Ethanol (CAS 64-17-5)  
 Ethylbenzene (CAS 100-41-4)  
 Methanol (CAS 67-56-1)  
 Silicon dioxide, crystalline silica-free (CAS 7631-86-9)  
 Xylene (CAS 1330-20-7)

**US. Rhode Island RTK**

Dibutyltin di(acetate) (CAS 1067-33-0)  
 Ethanol (CAS 64-17-5)  
 Ethylbenzene (CAS 100-41-4)  
 Methanol (CAS 67-56-1)  
 Xylene (CAS 1330-20-7)

**California Proposition 65****California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004

**California Proposition 65 - CRT: Listed date/Developmental toxin**

Ethanol (CAS 64-17-5) Listed: October 1, 1987  
 Methanol (CAS 67-56-1) Listed: March 16, 2012

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (CAS 41556-26-7)  
 Ethylbenzene (CAS 100-41-4)  
 Methanol (CAS 67-56-1)  
 Xylene (CAS 1330-20-7)

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

**Issue date** 19-October-2017  
**Revision date** 17-November-2017  
**Version #** 02

**NFPA ratings****List of abbreviations**

PEL: Permissible Exposure Limit.  
TWA: Time weighted average.  
STEL: Short term exposure limit.  
EC50: Effective Concentration, 50%.  
LD50: Lethal Dose, 50%.  
NOEC: No observed effect concentration.  
LC50: Lethal Concentration, 50%.  
VOC: Volatile organic compounds.  
CEN: European Committee for Standardisation.  
BCF: Bio Concentration Factor.  
QSAR: Quantitative Structure Activity Relation.

**Disclaimer**

IdeaPaint cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

## SAFETY DATA SHEET

### 1. Identification

<b>Product identifier</b>	<b>IdeaPaint CREATE CLEAR THIS (Part B)</b>	
<b>Other means of identification</b>	None.	
<b>Recommended use</b>	Dry erase coating.	
<b>Recommended restrictions</b>	None known.	
<b>Manufacturer/Importer/Supplier/Distributor information</b>		
<b>Manufacturer/Supplier</b>	IdeaPaint 40 Broad Street, 1st Floor Boston, MA 02109	
<b>Telephone number</b>	617.714.1050	
<b>e-mail</b>	marty@ideapaint.com	
<b>Emergency</b>	+1.866.519.4752 (US, Canada, Mexico) +1-760-476-3962 (US, Canada, Mexico) Access Code: 333641	

### 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 4
<b>Health hazards</b>	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 1B
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1
<b>OSHA defined hazards</b>	Not classified.	
<b>Label elements</b>		



<b>Signal word</b>	Danger	
<b>Hazard statement</b>	Combustible liquid. Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction.	
<b>Precautionary statement</b>		
<b>Prevention</b>	Keep away from flames and hot surfaces-No smoking. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.	
<b>Response</b>	If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse. In case of fire: Use water fog, foam, dry chemical powder, carbon dioxide (CO <sub>2</sub> ) to extinguish.	
<b>Storage</b>	Store in a well-ventilated place. Keep cool. Store locked up.	
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.	
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.	
<b>Supplemental information</b>	None.	

**3. Composition/information on ingredients****Mixtures**

Chemical name	CAS number	%
3-Aminopropyltriethoxysilane	919-30-2	99

**Composition comments** All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**4. First-aid measures****Inhalation**

Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact**

Remove contaminated clothing immediately and wash skin with soap and water. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

**Eye contact**

Immediately flush eyes with plenty of water for at least 15 minutes. Provide eyewash station. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

**Ingestion**

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

**Most important symptoms/effects, acute and delayed**

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract. Harmful if swallowed.

**Indication of immediate medical attention and special treatment needed**

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General information**

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

**5. Fire-fighting measures****Suitable extinguishing media**

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical**

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters**

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Fire fighting equipment/instructions**

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

**Specific methods**

Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards**

Combustible liquid. Will burn if involved in a fire.

**6. Accidental release measures****Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

**Environmental precautions****7. Handling and storage****Precautions for safe handling**

Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Persons susceptible to allergic reactions should not handle this product. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities**

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection****Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Additional components	Type	Value
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3 1000 ppm

**US. ACGIH Threshold Limit Values**

Additional components	Type	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Additional components	Type	Value
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3 1000 ppm

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles). Wear face shield if there is risk of splashes.

**Skin protection**

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**Skin protection**

**Other** Wear appropriate chemical resistant clothing, including apron and sleeves. Full body suit and boots are recommended when handling large volumes or in emergency situations.

**Respiratory protection**

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Remove contaminated clothing. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Colorless to yellowish.
<b>Odor</b>	Amine-like.
<b>Odor threshold</b>	Not available.
<b>pH</b>	11.3 at 20 °C
<b>Melting point/freezing point</b>	< -94 °F (< -70 °C)
<b>Initial boiling point and boiling range</b>	428 °F (220 °C)
<b>Flash point</b>	199.0 °F (92.8 °C)
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.

### Upper/lower flammability or explosive limits

<b>Explosive limit - lower (%)</b>	0.8 %
<b>Explosive limit - upper (%)</b>	4.5 %
<b>Vapor pressure</b>	0.02 hPa at 20 °C
<b>Vapor density</b>	Not available.
<b>Relative density</b>	0.94 g/cm <sup>3</sup>
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	5.4 g/l at 20°C
<b>Partition coefficient (n-octanol/water)</b>	1.7 QSAR-method (20 °C)
<b>Auto-ignition temperature</b>	572 °F (300 °C)
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	2 mPa·s DIN 53015 at 20 °C
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Molecular formula</b>	C9-H23-N-O3-Si
<b>Molecular weight</b>	221.42 g/mol
<b>Oxidizing properties</b>	Not oxidizing.
<b>Pounds per gallon</b>	7.88 lbs/gal
<b>VOC</b>	< 100 g/l

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Contact with water liberates ethanol. Polymerization will not occur unless product is mixed with epoxy resins, isocyanates or urethane prepolymers.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents. Strong acids.
<b>Hazardous decomposition products</b>	Ethanol in case of hydrolysis. Thermal decomposition of this product can generate carbon monoxide, carbon dioxide and nitrogen oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause irritation to the respiratory system.
<b>Skin contact</b>	Causes severe skin burns. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye damage.

<b>Ingestion</b>	Causes digestive tract burns. Harmful if swallowed.		
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract. Harmful if swallowed.		
<b>Information on toxicological effects</b>			
<b>Acute toxicity</b>	Harmful if swallowed.		
<b>Toxicological data</b>			
<b>Additional components</b>	<b>Species</b>	<b>Test Results</b>	
Ethanol (CAS 64-17-5)			
<b>Acute</b>			
<b>Inhalation</b>			
<i>Vapor</i>			
LC50	Mouse	39 g/m3, 4 Hours	
<b>Oral</b>			
LD50	Rat	7000 - 11000 mg/kg	
<b>Skin corrosion/irritation</b>	Causes severe skin burns.		
<b>Serious eye damage/eye irritation</b>	Causes serious eye damage.		
<b>Respiratory or skin sensitization</b>			
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.		
<b>Skin sensitization</b>	May cause an allergic skin reaction.		
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>			
Not listed.			
<b>NTP Report on Carcinogens</b>			
Not listed.			
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)</b>			
Not regulated.			
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.		
<b>Specific target organ toxicity - single exposure</b>	Not classified.		
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.		
<b>Aspiration hazard</b>	Not an aspiration hazard.		
<b>Further information</b>	Symptoms may be delayed. Ethanol may be released.		

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

<b>Additional components</b>	<b>Species</b>	<b>Test Results</b>
Ethanol (CAS 64-17-5)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	LC50	Ceriodaphnia dubia Daphnia magna 5012 mg/l, 48 hours 454 mg/l, 11 days
Fish	LC50	Pimephales promelas 13480 mg/l, 96 hours
<i>Chronic</i>		
Crustacea	NOEC	Ceriodaphnia dubia 9.6 mg/l, 10 days

### Persistence and degradability

IdeaPaint CREATE CLEAR THIS (Part B)

SDS US

909941 Version #: 01 Revision date: - Issue date: 19-October-2017

Page 16 of 19

Item Numbers: 50993-1050

5 / 8



**Biodegradability****Percent degradation (Aerobic biodegradation-ready)**

IdeaPaint CREATE CLEAR THIS (Part B) 67 % DOC; Die Away Test

**Bioaccumulative potential****Partition coefficient n-octanol / water (log Kow)**

IdeaPaint CREATE CLEAR THIS (Part B) 1.7 QSAR-method, (20 °C)

**Mobility in soil** The product is slightly soluble in water.**Other adverse effects** It will react with water and release ethanol.**13. Disposal considerations****Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.**Local disposal regulations** Dispose in accordance with all applicable regulations.**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.**14. Transport information****DOT**

**UN number** UN3267  
**UN proper shipping name** Corrosive liquid, basic, organic, n.o.s.  
**Transport hazard class(es)**  
**Class** 8  
**Subsidiary risk** -  
**Label(s)** 8  
**Packing group** II  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Special provisions** B2, IB2, T11, TP2, TP27  
**Packaging exceptions** 154  
**Packaging non bulk** 202  
**Packaging bulk** 242

**IATA**

**UN number** UN3267  
**UN proper shipping name** Corrosive liquid, basic, organic, n.o.s. (3-AMINOPROPYLTRIETHOXYSILANE)  
**Transport hazard class(es)**  
**Class** 8  
**Subsidiary risk** -  
**Label(s)** 8  
**Packing group** II  
**Environmental hazards** No  
**ERG Code** 8L  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**IMDG**

**UN number** UN3267  
**UN proper shipping name** Corrosive liquid, basic, organic, n.o.s. (3-AMINOPROPYLTRIETHOXYSILANE)  
**Transport hazard class(es)**  
**Class** 8  
**Subsidiary risk** -  
**Packing group** II  
**Environmental hazards**  
**Marine pollutant** No  
**EmS** F-A, S-B  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**SARA 313 (TRI reporting)**

Not regulated.

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

Ethanol (CAS 64-17-5)

Low priority

**US state regulations** California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**US. Massachusetts RTK - Substance List**

Ethanol (CAS 64-17-5)

**US. New Jersey Worker and Community Right-to-Know Act**

Ethanol (CAS 64-17-5)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Ethanol (CAS 64-17-5)

**US. Rhode Island RTK**

Ethanol (CAS 64-17-5)

**California Proposition 65**

**California Proposition 65 - CRT: Listed date/Developmental toxin**

Ethanol (CAS 64-17-5)

Listed: October 1, 1987

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 19-October-2017

**Revision date** -

**Version #** 01

**NFPA ratings**



**List of abbreviations**

TWA: Time weighted average.  
 STEL: Short term exposure limit.  
 CEN: European Committee for Standardisation.  
 BCF: Bio Concentration Factor.  
 VOC: Volatile organic compounds.  
 QSAR: Quantitative Structure Activity Relation.

**Disclaimer**

IdeaPaint cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.