

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: Gorilla Mounting Tape Tough, Clear and Gorilla Mounting Tape Heavy Duty, & Gorilla Mounting Tape Squares **Synonyms:** Pressure sensitive adhesive

Article Exemption: Within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]: this mixture is not considered a hazard when used in a manner which is consistent with the labeled directions. This mixture is considered an article in its final form.

Intended Use of the Product

Mounting Tape

Name, Address, and Telephone of the Responsible Party

Company The Gorilla Glue Company 2101 E. Kemper Road Cincinnati, Ohio 45241 513-271-3300 www.gorillatough.com

Emergency Telephone Number

Emergency number : 1-800-420-7186 (Prosar)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture Classification (GHS-US) Not classified Label Elements

GHS-US Labeling No labeling applicable

Other Hazards

Other Hazards Not Contributing to the Classification: No additional information available

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixture</u>

Within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]: this mixture is not considered a hazard when used in a manner which is consistent with the labeled directions. This mixture is considered an article in its final form.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

Skin Contact: Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed


General: Prolonged contact may cause irritation. Vapors may cause drowsiness and dizziness.

Inhalation: Prolonged, repeated inhalation of adhesive may cause dizziness and drowsiness.

Skin Contact: Repeated or prolonged skin contact may cause irritation.

Eye Contact: Contact may cause irritation due to mechanical abrasion.

Gorilla Mounting Tap Item Numbers: 54105-1002



Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated or prolonged skin contact may cause irritation.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: None known.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Keep area ventilated.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container.

Methods for Cleaning Up: Dispose of waste safely and in accordance with local, state, and federal regulations.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place. Store away from incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Specific End Use(s) Mounting Tape

Gorilla Mounting Tape SD

Version: 1.4



Safety Data Sheet - Gorilla Mounting Tape

Date Revised: 01/22/2020 Date Issued: 05/29/2015

Version: 1.4

FOR CHEMICAL EMERGENCY: During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Silica, amorphous (7631-	86-9)	
USA OSHA	OSHA PEL (TWA) (mg/m³)	6 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	20 mppcf (80mg/m ³ /%SiO ₂)
Nunavut	OEL TWA (mg/m³)	2 mg/m ³ (respirable mass)
		5 mg/m³ (total mass)
		0.05 mg/m ³ (regulated under Silica flour-respirable mass)
		0.15 mg/m ³ (regulated under Silica flour, total mass)
Northwest Territories	OEL TWA (mg/m³)	2 mg/m ³ (respirable mass)
		5 mg/m ³ (total mass)
		0.05 mg/m ³ (regulated under Silica flour-respirable mass)
		0.15 mg/m ³ (total mass, regulated under Silica flour)
Yukon	OEL TWA (mg/m³)	300 particle/mL (as measured by Konimeter
		instrumentation)
		20 mppcf (as measured by Impinger instrumentation)
		2 mg/m ³ (respirable mass)

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide sufficient ventilation to keep vapors below permissible exposure limit. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Safety glasses.



Materials for Protective Clothing: Not available

Hand Protection: Chemically resistant gloves are recommended, but not required.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable working clothes.

Respiratory Protection: Not required for normal conditions of use. If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Other Information: When using, do not eat, drink or smoke.

Information on Basic Physical and Chemical Properties					
Physical State	: Solid				
Appearance	: Clear (for Tough & Clear and Mounting Tape Squares); Black (for Heavy Duty)				
Odor	: Slight				
Odor Threshold	: Not available				
рН	: Not applicable				
Evaporation Rate	: Not available				
Melting Point	: Not available				

Item Numbers: 54105-1002

rilla Mounting Tape SD

Page 3 of 6



Safety Data Sheet - Gorilla Mounting Tape

Date Revised: 01/22/2020 Date Issued: 05/29/2015

Version: 1.4

FOR CHEMICAL EMERGENCY: During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Freezing Point	:	Not available				
Boiling Point	:	Not available				
Flash Point	:	Not available				
Auto-ignition Temperature	:	Not available				
Decomposition Temperature	:	Not available				
Flammability (solid, gas)	:	Not available				
Lower Flammable Limit	:	Not available				
Upper Flammable Limit		Not available				
Vapor Pressure		Not available				
Relative Vapor Density at 20 °C		Not available				
Relative Density		Not available				
Specific Gravity	:	1 g/cm ³ (+/- 0.1) for Tough & Clear; 0.75 g/cm ³ (+/- 0.1) for Heavy Duty				
Solubility	:	Water: Negligible				
Partition Coefficient: N-Octanol/Water		Not available				
Viscosity	:	Not available				
Explosion Data – Sensitivity to Mechanical Impact		Not expected to present an explosion hazard due to mechanical impact.				
Explosion Data – Sensitivity to Static Discharge		Not expected to present an explosion hazard due to static discharge.				
SECTION 10: STABILITY AND REACTIVITY						
Reactivity: None known.						
Chemical Stability: Stable under recommended handling and storage conditions (see section 7).						
Possibility of Hazardous Reactions: Hazardous po	olyr	nerization will not occur.				
Conditions to Avoid: Direct sunlight. Extremely hi	gh (or low temperatures.				
Incompatible Materials: Strong acids, strong base	:s, s	trong oxidizers.				
Hazardous Decomposition Products: Carbon oxid	es ((CO, CO ₂).				
SECTION 11: TOXICOLOGICAL INFORMATIO	Ν					
Information on Toxicological Effects - Product						
A substitution of the second						

Acute Toxicity: Not classified LD50 and LC50 Data: Not available Skin Corrosion/Irritation: Not classified pH: Not applicable Serious Eye Damage/Irritation: Not classified pH: Not applicable Respiratory or Skin Sensitization: Not classified Germ Cell Mutagenicity: Not classified Teratogenicity: Not available Carcinogenicity: Not classified Specific Target Organ Toxicity (Repeated Exposure): Not classified Reproductive Toxicity: Not classified Specific Target Organ Toxicity (Single Exposure): Not classified Aspiration Hazard: Not classified Symptoms/Injuries After Inhalation: Prolonged, repeated inhalation of adhesive may cause dizziness and drowsiness. Symptoms/Injuries After Skin Contact: Repeated or prolonged skin contact may cause irritation. Symptoms/Injuries After Eye Contact: Contact may cause irritation due to mechanical abrasion. Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated or prolonged skin contact may cause irritation.

Gorilla Mounting Tape SD

Item Numbers: 54105-1002

Page 4 of 6



Safety Data Sheet - Gorilla Mounting Tape

Date Revised: 01/22/2020 Date Issued: 05/29/2015

Version: 1.4

FOR CHEMICAL EMERGENCY: During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Information on Toxicological Effects	- Ingredient(s)
Silica, amorphous (7631-86-9) LD50 Oral Rat	> 5000 m = //m
	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 2.2 mg/l (Exposure time: 1 h)
Silica, amorphous (7631-86-9)	
IARC Group	3
SECTION 12: ECOLOGICAL INFORM	IATION
Toxicity Not classified	
Silica, amorphous (7631-86-9)	
LC50 Fish 1	5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)
Persistence and Degradability Not av	
Bioaccumulative Potential	
Silica, amorphous (7631-86-9)	
BCF Fish 1	(no bioaccumulation expected)
Mobility in Soil Not available	
Other Adverse Effects	
Other Information: Avoid release to the	
SECTION 13: DISPOSAL CONSIDER	
Sewage Disposal Recommendations: Do	·
	pose of waste material in accordance with all local, regional, national, provincial, territorial
and international regulations. SECTION 14: TRANSPORT INFORM	ΑΤΙΟΝ
	ated for transport
0	ated for transport
	ated for transport
-	ated for transport
SECTION 15: REGULATORY INFORM	MATION
US Federal Regulations	
Silica, amorphous (7631-86-9)	
Listed on the United States TSCA (Toxic S	Substances Control Act) inventory
US State Regulations	
Gorilla Mounting Tape	
California Prop 65: To the best of our kn	owledge, this product contains no listed substances known to the State of California to
cause cancer, birth defects or other repr	oductive harm, at levels which would require a warning under the statute.
Silica, amorphous (7631-86-9)	
U.S Massachusetts - Right To Know List	
U.S New Jersey - Right to Know Hazard	
U.S Pennsylvania - RTK (Right to Know)	List
Canadian Regulations	
Gorilla Mounting Tape	
Gorilla Mounting Tape SDS	Page 5 of 6
Gorma mounting rape SDS	Page 5 of 5

an or the second	Safety Data Sheet - Gorilla Mounting Tape Date Revised: 01/22/2020 Date Issued: 05/29/2015 Version	on: 1.4
GORILLA	FOR CHEMICAL EMERGENCY: During Business Hours: (800) 966-3458 Outside Business Hours: (800) 420-7186	
100% TONCH	According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations	
WHMIS Classification	This is not a controlled product under WHMIS. This product meets the definition of a "ma article" and is not subject to the regulations of the Hazardous Products Act.	anufactured
Silica, amorphous (7631-86-9)		
Listed on the Canadian DSL (De	omestic Substances List)	
Listed on the Canadian IDL (Ing	gredient Disclosure List)	
IDL Concentration 1 %		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
This product has been classifie contains all of the information	ed in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and n required by CPR.	the SDS

Revision Date

: 01/22/2020

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document

The Gorilla Glue Company +1 513-271-3300

The information presented in this Safety Data Sheet was prepared by qualified personnel and to the best of our knowledge is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser will independently determine the suitability of the product for this purpose. This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which The Gorilla Glue Company assumes legal responsibility. The data is submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial and local laws and regulations.

North America GHS US 2012 & WHMIS 2 GG