Date revised: 17.12.2021

MSDS for #63412 - MARABU EASY MARBLE

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1 / GB

Substance number: 13059039014 Replaces Version: -/GB Print date: 17.12.21

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Marabu easy marble 014, 15 ml MNA

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Use of the substance/preparation

**Paint** 

#### **Identified Uses**

SU21 Consumer uses: Private households (= general public = consumers)

PC9a Coatings and paints, thinners, paint removers

# 1.3. Details of the supplier of the safety data sheet

#### Address/Manufacturer

Marabu GmbH & Co. KG Asperger Strasse 4 71732 Tamm Germany

Telephone no. +49-7141/691-0 Fax no. +49-7141/691-147

Information provided Department product safety

by / telephone E-mail address of

address of PRSI@marabu.com

person responsible for this SDS

# 1.4. Emergency telephone number

(+49) (0)621-60-43333

## SECTION 2: Hazards identification

# 2.1. Classification of the substance or mixture

## Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226 STOT SE 3 H336

# 2.2. Label elements

# Labelling according to regulation (EC) No 1272/2008

## **Hazard pictograms**



# Signal word

Warning

## **Hazard statements**

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

**Precautionary statements** 

#### Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1 / GB Date revised: 17.12.2021

Substance number: 13059039014 Replaces Version: - / GB Print date: 17.12.21

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P405 Store locked up.

P501.9 Dispose of contents/container as problematic waste.

## Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics;

2-Methoxy-1-methylethyl acetate; 1-Methoxy-2-propanol

# 2.3. Other hazards

No special hazards have to be mentioned.

# SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

#### **Chemical characterization**

Paint based on alkyd resins and on solvents

#### **Hazardous ingredients**

## 1-Methoxy-2-propanol

CAS No. 107-98-2 EINECS no. 203-539-1

Registration no. 01-2119457435-35

Concentration >= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

STOT SE 3 H336 Flam. Lig. 3 H226

#### 2-Methoxy-1-methylethyl acetate

CAS No. 108-65-6 EINECS no. 203-603-9

Registration no. 01-2119475791-29

Concentration >= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226 STOT SE 3 H336

## Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

CAS No. 64742-48-9 EINECS no. 265-150-3

Registration no. 01-2119463258-33 (LIST NUMBER 919-857-5) Concentration >= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Asp. Tox. 1 H304 Flam. Liq. 3 H226 STOT SE 3 H336 EUH066

## 2-Butoxyethyl acetate

CAS No. 112-07-2 EINECS no. 203-933-3

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1 / GB Date revised: 17.12.202

Substance number: 13059039014 Replaces Version: -/GB Print date: 17.12.21

Registration no. 01-2119475112-47

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H332 Acute Tox. 4 H312 Acute Tox. 4 H302

2-Methoxypropanol

CAS No. 1589-47-5 EINECS no. 216-455-5

Concentration >= 0.1 < 0.3 %

Classification (Regulation (EC) No. 1272/2008)

 Skin Irrit. 2
 H315

 STOT SE 3
 H335

 Repr. 1B
 H360D

 Flam. Liq. 3
 H226

 Eye Dam. 1
 H318

# SECTION 4: First aid measures

## 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

## After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

## 4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

# 4.3. Indication of any immediate medical attention and special treatment needed Hints for the physician / treatment

Treat symptomatically

# SECTION 5: Firefighting measures

## 5.1. Extinguishing media

# Suitable extinguishing media

Recommended: alcohol resistant foam, CO2, powders, water spray/mist, Not be used for safety reasons: water jet

#### Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1 / GB

Substance number: 13059039014 Replaces Version: - / GB Print date: 17.12.21

## 5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO); dense black smoke; Nitrogen oxides (NOx)

Date revised: 17.12.202

## 5.3. Advice for firefighters

# Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

# SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

## 6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

## 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

#### 6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

# SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

# Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

# Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires B (Combustible liquid substances)

Temperature class T4

# 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1/GB

Date revised: 17.12.2021

Substance number: 13059039014 Replaces Version: - / GB Print date: 17.12.21

#### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

## 7.3. Specific end use(s)

Paint

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

# **Exposure limit values**

# 2-Methoxy-1-methylethyl acetate

List EH40
Type WEL
Value 274

Value 274 mg/m³ 50 ppm(V) Short term exposure limit 548 mg/m³ 100 ppm(V) Skin resorption / sensibilisation: Sk; Status: 2011

## 1-Methoxy-2-propanol

List EH40 Type WEL

Skin resorption / sensibilisation: Sk; Status: 2011

## 2-Butoxyethyl acetate

List EH40
Type WEL
Value 133

Value 133 20 ppm(V)
Short term exposure limit 332 50 ppm(V)
Skip recognition (separabilization) Skip Status; 2011

Skin resorption / sensibilisation: Sk; Status: 2011

# Derived No/Minimal Effect Levels (DNEL/DMEL)

## Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 300 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Mode of action Systemic effects

Concentration 300 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 300 mg/kg

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1 / GB Date revised: 17.12.2021

Substance number: 13059039014 Replaces Version: - / GB Print date: 17.12.21

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consumer

Long term

inhalative

Systemic effects

Concentration 900 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 1500 mg/m³

2-Methoxy-1-methylethyl acetate

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 796 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group
Duration of exposure
Route of exposure
Mode of action
Worker
Long term
inhalative
Systemic effects

Concentration 275 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 320 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consumer

Long term
inhalative

Systemic effects

Concentration 33 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Concentration

Concentration

Consumer

Long term

inhalative

Local effects

Concentration 33 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Mode of action Systemic effects

Concentration 36 mg/kg/d

data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1/GB

Print date: 17.12.21 Replaces Version: -/GB Substance number: 13059039014

Date revised: 17.12.2021

Type of value Derived No Effect Level (DNEL)

Reference group Worker Duration of exposure Lifetime inhalative Route of exposure Mode of action Local effects Concentration 550

mg/m³

1-Methoxy-2-propanol

Type of value Derived No Effect Level (DNEL)

Reference group Worker Duration of exposure Acute inhalative Route of exposure Local effects Mode of action Concentration 553.5

mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Worker Reference group Duration of exposure Long term Route of exposure dermal

Systemic effects Mode of action

Concentration mg/person/ 50,6

Derived No Effect Level (DNEL) Type of value

Reference group Worker Duration of exposure Long term Route of exposure inhalative Mode of action Systemic effects

Concentration 369

mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group General Population Long term

Duration of exposure Route of exposure dermal

Systemic effects Mode of action

Concentration 18,1 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term Route of exposure inhalative Mode of action Systemic effects

Concentration mg/m<sup>3</sup> 43,9

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term Route of exposure oral

Mode of action Systemic effects

Concentration 3,3 mg/kg/d

2-Butoxyethyl acetate

Reference substance 2-Butoxyethyl acetate

Type of value Derived No Effect Level (DNEL)

Reference group Worker Duration of exposure Long term

data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1/GB

Print date: 17.12.21 Replaces Version: -/GB Substance number: 13059039014

Date revised: 17.12.2021

Route of exposure inhalative

Mode of action Systemic effects

Concentration mg/m<sup>3</sup> 133

2-Butoxyethyl acetate

Type of value Derived No Effect Level (DNEL)

Reference group Worker Duration of exposure Short term Route of exposure inhalative Mode of action Local effects Concentration 333

mg/m<sup>3</sup>

2-Butoxyethyl acetate

Type of value Derived No Effect Level (DNEL)

Reference group Worker Duration of exposure Long term Route of exposure dermal

Mode of action Systemic effects

Concentration 169 mg/kg/d

2-Butoxyethyl acetate

Derived No Effect Level (DNEL) Type of value Reference group Worker

Duration of exposure Short term Route of exposure dermal

Mode of action Systemic effects

Concentration 120 mg/kg/d

2-Butoxyethyl acetate

Derived No Effect Level (DNEL) Type of value

General Population Reference group Duration of exposure Long term

Route of exposure inhalative Systemic effects Mode of action

Concentration mg/m<sup>3</sup>

2-Butoxyethyl acetate

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Short term Route of exposure inhalative Mode of action Local effects

Concentration 200 mg/m<sup>3</sup>

2-Butoxyethyl acetate

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term Route of exposure dermal

Systemic effects Mode of action

Concentration 102 mg/kg/d

2-Butoxyethyl acetate

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Short term Route of exposure dermal

Item Numbers: 63412-3042

Mode of action Systemic effects

Concentration

afety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1/GB

Print date: 17.12.21 Replaces Version: -/GB Substance number: 13059039014

> 72 mg/kg/d

2-Butoxyethyl acetate

Type of value Derived No Effect Level (DNEL)

General Population Reference group

Duration of exposure Long term

Route of exposure oral

Systemic effects Mode of action

Concentration 8,6 mg/kg/d

2-Butoxyethyl acetate

Type of value Derived No Effect Level (DNEL)

General Population Reference group

Duration of exposure Short term Route of exposure oral

Mode of action Systemic effects

Concentration mg/kg/d

**Predicted No Effect Concentration (PNEC)** 

2-Methoxy-1-methylethyl acetate

Reference substance 2-Methoxy-1-methylethyl acetate

Type of value **PNEC** Type Freshwater

0,635 Concentration mg/l

**PNEC** Type of value

Type Freshwater sediment

Concentration mg/kg 3,29

Type of value **PNEC** Type Soil

Concentration 0.29 mg/kg

Source Literature value

Type of value **PNEC** 

Type Sewage treatment plant (STP)

Concentration 100 mg/l

Source Literature value

Type of value **PNEC** 

Marine sediment Type

Concentration 0,329 mg/kg

Source Literature value

**PNEC** Type of value Type Saltwater

Concentration 0,0635 mg/l

1-Methoxy-2-propanol

Item Numbers: 63412-3042

Type of value **PNEC** Type Freshwater

Concentration 10 mg/l

**PNEC** Type of value Water Type

Concentration 41,6 mg/kg

Date revised: 17.12.2021

afety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1/GB

Date revised: 17.12.2021

Print date: 17.12.21 Substance number: 13059039014 Replaces Version: -/GB

Type of value **PNEC** Sediment Type

Concentration 41,6 mg/kg

PNFC Type of value

Type Marine sediment

Concentration 4,17 mg/kg

**PNEC** Type of value Type Soil

2,47 Concentration mg/kg

**PNEC** Type of value

Type Sewage treatment plant (STP)

Concentration mg/l

2-Butoxyethyl acetate

2-Butoxyethyl acetate Reference substance

Type of value **PNEC** Type Water

Concentration 0,304 mg/l

Literature value Source

2-Butoxyethyl acetate

Type of value **PNEC** Type Aquatic

Concentration 0,0304 g/I

Source Literature value

2-Butoxyethyl acetate

Type of value **PNEC** Type Sediment

Concentration 2,03 mg/kg

Source Literature value

2-Butoxyethyl acetate

Type of value **PNEC** 

Marine sediment Type

Concentration 0,203

mg/kg

Literature value Source

2-Butoxyethyl acetate

Type of value **PNEC** Soil Type

Concentration 0,68 mg/kg

Source Literature value

# 8.2. Exposure controls

# **Exposure controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

## Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

#### Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1 / GB Date revised: 17.12.202

Substance number: 13059039014 Replaces Version: -/GB Print date: 17.12.21

## Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

## Eye protection

Use safety eyewear designed to protect against splash of liquids.

#### **Body protection**

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

Form Liquid
Colour red
Odour solvent-like

Odour threshold

Remarks No data available

pH value

Remarks Not applicable

**Melting point** 

Remarks not determined

Freezing point

Remarks not determined

## Initial boiling point and boiling range

Value appr. 120 °C

Pressure 1.013 hPa

Source Literature value

Flash point

Value 30 °C

Method ASTM D 6450 (CCCFP)

Evaporation rate (ether = 1):

Remarks not determined

Flammability (solid, gas)

Not applicable

## Upper/lower flammability or explosive limits

Lower explosion limit appr. 0,7 %(V)
Upper explosion limit appr. 13,7 %(V)
Source Literature value

Vapour pressure

Item Numbers: 63412-3042

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1 / GB Date revised: 17.12.202

Substance number: 13059039014 Replaces Version: -/GB Print date: 17.12.21

Value 8 hPa Temperature 20 °C

Method calculated

Vapour density

Remarks not determined

**Density** 

Value 0,93 g/cm<sup>3</sup>

Temperature 20 °C Method DIN EN ISO 2811

Solubility in water

Remarks partially miscible

Partition coefficient: n-octanol/water

Remarks Not applicable

Ignition temperature

Value appr. 200 °C Source Literature value

**Viscosity** 

dynamic

Value 30 to 50 mPa.s Temperature 40 °C

Efflux time

Value 25 to 70 s Temperature 20 °C

Method DIN 53211 4 mm

**Explosive properties** 

evaluation no

**Oxidising properties** 

evaluation None known

#### 9.2. Other information

#### Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

# SECTION 10: Stability and reactivity

# 10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

#### 10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

## 10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

## 10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

## 10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1 / GB Date revised: 17.12.202

Substance number: 13059039014 Replaces Version: - / GB Print date: 17.12.21

# SECTION 11: Toxicological information

# 11.1. Information on toxicological effects

**Acute oral toxicity** 

ATE > 2.000 mg/kg Method calculated value (Regulation (EC) No. 1272/2008)

## **Acute oral toxicity (Components)**

1-Methoxy-2-propanol

Species rat

LD50 5200 mg/kg

2-Butoxyethyl acetate

Species rat

LD50 1880 mg/kg

Method OECD 401

Acute dermal toxicity

ATE > 2.000 mg/kg
Method calculated value (Regulation (EC) No. 1272/2008)

#### Acute dermal toxicity (Components)

1-Methoxy-2-propanol

Species rabbit

LD50 14000 mg/kg

2-Butoxyethyl acetate

Species rabbit

LD50 1480 mg/kg

Acute inhalational toxicity

ATE > 20 mg/l

Administration/Form Vapors

Method calculated value (Regulation (EC) No. 1272/2008)

ATE > 5 mg/l

Administration/Form Dust/Mist

Method calculated value (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

# Acute inhalative toxicity (Components)

2-Butoxyethyl acetate

Species rat

LD0 2,66 mg/l

Duration of exposure 4 h

Administration/Form Vapors Method OECD 403

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

# Skin corrosion/irritation (Components)

2-Methoxy-1-methylethyl acetate

Species rabbit evaluation non-irritant

Serious eye damage/irritation

Remarks Based on available data, the classification criteria are not met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

#### Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1 / GB Date revised: 17.12.202

Substance number: 13059039014 Replaces Version: -/GB Print date: 17.12.21

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

# **Specific Target Organ Toxicity (STOT)**

Single exposure

Remarks The classification criteria are met. evaluation May cause drowsiness or dizziness.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

# SECTION 12: Ecological information

## 12.1. Toxicity

#### **General information**

There are no data available on the mixture itself.Do not allow to enter drains or water courses.The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

# Fish toxicity (Components)

1-Methoxy-2-propanol

Species golden orfe (Leuciscus idus)

LC0 > 4600 mg/l

Duration of exposure 96 h

## **Daphnia toxicity (Components)**

1-Methoxy-2-propanol

Species Daphnia magna

EC50 23300 mg/l

Duration of exposure 48 h

#### Algae toxicity (Components)

## 1-Methoxy-2-propanol

Species Desmodesmus

#### Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1 / GB Date revised: 17.12.202

Substance number: 13059039014 Replaces Version: -/GB Print date: 17.12.21

EC50 > 1000 mg/l

Duration of exposure 168 h

## **Bacteria toxicity (Components)**

#### 1-Methoxy-2-propanol

Species activated sludge

EC50 > 1000 mg/l

# 12.2. Persistence and degradability

#### **General information**

No data available

#### **Biodegradability (Components)**

#### 1-Methoxy-2-propanol

Value 90 %

Duration of test 28 d

evaluation Readily biodegradable (according to OECD criteria)

Method OECD 301 F

#### 12.3. Bioaccumulative potential

#### **General information**

There are no data available on the mixture itself.

#### Partition coefficient: n-octanol/water

Remarks Not applicable

## 12.4. Mobility in soil

## **General information**

There are no data available on the mixture itself.

# 12.5. Results of PBT and vPvB assessment

## General information

There are no data available on the mixture itself.

#### 12.6. Other adverse effects

#### **General information**

There are no data available on the mixture itself.

# SECTION 13: Disposal considerations

# 13.1. Waste treatment methods

# Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

## Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

## afety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1/GB

Replaces Version: -/GB Substance number: 13059039014

Print date: 17.12.21

Date revised: 17.12.2021

# SECTION 14: Transport information

	Land transport ADR/RID	Marine transport	Air transport
		IMDG/GGVSee	ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label	***	3	3
14.4. Packing group	III	III	Ш
Special provision	640E		
Limited Quantity	51		
Transport category	3		
14.5. Environmental hazards		no	
	-		-

## Information for all modes of transport

# 14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

# Other information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

# SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## VOC

VOC (EU) 75,33 VOC (EU) 700,6 g/l

## Other information

The product does not contain substances of very high concern (SVHC).

#### Other information

All components are contained in the TSCA inventory or exempted.

All components are contained in the AICS inventory.

#### data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 014, 15 ml MNA

Version: 1/GB Date revised: 17.12.202

Print date: 17.12.21 Replaces Version: -/GB Substance number: 13059039014

All components are contained in the DSL inventory. All components are contained in the ENCS inventory.

#### 15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

# SECTION 16: Other information

# Hazard statements listed in Chapter 3

**EUH066** Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin. H315

Causes skin irritation.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. May damage the unborn child. H360D

#### **CLP categories listed in Chapter 3**

Acute toxicity, Category 4 Acute Tox. 4 Asp. Tox. 1 Aspiration hazard, Category 1 Eye Dam. 1 Serious eye damage, Category 1 Flam. Liq. 3 Flammable liquid, Category 3 Repr. 1B Reproductive toxicity, Category 1B

Skin Irrit. 2 Skin irritation, Category 2

STOT SE 3 Specific target organ toxicity - single exposure, Category 3

## Supplemental information

Item Numbers: 63412-3042

Relevant changes compared with the previous version of the safety data sheet are marked with: \*\*\* This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship. The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.