MSDS for #63412 - MARABU			63412-8152
	EASY MARBL	E	Page
Safety data sheet in accord	ance with regu	Hation (EC) No 1907/2006	
Frade name: Marabu easy m	arble 089, 15 m	nI MNA	
		Version: 1 / GB	Date revised: 13.01.2021
Substance number: 1305903	39089	Replaces Version: - / GB	Print date: 20.10.21
SECTION 1. Identific	ation of th	e substance/mixture	and of the
ompany/undertakin		<u>o ousotanoo/mixturo</u>	
1.1. Product identifier			
Marabu easy marble	089, 15 ml MN	A	
1.2. Relevant identified	uses of the	substance or mixture a	nd uses advised against
Use of the substance/p			
Paint	eparation		
Identified Uses			
SU21		ses: Private households (= gen	
PC9a	•	d paints, thinners, paint remove	ers
1.3. Details of the supp		afety data sheet	
Address/Manufactur			
Marabu GmbH & Co. Asperger Strasse 4	KG		
71732 Tamm			
Germany		4.0	
Telephone no. Fax no.	+49-7141/69 +49-7141/69		
Information provided		product safety	
by / telephone			
E-mail address of person responsible	PRSI@mara	bu.com	
for this SDS			
	one number		
1.4. Emergency telepho			
1.4. Emergency telepho (+49) (0)621-60-4333	55		
(+49) (0)621-60-4333		tion	
(+49) (0)621-60-4333 SECTION 2: Hazards	identifica		
(+49) (0)621-60-4333 SECTION 2: Hazards 2.1. Classification of th	identifica e substance	e or mixture	
SECTION 2: Hazards 2.1. Classification of th Classification (Regu	<mark>identifica</mark> e substance lation (EC) No	e or mixture o. 1272/2008)	
(+49) (0)621-60-4333 <u>SECTION 2: Hazards</u> 2.1. Classification of th Classification (Regularity) Classification (Regularity)	identifica e substance lation (EC) No. 1	e or mixture o. 1272/2008) 1272/2008)	
(+49) (0)621-60-4333 SECTION 2: Hazards 2.1. Classification of th Classification (Regu	identifica e substance lation (EC) No. 1	e or mixture o. 1272/2008) 1272/2008)	
(+49) (0)621-60-4333 <u>SECTION 2: Hazards</u> 2.1. Classification of th Classification (Regu Classification (Regula	identifica e substance lation (EC) No. 1 Flam. Liq. 3	e or mixture o. 1272/2008) 1272/2008) H226	
(+49) (0)621-60-4333 <u>SECTION 2: Hazards</u> 2.1. Classification of th Classification (Regu Classification (Regula 2.2. Label elements	identifica e substance lation (EC) No. 1 Flam. Liq. 3 STOT SE 3	e or mixture o. 1272/2008) ^{1272/2008)} H226 H336	
(+49) (0)621-60-4333 <u>SECTION 2: Hazards</u> 2.1. Classification of th Classification (Regu Classification (Regula 2.2. Label elements Labelling accordin	identifica e substance lation (EC) No. 1 Flam. Liq. 3 STOT SE 3	e or mixture o. 1272/2008) 1272/2008) H226	
(+49) (0)621-60-4333 <u>SECTION 2: Hazards</u> 2.1. Classification of th Classification (Regu Classification (Regula 2.2. Label elements	identifica e substance lation (EC) No. 1 Flam. Liq. 3 STOT SE 3	e or mixture o. 1272/2008) ^{1272/2008)} H226 H336	
(+49) (0)621-60-4333 <u>SECTION 2: Hazards</u> 2.1. Classification of th Classification (Regu Classification (Regula 2.2. Label elements Labelling accordin	identifica e substance lation (EC) No. 1 Flam. Liq. 3 STOT SE 3	e or mixture o. 1272/2008) ^{1272/2008)} H226 H336	
(+49) (0)621-60-4333 <u>SECTION 2: Hazards</u> 2.1. Classification of th Classification (Regu Classification (Regula 2.2. Label elements Labelling accordin	identifica e substance lation (EC) No. 1 Flam. Liq. 3 STOT SE 3	e or mixture o. 1272/2008) ^{1272/2008)} H226 H336	
(+49) (0)621-60-4333 <u>SECTION 2: Hazards</u> 2.1. Classification of th Classification (Regu Classification (Regula 2.2. Label elements Labelling accordin	identifica e substance lation (EC) No. 1 Flam. Liq. 3 STOT SE 3	e or mixture o. 1272/2008) ^{1272/2008)} H226 H336	
(+49) (0)621-60-4333 <u>SECTION 2: Hazards</u> 2.1. Classification of th Classification (Regu Classification (Regula 2.2. Label elements Labelling accordin	identifica e substance lation (EC) No. 1 Flam. Liq. 3 STOT SE 3	e or mixture o. 1272/2008) ^{1272/2008)} H226 H336	
(+49) (0)621-60-4333 <u>SECTION 2: Hazards</u> 2.1. Classification of th Classification (Regu Classification (Regula 2.2. Label elements Labelling accordin Hazard pictograms	identifica e substance lation (EC) No. 1 Flam. Liq. 3 STOT SE 3	e or mixture o. 1272/2008) ^{1272/2008)} H226 H336	
(+49) (0)621-60-4333 SECTION 2: Hazards 2.1. Classification of th Classification (Regular Classification (Regular 2.2. Label elements Labelling accordin Hazard pictograms Signal word	identifica e substance lation (EC) No. 1 Flam. Liq. 3 STOT SE 3	e or mixture o. 1272/2008) ^{1272/2008)} H226 H336	
(+49) (0)621-60-4333 SECTION 2: Hazards 2.1. Classification of the Classification (Regular Classification (Regular 2.2. Label elements Labelling accordin Hazard pictograms Signal word Warning	identifica e substance lation (EC) No. 1 Flam. Liq. 3 STOT SE 3 g to regulati	e or mixture o. 1272/2008) ^{1272/2008)} H226 H336	

						\sim
rade name: Marabu e	asy marble 089, 15					Maral
		Version:				Date revised: 13.01.202
Substance number: 13	8059039089	Replaces	Version	: -/G	В	Print date: 20.10.2
P101	If medical	advice is neede	d, have	product	container	or label at hand.
P102		of reach of child				
P210		y from heat, hot lo smoking.	surfaces	s, spark	s, open fla	mes and other ignition
P271		outdoors or in a	well-ven	tilated a	area	
P405	Store lock			matou t	il ou.	
P501.9	Dispose of	contents/conta	iner as p	oroblem	atic waste.	
Hazardous com	ponent(s) to be	indicated on	label (F	Regula	tion (EC)	No. 1272/2008)
contains		ons, C9-C11, n -1-methylethyl a				cs, < 2% aromatics; anol
2.3. Other hazards						
No special haz	ards have to be me	entioned.				
ECTION 3: Com	iposition/info	ormation o	n ingi	reale	nts	
3.2. Mixtures						
Chemical chara						
Paint based on	alkyd resins and o	n solvents				
Hazardous ingr	edients					
1-Methoxy-2-pro	panol					
CAS No.	107-98-2					
EINECS no.	203-539-1					
Registration no Concentration	. 01-211945 >=		< !	50	%	
Classification (I	Regulation (EC) No	0. 1272/2008)				
	STOT SE :		H336			
	Flam. Liq.	3	H226			
2-Methoxy-1-me	thylethyl acetate					
CAS No.	108-65-6					
EINECS no.	203-603-9					
Registration no	. 01-211947					
Concentration	>=	10	< 2	20	%	
Classification (I	Regulation (EC) No	0. 1272/2008)				
	Flam. Liq.		H226			
	STOT SE		H336			
Hydrocarbons, (C9-C11, n-alkanes	, isoalkanes, c	yclics, «	< 2% ar	omatics	
CAS No.	64742-48-	9				
EINECS no.	265-150-3			D 040 4		
Registration no Concentration	. 01-211946 >=	3258-33 (LIST 10		R 919-8 20	357-5) %	
Concentration	=<	10		20	70	
Classification (I	Regulation (EC) No					
	Asp. Tox.		H304			
	Flam. Liq. STOT SE :		H226 H336			
	5101 3E .		EUH066	;		
2-Butowyothyl o	cotato					
2-Butoxyethyl a CAS No.	cetate 112-07-2					

	marble 089, 15 m	Version:	1 / GB		6	Marabi Date revised: 13.01.2021
Substance number: 13059	039089	Replace	s Versio	n: -/G	В	Print date: 20.10.21
Registration no. Concentration	01-21194751 ⁻ >=	12-47 1	<	10	%	
Classification (Reg	ulation (EC) No. 12 Acute Tox. 4 Acute Tox. 4 Acute Tox. 4	272/2008)	H332 H312 H302			
2-Methoxypropanol CAS No. EINECS no. Concentration	1589-47-5 216-455-5 >=	0,1	<	0,3	%	
Classification (Reg	ulation (EC) No. 1 Skin Irrit. 2 STOT SE 3 Repr. 1B Flam. Liq. 3 Eye Dam. 1	272/2008)	H315 H335 H360D H226 H318			
artificial respiration. After skin contact				-	-	r stopped, administer
Remove contamina cleanser. Do NOT			oughly w	ith soap	and water c	or use recognised skin
minutes and seek in After ingestion If accidentally swall	mmediate medical	advice. outh with pl	enty of v	vater (on	ly if the per	e eyelids apart for at least 10 son is conscious) and obtain
immediate medical 4.2. Most important s	ymptoms and	effects, I			0	d
Until now no sympt 4.3. Indication of any	immediate me cian / treatment	dical att	ention	and sp	oecial trea	atment needed
Hints for the physic Treat symptomatica	,					
	hting measu	res				

MSDS for #63412 - M/	ARABU EASY MARBLE	
Safety data sheet in	accordance with regulation	(EC) No 1907/2006

Trade name: Marabu easy marble 089, 15 ml MNA

Version: 1/GB

Substance number: 13059039089

Date revised: 13.01.2021 Print date: 20.10.21

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); dense black smoke; Nitrogen oxides (NOx)

Replaces Version: - / GB

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires B (Combustible liquid substances) Temperature class T4

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

/ISDS for #63412 - MARABU EASY M Safety data sheet in accordance wit l	h regulation (EC) No 1907/20	06	Page - · ·
rade name: Marabu easy marble 089	9. 15 ml MNA		Ň
	Version: 1/GB		Date revised: 13.01.2021
Substance number: 13059039089	Replaces Version:	- / GB	Print date: 20.10.21
Hints on storage assembly Store away from oxidising age	nts. from strongly alkaline and	strongly acid	materials.
Further information on stora		etterigiy dela	
Observe label precautions. Sto sources of heat and direct sun	ore between 15 and 30 °C in a light. Keep container tightly clo rised access. Containers which	osed. Keep aw	
7.3. Specific end use(s) Paint			
ECTION 8: Exposure con	trols/personal protec	ction	
8.1. Control parameters	<u></u>		
Exposure limit values			
2-Methoxy-1-methylethyl aceta	ate		
List	EH40		
Туре	WEL		
Value	274 mg/m³	50	ppm(V)
Short term exposure limit Skin resorption / sensibilisation	548 mg/m ³ n: Sk; Status: 2011	100	ppm(V)
1-Methoxy-2-propanol			
List	EH40		
Туре	WEL		
Value	375 mg/m³	100	ppm(V)
Short term exposure limit Skin resorption / sensibilisation	560 mg/m³ n: Sk; Status: 2011	150	ppm(V)
2-Butoxyethyl acetate			
List	EH40		
Туре	WEL		
Value	133	20	ppm(V)
Short term exposure limit	332	50	ppm(V)
Skin resorption / sensibilisation			
Derived No/Minimal Effect Lo			
Hydrocarbons, C9-C11, n-alka			
Type of value Reference group	Derived No Effect Level (DI Worker		
Duration of exposure	Long term		
Route of exposure	dermal		
Mode of action	Systemic effects		
Concentration	300		mg/kg
Type of value	Derived No Effect Level (DI	NEL)	
Reference group	Consumer		
Duration of exposure	Long term		
Route of exposure	oral		
Mode of action Concentration	Systemic effects 300		mg/kg
Type of value	Derived No Effect Level (DI	NEL)	
Reference group	Consumer	,	
Duration of exposure	Long term		
	dermal		
Route of exposure			
Route of exposure Mode of action Concentration	Systemic effects 300		mg/kg

MSDS for #63412 - MARABU EASY N Safety data sheet in accordance wit	IAKBLE h regulation (EC) No 1907/2006	Page * *
rade name: Marabu easy marble 08	9, 15 ml MNA	Marab
	Version: 1 / GB	Date revised: 13.01.2021
Substance number: 13059039089	Replaces Version: - / GB	Print date: 20.10.21
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	900	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1500	mg/m³
2-Methoxy-1-methylethyl acet	ate	
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	796	mg/kg/d
Concentration	790	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	275	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	320	mg/kg/d
Type of value Reference group	Derived No Effect Level (DNEL) Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	33	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure Route of exposure	Long term	
•	inhalative Local effects	
Mode of action Concentration	33	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	36	mg/kg/d

Page 6 of 17

/ISDS for #63412 - MARABU EASY M Safety data sheet in accordance wit	AKBLE h regulation (EC) No 1907/2006	Page
-	2	Ň
rade name: Marabu easy marble 089		Marab
	Version: 1/GB	Date revised: 13.01.2021
Substance number: 13059039089	Replaces Version: - / GB	Print date: 20.10.21
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Lifetime	
Route of exposure Mode of action	inhalative Local effects	
Concentration	550	mg/m³
Concontration		
1-Methoxy-2-propanol		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Acute	
Route of exposure Mode of action	inhalative	
Concentration	Local effects	mg/m³
Concentration	553,5	mg/m ^s
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	50,6	mg/person/ d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure Mode of action	inhalative Systemic effects	
Concentration	369	mg/m³
Concentration	303	iiig/iii
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure Mode of action	dermal	
Concentration	Systemic effects 18,1	mg/kg
Concentration	10,1	iiig/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	43,9	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	malkald
Concentration	3,3	mg/kg/d
2-Butoxyethyl acetate		
Reference substance	2-Butoxyethyl acetate	
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	

Page 7 of 17

/ISDS for #63412 - MARABU EASY N Safety data sheet in accordance wit	IAKBLE In regulation (EC) No 1907/2006	Page
-		
rade name: Marabu easy marble 08		Marab
	Version: 1 / GB	Date revised: 13.01.202
Substance number: 13059039089	Replaces Version: - / GB	Print date: 20.10.2
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	133	mg/m³
		5
	2-Butoxyethyl acetate	
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker Short torm	
Duration of exposure	Short term	
Route of exposure Mode of action	inhalative	
Concentration	Local effects 333	mg/m³
Concentration	333	ing/ins
	2-Butoxyethyl acetate	
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	169	mg/kg/d
	2-Butoxyethyl acetate	
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	120	mg/kg/d
	2-Butoxyethyl acetate	
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	80	mg/m³
	2-Butoxyethyl acetate	
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	200	mg/m³
	2 Putovuoto di acatata	
	2-Butoxyethyl acetate	
Type of value Reference group	Derived No Effect Level (DNEL) General Population	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	102	mg/kg/d
	2-Butoxyethyl acetate	
Type of value	Derived No Effect Level (DNEL)	
Reference group Duration of exposure	General Population Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
	Cysternic enects	

Page 8 of 17

MSDS for #63412 - MARABU EASY M Safety data sheet in accordance wit	ARBLE h regulation (EC) No 1997/2006	Page A m	
rade name: Marabu easy marble 089	9, 15 ml MNA	Marah	
	Version: 1 / GB	Date revised: 13.01.202	
Substance number: 13059039089	Replaces Version: - / GB	Print date: 20.10.2	
Concentration	72	mg/kg/d	
	0. Dutou with discontate		
	2-Butoxyethyl acetate		
Type of value	Derived No Effect Level (DNEL)		
Reference group	General Population		
Duration of exposure	Long term		
Route of exposure	oral		
Mode of action	Systemic effects		
Concentration	8,6	mg/kg/d	
	2-Butoxyethyl acetate		
Type of value	Derived No Effect Level (DNEL)		
Reference group	General Population		
Duration of exposure	Short term		
Route of exposure	oral		
Mode of action	Systemic effects		
Concentration	36	mg/kg/d	
Predicted No Effect Concent	tration (PNEC)		
2-Methoxy-1-methylethyl acet			
Reference substance	2-Methoxy-1-methylethyl acetate		
Type of value	PNEC		
Type	Freshwater		
Concentration	0,635	mg/l	
Concentration	0,033	iiig/i	
Type of value	PNEC		
Туре	Freshwater sediment		
Concentration	3,29	mg/kg	
Type of value	PNEC		
Туре	Soil		
Concentration	0,29	mg/kg	
Source	Literature value		
Type of value	PNEC		
Туре	Sewage treatment plant (STP)		
Concentration	100	mg/l	
Source	Literature value	<u> </u>	
Type of value	PNEC		
Туре	Marine sediment		
Concentration	0,329	mg/kg	
Source	Literature value	5. 5	
Type of value	PNEC		
Туре	Saltwater		
Concentration	0,0635	mg/l	
1-Methoxy-2-propanol			
Type of value	PNEC		
Type	Freshwater		
Concentration	10	mg/l	
Type of value	PNEC		
Type	Water		
Concentration	41,6	mg/kg	
	,•		

de name: Marabu easy marble 089	9. 15 ml MNA		
· · · · · · · · · · · · · · · · · · ·	Version: 1/GB	Date revised: 13.01.202	
bstance number: 13059039089	Replaces Version: - / GB	Print date: 20.10.2	
Type of value	PNEC		
Туре	Sediment		
Concentration	41,6	mg/kg	
Type of value	PNEC		
Туре	Marine sediment		
Concentration	4,17	mg/kg	
Concentration		iiig/kg	
Type of value	PNEC		
Туре	Soil		
Concentration	2,47	mg/kg	
Type of value	PNEC		
Туре	Sewage treatment plant (STP)		
Concentration	100	mg/l	
0 Destauranthad a set of s			
2-Butoxyethyl acetate	0. Dutau vathul a satata		
Reference substance	2-Butoxyethyl acetate		
Type of value	PNEC		
Туре	Water		
Concentration	0,304	mg/l	
Source	Literature value		
	2-Butoxyethyl acetate		
Type of value	PNEC		
Туре	Aquatic		
Concentration	0,0304	g/l	
Source	Literature value	g/1	
	2-Butoxyethyl acetate		
Type of value	PNEC		
Туре	Sediment		
Concentration	2,03	mg/kg	
Source	Literature value		
	2-Butoxyethyl acetate		
Type of value	PNEC		
Type	Marine sediment		
Concentration	0,203	mg/kg	
		iiig/kg	
Source	Literature value		
	2-Butoxyethyl acetate		
Type of value	PNEC		
Туре	Soil		
Concentration	0,68	mg/kg	
Source	Literature value	· · · · · · · · · · · · · · · · · · ·	

Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

DS for #63412 - MARABU EASY	MARBLE 'ith regulation (EC) No 1907/2006	Page
ety data sheet in accordance w		
de name: Marabu easy marble 0	89, 15 ml MNA	
	Version: 1 / GB	Date revised: 13.01.202
bstance number: 13059039089	Replaces Version: - / GB	Print date: 20.10.2
Hand protection		
-	ial or combination of materials that will	give unlimited resistance to any
individual or combination of	chemicals.	
	andling nitrile rubber gloves with textile	undergloves are required.
Material thickness Breakthrough time	> 0,5 mm < 30 min	
	t be greater than the end use time of the	e product.
	ation provided by the glove manufacture	
Gloves should be replaced r	egularly and if there is any sign of dama	
	re free from defects and that they are s	
maintenance.	eness of the glove may be reduced by p	onysical/ chemical damage and poor
	protect the exposed areas of the skin, th	ney should however not be applied
Eye protection	a.	
	ed to protect against splash of liquids.	
• • •	a to protoot against spiasit of liquids.	
Body protection	vorollo or opvorollo oro pormally suitable	
Collon of cotton/synthetic ov	veralls or coveralls are normally suitable	÷.
<u>CTION 9: Physical and</u> 1. Information on basic phy Form	ysical and chemical properties	
1. Information on basic phy	ysical and chemical properties	
1. Information on basic phy Form Colour	ysical and chemical properties Liquid coloured	
1. Information on basic phy Form Colour Odour	ysical and chemical properties Liquid coloured	
1. Information on basic phy Form Colour Odour Odour threshold	ysical and chemical properties Liquid coloured solvent-like	
1. Information on basic phy Form Colour Odour Odour threshold Remarks	ysical and chemical properties Liquid coloured solvent-like	
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks	ysical and chemical properties Liquid coloured solvent-like No data available	
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value	ysical and chemical properties Liquid coloured solvent-like No data available	
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable	
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable	
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined not determined	
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined not determined	℃
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boi Value Pressure	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined iling range appr. 120 1.013 hPa	
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boi Value Pressure Source	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined iling range appr. 120	
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boi Value Pressure Source Flash point	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined iling range appr. 120 1.013 hPa	°C
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boi Value Pressure Source Flash point Value	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined iling range appr. 120 1.013 hPa Literature value 30	
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boi Value Pressure Source Flash point Value Method	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined illing range appr. 120 1.013 hPa Literature value 30 ASTM D 6450 (CCCFP)	°C
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boi Value Pressure Source Flash point Value Method Evaporation rate (ether = 1	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined illing range appr. 120 1.013 hPa Literature value 30 ASTM D 6450 (CCCFP)):	°C
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boi Value Pressure Source Flash point Value Method Evaporation rate (ether = 1 Remarks	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined illing range appr. 120 1.013 hPa Literature value 30 ASTM D 6450 (CCCFP)	°C
 Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boil Value Pressure Source Flash point Value Method Evaporation rate (ether = 1 Remarks Flammability (solid, gas) 	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined illing range appr. 120 1.013 hPa Literature value 30 ASTM D 6450 (CCCFP)):	°C
 Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boi Value Pressure Source Flash point Value Method Evaporation rate (ether = 1 Remarks Flammability (solid, gas) Not applicable 	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined iling range appr. 120 1.013 hPa Literature value 30 ASTM D 6450 (CCCFP)): not determined	°C
1. Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boi Value Pressure Source Flash point Value Method Evaporation rate (ether = 1 Remarks Flammability (solid, gas) Not applicable	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined iling range appr. 120 1.013 hPa Literature value 30 ASTM D 6450 (CCCFP)): not determined	°C
 Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boi Value Pressure Source Flash point Value Method Evaporation rate (ether = 1 Remarks Flammability (solid, gas) Not applicable Upper/lower flammability on Lower explosion limit 	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined iling range appr. 120 1.013 hPa Literature value 30 ASTM D 6450 (CCCFP)): not determined pr explosive limits appr. 0,7	°C °C
 Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boi Value Pressure Source Flash point Value Method Evaporation rate (ether = 1 Remarks Flammability (solid, gas) Not applicable Upper/lower flammability of Lower explosion limit Upper explosion limit 	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined illing range appr. 120 1.013 hPa Literature value 30 ASTM D 6450 (CCCFP)): not determined or explosive limits appr. 0,7 appr. 13,7	°C
 Information on basic phy Form Colour Odour Odour threshold Remarks pH value Remarks Melting point Remarks Freezing point Remarks Initial boiling point and boi Value Pressure Source Flash point Value Method Evaporation rate (ether = 1 Remarks Flammability (solid, gas) Not applicable Upper/lower flammability on Lower explosion limit 	ysical and chemical properties Liquid coloured solvent-like No data available Not applicable not determined iling range appr. 120 1.013 hPa Literature value 30 ASTM D 6450 (CCCFP)): not determined pr explosive limits appr. 0,7	°C °C

ade name: Marabu easy marble		Version:			Date	e revised: 13.01.2021
ubstance number: 13059039089	9	Replaces '	Version:	- / GB		Print date: 20.10.21
Value Temperature		8 20	°C		hPa	
Method	calcula	ited				
Vapour density						
Remarks	not det	ermined				
Density					4	
Value Temperature		1,01 20	°C		g/cm³	
Method		20 NISO 281 ⁻	-			
Solubility in water	DINE	100 201	•			
Remarks	partiall	y miscible				
Partition coefficient: n-oc		-				
Remarks	Not ap	plicable				
Ignition temperature						
Value Source	appr.	200 Jre value			°C	
	Literati	lie value				
Viscosity						
dynamic				50		
Value		30 40	to °C	50	mPa.s	
		40	C			
Efflux time		05		70	_	
Value Temperature		25 20	to °C	70	S	
Method	DIN 53	20 211 4 mm	-			
Explosive properties						
evaluation	no					
Oxidising properties	110					
evaluation	None k	noun				
	None R	nown				
2. Other information						
Other information						
The physical specifications	s are approxin	nate value	s and ref	fer to the	used safety releva	ant component(s).
<u>ECTION 10: Stability an</u>	<u>nd reactiv</u>	<u>/ity</u>				
0.1. Reactivity						
No hazardous reactions w	hen stored an	d handled	accordir	na to pres	scribed instruction	3
		a nanalea	accordin	ig to prot		
0.2. Chemical stability Stable under recommende	ed storage and	d handling	conditio	ns (see s	ection 7).	
0.3. Possibility of hazardo Keep away from oxidising exothermic reactions.			e and str	ongly aci	d materials in orde	er to avoid
0.4. Conditions to avoid When exposed to high tem	nperatures ma	y produce	hazardo	ous deco	mposition products	5.
0.5. Incompatible material	c					

Page 12(17)

/ISDS for #63412 - MARABU EASY Safety data sheet in accordance v			No 1007/2	006			Page + + + +
Juicty data sheet in decordance	. reg t		, 110 1301/2				
rade name: Marabu easy marble	089, 15 r	nl MNA					Marril
		Versio	n: 1/GB			Date revised:	13.01.202
Substance number: 13059039089		Replac	es Version:	- / GB		Print d	ate: 20.10.2
ECTION 11: Toxicologi	cal inf	ormatio	on				
11.1. Information on toxicol							
Acute oral toxicity	- 3						
ATE	>	2.000			mg/kg		
Method	calcul	ated value	(Regulation	EC) No.	1272/2008)		
Acute oral toxicity (Comp	onents)						
1-Methoxy-2-propanol							
Species	rat	5000					
LD50		5200			mg/kg		
2-Butoxyethyl acetate Species	rat						
LD50	iat	1880			mg/kg		
Method	OECE						
Acute dermal toxicity							
ATE	>	2.000			mg/kg		
Method	calcul	ated value	(Regulation	EC) No.	0 0		
Acute dermal toxicity (Co	mponer	nts)					
1-Methoxy-2-propanol	-	-					
Species	rabbit						
LD50		14000			mg/kg		
2-Butoxyethyl acetate							
Species	rabbit						
LD50		1480			mg/kg		
Acute inhalational toxicity	/						
ATE Administration/Form	> Vonor	20			mg/l		
Method	Vapor		(Regulation	EC) No	1272/2008)		
ATE	>	5	(itegulation)	LO) NO.	mg/l		
Administration/Form	Dust/N	Vist			0		
Method			(Regulation				
Remarks			ole data, the	classifica	ation criteria a	ire not met.	
Acute inhalative toxicity (Compoi	nents)					
2-Butoxyethyl acetate							
Species	rat	2.66			ma/l		
LD0 Duration of exposure		2,66 4	h		mg/l		
Administration/Form	Vapor	-					
Method	OECE	0 403					
Skin corrosion/irritation							
Remarks	Based	d on availat	ole data, the	classifica	tion criteria a	ire not met.	
Skin corrosion/irritation (Compor	nents)					
2-Methoxy-1-methylethyl ac	=	-					
Species	rabbit						
evaluation	non-ir	ritant					
Serious eye damage/irrita	tion						
Remarks	Based	d on availat	ole data, the	classifica	ation criteria a	ire not met.	
Sensitization							
Remarks	Based	d on availat	le data. the	classifica	tion criteria a	re not met.	

Page 13(17)

MSDS for #63412 - MARABU EA	SY MARBLE		Page 14 of
Safety data sheet in accordance		lo 1907/2006	
Trade name: Marabu easy mark	ole 089, 15 ml MNA		
	Version:	1 / GB	Date revised: 13.01.2021
Substance number: 130590390	89 Replaces	Version: -/GB	Print date: 20.10.21
Mutagenicity			
Remarks	Based on available	data, the classification c	riteria are not met.
Reproductive toxicity			
Remarks	Based on available	data, the classification c	riteria are not met.
Carcinogenicity			
Remarks		data, the classification c	criteria are not met.
Specific Target Organ	Toxicity (STOT)		
Single exposure			
Remarks	The classification c		
evaluation	May cause drowsin	ess of uizziness.	
Repeated exposure Remarks	Based on available	data, the classification c	riteria are not met.
Aspiration hazard Based on available data	, the classification criteria	are not met.	
Experience in practice	, e elacomodion ontona		
and adverse effects on I dizziness, fatigue, musc Solvents may cause sor contact with the mixture dermatitis and absorptio reversible damage. Inge known, delayed and imm long-term exposure by c Other information There are no data availa The mixture has been a	kidney, liver and central nular weakness, drowsines ne of the above effects by may cause removal of na n through the skin. The lives stion may cause nausea,	ervous system. Symptor as and in extreme cases, absorption through the tural fat from the skin re quid splashed in the eyes diarrhoea and vomiting. hronic effects of compor I routes of exposure and	skin. Repeated or prolonged sulting in non-allergic contact s may cause irritation and This takes into account, where nents from short-term and eye contact.
SECTION 12: Ecologic	al information		
12.1. Toxicity			
mixture has been asses	able on the mixture itself.E sed following the summat langerous for the environ	ion method of the CLP F	ins or water courses.The Regulation (EC) No 1272/2008
Fish toxicity (Compone	ents)		
1-Methoxy-2-propanol Species LC0 Duration of exposure	golden orfe (Leucis > 4600 96	cus idus) mg/l	
Daphnia toxicity (Comp	oonents)		
1-Methoxy-2-propanol Species EC50 Duration of exposure	Daphnia magna 23300 48	mg/l	
Algae toxicity (Compor	nents)		
1-Methoxy-2-propanol Species	Desmodesmus		
0,000	2.000000000		

Safety data sheet in accordance w	nin lega		110 100172		
rade name: Marabu easy marble 0	89, 15 m	nl MNA			Marah
		Version:	1 / GB		Date revised: 13.01.2021
Substance number: 13059039089		Replace	s Version:	- / GB	Print date: 20.10.21
EC50	>	1000		mg/l	
Duration of exposure		168	h		
Bacteria toxicity (Compone	ents)				
1-Methoxy-2-propanol	o otivot				
Species EC50	>	ed sludge 1000		mg/l	
12.2. Persistence and degrad	dability	,		-	
General information					
No data available					
Biodegradability (Compon	ents)				
1-Methoxy-2-propanol					
Value Duration of test		90 28	d	%	
evaluation	Readil		d able (accor	ding to OECD c	riteria)
Method	OECD		,	0	,
12.3. Bioaccumulative poten	tial				
General information					
There are no data available	on the m	nixture itself	•		
Partition coefficient: n-oct	anol/wa	iter			
Remarks	Not	applicable			
12.4. Mobility in soil					
General information					
There are no data available	on the m	nixture itself	•		
12.5. Results of PBT and vPv	vB asse	essment			
General information					
There are no data available	on the m	nixture itself			
12.6. Other adverse effects					
General information					
There are no data available	on the m	nixture itself			
ECTION 13: Disposal co	onside	rations			
13.1. Waste treatment metho					
		o			
Disposal recommendation Do not allow to enter drains		-			
Wastes and emptied contain			ified in acco	ordance with rele	evant national regulation.
The European Waste Catalo	-				
EWC waste code	08 01 '		ste paint an gerous sub		ning organic solvents or other
If this product is mixed with	other wa		0		າay no longer apply and the
appropriate code should be For further information conta			authority		
Disposal recommendation	,		cathonity.		
-	-		eet, advice	should be obtai	ned from the relevant waste
authority on the classificatio	n of emp	ty containe	s.		
Empty containers must be s	crapped	or reconditi		umber 150110)	

MSDS for #63412 - MARABU EASY MARBLE Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Marabu easy marble 089, 15 ml MNA

Version: 1/GB

Replaces Version: - / GB

Date revised: 13.01.2021 Print date: 20.10.21

Substance number: 13059039089

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label			<u>×</u>
14.4. Packing group	Ш	Ш	ш
Special provision	640E		
Limited Quantity	51		
Transport category	3		
14.5. Environmental hazards	-	no	-

Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7.	Transport in bulk	according to Anne	ex II of Marpol and	I the IBC Code

no

SECTION 15: Regulatory information

15.1. Safety, health or mixture	and en	vironmental reg	ulations/I	egislation sp	ecific	for the subs	tance
Major-accident o	categorie	es acc. 96/82/EC					
Category	6	Flammable		5.000.000	kg	50.000.000	kg
VOC							
VOC (EU) VOC (EU)		69,78	% 697,8	g/l			
Other information	on						

The product does not contain substances of very high concern (SVHC).

Item Numbers: 63412-8152

Page 16(17)

Page 🗠

de name: Marabu easy marble	89, 15 ml MNA	
	Version: 1/GB	Date revised: 13.01.202
bstance number: 13059039089	Replaces Version: - / GB	Print date: 20.10.2
	cal safety assessment has not been carried	out.
CTION 16: Other infor Hazard statements listed		
EUH066	Repeated exposure may cause skin dryne	ess or cracking
H226	Flammable liquid and vapour.	so or ordoning.
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airwa	avs.
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H360D	May damage the unborn child.	
CLP categories listed in C	napter 3	
Acute Tox. 4	Acute toxicity, Category 4	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Dam. 1	Serious eye damage, Category 1	
Flam. Liq. 3	Flammable liquid, Category 3	
Repr. 1B	Reproductive toxicity, Category 1B	
Skin Irrit. 2	Skin irritation, Category 2	
STOT SE 3	Specific target organ toxicity - single expos	sure, Category 3
Supplemental information		
Relevant changes compare This information is based o guarantee for any specific p The information in this Safe legislation. It provides guidance on hea construed as any guarante The product should not be to the supplier and obtainin As the specific conditions of for ensuring that the require The information contained	d with the previous version of the safety data our present state of knowledge. However, it roduct properties and shall not establish a le y Data Sheet is based on the present state of th, safety and environmental aspects of the of technical performance or suitability for pa sed for purposes other than those shown in y written handling instructions. use of the product are outside the supplier's ments of relevant legislation are complied wi h this safety data sheet does not constitute th by other health and safety legislation.	t should not constitute a gally valid relationship. of knowledge and current product and should not be articular applications. Section 1 without first referring s control, the user is responsible ith.