

63993-1060

|  | TECHNICAL DATA<br><b>RUST-OLEUM® SPECIALTY<br/>GLITTER INTERIOR WALL EFFECT</b> | SPC-69 |
|--|---|--------|
|  |   |        |

**DESCRIPTION AND USES**

Rust-Oleum® Glitter Interior Wall Effect is an intense glitter paint that provides multi-dimensional shimmer and sparkle. Can be applied to primed drywall, wood, metal, plastic and hardboard. Formulated to provide a decorative, slightly textured glitter finish to most surfaces.

**PRODUCTS**

| SKU    | DESCRIPTION (28 fl. oz.) |
|--------|--------------------------|
| 360218 | Harvest Gold             |
| 360219 | Sterling Silver          |
| 323860 | Iridescent Clear         |
| 360221 | Rose Gold                |
| 360222 | Copper                   |

**PRODUCT APPLICATION**

**READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT.**

**SURFACE PREPARATION**

Remove loose paint and rust with wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry. Tape around the area you wish to paint before beginning.

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC.** EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**PRIMING**

To provide superior adhesion and coverage, Zinsser® Bulls Eye 1-2-3® white primer is recommended on bare wood, drywall, metal and other porous surfaces. After priming bare wood, sand lightly to smooth surface. Follow primer manufacturer's instructions for dry time.

**BASECOAT**

After priming and for best results, we recommend applying a complimentary colored basecoat before painting to increase hiding.

See recommended colored basecoats. Follow basecoat manufacturer's instructions for dry time.

**RECOMMENDED COLORED BASECOATS**

Sterling Silver: Zinsser® Bulls Eye 1-2-3® gray primer  
Harvest Gold: Golden brown satin or non-flat paint  
Iridescent Clear: Use any color satin or non-flat paint

**PRODUCT APPLICATION (cont.)****APPLICATION**

For interior use only. Do not apply paint on surfaces which are exposed to high humidity. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying.

**PAINTING:** Rust-Oleum® Glitter Interior Wall Effect can be applied with a roller, brush or paint sprayer. With all application methods, use multiple thin, uniform coats to build glitter effect. Stir paint every couple of minutes during application. The Glitter Paint may appear to have a gray tint inside the can and when applied. This will disappear as the paint dries on the surface.

**ROLL (Recommended):** Stir thoroughly. Use a 3/8" nap roller for best results. Fully wet roller with paint and remove excess before applying to wall. Roll glitter on the wall by rolling up and down as well as side to side until it is evenly distributed on the surface. Rewet roller as needed.

**BRUSH:** Stir thoroughly. Use a good quality synthetic brush. Brush light coats and spread glitter evenly over surface. For best results, alternate brushing directions with successive coats to ensure even coverage. Use light, even strokes to ensure the smoothest finish.

**SPRAY:** Stir thoroughly. Mix well in spray gun before application. DO NOT shake. Use fan pattern for best results. Dries to recoat in approximately 1-2 hours.

**Note:** If thinning is necessary, thin 5-10% by volume with water.

**EDGING:** Stir thoroughly. Use a good quality synthetic brush. Brush a light coat then immediately lightly dab to evenly distribute glitter for best coverage. Rewet brush as needed.

**NOTE:** When Glitter Interior Wall Effect is no longer desired, simply prime and re-paint. Sanding is not required, but may be needed for a smoother surface.

**DRY AND RECOAT TIMES**

Based on 77°F (25°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 2 hours, to handle in 6 hours. Wait 24 hours before using painter's tape over glitter coating. Hang pictures in 3-5 days. Fully dry in 7 days. Allow additional coats to dry 2-4 hours between coats.

**COVERAGE**

Up to 30 sq. ft. per quart. For best coverage results, use the basecoat suggestions. The first coat does not provide full coverage; full coverage requires 3-5 coats.

**CLEAN UP**

Clean brush and other application tools immediately with soap and water. Follow spray gun manufacturer's instructions for cleaning equipment.

|   |                   | TECHNICAL DATA   | SPC-69 |  |  |
|---|-------------------|--|--------|--|--|
|  |                   | <b>RUST-OLEUM® SPECIALTY<br/>GLITTER INTERIOR WALL EFFECT</b>                        |        |  |  |
| <b>PHYSICAL PROPERTIES</b>  |                   |  |        |  |  |
|   |                   |  |        |  |  |
|   |                   | <b>GLITTER INTERIOR WALL EFFECT</b>  |        |  |  |
| <b>Resin Type</b>   |                   | Water-based  |        |  |  |
| <b>Weight</b>   | <b>Per Gallon</b> | 8.6–8.8 lbs.   |        |  |  |
|   | <b>Per Liter</b>  | 1.03–1.05 kg   |        |  |  |
| <b>Solids</b>   | <b>By Weight</b>  | 32.6–33.1%   |        |  |  |
|   | <b>By Volume</b>  | 29.3–30.2%   |        |  |  |
| <b>Volatile Organic Compounds</b>   |                   | <50 g/l  |        |  |  |
| <b>Practical Coverage<br/>(assume 15% material loss)</b>                          |                   | 1-2 coats for light coverage and 3-5 coats for full coverage<br>Up to 30 sq. ft./qt. |        |  |  |
| <b>Dry Times at 70-80°F<br/>(21-27°C) and 50%<br/>Relative Humidity</b>           | <b>Touch</b>      | 2 hours  |        |  |  |
|   | <b>Handle</b>     | 6 hours  |        |  |  |
|   | <b>Recoat</b>     | 2-4 hours<br>1-2 hours if applied by paint sprayer                                   |        |  |  |
|   | <b>Full Cure</b>  | 3-5 days to hang pictures<br>Fully dry in 7 days                                     |        |  |  |
| <b>Shelf Life</b>   |                   | 2 years  |        |  |  |
| <b>Flash Point</b>  |                   | >200°F   |        |  |  |
| <b>Safety Information</b>   |                   | For additional information, see SDS  |        |  |  |

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Item Numbers: 63993-1060

Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, Illinois 60061

Phone: 800-481-4785  
[www.rustoleum.com](http://www.rustoleum.com)

Form: ARJ-1484  
Rev.: 091321

Page 2 of 2