

## SAFETY DATA SHEET

76099-0512

## 1. Product identification

<u>TRADE NAME (AS LABELED):</u>	<b>GLOSS</b>
<u>PART NUMBER:</u>	DAS12-7
<u>SKU#:</u>	
<u>UPC#:</u>	
<u>PRODUCT USE:</u>	Aerosol coating
<u>CHEMICAL NAME:</u>	Mixture
<u>CHEMICAL FAMILY:</u>	Aerosol Coating
<u>SUPPLIER NAME:</u>	DECOART, INC.
<u>SUPPLIER ADDRESS:</u>	49 Cotton Ave Stanford, KY 40484
<u>SUPPLIER EMERGENCY PHONE:</u>	(800) 424-9300 CHEMTREC
<u>SUPPLIER BUSINESS PHONE:</u>	(606) 365-3193
<u>SUPPLIER FAX NUMBER:</u>	(606) 365-9739
<u>DISTRIBUTOR NAME:</u>	Sillard and Rendich Ltda Ruth: 77013940-6
<u>DISTRIBUTOR ADDRESS:</u>	3 Poniente 555 Vina del Mar - Chile
<u>DISTRIBUTOR PHONE:</u>	+56 322884392
<u>MANUFACTURER NAME:</u>	Quest Industrial Products, LLC.
<u>MANUFACTURER ADDRESS:</u>	N92 W14701 Anthony Avenue Menomonee Falls, WI, 53051 United States
<u>MANUFACTURER PHONE:</u>	(262) 255-9500
<u>DATE OF PREPARATION:</u>	March 3, 2021

## 2. Hazard identification

**Hazard Statement:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

**EU LABELING AND CLASSIFICATION:**

Classification of the substance or mixture according to Regulation (EC) No1272/2008

**GHS Classification:** Flammable Aerosols - Category 1

Gases under pressure - Liquefied Gas

Serious eye damage/irritation - Category 2A

Reproductive toxicity - Category 2

Specific target organ toxicity, single exposure - Category 3 narcotic effects

Specific target organ toxicity, repeated exposure - Category 2

Hazardous to the aquatic environment, acute hazard - Category 3

Hazardous to the aquatic environment, long-term hazard - Category 3

**Components Contributing to Hazard:****Label Elements:**

Pictogram



**Signal Word:** Danger!

# SAFETY DATA SHEET

**Precautionary Statement:**

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. -No smoking- Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison control center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazards Not Otherwise Classified (HNOC):** None known.

**Supplemental Information:** 89.48% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 89.48% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

**NOTE:**

ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250: 2000.

## 3. Composition and information on ingredients

## SAFETY DATA SHEET

Hazardous Ingredients	CAS #	EINECS #	ICSC #	WT #	Hazard Symbol Risk Phrases
ACETONE	67-64-1	200-662-2		<=40%	
N-BUTANE	106-97-8	203-448-7		<=20%	
PROPANE	74-98-6	200-827-9		<=20%	
PROPYLENE GLYCOL METHYL ETHER ACETATE	108-65-6	203-603-9		<=10%	
TOLUENE	108-88-3	203-625-9		<=10%	
2-METHYLPROPYL ISOBUTYRATE	97-85-8	202-612-5		<=5%	
ISOBUTYL ACETATE	110-19-0	203-745-1		<=5%	
N-BUTYL ACETATE	123-86-4	204-658-1		<=5%	
Other components below reportable levels				<=10%	

### 4. First-aid measures

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved. Show this safety data sheet to the doctor in attendance.

**INHALATION:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

**SKIN EXPOSURE:** Wash with soap and water. If skin irritation occurs/persists: Get medical advice/attention.

**EYE EXPOSURE:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**INGESTION:** Not likely, due to the form of the product. Rinse mouth. In the unlikely event of swallowing contact a physician or poison control center.

**Most Important Symptoms/Effects, Acute and Delayed:** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.

**Indication of Immediate Medical Attention and Special Treatment Needed:** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

### 5. Fire-fighting measures

**Suitable Extinguishing Media:** Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media:** Do not use water jet as an extinguisher, as this will spread the fire.

# SAFETY DATA SHEET

**Specific Hazards Arising from the Chemical:** Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

**Special Protective Equipment and Precautions for**


**Firefighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SBCA.

**Fire Fighting Equipment/Instructions:** In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

**Specific Methods:** Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from the fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

**General Fire Hazards:** Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

**NFPA RATING**



Hazard Scale: **0** = Minimal **1** = Slight  
**2** = Moderate  
**3** = Serious **4** = Severe

## 6. Accidental release measures

**SPILL AND LEAK RESPONSE:**

Remove all ignition sources. Avoid heat, sparks, flames or anything that could cause a fire. Ventilate area of spill and adjacent low lying areas

Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand, or earth and place into containers. Following product recovery, flush area with water.

**Personal precautions, Protective Equipment, and Emergency Procedures:** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean up. Do not breathe mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Small Spills: Wipe up with absorbant material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental Protections:** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses, or onto the ground.

## 7. Handling and storage

**Precautions for Safe Handling:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces - No Smoking-. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be

## SAFETY DATA SHEET

prevented. Do not allow backfeed into the container. Purge air from the system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink, or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

**Conditions for Safe Storage, Including any Incompatibilities:** Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate, or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store in a well-ventilated place. Store away from incompatible materials (see section 10 of the SDS).

### 8. Exposure controls - personal protection

#### Exposure Controls/Personal Protection

##### EXPOSURE LIMITS/GUIDELINES

Component Name:	CAS #	ACGIH TLVs	OSHA-PELs	NIOSH-TLVs	Other
ACETONE	67-64-1	STEL 750ppm TWA 500ppm	PEL 1000ppm	TWA 250ppm	
N-BUTANE	106-97-8	STEL 1000ppm		TWA 800ppm	
PROPANE	74-98-6		PEL 1000ppm	TWA 250ppm	
PROPYLENE GLYCOL METHYL ETHER ACETATE	108-65-6				WEEL: twa 50 PPM
TOLUENE	108-88-3	TWA 20ppm	Ceiling 300ppm TWA 200ppm	STEL 150ppm TWA 100ppm	
2-METHYLPROPYL ISOBUTYRATE	97-85-8				
ISOBUTYL ACETATE	110-19-0	TWA 150 ppm	PEL 150 ppm	TWA 150 ppm	
N-BUTYL ACETATE	123-86-4	STEL 200 ppm TWA 150 ppm	PEL 150 ppm	STEL 200 ppm TWA 150 ppm	
Other components below reportable levels					

International exposure limits may be established for the components of this product. Please check with competent authority in each country for the most recent limits in place.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

#### **Exposure Guidelines:**

# SAFETY DATA SHEET

**US - California OELs: Skin Designation** - PROPYLENE GLYCOL METHYL ETHER ACETATE (CAS 108-65-6) - Can be absorbed through the skin.

TOLUENE (CAS 108-88-3) - Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin Designation Applies** -TOLUENE (CAS 108-88-3) - Skin designation applies.

**Appropriate Engineering Controls:** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

## Individual Protection Measures, Such as Personal Protective Equipment

**Eye/Face Protection:** Wear safety glasses with side shields (or goggles).

**Skin Protection: Hand Protection** - For prolonged or repeated skin contact use suitable gloves. **Other** - Wear appropriate chemical resistant clothing.

**Respiratory Protection** If permissible levels are exceeded use NIOSH mechanical filter/organic vapor cartridge of an air-supplied respirator.

**Thermal Hazards:** Wear appropriate thermal protective clothing, when necessary.

**General Hygiene Considerations** - Observe any medical surveillance requirements. When using, do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

<b>Physical State</b>	Liquid
<b>Form</b>	Aerosol. Liquefied gas.
<b>Color</b>	Not Available
<b>Odor</b>	Not Available
<b>Odor Threshold</b>	Not Available
<b>pH</b>	Not Available
<b>Melting Point/Freezing Point</b>	-305.68°F (-187.6°C) estimated
<b>Initial Boiling Point</b>	-43.78°F (-42.1°C) estimated
<b>Flash Point</b>	-156°F (-104.4°C) estimated
<b>Evaporation Rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammability Limit - Lower (%)</b>	1.3% estimated
<b>Flammability Limit - Upper (%)</b>	12.8% estimated
<b>Explosive Limit - Lower (%)</b>	Not available.
<b>Explosive Limit - Upper (%)</b>	Not available.
<b>Vapor Pressure</b>	2216.58 hPa estimated
<b>Vapor Density</b>	Not available.
<b>Relative Density</b>	Not available.
<b>Solubility (water)</b>	Not available.
<b>Partition Coefficient (n-octanol/water)</b>	Not available.

# SAFETY DATA SHEET

<b>Auto-Ignition Temperature</b>	550°F (287.78°C) estimated
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Density</b>	6.14 lbs/gal
<b>Explosive Properties</b>	Not explosive.
<b>Flammability Class</b>	Flammable IA estimated
<b>Heat of Combustion (NFPA 30B)</b>	29.05 kJ/g estimated
<b>Oxidizing Properties</b>	Not oxidizing
<b>Percent Volatile</b>	91.68%
<b>Specific Gravity</b>	0.74
<b>VOC</b>	<ul style="list-style-type: none"> <li>• 611.86 g/L Regulatory</li> <li>• 3.3 lbs/gal Material</li> <li>• 395.26 g/l Material</li> <li>• 5.11 lbs/gal Regulatory</li> </ul>

## 10. Stability and reactivity

**Reactivity:** The product is stable and non-reactive under normal conditions of use, storage, and transport.

**Chemical Stability:** Material is stable under normal conditions.

**Possibility of Hazardous Reactions:** Hazardous polymerization does not occur.

**Conditions to Avoid:** Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible Materials:** Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

**Hazardous Decomposition Products:** No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation:** May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea. Vomiting.

**Skin Contact:** No adverse effects due to skin contact are expected.

**Eye Contact:** Causes serious eye irritation.

**Ingestion:** Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical, and toxicological characteristics:** May cause drowsiness and dizziness. Headache. Nausea. Vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

### Information on toxicological effects

**Acute Toxicology:** Narcotic effects.

Components	Species	Test Results
ACETONE (CAS 67-64-1)		
Acute		
Dermal		

## SAFETY DATA SHEET

LD50 Rabbit >15800 mg/kg

Inhalation  
LC50 Rat 76 mg/l, 4 Hours

Oral  
LD50 Mouse 3000 mg/kg  
Rat 5800 mg/kg

### ISOBUTYL ACETATE (CAS 110-19-0)

Acute

Oral  
LD50 Rabbit 4.8 g/kg

### N-BUTANE (CAS 106-97-8)

Acute

Inhalation  
LC50 Mouse 680 mg/l, 2 Hours  
Rat 658 mg/l, 4 Hours

### N-BUTYL ACETATE (CAS 123-86-4)

Acute

Inhalation  
LC50 Wistar Rat 160 mg/l, 4 Hours

Oral  
LD50 Rat 14000 mg/kg

### PROPANE (CAS 74-98-6)

Acute

Inhalation  
LC50 Rat >1442.84 mg/l, 15 minutes

### TOLUENE (CAS 108-88-3)

Acute

Dermal  
LD50 Rabbit 12124 mg/kg  
14.1 ml/kg

Inhalation

LC50 Mouse 5320ppm, 8 Hours  
400ppm, 24 Hours  
Rat 26700ppm, 1 Hours  
12200ppm, 2 Hours  
8000ppm, 4 Hours

# SAFETY DATA SHEET

LD50

Rat

2.6 g/kg

**Skin Corrosion/Irritation:** Prolonged skin contact may cause temporary irritation.

**Serious Eye Damage/Eye Irritation:** Causes serious eye irritation.

**Respiratory Sensitization:** Not a respiratory sensitizer.

**Skin Sensitization:** The product is not expected to cause skin sensitization.

**Germ Cell Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity:** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

- **IARC Monographs. Overall Evaluation of Carcinogenicity**
  - TOLUENE (CAS 108-88-3) - 3 Not classifiable as to carcinogenicity to humans.
- **OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)** - Not regulated.
- **US National Toxicology Program (NTP) Report on Carcinogens** - Not listed

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child.

**Specific Target Organ Toxicity - Single Exposure:** May cause drowsiness or dizziness.

**Specific Target Organ Toxicity - Repeated Exposure** - May cause damage to organs through prolonged or repeated exposure.

**Aspiration Hazard:** Not an aspiration hazard.

**Chronic Effects:** May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

## 12. Ecological information

**Ecotoxicity:** Harmful to aquatic life with long lasting effects.

### Components

#### ACETONE (CAS 67-64-1)

Crustacea	EC50	Water flea (Daphnia magna)	10294-17704 mg/l, 48 Hours
Fish	LC50	Rainbow trout (Oncorhynchus mykiss)	4740-6330 mg/l, 96 Hours

#### N-BUTYL ACETATE (CAS 123-86-4)

Fish	LC50	Fathead minnow (Pimephales promelas)	17-19 mg/l, 96 Hours
------	------	--------------------------------------	----------------------

#### TOLUENE (CAS 108-88-3)

Crustacea	EC50	Water flea (Daphnia magna)	5.46-9.83 mg/l, 48 Hours
Fish	LC50	Coho salmon (Onchorhynchus kisutch)	8.11 mg/l, 96 Hours

**Persistence and Degradability:** No data is available on the degradability of this product.

### Bioaccumulative Potential:

#### Partition coefficient n-octanol/water (log Kow)

- ACETONE: -0.24
- ISOBUTYL ACETATE: 1.78
- N-BUTANE: 2.89
- N-BUTYL ACETATE: 1.78

# SAFETY DATA SHEET

- PROPANE: 2.36
- TOLUENE: 2.73

**Mobility in Soil:** No data available.

**Other Adverse Effects:** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal Instructions:** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate, or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways, or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local Disposal Regulations:** Dispose in accordance with all applicable regulations.

**Hazardous Waste Code:** The waste code should be assigned in discussion between the user, the producer, and the waste disposal company.

**Waste from Residues/Unused Products:** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see Disposal Instructions).

**Contaminated Packaging:** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

## 14. Transportation information

### DOT

- **UN Number** - UN1950
- **UN Proper Shipping Name** - UN1950, Aerosols, Flammable
- **Transport Hazard Class(es)**
  - **Class** - 2.1
  - **Subsidiary Risk** - --
  - **Label(s)** - 2.1
- **Packing Group** - Not applicable
- **Special Precautions for User** - Read safety instructions, SDS and emergency procedures before handling.
- **Special Provisions** - N82
- **Packaging Exceptions** - 306
- **Packaging Non Bulk** - None
- **Packaging Bulk** - None

### IATA

- **UN Number** - UN1950
- **UN Proper Shipping Name** - Aerosols, Flammable
- **Transport Hazard Class(es)**
  - **Class** - 2.1
  - **Subsidiary Risk** - --
  - **Label(s)** - 2.1
- **Packing Group** - Not applicable
- **Environmental Hazards** - No
- **Special Precautions for User** - Read safety instructions, SDS and emergency procedures before handling.
- **Other Information:**
  - **Passenger and Cargo Aircraft** - Allowed
  - **Cargo Aircraft Only** - Allowed

# SAFETY DATA SHEET

## IMDG

- **UN Number** - UN1950
- **UN Proper Shipping Name** - Aerosols, Flammables
- **Transport Hazard Class(es)**
  - **Class** - 2.1
  - **Subsidiary Risk** - --
  - **Label(s)** - 2.1
- **Packing Group** - Not applicable
- **Environmental Hazards**
  - **Marine Pollutant** - No
- **EmS** - Not available
- **Special Precautions for User** - Read safety instructions, SDS and emergency procedures before handling.
- **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** - Not established.

## DOT



## IATA; IMDG



**General Information:** Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

## 15. Regulatory information

~~US Federal Regulations:~~ This product is a "Hazardous Chemical" as defined by the OSHA Communication Standard, Item Numbers: 76099-0512

# SAFETY DATA SHEET

29 CFR 1910.1200.

- **TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**
  - Not regulated.
- **CERCLA Hazardous Substance List (40 CFR 302.4)**
  - ACETONE (CAS 67-64-1) - Listed
  - ISOBUTYL ACETATE (CAS 110-19-0) - Listed
  - N-BUTANE (CAS 106-97-8) - Listed
  - N-BUTYL ACETATE (CAS 123-86-4) - Listed
  - PROPANE (CAS 74-98-6) - Listed
  - TOLUENE (CAS 108-88-3) - Listed
- **SARA 304 Emergency Release Notification**
  - Not regulated
- **OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**
  - Not regulated

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

- **Hazard Categories**
  - Immediate Hazard - Yes
  - Delayed Hazard - Yes
  - Fire Hazard - Yes
  - Pressure Hazard - No
  - Reactivity Hazard - No
- **SARA 302 Extremely Hazardous Substance**
  - Not listed
- **SARA 311/312 Hazardous Chemical**
  - No
- **SARA 313 (TRI Reporting)**
  - TOLUENE (CAS 108-88-3) - <10% by wt

## Other Federal Regulations

- **Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**
  - TOLUENE (CAS 108-88-3)
- **Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**
  - N-BUTANE (CAS 106-97-8)
  - PROPANE (CAS 74-98-6)
- **Safe Drinking Water Act (SDWA) - Not regulated**
  - **Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**
    - ACETONE (CAS 67-64-1) - 6532
    - TOLUENE (CAS 108-88-3) - 6594
  - **Drug Enforcement Administration (DEA). List 1 and 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**
    - ACETONE (CAS 67-64-1) -- 35%WV
    - TOLUENE (CAS 108-88-3) -- 35%WV
  - **DEA Exempt Chemical Mixtures Code Number**
    - ACETONE (CAS 67-64-1) - 6532
    - TOLUENE (CAS 108-88-3) - 594
  - **FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**
    - ACETONE (CAS 67-64-1) - Low Priority
    - ISOBUTYL ACETATE (CAS 110-19-0) - Low Priority
    - N-BUTYL ACETATE (CAS 123-86-4) - Low Priority

## US State Regulations

- **US California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**
  - Not listed
- **US California Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3 subd. (a))**
  - ACETONE (CAS 67-64-1)
  - N-BUTANE (CAS 106-97-8)
  - TOLUENE (CAS 108-88-3)

# SAFETY DATA SHEET

- **US Massachusetts RTK - Substance List**
  - ACETONE (CAS 67-64-1)
  - ISOBUTYL ACETATE (CAS 110-19-0)
  - N-BUTANE (CAS 106-97-8)
  - N-BUTYL ACETATE (CAS 123-86-4)
  - PROPANE (CAS 74-98-6)
  - TOLUENE (CAS 108-88-3)
- **US New Jersey Worker and Community Right-to-Know Act**
  - ACETONE (CAS 67-64-1)
  - ISOBUTYL ACETATE (CAS 110-19-0)
  - N-BUTANE (CAS 106-97-8)
  - N-BUTYL ACETATE (CAS 123-86-4)
  - PROPANE (CAS 74-98-6)
  - TOLUENE (CAS 108-88-3)
  - 2-METHYLPROPYL ISOBUTYRATE (CAS 97-85-8)
- **US Pennsylvania Worker and Community Right-to-Know Act**
  - ACETONE (CAS 67-64-1)
  - ISOBUTYL ACETATE (CAS 110-19-0)
  - N-BUTANE (CAS 106-97-8)
  - N-BUTYL ACETATE (CAS 123-86-4)
  - PROPANE (CAS 74-98-6)
  - TOLUENE (CAS 108-88-3)
- **US Rhode Island RTK**
  - ACETONE (CAS 67-64-1)
  - ISOBUTYL ACETATE (CAS 110-19-0)
  - N-BUTANE (CAS 106-97-8)
  - N-BUTYL ACETATE (CAS 123-86-4)
  - PROPANE (CAS 74-98-6)
  - TOLUENE (CAS 108-88-3)
- **US California Proposition 65:** WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.
  - **US California Proposition 65 - CRT: Listed Date/Developmental Toxin**
    - TOLUENE (CAS 108-88-3) - Listed: January 1, 1991
  - **US California Proposition 65 - CRT: Listed Date/Female Reproductive Toxin**
    - TOLUENE (CAS 108-88-3) - Listed: August 7, 2009

## International Inventories

- **Country(s) or Region/Inventory Name/On Inventory (yes/no\*)**
- Australia - Australian Inventory of Chemical Substances (AICS) - No
- Canada - Domestic Substances List (DSL) - No
- Canada - Non-Domestic Substances List (NDSL) - No
- Chile - NCh 2245:2015 - No
- China - Inventory of Existing Chemical Substances in China (IECSC) - No
- Europe - European Inventory of Existing Commercial Chemical Substances (EINECS) - No
- Europe - European List of Notified Chemical Substances (ELINCS) - No
- Japan - Inventory of Existing and New Chemical Substances ENCS) - No
- Korea - Existing Chemicals List (ECL) - No
- New Zealand - New Zealand Inventory - No
- Philippines - Philippine Inventory of Chemicals and Chemical Substances (PICCS) - No
- United States & Puerto Rico - Toxic Substances Control Act (TSCA) Inventory - No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).



---

# SAFETY DATA SHEET

## 16. Other information

**PREPARED BY:** DecoArt, Inc

**DATE OF PREPARATION:** March 3, 2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.