

76154-0554

Safety Data Sheet

Issue Date: 29-Jun-2015

Revision Date: 05-May-2022

Version 1

1. IDENTIFICATION**Product Identifier****Product Name** Water and Stain Repellant**Other means of identification****SDS #** ASP-019**Product Code** Angelus 851-05-000**UN/ID No** UN1950**Recommended use of the chemical and restrictions on use****Recommended Use** Water and stain repellent.**Details of the supplier of the safety data sheet****Supplier Address**

Angelus Shoe Polish Co.
 Florence Ave.
 Santa Fe Springs, CA 90670
 Ph: 562-941-4242

Emergency Telephone Number

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
 1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION**Appearance** Aerosol spray**Physical state** Aerosol**Classification**

Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases Under Pressure	Compressed Gas

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Signal Word**Danger****Hazard statements**

Causes skin irritation
 Suspected of damaging fertility or the unborn child
 May cause drowsiness or dizziness
 May cause damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Extremely flammable aerosol
 Contains gas under pressure; may explode if heated

ASP-019 - Water and Stain Repellant

Revision Date: 05-May-2022

**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do not induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Hexane	110-54-3	60-90
Hydrocarbon Propellant	68476-86-8	5-30

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
Skin Contact	Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

ASP-019 - Water and Stain Repellant

Revision Date: 05-May-2022

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician. If breathing has stopped, give artificial respiration.
Ingestion	Do not induce vomiting without medical advice. If vomiting occurs spontaneously, keep head below hips to prevent aspirating vomitus into lungs. If drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down. Immediately call a poison center or doctor/physician.

Most important symptoms and effects

Symptoms	May be harmful in contact with skin. Causes skin irritation. Dermatitis may occur. Can cause defatting of skin tissue. May cause drowsiness or dizziness. High vapor/aerosol concentrations are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.
---------------------------	--

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Dry chemical. Foam. Water spray (fog).

Unsuitable Extinguishing Media Avoid spraying water directly into storage containers due to a danger of boil over.**Specific Hazards Arising from the Chemical**

Contains gas under pressure; may explode if heated. Product is an extremely flammable aerosol. This product releases Flammable Vapors at well below ambient temperatures and readily forms flammable mixtures with air exposed to an ignition source. It will burn in the open or be explosive in confined spaces. Its vapors are heavier than air and may travel long distances to a point of ignition, and then flash back. Alkaline/chlorine gas mixtures have produced explosions.

Hazardous Combustion Products Carbon oxides.**Explosion Data****Sensitivity to Static Discharge** Prevent electrostatic charge build-up by using common bonding and ground techniques.**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Gas fires should not be extinguished unless the gas flow can be stopped immediately. Allow the fire to burn itself out. If the source cannot be shut off immediately, all equipment and surfaces exposed to the fire should be cooled with water to prevent over-heating, flash-backs, or explosions. Control fire until gas supply can be shut off. Use proper protective equipment. Use fresh air respirator when exposure to hazardous concentrations of toxic gases is possible.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal Precautions** Wear protective clothing as described in Section 8 of this safety data sheet.**Environmental precautions****Environmental precautions** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

ASP-019 - Water and Stain Repellant

Revision Date: 05-May-2022

Methods and material for containment and cleaning up

Methods for Containment	Persons not wearing protective equipment should leave area until cleanup is completed. Eliminate all ignition sources. Ventilate area of leak or spill. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.
Methods for Clean-Up	Use non-sparking hand tools and explosion-proof electrical equipment. Sweep up absorbed material and shovel into suitable containers for disposal. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on Safe Handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands, and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Do not expose to temperatures exceeding 50 °C/122°F. Protect from sunlight.
Packaging Materials	Empty containers retain product residue and can be hazardous.
Incompatible Materials	Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Hexane 110-54-3	TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³

Appropriate engineering controls

Engineering Controls	Apply technical measures to comply with the occupational exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure. The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.
-----------------------------	---

ASP-019 - Water and Stain Repellant

Revision Date: 05-May-2022

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Face shield and chemical anti-splash safety goggles. Refer to 29 CFR 1910.133 for eye and face protection regulations.
Skin and Body Protection	Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene gloves have been suggested. Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse. Refer to 29 CFR 1910.138 for appropriate skin and body protection.
Respiratory Protection	If TLV is exceeded, use a NIOSH/MSHA approved respirator for organic vapors. Refer to 29 CFR 1910.134 for respiratory protection requirements.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Aerosol	Odor	Not determined
Appearance	Aerosol spray	Odor Threshold	Not determined
Color	Not determined		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	Not determined	
Flash Point	-93.3 °C / -136 °F	
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Flammability Limits in Air		
Upper Flammability Limits	Not determined	
Lower Flammability Limit	Not determined	
Vapor Pressure	Not determined	
Vapor Density	Not determined	
Relative Density	Not determined	
Water Solubility	Completely soluble	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY**Reactivity**

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

ASP-019 - Water and Stain Repellant

Revision Date: 05-May-2022

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.**Conditions to Avoid**

Do not expose to temperatures exceeding 50 °C/122°F.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information****Eye Contact** Eye contact may result in tearing, redness & pain.**Skin Contact** May be harmful in contact with skin. Causes skin irritation. May include redness, drying and cracking of skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.**Inhalation** May cause drowsiness or dizziness. May cause irritation to the mucous membranes and upper respiratory tract.**Ingestion** May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.**Component Information**

Chemical Name	ATEmix (oral)	ATEmix (dermal)	Inhalation LC50
Hexane 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h

Information on physical, chemical and toxicological effects**Symptoms** Please see section 4 of this SDS for symptoms.**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Carcinogenicity** Based on the information provided, this product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.**Reproductive toxicity** Suspected of damaging fertility or the unborn child.**STOT - single exposure** May cause drowsiness or dizziness.**STOT - repeated exposure** May cause damage to organs through prolonged or repeated exposure.**Aspiration hazard** May be fatal if swallowed and enters airways.

ASP-019 - Water and Stain Repellant

Revision Date: 05-May-2022

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	27,778.00 mg/kg
ATEmix (dermal)	3,333.00 mg/kg
ATEmix (inhalation-vapor)	187.96 mg/L

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Hexane 110-54-3		2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through	1000: 24 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Hydrocarbon Propellant 68476-86-8	2.8

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Empty, depressurized containers can not be reused. Can which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Hexane 110-54-3	Toxic Ignitable

14. TRANSPORT INFORMATION**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No	Limited Quantity UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1

ASP-019 - Water and Stain Repellant

Revision Date: 05-May-2022

IATA

UN/ID No UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1

IMDG

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION**International Inventories**

Chemical Name	TSCA	DSL/NDL	EINECS/E LINC	ENCS	IECSC	KECL	PICCS	AICS
Hexane	X	X	X	Present	X	Present	X	X
Hydrocarbon Propellant	X	X	X		X	Present	X	X

Legend:*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINC - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS - Japan Existing and New Chemical Substances**IECSC - China Inventory of Existing Chemical Substances**KECL - Korean Existing and Evaluated Chemical Substances**PICCS - Philippines Inventory of Chemicals and Chemical Substances**AICS - Australian Inventory of Chemical Substances***US Federal Regulations****CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Hexane 110-54-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Hexane - 110-54-3	110-54-3	60-90	1.0

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Hexane 110-54-3	X	X	X

ASP-019 - Water and Stain Repellant

Revision Date: 05-May-2022

16. OTHER INFORMATION

NFPA**Health Hazards****Flammability****Instability****Special Hazards****HMIS**

Not determined

Not determined

Not determined

Not determined

Health Hazards**Flammability****Physical hazards****Personal Protection**

Not determined

Not determined

Not determined

Not determined

Issue Date:

29-Jun-2015

Revision Date:

05-May-2022

Revision Note:

New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet