81910-5380

EU safety data sheet



Trade name: edding Porcelain marker ink (steel blue) contained in: edding 4200

Current version: 4.0.0, issued: 09.12.2021

Replaced version: 3.0.0, issued: 05.08.2020 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifier**

Trade name

edding Porcelain marker ink (steel blue) contained in: edding 4200

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses of the substance or mixture

Ink for use in felt pens

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH Bookkoppel 7 D-22926 Ahrensburg

Telephone no.

+49 (0) 41 02 / 80 8-0 Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

Emergency telephone number

For medical advice (in German and English): +49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Skin Sens. 1; H317

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP

2.2

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



Signal word

Warning

Hazardous component(s) to be indicated on label:

1,2-benzisothiazol-3(2H)-one

Hazard statement(s)

H317 May cause an allergic skin reaction.

Hazard statements (EU)



Trade name: edding Porcelain marker ink (steel blue) contained in: edding 4200

Current version: 4.0.0, issued: 09.12.2021

Region: GB

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -

Replaced version: 3.0.0, issued: 05.08.2020

isothiazol-3-one (3:1). May produce an allergic reaction.

Precautionary statement(s)

P101 Íf medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P501 Dispose of contents/container to a facility in accordance with local and national

regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

Substances

Not applicable. The product is not a substance.

Chemical characterization

Mixture (preparation)

Hazardous ingredients

No	Substance name			Additional information		
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Conc	entration		%
	REACH no					
1	ethanediol					
	107-21-1	Acute Tox. 4*; H302	<	2.50		wt%
	203-473-3					
	603-027-00-1					
	-					
2	ammonia					
	1336-21-6	Aquatic Acute 1; H400	<	0.50		wt%
	215-647-6	Skin Corr. 1B; H314				
	007-001-01-2	Eye Dam. 1; H318				
	-					
3	1,2-benzisothiazol-					
	2634-33-5	Acute Tox. 4*; H302	>=	0.05 - <	1.00	wt%
	220-120-9	Aquatic Acute 1; H400				
	613-088-00-6	Eye Dam. 1; H318				
	-	Skin Irrit. 2; H315				
		Skin Sens. 1; H317				
4	pyridine-2-thiol 1-c					
	3811-73-2	Acute Tox. 4; H302	<	0.10		wt%
	223-296-5	Acute Tox. 3; H311				
	-	Acute Tox. 4; H332				
	-	Aquatic Acute 1; H400				
		Eye Irrit. 2; H319				
		Skin Irrit. 2; H315				
		Aquatic Chronic 2; H411				
		Skin Sens. 1; H317				
		STOT RE 1; H372i				
5		5-chloro-2-methyl-4-isothiazolin-3-one and 2-				
	methyl-2H -isothia:			0.0015		107
	55965-84-9	Acute Tox. 2; H310	<	0.0015		wt%
	613 167 00 5	Acute Tox. 2; H330				
	613-167-00-5	Acute Tox. 3; H301				
	-	Aquatic Acute 1; H400				
		Aquatic Chronic 1; H410				
		EUH071				
		Eye Dam. 1; H318				
		Skin Corr. 1C; H314				



Trade name: edding Porcelain marker ink (steel blue) contained in: edding 4200

Current version : 4.0.0, issued: 09.12.2021 **Replaced version:** 3.0.0, issued: 05.08.2020 **Region:** GB

		Skin Sens. 1A; H317			
6	glycerol				
	56-81-5	-	<	5.00	wt%
	200-289-5				
	-				
	-				
7	Tetrabenzo-5,10,15	,20-diazaporphyrinephthalocyanine (C.I.Pigment			
	#74160 Blue 15:3)				
	147-14-8	-	<	5.00	wt%
l	205-685-1				
	-				

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(*,**,***,****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
2	-	STOT SE 3: H335: C >= 5%	-	-
3	-	Skin Sens. 1; H317: C >= 0.05%	-	-
4	-	-	M = 100	-
5	В	Skin Sens. 1A; H317: C >= 0.0015% Eye Irrit. 2; H319: C >= 0.06% Skin Irrit. 2; H315: C >= 0.06% Skin Corr. 1C; H314: C >= 0.6% Eye Dam. 1; H318: C >= 0.6%	M = 100	M = 100

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
4	H372
	inhalational; central nervous system; -

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed No data available.

4.3 Indication of any immediate medical attention and special treatment needed No data available.

SECTION 5: Firefighting measures



Trade name: edding Porcelain marker ink (steel blue) contained in: edding 4200

Current version: 4.0.0, issued: 09.12.2021 Replaced version: 3.0.0, issued: 05.08.2020 Region: GB

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	glycerol	56-81-5	200-289-5



Trade name: edding Porcelain marker ink (steel blue) contained in: edding 4200

Current version : 4.0.0, issued: 09.12.2021 **Replaced version:** 3.0.0, issued: 05.08.2020 **Region:** GB

List of approved workplace exposure limits (WELs) /	EH40			
Glycerol mist				
WEL long-term (8-hr TWA reference period)	10	mg/m³		
Tetrabenzo-5,10,15,20-	147-14-8		205-685-1	
diazaporphyrinephthalocyanine (C.I.Pigment #74160				
Blue 15:3)				
List of approved workplace exposure limits (WELs) /	EH40			
Copper and compounds (as Cu) dusts and mists				
WEL short-term (15 min reference period)	2	mg/m³		
WEL long-term (8-hr TWA reference period)	1	mg/m³		
ethanediol	107-21-1		203-473-3	
2000/39/EC				
Ethylene glycol				
WEL short-term (15 min reference period)	104	mg/m³	40	ppm
WEL long-term (8-hr TWA reference period)	52	mg/m³	20	ppm
Skin resorption / sensibilisation	Skin			
List of approved workplace exposure limits (WELs) /	EH40			
Ethane-1,2-diol vapour				
WEL short-term (15 min reference period)	104	mg/m³	40	ppm
WEL long-term (8-hr TWA reference period)	52	mg/m³	20	ppm
Comments	Sk			
List of approved workplace exposure limits (WELs) /	EH40			
Ethane-1,2-diol particulate				
WEL long-term (8-hr TWA reference period)	10	mg/m³		
Comments	Sk			
	Glycerol mist WEL long-term (8-hr TWA reference period) Tetrabenzo-5,10,15,20- diazaporphyrinephthalocyanine (C.I.Pigment #74160 Blue 15:3) List of approved workplace exposure limits (WELs) / Copper and compounds (as Cu) dusts and mists WEL short-term (15 min reference period) WEL long-term (8-hr TWA reference period) ethanediol 2000/39/EC Ethylene glycol WEL short-term (15 min reference period) WEL long-term (8-hr TWA reference period) WEL long-term (8-hr TWA reference period) Skin resorption / sensibilisation List of approved workplace exposure limits (WELs) / Ethane-1,2-diol vapour WEL short-term (15 min reference period) WEL long-term (8-hr TWA reference period) Comments List of approved workplace exposure limits (WELs) / Ethane-1,2-diol particulate WEL long-term (8-hr TWA reference period)	WEL long-term (8-hr TWA reference period) 10 Tetrabenzo-5,10,15,20- 147-14-8 diazaporphyrinephthalocyanine (C.I.Pigment #74160 Blue 15:3) List of approved workplace exposure limits (WELs) / EH40 Copper and compounds (as Cu) dusts and mists WEL short-term (15 min reference period) 2 WEL long-term (8-hr TWA reference period) 1 2000/39/EC Ethylene glycol WEL short-term (15 min reference period) 104 WEL long-term (8-hr TWA reference period) 52 Skin resorption / sensibilisation Skin List of approved workplace exposure limits (WELs) / EH40 Ethane-1,2-diol vapour WEL short-term (15 min reference period) 52 Comments Sk List of approved workplace exposure limits (WELs) / EH40 Ethane-1,2-diol particulate WEL long-term (8-hr TWA reference period) 52 Comments Sk List of approved workplace exposure limits (WELs) / EH40 Ethane-1,2-diol particulate	Glycerol mist WEL long-term (8-hr TWA reference period) 10 mg/m³ Tetrabenzo-5,10,15,20- diazaporphyrinephthalocyanine (C.I.Pigment #74160 Blue 15:3) List of approved workplace exposure limits (WELs) / EH40 Copper and compounds (as Cu) dusts and mists WEL short-term (15 min reference period) 2 mg/m³ WEL long-term (8-hr TWA reference period) 107-21-1 2000/39/EC Ethylene glycol WEL short-term (15 min reference period) 104 mg/m³ WEL long-term (8-hr TWA reference period) 52 mg/m³ Skin List of approved workplace exposure limits (WELs) / EH40 Ethane-1,2-diol vapour WEL short-term (15 min reference period) 104 mg/m³ WEL long-term (8-hr TWA reference period) 52 mg/m³ Comments Sk List of approved workplace exposure limits (WELs) / EH40 Ethane-1,2-diol particulate WEL long-term (8-hr TWA reference period) 10 mg/m³	Glycerol mist WEL long-term (8-hr TWA reference period) Tetrabenzo-5,10,15,20- diazaporphyrinephthalocyanine (C.I.Pigment #74160 Blue 15:3) List of approved workplace exposure limits (WELs) / EH40 Copper and compounds (as Cu) dusts and mists WEL short-term (15 min reference period) VEL long-term (8-hr TWA reference period) Ethylene glycol WEL short-term (15 min reference period) WEL long-term (8-hr TWA reference period) Skin List of approved workplace exposure limits (WELs) / EH40 Ethane-1,2-diol vapour WEL short-term (15 min reference period) WEL short-term (15 min reference period) Skin List of approved workplace exposure limits (WELs) / EH40 Ethane-1,2-diol paperoved workplace exposure limits (WELs) / EH40 Ethane-1,2-diol particulate WEL long-term (8-hr TWA reference period) Ethane-1,2-diol particulate WEL long-term (8-hr TWA reference period) MEL long-term (8-hr TWA reference period) MEL long-term (8-hr TWA reference period)

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form/Colour	
liquid	
dark blue	



Trade name: edding Porcelain marker ink (steel blue) contained in: edding 4200

Current version : 4.0.0, issued: 09.12.2021 **Replaced version:** 3.0.0, issued: 05.08.2020 **Region:** GB

Odour

characteristic

pH value

No data available

Boiling point / boiling range

No data available

Melting point/freezing point

No data available

Decomposition temperature

No data available

Flash point

No data available

Ignition temperature

No data available

Flammability

No data available

Lower explosion limit

No data available

Upper explosion limit

No data available

Vapour pressure

No data available

Relative vapour density

No data available

Relative density
No data available

Density

No data available

Solubility

No data available

Partition coefficient n-octanol/water (log value)

No data available

Viscosity

No data available

Particle characteristics

No data available

9.2 Other information

Other information

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.



Trade name: edding Porcelain marker ink (steel blue) contained in: edding 4200

Current version : 4.0.0, issued: 09.12.2021 **Replaced version: 3**.0.0, issued: 05.08.2020 **Region: GB**

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

No data available.

10.6 Hazardous decomposition products

No data available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity (result of the ATE calculation for the mixture)				
No	Product Name	Product Name		
1	edding Porcelain marker ink (steel blue) contained			
	in: edding 4200			
Com	nments	The result of the applied calculation method according to the		
		European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6,		
		Part 3 of Annex I is outside the values that imply a classification /		
		labelling of this mixture according to table 3.1.1 defining the		
		respective categories (ATE oral > 2000 mg/kg).		

Acu	Acute oral toxicity					
No	Substance name	CAS no.		EC no.		
1	ethanediol	107-21-1		203-473-3		
LD50			5840	mg/kg bodyweight		
Species		rat				
Source		Manufacturer				

Acute dermal toxicity				
No	Substance name	CAS no.		EC no.
1	ethanediol	107-21-1		203-473-3
LD50			9530	mg/kg bodyweight
Species		rabbit		
Source		Manufacturer		

Acute inhalational toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity No data available

TO data available

Reproduction toxicity No data available

Carcinogenicity

No data available STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration hazard



Trade name: edding Porcelain marker ink (steel blue) contained in: edding 4200

Current version: 4.0.0, issued: 09.12.2021 Replaced version: 3.0.0, issued: 05.08.2020 Region: GB

No data available

11.2 Information on other hazards

Endocrine disrupting properties

No data available

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)

No data available

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No data available

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified



Trade name: edding Porcelain marker ink (steel blue) contained in: edding 4200

Current version: 4.0.0, issued: 09.12.2021 Replaced version: 3.0.0, issued: 05.08.2020 Region: GB

by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU regulations</u>

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex No XVII.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH071

Corrosive to the respiratory tract.



Trade name: edding Porcelain marker ink (steel blue) contained in: edding 4200

Current version: 4.0.0, issued: 09.12.2021 Replaced version: 3.0.0, issued: 05.08.2020 Region: GB

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H372i	Causes damage to organs through prolonged or repeated exposure if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg
Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 636510