SAFETY DATA SHEET

DATE: REVISION: 22-Jul-2020 -

RODUCT INFOR		TION Iga Liner White	е	Product Number:	EH19-21	1/000
Manga Liner Black				EH19-21		
Recommend Applic	ation:	Marker (a	s Ink)		
Company Informatio	on:	Company Nam Address: Tel: Emergency Te Fax: E-mail:		Higashiyama Corporation 575-1, Minamikyobate-cho, 7-chom +81. 742. 62. 1120 +81. 742. 62. 1120 +81. 742. 62. 1124 m-okuda@east-hill.co.jp	e, Nara-sh	ni, Nara, 630-8141, Japan
AZARDS IDENT GHS Classification	IFIC	ATION				
Physical hazar	ds		Flar	nmable liquid		Out of Division
Health hazards Specially	Targe	et Organ tematic Toxicity	Acu Acu Skir Sen Skir Ger Caro Rep Sing	te toxicity (Oral) te toxicity (Endermic) te toxicity (Inhale : Gas) te toxicity (Inhale : Dust, Mist) a corrosion / irritative tous eye damage / eye irritation sitizing property of apparatus respira a sensitizing property herate cell mutagenicity cinogen productive effect gle exposure	Not Class Category	
			Asp	iration hazard		Out of Division
Environmental	haza	rds	Chr	te aquatic hazard onic aquatic hazard ardous to the ozone layer		Not Classification Not Classification Out of Division
Label element	Picto	ogram				
	Sign	al words	Dan	nger		

Hazardous Information

Causes serious eye irritation May cause cancer May damage fertility or the unborn child Causes damage to organs (Liver) through prolonged or repeated exposure

Item Numbers: 82344-1020, 82344-2020 Higashiyama Corporation Page 1 of 5 SDS No. EH1921-1-1 May cause damage to organs (Central nervous system) through prolonged or repeated exposure

	may cause damage to organs (Central nervous system) through prolonged of repeated ex
Instruction	
[Measure for Sa	lfety]
	Obtain special instructions before use.
	Do not handle until all safety precautions have been read and understood.
	Wear protective gloves and eye/face protection.
	Do not breathe dust/fume/gas/mist/vapours/spray.
	Wash hands after handling.
	Do not eat, drink or smoke when using this product.
【First Aid】	IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do. Continue rinsing.
	Immediately call a POISON CENTER or doctor/physician.
	IF exposed or concerned: Get medical attention/advice.
	Get medical attention/advice if you feel unwell.
[Storage]	Store locked up.
[Disposal]	Dispose of contents/container in accordance with local/regional/international regulation.

Country / Community Information: No data

3. COMPOSITION AND INGREDIENT INFORMATION

Mixture

Single, Mixture:

redient and content		
Ingredient name	CAS No.	Concentration (wt%)
Titanium dioxide (only White)	13463-67-7	20 - 40
Carbon black (only Black)	1333-86-4	5 - 15
Ethanol	64-17-5	1 - 4
2-propanol	67-63-0	< 0.7
Resin	-	10 - 20
Butyl cellosolve	111-76-2	< 0.4
Poly(oxyethylene)octylphenyl ether	9036-19-5	< 0.6
Water	7732-18-5	35 - 70

4. FIRST AID

	For Inhale:	Remove the victim to the fresh air area. If feel bad, see a doctor.
	For Skin:	Put off the all polluted clothes immediately. Clean with the proper temp. and slow flowing water for over 15 minutes. If have irritate the skin, see a doctor. Call a doctor if feel bad. Before re-use
		the put off clothes, clean it up and remove the pollution.
	For Eyes:	Put off the contacts if possible, and continue to clean. Clean the eyes carefully for a few minutes. If the eyes get this product, clean the eye immediately and wash away completely. If the cleaning eyes not enough, it may cause irreversible eye damage. If irritate to the eyes continue, see a doctor.
	For Swallow:	Call a doctor, if feel bad. Rinse the mouth out. Do not have the victim vomit.
	Expected acute symptom	n and late symptom:
		Sialorrhea, face flash, cough, dizzy, lethargy, headache, sore throat, deliquim animi barf, vomition
	Most important sign and	symptom:
		No data
	Protect the person receiv	ved first aid:
		Rescuer must wear proper protective equipment according to the situation.
	Special notandum for do	ctor:
		Symptom will appear later, so that if the patient exposed excessively, it needs medical follow progress.
. F	FIRE-FIGHTING MEA	SURE

Extinguishing Media:Small fire / Carbon dioxide, dry chemical extinguishing media, water spray, alcoholic resistance foam.Great Conflagration:Water spray, mist water, alcoholic resistance form.Forbidden Extinguishing Media:

Cylindrical pouring water.

Item Numbers: 82344-1020, 82344-2020 Higashiyama Corporation

5.

Special Dangerous and Harmful Effect:

The irritative, toxicity and corrosive gas is generated by fire. The container will be burst by heating. If it is not dangerous, move the container from the fire area.

If it is impossible to move, cool the container and around by spraying water. After extinguishing a fire, cool the container completely by large quantity of water.

Protect the Person Extinguish a Fire:

For fighting fire, wear compressed air open-circuit SBCA and protect equipment for chemical. Fight a fire from up wind.

6. ACCIDENTAL RELEASE MEASURES

Notandum for Human Body, Protective Equipment and Emergency Measure:

The worker must wear proper protector (refer to section 8) not to get the paint on the skin or into eyes. Do not touch the leakage material or walk into it. Keep the proper distance in all direction as the leakage area immediately. No unauthorized entry. If leakage but not occur a fire, wear the occlusive and impervious protect wear. Stay in the wind. Move away from the low ground. Ventilate before enter the sealed area. Notandum for Environment: Prevent from influx into the drain ditch, sewer, basement and closed area. Take notice not to affect the environment by discharge the paint into the river. Collect Neutralization: In small quantity case, absorb the leakage material by dry sand and nonflammable material or collect it in the sealed type container then dispose it. In small quantity case, collect the absorbed material by clean antistatic tools. In large quantity case, yard the leakage material by mound to prevent flow out and lead it into safety area then collect it. In large quantity case, water spray lower the steam temperature but it may not inhibit combustion at the sealed area. Containment or Depurant and Equipment: If it is not danger, stop the leakage. Ground all equipment which need for handle the leakage material. Use steam retard foam for lower the steam concentration.

Precaution of Second Disaster:

Clear away all ignition source immediately (Do not smoking near around, forbid firework and flame) In case large steam generating, retard it by mist spray. Call related agency and ask the help.

7. HANDLING AND STORAGE

Handling

Do the equipment measure described on the section 8 and wear protector.

Local exhaust ventilation, whole ventilation:

Do the local exhaust ventilation and whole ventilation described on section 8. Prevent leakage the liquid and steam as possible.

Safe handling notandum:

This product irritate the eyes so that care not to get it into the eyes. This product may cause sleep or vertigo, irritate the apparatus respiratorius and damage organ parts so that do not touch, inhale and swallow it. Do not fall, drop, shock or drag the container. Clean hands well after use this product. Use this product outside or well ventilated area only. Avoid touching, refer to the section10.

Keep away from high temperature materials spark and fire, and avoid touching oxidizer and organic peroxide.

Storage Keep the container airtight and stock it in well ventilated place. Stock in the fulfilled and ventilated and cool place. Keep away from oxidant. Keep away from direct sunlight and fire. The inventory location must be fire-proof construction and the floor must be impermeable to prevent permeate the basement and spill to outside. Lock up the container.

Dangerous goods if mixed:

Refer to the section 10.

Container material:

Use the container regulated by fire law and UN transportation law.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Install the eyewashing devices and safety shower where handle or stock this product.

Protection Equipment

For apparatus respi	iratorius:
	Wear proper respiratory protect equipment such as gas mask for organic gas (if high
	concentration, wear air-supplied respirator).
For hands:	Wear the gloves designated by manufacturer.
For eyes:	Wear the eye protector designated by manufacturer.
For skin and Body:	Wear protect boots, oil resistant apron (impermeable and antistatic) and protect clothes (antistatic) designated by manufacturer.
Hygiene Measure	

Check the protect equipments regularly with check sheet. Clean hands well after use this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Properties	Condition (20°C)	Liquid
	Odor	No data
	Boiling point	No data
	Vapor pressure	No data
	Specific gravity (20°C)	No data
	pH (against water base)	No data
	Other	No data
Hazardous Information	Flash point	No data
	Ignition point	No data
	Explosion limit	No data
Other Hazardous Information		No data

10. STABILITY AND REACTIVITY

Stability:	Under usually storage condition, it is stable.
Hazardous Reactivity:	Nothing
Avoid Condition	Nothing
Avoid Touching	Nothing
Hazardous Decomposition	on Product:

Generates harmful gas such as carbon monoxide and carbon dioxide.

11. TOXICOLOGICAL INFORMATION

Harmful ingredient and exposure limit.

Name	ACGIH (TLV)	IARC	OTHER
Titanium dioxide (only White)	TWA 10mg/m ³	2B	LD ₅₀ (oral, rat) >20000 mg/kg
Carbon black (only Black)	3mg/m ³	2B	LD ₅₀ (oral, rat) 15400 mg/kg
Ethanol	STEL 1000ppm	1	LD ₅₀ (oral, rat) 6200-15000 mg/kg
2-propanol	TWA 200ppm	3	LD ₅₀ (oral, rat) 1870-5500 mg/kg
Butyl cellosolve	20ppm	3	LD ₅₀ (oral, rat) 470-3000 mg/kg
Poly(oxyethylene)octylphenyl ether	-	-	LD ₅₀ (oral, rat) 4190 mg/kg

Other harmful information relevant to composition:	No data
Harmful information for product:	No data
ECOLOGICAL INFORMATION	
Acute Hazardous Aquatic Environment:	No data
Inveteracy Hazardous Aquatic Environment:	No data

13. DISPOSAL CONSIDERATIONS

For dispose, follow the related regulation and standard of local governments. Ask the licensed industrial waste disposal company or local governments.

For Burning:

Residue Waste:

12.

Spray the incinerator with waste liquid directly or mix with flammable solvent in small quantity to burn. Activated sludge process.

Item Numbers: 82344-1020, 82344-2020 Higashiyama Corporation Polluted container and package:

Clean the container and recycle or treat it in accordance with the related regulation or local governments. If dispose the container, remove the content completely.

14. TRANSPORT INFORMATION

Common:	Please follow the section7. Check if there are no leakage from container and take cargo without
	falling, dropping and damage.
Land Transportation:	In case of fall under the Fire Law, Industrial Safety and Health Law, Poisonous Material Control
	Law follow each relevant mode of transportation.
Marine Transportation:	Please follow the Law for Safety of Vessel.
Air Transportation:	Please follow the Aviation Law and regulation of ICAO.
UN No.	N/A
Packing group	N/A
Packing group	N/A

15. REGULATORY INFORMATION

Regulatory information with regard to this substance in your country or region should be examined by your own responsibility.

16. OTHER INFORMATION

Main cited item

JPMA "Data Base for raw material MSDS" JPMA "MSDS Guide Book [Mixture (for paint)]" 4th version JPMA "MSDS Guide Book [Mixture (for paint)]" 4th version-addenda version Solvent pocket book Raw material manufacturer SDS

Regarding to the description content:

The description content of this data sheet is based on the documentation, information and data that we can garner at the present moment so that it might be change depend on new information. And it is recommend for usual handling so that in case of special handling, use it before take safety measure that suitable for your application and usage.

The description content is information service and not certification.

N/A = Not Applicable