



83843-1003
SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

ALCOLIN STICKY PUTTY PLASTI-TAK
Revision Number 1

Revision date 11-Mar-2024
Supersedes Date: Not applicable

1. Identification

1.1. Product identifier

Product Name ALCOLIN STICKY PUTTY PLASTI-TAK

Other means of identification

Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use No information available

Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1(800) 726-7845 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)

Manufacturer

Bostik South Africa
1 Beverley Close
Montague Gardens
Cape Town
South Africa
7441
Tel: +27 21 555 7400

E-mail msds@bostik.com

1.4. Emergency telephone number

Emergency Telephone CHEMTREC (Chemical Transportation Emergency Center)
Chemtrec: 1-800-424-9300 (US) , 1-703-527-3887 (Outside U.S.)
Rocky Mountain Poison Center: 1-866-767-5089

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Not a dangerous substance or mixture according to OSHA 29 CFR 1910.1200.

Hazards not otherwise classified (HNOC)

Not applicable

2.2. Label elements

EMERGENCY OVERVIEW

Not a dangerous substance or mixture according to OSHA 29 CFR 1910.1200.

Appearance No information available

Physical state Solid

Odor Odorless

SAFETY DATA SHEET

ALCOLIN STICKY PUTTY PLASTI-TAK
Revision Number 1

Revision date 11-Mar-2024
Supersedes Date: 11-Mar-2024

2.3. Other Information

No information available.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%
Limestone	1317-65-3	30 - 60
Carbonic acid, calcium salt (1:1)	471-34-1	10 - 30
Kaolin	1332-58-7	5 - <10
White mineral oil, petroleum	8042-47-5	5 - <10
Titanium dioxide	13463-67-7	1 - <5
Carbonic acid, magnesium salt (1:1)	546-93-0	1 - <5
Quartz (fine fraction)	14808-60-7	0.1 - <1

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. First-aid measures

4.1. Description of first aid measures

Inhalation

Remove to fresh air. If symptoms persist, call a physician.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Do not rub affected area. Get medical attention if irritation develops and persists.

Skin contact

Wash off immediately with plenty of water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. If symptoms persist, call a physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. Fire-fighting measures

US - EN

Page 2 / 12

SAFETY DATA SHEET

ALCOLIN STICKY PUTTY PLASTI-TAK
Revision Number 1

Revision date 11-Mar-2024
Supersedes Date: 11-Mar-2024

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical, CO₂, alcohol-resistant foam or water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical No information available.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂). Silicon dioxide.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Do not touch or walk through spilled material. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

6.2. Environmental precautions

Environmental precautions Keep out of drains, sewers, ditches and waterways. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Use personal protective equipment as required. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly.

Reference to other sections See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Handle in accordance with good industrial hygiene and US - EN

Page 3 / 12

SAFETY DATA SHEET

ALCOLIN STICKY PUTTY PLASTI-TAK
Revision Number 1

Revision date 11-Mar-2024
Supersedes Date: 11-Mar-2024

safety practice. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep from freezing.

7.3 References to other sections

Reference to other sections Section 10: STABILITY AND REACTIVITY
Section 13: DISPOSAL CONSIDERATIONS

8. Exposure controls/personal protection

8.1. Control parameters

Exposure Limits This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Limestone 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Carbonic acid, calcium salt (1:1) 471-34-1	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Kaolin 1332-58-7	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
White mineral oil, petroleum 8042-47-5	5 mg/m ³ (inhalable fraction)	-	-
Titanium dioxide 13463-67-7	TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ finescale respirable particulate matter	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Carbonic acid, magnesium salt (1:1) 546-93-0	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Quartz (fine fraction) 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

SAFETY DATA SHEET

ALCOLIN STICKY PUTTY PLASTI-TAK
 Revision Number 1

Revision date 11-Mar-2024
 Supersedes Date: 11-Mar-2024

Chemical name	Argentina	Brazil	Chile	Colombia
Limestone 1317-65-3	TWA: 10 mg/m ³	-	LPP: 7 mg/m ³ LPP: 5 mg/m ³	-
Kaolin 1332-58-7	TWA: 2 mg/m ³	TWA: 2 mg/m ³	LPP: 13 mg/m ³ LPP: 4.5 mg/m ³	TWA: 2mg/m ³
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 0.2 mg/m ³ TWA: 2.5 mg/m ³	-	TWA: 0.2mg/m ³ TWA: 2.5mg/m ³
Quartz (fine fraction) 14808-60-7	TWA: 0.05 mg/m ³	TWA: 0.025 mg/m ³	LPP: 0.08 mg/m ³	TWA: 0.025mg/m ³

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Carbonic acid, calcium salt (1:1) 471-34-1	-	TWA: 10mg/m ³	-	TWA: 10 mg/m ³
Kaolin 1332-58-7	TWA: 2mg/m ³	TWA: 2mg/m ³	2 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	TWA: 2 mg/m ³
Titanium dioxide 13463-67-7	TWA: 10mg/m ³	TWA: 10mg/m ³	0.2 mg/m ³ TWA (nanoscale, respirable particulate matter); 2.5 mg/m ³ TWA (finescale, respirable particulate matter)	TWA: 10 mg/m ³
Quartz (fine fraction) 14808-60-7	TWA: 0.025mg/m ³	TWA: 0.05mg/m ³	0.025 mg/m ³ TWA (respirable particulate matter)	TWA: 0.025 mg/m ³

8.2. Exposure controls

Appropriate engineering controls

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Avoid contact with eyes.

Hand protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

Skin and body protection Wear suitable protective clothing.

Respiratory protection Use appropriate respiratory protection.

General hygiene considerations Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Regular cleaning of equipment, work area and clothing is

SAFETY DATA SHEET

ALCOLIN STICKY PUTTY PLASTI-TAK
Revision Number 1

Revision date 11-Mar-2024
Supersedes Date: 11-Mar-2024

recommended.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid	
Appearance	No information available	
Color	Off-white	
Odor	Odorless	
Odor threshold	No information available	
Property	Values	Remarks • Method
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flash point	No data available	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	Insoluble in water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
9.2. Other information		
Explosive properties	No information available	
Oxidizing properties	No information available	
Solvent content (%)	No information available	
Solid content (%)	100	
Softening point	No information available	
Molecular weight	No information available	
VOC content		No information available
Density	1.5	
Bulk density	No information available	

10. Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

SAFETY DATA SHEET

ALCOLIN STICKY PUTTY PLASTI-TAK
Revision Number 1

Revision date 11-Mar-2024
Supersedes Date: 11-Mar-2024

Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied

11. Toxicological information

11.1. Information on toxicological effects

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapor)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (Rattus)	-	-
Carbonic acid, calcium salt (1:1) 471-34-1	LD50 > 2000 mg/kg (Rattus) OECD 420	LD50 >2000 mg/kg (Rattus) OECD 402	LC50 (4h) >3mg/ml (Rattus)
Kaolin 1332-58-7	LD50 (Rattus) > 2000 mg/kg	> 5000 mg/kg (Rattus)	1.5 mg/l 4hr
White mineral oil, petroleum	>5000 mg/kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	LC50 (4h) >5 mg/L

SAFETY DATA SHEET

ALCOLIN STICKY PUTTY PLASTI-TAK
Revision Number 1

Revision date 11-Mar-2024
Supersedes Date: 11-Mar-2024

8042-47-5	OECD 401	OECD 402	OECD 403
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
Carbonic acid, magnesium salt (1:1) 546-93-0	>2000 mg/Kg Rat	-	-
Quartz (fine fraction) 14808-60-7	>2000 mg/kg (Rattus)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

White mineral oil, petroleum (8042-47-5)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD 404	Rabbit	Dermal			Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Quartz (fine fraction) (14808-60-7)

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

White mineral oil, petroleum (8042-47-5)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD 405	Rabbit	eye			Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity

This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	A3	Group 2B	-	X
Quartz (fine fraction) 14808-60-7	A2	Group 1	Known	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

US - EN

Page 8 / 12

SAFETY DATA SHEET

ALCOLIN STICKY PUTTY PLASTI-TAK
Revision Number 1

Revision date 11-Mar-2024
Supersedes Date: 11-Mar-2024

Group 1 - Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans
NTP (National Toxicology Program)
Known - Known Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	Based on available data, the classification criteria are not met.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Target organ effects	Respiratory system, Eyes, Skin, Lungs, Gastrointestinal tract (GI).
Aspiration hazard	Based on available data, the classification criteria are not met.
Other adverse effects	No information available.
Interactive effects	No information available.

12. Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (<i>Desmondesmus subspicatus</i>)	CL50 (96h)>10000mg/L (<i>Oncorhynchus mykiss</i>)	-	CE50 (48h) >1000 mg/L <i>Daphnia Magna</i>
Carbonic acid, calcium salt (1:1) 471-34-1	IC50 72H Algae >1000 mg/l	CL50 96H >1000 mg/l	-	EC50 48H <i>Daphnia</i> >1000 mg/l
Kaolin 1332-58-7	IC 50 (72h) > 1000 mg/l	LC 50 (96h) > 1000 mg/l	-	EC 50 (48h) > 1000 mg/l (<i>Daphnia magna</i>)
White mineral oil, petroleum 8042-47-5	-	LC50: >10000mg/L (96h, <i>Lepomis macrochirus</i>)	-	-
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (<i>Cyprinodon variegatus</i>) OECD 203	-	-	-

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

SAFETY DATA SHEET

ALCOLIN STICKY PUTTY PLASTI-TAK
Revision Number 1

Revision date 11-Mar-2024
Supersedes Date: 11-Mar-2024

Component Information

Chemical name	Partition coefficient
Limestone 1317-65-3	0.9
White mineral oil, petroleum 8042-47-5	6

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

13. Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Contaminated packaging Dispose of in accordance with federal, state and local regulations.

14. Transport information

Note: Keep from freezing.

DOT Not regulated

IATA Not regulated

IMDG Not regulated

15. Regulatory information

International Inventories

TSCA	Listed
DSL	Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any

US - EN

Page 10 / 12

SAFETY DATA SHEET

ALCOLIN STICKY PUTTY PLASTI-TAK
Revision Number 1

Revision date 11-Mar-2024
Supersedes Date: 11-Mar-2024

chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation. This document is based on the information given to us by our own suppliers at the date of this document.

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation

Prepared By Product Safety & Regulatory Affairs.

Revision date 11-Mar-2024

Revision Note No information available.

Disclaimer

All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik Inc. ("Company") expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user's application(s). NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN. The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at <https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-management/medical-device-policy/> which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device

SAFETY DATA SHEET

ALCOLIN STICKY PUTTY PLASTI-TAK
Revision Number 1

Revision date 11-Mar-2024
Supersedes Date: 11-Mar-2024

applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

End of Safety Data Sheet