

83847-1003

Super Fabri-Tac**SDS Preparation Date (mm/dd/yyyy): 09/27/2022**

Page 1 of 9

SAFETY DATA SHEET**SECTION 1. IDENTIFICATION****Product identifier used on the label****: Super Fabri-Tac****Other means of identification: Super Fabri-Tac****Recommended use of the chemical and restrictions on use****: Adhesive**
Restriction on use: None known**Chemical family : Mixture****Name, address, and telephone number
of the supplier:****Beacon Adhesives**125 Macquesten Parkway South
Mount Vernon, NY, USA
10550

Supplier's Telephone # : (914) 699 3400

24 Hr. Emergency Tel # : Not available.**Name, address, and telephone number
of the manufacturer:**

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION**Classification of the chemical**

Clear colorless liquid. Alcohol odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Hazard classification

Flammable liquids - Category 2

Serious eye damage/eye irritation - Category 2A

Specific target organ toxicity, single exposure - Category 3 (respiratory)

Specific target organ toxicity, single exposure - Category 3 (narcotic effects)

Label elements**Hazard pictogram(s)****Signal Word****DANGER!****Hazard statement(s)**Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.

Super Fabri-Tac

SDS Preparation Date (mm/dd/yyyy): 09/27/2022

Page 2 of 9

SAFETY DATA SHEET**Precautionary statement(s)**

Keep away from heat, open flames and hot surfaces. - No smoking.
 Keep container tightly closed.
 Ground and bond container and receiving equipment.
 Use explosion-proof electrical and ventilating equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing mist or vapours.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves and eye/face protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 If eye irritation persists: get medical advice/attention.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER or doctor/physician if you feel unwell.
 In case of fire: Use water fog, dry chemical, CO2 or 'alcohol' foam to extinguish.

Store in a well-ventilated place. Keep cool.
 Keep container tightly closed.
 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Other hazards which do not result in classification: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Pure substance**

Chemical name	Common name and synonyms	CAS #	Concentration (% by weight)
Acetone	2-Propanone Methyl ketone	67-64-1	65.0 - 85.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES**Description of first aid measures**

- Ingestion** : Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. Never give anything by mouth to an unconscious person.
- Inhalation** : If inhaled, move to fresh air. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing has stopped, give artificial respiration. Get medical attention if symptoms persist.
- Skin contact** : Wash off with soap and plenty of water. If irritation or symptoms develop, seek medical attention. Wash contaminated clothing before re-use.
- Eye contact** : Immediately flush eyes with running water for at least 15 minutes. Obtain medical attention if irritation persists.

Most important symptoms and effects, both acute and delayed

- : Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis. Direct skin contact may cause slight or mild, transient irritation. May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. May cause central nervous system effects. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Indication of any immediate medical attention and special treatment needed

Item Numbers: 83847-1003, 83847-1004

- : Treat symptomatically. This product is a CNS depressant.

Page 2 of 9

Super Fabri-Tac

SDS Preparation Date (mm/dd/yyyy): 09/27/2022

Page 3 of 9

SAFETY DATA SHEET**SECTION 5. FIRE-FIGHTING MEASURES****Extinguishing media***Suitable extinguishing media*

- : Use water fog or fine spray, foams, carbon dioxide or dry chemical. Do not use a solid water stream as it may scatter and spread fire.

Unsuitable extinguishing media

- : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Highly flammable liquid and vapor. Vapors may travel considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. Static discharge, impact, friction, and heat may ignite exposed chemical material.

Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable liquids - Category 2

Hazardous combustion products

- : Carbon monoxide, carbon dioxide, toxic vapours, gases or particulates.

Special protective equipment and precautions for firefighters*Protective equipment for fire-fighters*

- : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Do not enter without wearing specialized protective equipment suitable for the situation. Firefighter's normal protective clothing (Bunker Gear) will not provide adequate protection. A full-body encapsulating chemical protective suit with positive pressure self-contained breathing apparatus (NIOSH approved or equivalent) may be necessary.

Special fire-fighting procedures

- : Fight fires from a safe distance. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.

SECTION 6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

- : Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. Individuals involved in the cleanup must wear appropriate personal protective equipment. For personal protection see section 8.

Environmental precautions

- : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up

- : Ventilate area of release. Stop spill or leak at source if safely possible. Dike for water control. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with inert, non-combustible absorbent material (e.g. sand, vermiculite), then place material into open, unsealed containers. For waste disposal, see Section 13 of the SDS.

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ): Acetone (5000 lbs / 2270 kg)

SECTION 7. HANDLING AND STORAGE**Precautions for safe handling**

- : Use only in well-ventilated areas. Wear suitable protective equipment during handling. Do not ingest or swallow. Avoid breathing vapours. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Keep away from heat, sparks and open flames. Use only non-sparking tools with this material. Avoid contact with incompatible materials. Keep containers tightly closed when not in use. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not use pressure to empty drums. Do not cut, weld, drill or grind on or near this container. Follow labeled warnings even after container is emptied.

Super Fabri-Tac

SDS Preparation Date (mm/dd/yyyy): 09/27/2022

Page 4 of 9

SAFETY DATA SHEET

Conditions for safe storage : Store in a cool, dry, well-ventilated area. Store away from incompatible materials. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

Incompatible materials : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure Limits:**

<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Acetone	250 ppm	500 ppm	1000 ppm (2400 mg/m ³)	N/Av

Exposure controls**Ventilation and engineering measures**

: Ensure adequate ventilation, especially in confined areas. Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Use explosion-proof electrical and ventilating equipment.

Respiratory protection

: Respiratory protection is required if the concentrations exceed the TLV. NIOSH-approved respirators are recommended. Advice should be sought from respiratory protection specialists. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection

: Wear impervious gloves, such as nitrile rubber. Advice should be sought from glove suppliers.

Eye / face protection

: Chemical splash goggles are recommended. A full face shield may also be necessary.

Other protective equipment : An eyewash station and safety shower should be made available in the immediate working area. Depending on conditions of use, an impervious apron should be worn. Other equipment may be required depending on workplace standards.

General hygiene considerations

: Avoid breathing vapor or mist. Avoid contact with skin, eyes and clothing. Do not ingest. Do not eat, drink or smoke when using this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Clear colorless liquid.

Odor : Alcohol

Odor threshold : Not available.

pH : N/Av

Melting Point/Freezing point : -95°C

Initial boiling point and boiling range

: 56.1°C

Flash point : -20°C

Flashpoint (Method) : Tag closed cup

Evaporation rate (BuAe = 1) : Not available.

Flammability (solid, gas) : Not applicable.

Lower flammable limit (% by vol.)

: Not available.

Upper flammable limit (% by vol.)

: Not available.

Oxidizing properties : None.

Explosive properties : Not explosive

Vapor pressure : Not available.

Super Fabri-Tac

SDS Preparation Date (mm/dd/yyyy): 09/27/2022

Page 5 of 9

SAFETY DATA SHEET

Vapor density : Not available.
Relative density / Specific gravity : 0.9
Solubility in water : Insoluble.
Other solubility(ies) : Not available.
Partition coefficient: n-octanol/water or Coefficient of water/oil distribution : Not available.
Auto-ignition temperature : Not available.
Decomposition temperature : Not applicable.
Viscosity : 8000 cps
Volatiles (by weight) : 4.8 lbs per gallon
Volatile organic Compounds (VOC's) : 60%
Absolute pressure of container : N/Ap
Flame projection length : N/Ap
Other physical/chemical comments : None known or reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.
Chemical stability : Stable under the recommended storage and handling conditions prescribed.
Possibility of hazardous reactions : Hazardous polymerization will not occur.
Conditions to avoid : Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Avoid contact with incompatible materials. Do not use in areas without adequate ventilation. Avoid heat, open flames, sparks, static electricity and electrical equipment.
Incompatible materials : Oxidizing agents
Hazardous decomposition products : None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure:**

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption : NO

Potential Health Effects:**Signs and symptoms of short-term (acute) exposure***Sign and symptoms Inhalation*

: May cause irritation of the nose, throat, mucous membranes, and respiratory tract. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.

Sign and symptoms ingestion

: May cause irritation of mouth, throat, and stomach.

Sign and symptoms skin

: May cause mild skin irritation.

Sign and symptoms eyes

: May cause severe eye irritation.

Potential Chronic Health Effects

: Prolonged or repeated skin contact may cause drying and irritation. Prolonged overexposure may cause liver and kidney effects.

Super Fabri-Tac

SDS Preparation Date (mm/dd/yyyy): 09/27/2022

Page 6 of 9

SAFETY DATA SHEET

Mutagenicity : Not expected to be mutagenic in humans.
Carcinogenicity : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.
Reproductive effects & Teratogenicity : Not expected to have other reproductive effects.
Sensitization to material : Not expected to be a skin or respiratory sensitizer.
Specific target organ effects : This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:
 Specific target organ toxicity, single exposure - Category 3 (respiratory)
 Specific target organ toxicity, single exposure - Category 3 (narcotic effects)

May cause respiratory irritation. May cause drowsiness or dizziness.

Not classified as specific target organ toxicity-repeated exposure.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye and respiratory disorders.

Synergistic materials

: None known or reported by the manufacturer.

Toxicological data

: See below for toxicological data on the substance.

<u>Chemical name</u>	<u>LC₅₀(4hr)</u>	<u>LD₅₀</u>	
	<u>inh, rat</u>	<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Acetone	30 000 ppm (71 mg/L) (vapor)	5800 mg/kg	> 15 800 mg/kg

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity : Not expected to be harmful to aquatic organisms. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Ecotoxicity data:

<u>Ingredients</u>	<u>CAS #</u>	<u>Toxicity to Fish</u>		
		<u>LC₅₀ / 96h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Acetone	67-64-1	6210 mg/L (Fathead minnow)	N/Av	None.

<u>Ingredients</u>	<u>CAS #</u>	<u>Toxicity to Daphnia</u>		
		<u>EC₅₀ / 48h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Acetone	67-64-1	15 800 mg/L (Daphnia magna)	1660 mg/L	None.

<u>Ingredients</u>	<u>CAS #</u>	<u>Toxicity to Algae</u>		
		<u>EC₅₀ / 96h or 72h</u>	<u>NOEC / 96h or 72h</u>	<u>M Factor</u>
Acetone	67-64-1	7000 mg/L/96hr (Green algae)	N/Av	None.

Persistence and degradability

: Acetone is considered to be readily biodegradable.

Item Numbers: 83847-1003, 83847-1004

Bioaccumulation potential

: Does not significantly accumulate in organisms.

Page 6 of 9

Super Fabri-Tac

SDS Preparation Date (mm/dd/yyyy): 09/27/2022

Page 7 of 9

SAFETY DATA SHEET

Components	Partition coefficient n-octanol/water (log K _{ow})	Bioconcentration factor (BCF)
Acetone (CAS 67-64-1)	0.24	0.69 species: fish

Mobility in soil : No data is available on the product itself.

Other Adverse Environmental effects

: No data is available on the product itself.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal : See Section 7 (Handling and Storage) for further details. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not cut, weld, drill or grind on or near this container.

Methods of Disposal : Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method.

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1133	Adhesives	3	II	
49CFR/DOT Additional information	May be shipped as LIMITED QUANTITY when transported in quantities no larger than 1 Litre, in packages not exceeding 30 kg gross mass.				
TDG	UN1133	ADHESIVES	3	II	
TDG Additional information	May be shipped as LIMITED QUANTITY when transported in quantities no larger than 1 Litre, in packages not exceeding 30 kg gross mass.				
ICAO/IATA	UN1133	Adhesives	3	II	
ICAO/IATA Additional information	Refer to the appropriate Packing Instruction, prior to shipping this material. Review all State and Operator Variations, prior to shipping this material.				
IMDG	UN1133	ADHESIVES	3	II	
IMDG Additional information	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass.				

Special precautions for user : Keep away from heat, sparks and open flame - No smoking.

Environmental hazards : This product does not meet the criteria for an environmentally hazardous mixture, according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

Super Fabri-Tac

SDS Preparation Date (mm/dd/yyyy): 09/27/2022

Page 8 of 9

SAFETY DATA SHEET

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	de minimus Concentration
Acetone	67-64-1	Yes	5000 lb/ 2270 kg	None.	No	N/Ap

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Flammable; Eye irritation Specific target organ toxicity, single exposure. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

Ingredients	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Acetone	67-64-1	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

WHMIS Classification: Refer to Section 2 for a WHMIS Classification for this product.
All ingredients are present on the DSL.

International Information:

Components listed below are present on the following International Inventory list:

Ingredients	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Acetone	67-64-1	200-662-2	Present	Present	(2)-542	KE-29367	Present	HSR001070

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists

CA: California

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980

CFR: Code of Federal Regulations

CNS: Central Nervous System

CSA: Canadian Standards Association

DOT: Department of Transportation

EPA: Environmental Protection Agency

HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

LC: Lethal Concentration

LD: Lethal Dose

MA: Massachusetts

MN: Minnesota

N/Ap: Not Applicable

N/Av: Not Available

Super Fabri-Tac

SDS Preparation Date (mm/dd/yyyy): 09/27/2022

Page 9 of 9

SAFETY DATA SHEET

NIOSH: National Institute of Occupational Safety and Health
 NJ: New Jersey
 NTP: National Toxicology Program
 OSHA: Occupational Safety and Health Administration
 PA: Pennsylvania
 PEL: Permissible exposure limit
 RCRA: Resource Conservation and Recovery Act
 RI: Rhode Island
 RTECS: Registry of Toxic Effects of Chemical Substances
 SARA: Superfund Amendments and Reauthorization Act
 STEL: Short Term Exposure Limit
 TDG: Canadian Transportation of Dangerous Goods Act & Regulations
 TLV: Threshold Limit Values
 TWA: Time Weighted Average
 WHMIS: Workplace Hazardous Materials Identification System

References

- 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for
- 2. ECHA - European Chemical Agency
- 3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, (Chempendium, HSDB and RTECs).
- 4. Safety Data Sheets from manufacturer.
- 5. US EPA Title III List of Lists
- 6. California Proposition 65 List
- 7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal

Preparation Date (mm/dd/yyyy)

: 09/27/2022

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

Prepared for: Beacon Adhesives 125 Macquesten Parkway South Mount Vernon, NY 10550 Telephone: (914) 699 3400	
Prepared by: ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada) http://www.thecompliancecenter.com	 ComplianceCenter

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by / obtained from Beacon Adhesives and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Beacon Adhesives expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process. This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Beacon Adhesives.

END OF DOCUMENT