83863-2135

## **Safety Data Sheet**



Revision Number: 001.4 Issue date: 11/07/2018

### PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name: **Loctite Professional Performance** 

**Spray Adhesive** 

Product type: Adhesive Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067

Region: United States Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

2267077

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

### **HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW** 

DANGER: EXTREMELY FLAMMABLE AEROSOL.

CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

MAY CAUSE DROWSINESS OR DIZZINESS.

CAUSES SERIOUS EYE IRRITATION.

**HAZARD CLASS** HAZARD CATEGORY FLAMMABLE AEROSOL SKIN IRRITATION **EYE IRRITATION** 2A SKIN SENSITIZATION SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE GASES UNDER PRESSURE Compr. Gas



#### **Precautionary Statements**

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an

open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist or spray. Wash affected area thoroughly after handling. Use only outdoors or in a wellventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear

protective gloves, eye protection, and face protection.

IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at Response:

rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

IDH number: 2267077 Product name: Loctite Professional Performance Spray Adhesive

Page 1 of 7

Page 1 of 7 Item Numbers: 83863-2135

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

5 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Acetone	67-64-1	30 - 60	
Butane	106-97-8	10 - 30	
Propane	74-98-6	10 - 30	
Dimethyl ether	115-10-6	5 - 10	
Hydrocarbons, C9-unsatd., polymd.	71302-83-5	5 - 10	
Methyl acetate	79-20-9	5 - 10	
Modified Rosin Ester		5 - 10	
Naphtha, petroleum, hydrotreated light	64742-49-0	5 - 10	
4-Chloroalpha.,.alphaalpha trifluorotoluene	98-56-6	5 - 10	
Alkanes, C12-14-iso	68551-19-9	1 - 5	
n-Heptane	142-82-5	1 - 5	
Methylcyclohexane	108-87-2	1 - 5	
Remainder		5 - 10	

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

Skin contact: Remove contaminated clothes. Wash affected area immediately with soap and

water. Obtain medical attention if irritation persists.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.

minutes, and seek immediate medical attention.

Get immediate medical attention. Do not induce vomiting.

Symptoms: See Section 11.

Ingestion:

# 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses. Contents under pressure. Do not puncture or incinerate pressurized containers. Exposure to temperatures above 49°C

(120°F) may cause container to burst.

IDH number: 2267077 Product name: Loctite Professional Performance Spray Adhesive

Page 2 of 7

Item Numbers: 83863-2135 Page 2 of 7

Upon decomposition, this product emits carbon monoxide, carbon dioxide Hazardous combustion products:

and/or low molecular weight hydrocarbons. Oxides of nitrogen.

### **ACCIDENTAL RELEASE MEASURES**

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

**HANDLING AND STORAGE** 

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Avoid breathing vapors or mists of this product. Do not take internally.

Storage:

For safe storage, store at or below 48.8 °C (119.8 °F) Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Acetone	250 ppm TWA 500 ppm STEL	1,000 ppm (2,400 mg/m3) PEL	None	None
Butane	1,000 ppm STEL (Simple asphyxiant.)	None	None	None
Propane	D: Simple asphyxiant, EX: Explosion hazard (Simple asphyxiant.)	1,000 ppm (1,800 mg/m3) PEL	None	None
Dimethyl ether	None	None	1,000 ppm (1,880 mg/m3) TWA	None
Hydrocarbons, C9-unsatd., polymd.	None	None	None	None
Methyl acetate	200 ppm TWA 250 ppm STEL	200 ppm (610 mg/m3) PEL	None	None
Modified Rosin Ester	None	None	None	None
Naphtha, petroleum, hydrotreated light	None	100 ppm (400 mg/m3) PEL	None	None
4-Chloroalpha.,.alpha., alpha trifluorotoluene	None	None	None	None
Alkanes, C12-14-iso	None	None	None	None
n-Heptane	400 ppm TWA 500 ppm STEL	500 ppm (2,000 mg/m3) PEL	None	None
Methylcyclohexane	400 ppm TWA	500 ppm (2,000 mg/m3) PEL	None	None
Remainder	None	None	None	None

**Engineering controls:** 

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

IDH number: 2267077

Product name: Loctite Professional Performance Spray Adhesive

Page 3 of 7

Page 3 of 7 Item Numbers: 83863-2135

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or Respiratory protection:

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended.

## PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Aerosol

Color: No information available. Odor: Not available.

Odor threshold: Not available. pH: Vapor pressure: Not available. Not available. Boiling point/range: 72.1 °C (161.8 °F) Melting point/ range: Vapor density: Not available. Not available.

Flash point: -104.4 °C (-155.92 °F)

Flashback: This product exhibits flashback when tested for flame extension.

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Not available. Not available. Autoignition temperature: Not available.

Flammability: Extremely flammable aerosol.

Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water): Not available. Not available Not available.

38.8 % (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method) VOC content:

Viscosity: Decomposition temperature: Not available. Not available.

### 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low Hazardous decomposition

molecular weight hydrocarbons. Oxides of nitrogen. products:

Incompatible materials: This product may react with strong acids, bases and oxidizing agents.

Reactivity: Not available

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

## **TOXICOLOGICAL INFORMATION**

Relevant routes of exposure: Skin, Inhalation, Eyes

IDH number: 2267077 Product name: Loctite Professional Performance Spray Adhesive

Page 4 of 7

Page 4 of 7 Item Numbers: 83863-2135

### Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system. May

cause central nervous system effects with nausea, dizziness and headache. Causes skin irritation. May cause allergic skin reaction. Causes serious eye irritation.

Skin contact: Eye contact: Ingestion:

Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Acetone	Oral LD50 (Mouse) = 5.2 g/kg Oral LD50 (Mouse) = 3,000 mg/kg Oral LD50 (Rabbit) = 5,340 mg/kg Oral LD50 (Rat) = 5,800 mg/kg Oral LD50 (Rat) = 9,800 mg/kg Dermal LD50 (Rabbit) = 20,000 mg/kg	Central nervous system, Irritant
Butane	None	Cardiac, Central nervous system, Irritant
Propane	None	Cardiac, Central nervous system, Irritant
Dimethyl ether	None	Irritant, Central nervous system
Hydrocarbons, C9-unsatd., polymd.	None	No Records
Methyl acetate	Oral LD50 (Rabbit) = 3.7 g/kg	Blood, Central nervous system, Eyes, Irritant
Modified Rosin Ester	None	No Data
Naphtha, petroleum, hydrotreated light	None	Central nervous system, Irritant, Kidney, Lung
4-Chloroalpha.,.alpha.,.alpha.trifluorotoluene	None	Adrenals, Blood, Central nervous system, Immune system, Irritant, Kidney, Liver, Lung, Skin, Thyroid
Alkanes, C12-14-iso	None	No Data
n-Heptane	None	Central nervous system, Irritant
Methylcyclohexane	None	Central nervous system, Irritant, Kidney, Liver
Remainder	None	No Data

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Acetone	No	No	No
Butane	No	No	No
Propane	No	No	No
Dimethyl ether	No	No	No
Hydrocarbons, C9-unsatd., polymd.	No	No	No
Methyl acetate	No	No	No
Modified Rosin Ester	No	No	No
Naphtha, petroleum, hydrotreated light	No	No	No
4-Chloroalpha.,.alpha.,.alpha trifluorotoluene	No	No	No
Alkanes, C12-14-iso	No	No	No
n-Heptane	No	No	No
Methylcyclohexane	No	No	No
Remainder	No	No	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** 

Harmful to aquatic organisms.

IDH number: 2267077 Product name: Loctite Professional Performance Spray Adhesive Page 5 of 7

Page 5 of 7 Item Numbers: 83863-2135

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number: It is the responsibility of the user to determine if an item is hazardous as

defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
DOT Hazardous Substance(s):

Aerosols
2.1
UN 1950
None
Acetone

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable

Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS (Heptanes)

Hazard class or division:

Identification number:
Packing group:
Warine pollutant:

UN 1950
None
Heptanes

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: Chloro-fluoro solvent (CAS# 98-56-6).

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:
None above reporting de minimis.
None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

IDH number: 2267077 Product name: Loctite Professional Performance Spray Adhesive

Page 6 of 7

Item Numbers: 83863-2135 Page 6 of 7

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2,3,8,11,16

Prepared by: Product Safety and Regulatory Affairs

Issue date: 11/07/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 2267077 Product name: Loctite Professional Performance Spray Adhesive Page 7 of 7

Item Numbers: 83863-2135 Page 7 of 7