

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name or designation of the mixture Galkyd Gel, Neo Megilp
Registration number -
Synonyms None.
Issue date 22-September-2020
Version number 03
Revision date 07-January-2021
Supersedes date 22-September-2020

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Mixing agent for artist's oil colors.
Uses advised against Keep out of reach of children.

1.3. Details of the supplier of the safety data sheet

Supplier Gamblin Artists Colors
2734 SE Raymond St.
Portland, OR 97202
USA
Telephone number +1 503-235-1945
Website www.gamblincolors.com

Manufacturer Gamblin Artists Colors
2734 SE Raymond St.
Portland, OR 97202
USA

Telephone number +1 503-235-1945

1.4 Emergency telephone number For Chemical Emergency ONLY, call:
+1 503-235-1945

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Hazard summary Not classified for health hazards.

2.2. Label elements**Label according to Regulation (EC) No. 1272/2008 as amended**

Contains: Propylene glycol, Silica, amorphous, fumed, cryst.-free
Hazard pictograms None.
Signal word None.
Hazard statements The mixture does not meet the criteria for classification.

Precautionary statements

Prevention Observe good industrial hygiene practices.
Response Wash hands after handling.
Storage Store away from incompatible materials.
Disposal Dispose of waste and residues in accordance with local authority requirements.

Supplemental label information None.

Galkyd Gel, Neo Megilp

SDS EU

953395 Version #: 03 Revision date: 07-January-2021 Issue date: 22-September-2020
Item Numbers: 00456-1504, 00456-1605, 00456-1606

1 / 10
Page 1 of 10

2.3. Other hazards

MSDS for #00456 - GAMBLIN (OIL MEDIUM)

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	EC No.	REACH Registration No.	Notes
Alkyd resin	45 - 55	Proprietary	-	
Classification: -				
Petroleum Naptha	40 - 60	920-901-0	-	
Classification: Flam. Liq. 4;H227, Asp. Tox. 1;H304				
Silica, amorphous, fumed, cryst.-free	3 - 6	231-545-4	-	P
Classification: -				
Propylene glycol	1 - 3	200-338-0	-	
Classification: -				

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Note P: The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

Exposure may cause temporary irritation, redness, or discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards

No unusual fire or explosion hazards noted. The product is combustible.

5.1. Extinguishing media

Suitable extinguishing media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
For emergency responders	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Use water spray to reduce vapours or divert vapour cloud drift.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid prolonged exposure. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

7.3. Specific end use(s)

Mixing agent for artist's oil colors.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits****Austria. MAK List Components**

Components	Type	Value	Form
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	MAK	4 mg/m ³	Inhalable fraction.

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work Components

Components	Type	Value	Form
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TWA	10 mg/m ³	Inhalable fraction.
		0,07 mg/m ³	Respirable fraction.

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Components

Components	Type	Value	Form
Propylene glycol (CAS 57-55-6)	MAC	10 mg/m ³	
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	MAC	150 ppm	
		6 mg/m ³	Total dust.
		0,1 mg/m ³	Respirable dust.

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended. Components

Components	Type	Value	Form
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TWA	2 mg/m ³	

Czech Republic. OELs. Government Decree 361 Components

Components	Type	Value	Form
Petroleum Naptha (CAS 64742-48-9)	Ceiling	1000 mg/m ³	
	TWA	200 mg/m ³	

Components	Type	Value	Form
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TWA	4 mg/m3	Dust.
Denmark. Exposure Limit Values			
Components	Type	Value	
Petroleum Naptha (CAS 64742-48-9)	TLV	25 ppm	
Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)			
Components	Type	Value	Form
Petroleum Naptha (CAS 64742-48-9)	STEL	300 mg/m3	
		50 ppm	
	TWA	150 mg/m3	
		25 ppm	
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TWA	2 mg/m3	Fine dust, respiratory fraction
Finland. Workplace Exposure Limits			
Components	Type	Value	
Petroleum Naptha (CAS 64742-48-9)	TWA	500 mg/m3	
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TWA	5 mg/m3	
Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)			
Components	Type	Value	Form
Petroleum Naptha (CAS 64742-48-9)	TWA	300 mg/m3	
		50 ppm	
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TWA	4 mg/m3	Inhalable fraction.
Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace			
Components	Type	Value	Form
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	AGW	4 mg/m3	Inhalable fraction.
Iceland. OELs. Regulation 154/1999 on occupational exposure limits			
Components	Type	Value	Form
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TWA	5 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
		0,5 mg/m3	Dust.
Ireland. Occupational Exposure Limits			
Components	Type	Value	Form
Propylene glycol (CAS 57-55-6)	TWA	470 mg/m3	Total vapour and particulates.
		10 mg/m3	Particulate.
		150 ppm	Total vapour and particulates.
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TWA	6 mg/m3	Total inhalable dust.

Components	Type	Value	Form
		2,4 mg/m3	Respirable dust.
Latvia. OELs. Occupational exposure limit values of chemical substances in work environment			
Components	Type	Value	
Propylene glycol (CAS 57-55-6)	TWA	7 mg/m3	
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TWA	1 mg/m3	
Lithuania. OELs. Limit Values for Chemical Substances, General Requirements (Hygiene Norm HN 23:2007)			
Components	Type	Value	
Propylene glycol (CAS 57-55-6)	TWA	7 mg/m3	
Norway. Administrative Norms for Contaminants in the Workplace			
Components	Type	Value	Form
Propylene glycol (CAS 57-55-6)	TLV	79 mg/m3	
		25 ppm	
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TLV	1,5 mg/m3	Respirable dust.
Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817			
Components	Type	Value	Form
Petroleum Naptha (CAS 64742-48-9)	STEL	900 mg/m3	
	TWA	300 mg/m3	
Propylene glycol (CAS 57-55-6)	TWA	100 mg/m3	Inhalable fraction and vapour.
Slovakia. OELs. Decree of the government of the Slovak Republic concerning protection of health in work with chemical agents			
Components	Type	Value	
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TWA	0,3 mg/m3	
Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)			
Components	Type	Value	Form
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TWA	4 mg/m3	Inhalable fraction.
Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)			
Components	Type	Value	
Petroleum Naptha (CAS 64742-48-9)	STEL	300 mg/m3	
		50 ppm	
	TWA	150 mg/m3	
		25 ppm	
Switzerland. SUVA Grenzwerte am Arbeitsplatz			
Components	Type	Value	
Petroleum Naptha (CAS 64742-48-9)	STEL	600 mg/m3	
		100 ppm	
	TWA	300 mg/m3	
		50 ppm	

Component	Type	Value	Form
Propylene glycol (CAS 57-55-6)	TWA	474 mg/m3	Total vapour and particulates.
		10 mg/m3	Particulate.
		150 ppm	Total vapour and particulates.
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5)	TWA	6 mg/m3	Inhalable dust.
		2,4 mg/m3	Respirable dust.
Biological limit values	No biological exposure limits noted for the ingredient(s).		
Recommended monitoring procedures	Follow standard monitoring procedures.		
Derived no effect levels (DNELs)	Not available.		
Predicted no effect concentrations (PNECs)	Not available.		
8.2. Exposure controls			
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
Individual protection measures, such as personal protective equipment			
General information	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.		
Eye/face protection	Wear safety glasses with side shields (or goggles).		
Skin protection			
- Hand protection	Wear protective gloves.		
- Other	Wear appropriate chemical resistant clothing.		
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.		
SECTION 9: Physical and chemical properties			
9.1. Information on basic physical and chemical properties			
Appearance			
Physical state	Liquid.		
Form	Liquid Gel		
Colour	Amber.		
Odour	Characteristic hydrocarbon.		
Odour threshold	Not available.		
pH	Not available.		
Melting point/freezing point	Not available.		
Initial boiling point and boiling range	158,89 - 198,89 °C (318 - 390 °F)		
Flash point	> 70,0 °C (> 158,0 °F) Pensky-Martens Closed Cup		
Evaporation rate	0,2		
Flammability (solid, gas)	Not applicable.		
Upper/lower flammability or explosive limits			
Flammability limit - lower (%)	Not available.		

Vapour pressure	< 0,1 kPa @ 68°F (20°C)
Vapour density	5
Relative density	Not available.
Solubility(ies)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	230 °C (446 °F)
Decomposition temperature	Not available.
Viscosity	Thixotropic gel.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Chlorine. Fluorine. Strong oxidizers.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.
Information on likely routes of exposure	
Inhalation	Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms	Exposure may cause temporary irritation, redness, or discomfort.

11.1. Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Petroleum Naptha (CAS 64742-48-9)		
Acute		
Dermal		
<i>Liquid</i>		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
<i>Vapour</i>		
LC50	Rat	> 5000 mg/m ³ , 4 hr
Oral		
<i>Liquid</i>		
LD50	Rat	> 5000 mg/kg
Propylene glycol (CAS 57-55-6)		
Acute		
Dermal		
LD50	Rabbit	20800 mg/kg
Oral		
LD50	Rat	22000 mg/kg

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.

Germ cell mutagenicity Based on available data, the classification criteria are not met.
Carcinogenicity Based on available data, the classification criteria are not met.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Petroleum Naptha (CAS 64742-48-9)

IARC Monographs. Overall Evaluation of Carcinogenicity

Petroleum Naptha (CAS 64742-48-9) 3 Not classifiable as to carcinogenicity to humans.
Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Based on available data, the classification criteria are not met.
Specific target organ toxicity - single exposure Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Not an aspiration hazard.

Mixture versus substance information No information available.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic environment.

Components	Species	Test Results
Petroleum Naptha (CAS 64742-48-9)		
Aquatic		
<i>Acute</i>		
Algae	EL0	Pseudokirchnerella subcapitata 1000 mg/l, 72 hr
	NOELR	Pseudokirchnerella subcapitata 1000 mg/l, 72 hr
Crustacea	EL0	Daphnia magna 1000 mg/l, 48 hr
Fish	LL0	Oncorhynchus mykiss 1000 mg/l, 96 hr
<i>Chronic</i>		
Crustacea	NOELR	Daphnia magna 1 mg/l, 21 d
Propylene glycol (CAS 57-55-6)		
Aquatic		
<i>Acute</i>		
Algae	EC50	Selenastrum capricornutum 19000 mg/l, 72 hours
Crustacea	LC50	Ceriodaphnia 18340 mg/l, 48 hours
Fish	LC50	Pimephales promelas 46500 mg/l, 96 hours

12.2. Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil The product is insoluble in water.

12.5. Results of PBT and vPvB assessment This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

12.7. Additional information

Estonia Dangerous substances in soil Data

Silica, amorphous, fumed, cryst.-free (CAS 112945-52-5) Chemical pesticides (As the total sum of the active substances) 0,5 mg/kg
Chemical pesticides (As the total sum of the active substances) 20 mg/kg
Chemical pesticides (As the total sum of the active substances) 5 mg/kg

13.1. Waste treatment methods

Residual waste	Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information**ADR**

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations**

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Petroleum Naptha (CAS 64742-48-9)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Petroleum Naptha (CAS 64742-48-9)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations

MSDS for #00456 - GAMBLINOLUMEDIAN
The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP) and Regulation (EC) No 1907/2006, as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information**List of abbreviations**

PBT: Persistent, bioaccumulative and toxic.
EC50: Effective Concentration, 50%.
EL0: Effective level, 0%.
IC50: Inhibitory concentration, 50%.
LC50: Lethal Concentration, 50%.
LD50: Lethal Dose, 50%.
LL0: Lethal level, 0%.
NOELR: No Observed Effect Loading Rate
STEL: Short-Term Exposure Limit.
TWA: Time Weighted Average Value.
vPvB: Very persistent and very bioaccumulative.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H227 Combustible liquid.
H304 May be fatal if swallowed and enters airways.

Training information

Follow training instructions when handling this material.

Disclaimer

The information in this Safety Data Sheet has been obtained from current and reliable sources. However, the data is provided without warranty, express or implied, regarding its correctness or accuracy. It is the user's responsibility to determine safe conditions for use of this product and to assume liability for loss injury, damage, or expense resulting from improper use of this product.