

00628-0044

Safety Data Sheet

Section 1 - Identification

Product Name(s):	Product Code(s):
Gloss MSA Varnish with UVLS	7730
Satin MSA Varnish with UVLS	7735
Matte MSA Varnish with UVLS	7740
Semi-Gloss MSA Varnish with UVLS	7746

GOLDEN ARTIST COLORS, INC.
188 BELL ROAD
NEW BERLIN, NY 13411

Phone: (607)847-6154
In US only: (800)959-6543

Prepared by: Regulatory Department
Product Use: Artist's Paint
Not recommended for: Use by children

Section 2 - Hazards Identification

GHS Ratings:

Flammable liquid	3	Flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$ (140°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: ≥ 2.3 < 4.0 or persistent inflammation
Skin sensitizer	1	Skin sensitizer
Carcinogen	2	Limited evidence of human or animal carcinogenicity
Reproductive toxin	2	Human or animal evidence possibly with other information
Organ toxin single exposure	3	Transient target organ effects- Narcotic effects- Respiratory tract irritation
Organ toxin repeated exposure	2	Presumed to be harmful to human health- Animal studies with significant toxic effects relevant to humans at generally moderate exposure (guidance)- Human evidence in exceptional cases
Acute aquatic toxicity	A2	Acute toxicity > 1.00 but ≤ 10.0 mg/l
Chronic aquatic toxicity	C2	Acute toxicity > 1.00 but ≤ 10.0 mg/l and lack of rapid degradability and log Kow ≥ 4 unless BCF < 500 and unless chronic toxicity > 1 mg/l

GHS Hazards

H226	Flammable liquid and vapor
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking

SDS for: MSA Varnishes

Page 1 of 7

Item Numbers: 00628-0044, 00628-0047, 00628-0054, 00628-0056, 00628-0057, 00628-0059, 00628-0065, 00628-0066, 00628-0067, 00628-1205, 00628-1206, 00628-1209, 00628-1215, 00628-1504, 00628-1505, 00628-1506, 00628-1507, 00628-1514, 00628-1515, 00628-1516, 00628-1517, 00628-1524, 00628-1525, 00628-1526, 00628-1527, 00628-2034, 00628-2035, 00628-2036, 00628-2037, 00628-2039, 00628-9007, 00628-9008

Printed: 2/27/2019 at 9:22 AM

P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/...equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P260	Do not breathe dust/fume/gas/mist/vapors/spray
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash hands with soap and water thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P272	Contaminated work clothing should not be allowed out of the workplace
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P314	Get Medical advice/attention if you feel unwell
P321	Specific treatment, see Section 4
P362	Take off contaminated clothing and wash before reuse
P363	Wash contaminated clothing before reuse
P391	Collect spillage
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P370+P378	In case of fire: Use ... for extinction
P405	Store locked up
P403+P233	Store in a well ventilated place. Keep container tightly closed
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container according to Section 13

Signal Word: Warning**Section 3 - Hazardous Composition**

Chemical Name	CAS number	Weight Concentration %
Mineral Spirits	8052-41-3	30.00% - 50.00%
Solvent Naptha, Petroleum, Heavy Aromatic	64742-94-5	1.00% - 5.00%
1,2,4-Trimethylbenzene	95-63-6	1.00% - 5.00%
Nonane	111-84-2	1.00% - 5.00%
Mineral Spirits	64742-88-7	0.00% - 5.00%
Toluene	108-88-3	0.10% - 1.00%
Bis(1,2,2,6,6-pentamethyl-4-piperidinyI)	41556-26-7	0.10% - 1.00%
Naphthalene	91-20-3	0.10% - 1.00%
Ethylbenzene	100-41-4	0.10% - 1.00%
Methyl1,2,2,6,6-pentamethyl-4-piperidinyI)	82919-37-7	0.10% - 1.00%

(1) Napthalene - WARNING: This product contains a chemical known to the State of California to cause cancer.

(2) Ethyl Benzene - WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 4 - First Aid

Inhalation: Remove subject to fresh air. Give artificial respiration if breathing has stopped. Seek medical attention.

Eye: Flush with water for 15 minutes. Remove contact lenses, if present and easy to do so. If symptoms develop and persist seek medical attention.

Skin: Wash with soap and water. Remove contaminated clothing. Seek medical attention for irritation.

Ingestion: If swallowed, dilute by giving 2 or more glasses of water to drink ONLY IF CONSCIOUS! Do not induce vomiting. Seek medical attention IMMEDIATELY.

Section 5 - Fire Fighting

Flash Point: 37 C (99 F)

LEL: N/A

UEL: N/A

Extinguishing Media: Foam, Carbon Dioxide, Dry Chemical, Powder. Do NOT use high pressure Water Spray, as this will spread the fire.

Unusual Fire and Explosion Hazards: Vapors can travel to a source of ignition and flash back. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat. During a fire, irritating and highly toxic gases and/or fumes may generate during combustion or decomposition.

Hazardous Byproducts: Combustion will yield oxides of carbon and nitrogen, as well as, monomer fume.

Fire Fighting Procedures: Move containers promptly out of fire zone. If removal is impossible, keep containers cool with water spray. Remain upwind and avoid breathing smoke or fumes.

Special Precautions: Wear self-contained breathing apparatus and full protective gear.

Section 6 - Release

Personal precautions, protective equipment and emergency procedures: Appropriate protective equipment must be worn when handling a spill of this material. See Section - 8 Exposure Control for recommendations. If exposed to material during clean-up operations, see Section 4 - First Aid for actions to follow.

Environmental precautions: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Methods and materials for containment and clean-up: Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area to dissipate vapor. Floor may be slippery; use care to avoid falling. Soak up spills with inert absorbent material. Sweep up and collect in suitable container for disposal. Avoid breathing vapor.

Section 7 - Handling

Precautions and safe handling: Use only in well-ventilated areas. Avoid inhalation of vapors/spray and contact with skin and eyes. Wear appropriate personal protective equipment. The mixture is flammable, and heating may generate vapors which may form explosive vapor/air mixtures. Do not smoke or use near other sources of ignition. Read label before use.

Conditions for safe storage: Keep away from heat, sparks and open flame. Store in a cool, well-ventilated place. Keep out of the reach of children.

Section 8 - Exposure Control

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Mineral Spirits 8052-41-3	PEL TWA 500 PPM TWA 2900 mg/m ³ REL TWA 350 mg/m ³	TLV 100 PPM	Not Established
Solvent Naptha, Petroleum, Heavy Aromatic 64742-94-5	PEL 500 PPM	Not Established	Not Established
1,2,4-Trimethylbenzene 95-63-6	Not Established	TWA 25 ppm	NIOSH TWA 25ppm/125 mg/m ³
Nonane 111-84-2	TWA 200 PPM	TWA 200 ppm	Not Established
Mineral Spirits 64742-88-7	PEL 2900 mg/m ³ , 500 ppm TWA 525 mg/m ³ , 100 ppm	Not Established	Not Established
Toluene 108-88-3	TWA 100PPM/375 mg/m ³ STEL 150ppm/560 mg/m ³	Not Established	Not Established
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) 41556-26-7	Not Established	Not Established	Not Established
Naphthalene 91-20-3	TWA 10ppm/50 mg/m ³ ST 15ppm/ 75 mg/m ³	TWA 10 ppm SKIN	Not Established
Ethylbenzene 100-41-4	TWA 100 ppm/435 mg/m ³ ST 125 ppm/545 mg/m ³	TWA 20 ppm	Not Established
Methyl1,2,2,6,6-pentamethyl-4-piperidinyl) 82919-37-7	Not Established	Not Established	Not Established

Engineering Controls: Use explosion proof ventilation equipment. Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of possible vapor. Provide easy access to water supply, eye wash or emergency shower.

General Hygiene Considerations: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Private clothes and work clothes should be kept separate.

Personal Protective Equipment: Wear approved safety glasses or goggles. Wear solvent-resistant gloves. Be aware that liquid may penetrate the gloves, suitable gloves can be recommended by the glove supplier.

Section 9 - Properties

Properties listed are typical and not to be used as a specification.

<p>Appearance: Liquid</p> <p>Vapor Pressure: Not available</p> <p>Vapor Density: Not available</p> <p>Density: 0.88 - 0.90</p> <p>Freezing point: Not available</p> <p>Boiling range: Not available</p>	<p>Odor: Mineral Spirits</p> <p>Odor threshold: Not available</p> <p>pH: Not applicable</p> <p>Melting point: Not applicable</p> <p>Solubility: Not soluble</p> <p>Flash point: 37°C, 99°F</p>
---	--

Evaporation rate: Not available Explosive Limits: Not available Auto ignition temperature: Not available Viscosity: 600-4500 cPs MIR 1.01 – 1.09	Flammability: Not applicable Partition coefficient (n-octanol/water): Not available Decomposition temperature: Not available Grams/Liter VOC less water: 512 - 536
---	---

Section 10 - Reactivity

Under normal conditions this mixture is considered to be:
STABLE

Materials that are known to be incompatible with this mixture and should be avoided, if applicable:

Not Applicable

Risk of hazardous decomposition:

Not Applicable

Hazardous polymerization will not occur.

Section 11 - Toxicology

Mixture Toxicity

Oral Toxicity LD50: 601mg/kg

Inhalation Toxicity LC50: 15mg/L

Component Toxicity

Possible routes of entry or exposure:

Inhalation Skin Contact Eye Contact Ingestion

Possible target organs of exposure to this mixture:

Eyes Kidneys Liver Lungs GI Tract Respiratory System

Effects of Overexposure

Carcinogenicity: This mixture as a whole has not been tested to determine its carcinogenic properties. The components of this mixture that are reported as possible or known carcinogens are as follows:

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
100-41-4	Ethylbenzene	0.1% - 1.0%	Ethylbenzene: Caused cancer in laboratory animal studies. The relevance of these findings to humans is uncertain.
91-20-3	Naphthalene	0.1% - 1.0%	Naphthalene: Caused cancer in laboratory animal studies. The relevance of these findings to humans is uncertain.

Acute Toxicity: May cause central nervous system effects.

Section 12 - Ecological Toxicity

Ecotoxicity: This mixture as a whole has not been tested to determine its ecological toxicity. The components of this mixture with documented ecological data are as follows:

Component Ecotoxicity

SDS for: MSA Varnishes

Solvent Naptha, Petroleum, Heavy Aromatic	LC50, RAINBOW TROUT, 96h, 3.6 mg/l EC50, WATER FLEA, 48h, 1.1 mg/l EC50, GREEN ALGAE, 72h 7.2 mg/l
1,2,4-Trimethylbenzene	LC50, FATHEAD MINNOW, 96h, 7.72mg/l EC50, WATER FLEA, 48h, 3.6mg/l
Nonane	EC50, WATER FLEA, 48 h, 0.2 mg/l
Toluene	LC50, RAINBOW TROUT, 96h, 7.63mg/l EC50, WATER FLEA, 24h, 8.00 mg/l EC50, GREEN ALGAE, 24h, 10.00 mg/l
Bis(1,2,2,6,6-pentamethyl-4-piperid inyl)	LC50 Lepomis Macrochirus 1 mg/l 96h EC50 Water Flea 20 mg/l 48h
Naphthalene	LC50, RAINBOW TROUT, 96h, 0.11 mg/l EC50, WATER FLEA, 48h, 1.6 - 24.1 mg/l
Ethylbenzene	LC50, RAINBOW TROUT, 96h, 4.2 mg/l EC50, WATER FLEA, 1d, 2.2 mg/l EC50, GREEN ALGAE, 72h, GROWTH INHIBITION 3.6 - 4.6 mg/l

Section 13 - Disposal

Disposal Instructions: Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities. Do not discharge into drains, water courses or onto the ground. Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 14 - Transport

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing</u>	<u>Hazard Class</u>
DOT	PAINT Marine Pollutant	1263	III	3
IATA	PAINT Environmental Hazard	1263	III	3
IMDG	PAINT Marine Pollutant	1263	III	3

Section 15 - Regulatory

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

108-88-3	Toluene	Reproductive Toxin
91-20-3	Naphthalene	Carcinogen
100-41-4	Ethylbenzene	Carcinogen

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
AUSTRALIA	AICS- Australian Inventory of Chemical Substances	Yes
CANADA	Domestic Substances List (DSL) and Non-Domestic	Yes
EUROPE	European Inventory of Existing Commercial Chemical	Yes
EUROPE	European List of Notified Chemical Substances	No

JAPAN	Inventory of Existing and New Chemical Substances	No
CHINA	Inventory of Existing Chemical Substances in China	Yes
KOREA	Korean Existing Chemicals Inventory (KECI)	Yes
NEW ZEALAND	New Zealand Inventory of Chemicals (NZIoC)	Yes
PHILLIPPINES	Philippine Inventory of Chemicals and Chemical	Yes
USA	Toxic Substances Control Act (TSCA) Inventory	Yes

Section 16 - Other Information

While Golden Artist Colors, Inc. believes the data set forth herein is accurate as of the date hereof, Golden Artist Colors, Inc. makes no warranty with respect to the accuracy of this date and expressly disclaims all liability for reliance thereon. Such data is offered solely for your consideration, investigation, and verification.

Date revised: 2018-11-06
Date Prepared: 2/27/2019

Reviewer Revision