



















	MTN PRO CHALK WATER BASED Code: EX00W9011C																							
Version: 1 Date of compilation: 24/11/2017		Date of printing: 08/11/2018																						
<b>SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING</b>																								
1.1	<u>PRODUCT IDENTIFIER:</u> MTN PRO CHALK WATER BASED Code: EX00W9011C																							
1.2	<u>RELEVANT IDENTIFIED USES AND USES ADVISED AGAINST:</u> <u>Intended uses (main technical functions):</u> Paint. <span style="float: right;">[ ] Industrial [X] Professional [X] Consumers</span> <u>Sectors of use:</u> Professional uses (SU22). Consumer uses (SU21). <u>Uses advised against:</u> This product is not recommended for any use or sector of use industrial, professional or consume other than those previously listed as 'Intended or identified uses'. <u>Restrictions on manufacture, placing on market and use:</u> Nor restricted.																							
1.3	<u>DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:</u> MONTANA COLORS, S.L. Pol. Ind. Pla de les Vives - c/AnaisNi n 6 - 08295 Sant Vicenç de Castellet (Barcelona) ESPAÑA Phone: +34 93 8332760 - Fax: +34 93 8332761 - www.montanacolors.com <u>E-mail address of the person responsible for the safety data sheet:</u> e-mail: msds@montanacolors.com																							
1.4	<u>EMERGENCY TELEPHONE NUMBER:</u> +34 93 8332787 (9:00-17:00 h.) (working hours)																							
<b>SECTION 2 : HAZARDS IDENTIFICATION</b>																								
2.1	<u>CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:</u>  <u>HMIS Hazard Ratings:</u> <table border="1" data-bbox="600 756 779 840"> <tr><td>3</td><td>HEALTH</td></tr> <tr><td>4</td><td>FLAMMABILITY</td></tr> <tr><td>1</td><td>REACTIVITY</td></tr> <tr><td>G</td><td>PPE</td></tr> </table> <div style="float: right; margin-left: 20px;">           (3) Serious chronic health hazard            (4) Very high flammability hazard            (1) Low physicochemical hazard            (G) Safety glasses, gloves and vapor respirator         </div> <p>Note: HMIS Hazard Ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of the material, all the information contained in this SDS must be considered.</p> <p><u>Classification in accordance with Regulation (EU) No. 1272/2008-1221/2015 (CLP):</u> DANGER: Flam. Aerosol 1:H222+H229</p> <table border="1" data-bbox="138 966 1526 1218"> <thead> <tr> <th>Danger class</th> <th>Classification of the mixture</th> <th>Cat.</th> <th>Routes of exposure</th> <th>Target organs</th> <th>Effects</th> </tr> </thead> <tbody> <tr> <td> <u>Physicochemical:</u>   </td> <td rowspan="3">Flam. Aerosol 1:H222+H229</td> <td rowspan="3">Cat.1</td> <td rowspan="3">-</td> <td rowspan="3">-</td> <td rowspan="3">-</td> </tr> <tr> <td> <u>Human health:</u> Not classified         </td> </tr> <tr> <td> <u>Environment:</u> Not classified         </td> </tr> </tbody> </table> <p>Full text of hazard statements mentioned is indicated in section 16.</p> <p>Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.</p>		3	HEALTH	4	FLAMMABILITY	1	REACTIVITY	G	PPE	Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects	<u>Physicochemical:</u> 	Flam. Aerosol 1:H222+H229	Cat.1	-	-	-	<u>Human health:</u> Not classified	<u>Environment:</u> Not classified
3	HEALTH																							
4	FLAMMABILITY																							
1	REACTIVITY																							
G	PPE																							
Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects																			
<u>Physicochemical:</u> 	Flam. Aerosol 1:H222+H229	Cat.1	-	-	-																			
<u>Human health:</u> Not classified																								
<u>Environment:</u> Not classified																								
2.2	<u>LABEL ELEMENTS:</u>  <div style="text-align: center; margin-top: 10px;">This product is labelled with the signal word DANGER</div> <p><u>Hazard statements:</u> H222 Extremely flammable aerosol. H229 Pressurized container: may burst if heated.</p> <p><u>Precautionary statements:</u> P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P271-P260d Use only outdoors or in a well-ventilated area. Do not breathe aerosol. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501a Dispose of contents/container in accordance with local regulations.</p> <p><u>Supplementary statements:</u> None.</p> <p><u>Substances that contribute to classification:</u> None in a percentage equal to or higher than the limit for the name.</p>																							

		MTN PRO CHALK WATER BASED Code: EX00W9011C																		
2.3	<p><b>OTHER HAZARDS:</b>            Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:  <u>Other physicochemical hazards:</u> Vapours may form with air a mixture potentially flammable or explosive.  <u>Other adverse human health effects:</u> Prolonged exposure to vapours may produce transient drowsiness. In case of prolonged contact, the skin may become dry.  <u>Other negative environmental effects:</u> No other adverse effects are known.</p>																			
<b>SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS</b>																				
3.1	<p><b>SUBSTANCES:</b>            Not applicable (mixture).</p>																			
3.2	<p><b>MIXTURES:</b>            This product is a mixture.  <u>Chemical description:</u>            Aerosol.</p> <p><b>HAZARDOUS INGREDIENTS:</b>            Substances taking part in a percentage higher than the exemption limit:</p> <table border="1"> <tbody> <tr> <td>  </td> <td>           30 &lt; 40 %         </td> <td> <b>Dimethyl ether</b>            CAS: 115-10-6 , EC: 204-065-8            Danger: Flam. Gas 1:H220   Press. Gas:H280         </td> </tr> <tr> <td>   </td> <td>           20 &lt; 25 %         </td> <td> <b>Ethyl alcohol</b>            CAS: 64-17-5 , EC: 200-578-6            Danger: Flam. Liq. 2:H225   Eye Irrit. 2:H319         </td> </tr> </tbody> </table> <p><u>Impurities:</u>            Does not contain other components or impurities which will influence the classification of the product.</p> <p><u>Stabilizers:</u>            None</p> <p><u>Reference to other sections:</u>            For more information, see sections 8, 11, 12 and 16.</p>						30 < 40 %	<b>Dimethyl ether</b> CAS: 115-10-6 , EC: 204-065-8 Danger: Flam. Gas 1:H220   Press. Gas:H280	 	20 < 25 %	<b>Ethyl alcohol</b> CAS: 64-17-5 , EC: 200-578-6 Danger: Flam. Liq. 2:H225   Eye Irrit. 2:H319									
	30 < 40 %	<b>Dimethyl ether</b> CAS: 115-10-6 , EC: 204-065-8 Danger: Flam. Gas 1:H220   Press. Gas:H280																		
 	20 < 25 %	<b>Ethyl alcohol</b> CAS: 64-17-5 , EC: 200-578-6 Danger: Flam. Liq. 2:H225   Eye Irrit. 2:H319																		
<b>SECTION 4 : FIRST AID MEASURES</b>																				
4.1	<p><b>DESCRIPTION OF FIRST-AID MEASURES:</b></p> <p> Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.</p> <table border="1"> <thead> <tr> <th>Route of exposure</th> <th>Symptoms and effects, acute and delayed</th> <th>Description of first-aid measures</th> </tr> </thead> <tbody> <tr> <td><u>Inhalation:</u></td> <td>Normally does not produce symptoms.</td> <td>Should there be any symptoms, transfer the person affected to the open air.</td> </tr> <tr> <td><u>Skin:</u></td> <td>In case of prolonged contact, the skin may become dry.</td> <td>Remove contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.</td> </tr> <tr> <td><u>Eyes:</u></td> <td>Contact with the eyes produces redness and pain.</td> <td>Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water, holding the eyelids apart. If irritation persists, consult a physician.</td> </tr> <tr> <td><u>Ingestion:</u></td> <td>If swallowed in high doses, may cause gastrointestinal disturbances.</td> <td>If swallowed, seek immediate medical attention. Do not induce vomiting. Keep the patient at rest.</td> </tr> </tbody> </table>					Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures	<u>Inhalation:</u>	Normally does not produce symptoms.	Should there be any symptoms, transfer the person affected to the open air.	<u>Skin:</u>	In case of prolonged contact, the skin may become dry.	Remove contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.	<u>Eyes:</u>	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water, holding the eyelids apart. If irritation persists, consult a physician.	<u>Ingestion:</u>	If swallowed in high doses, may cause gastrointestinal disturbances.	If swallowed, seek immediate medical attention. Do not induce vomiting. Keep the patient at rest.
Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures																		
<u>Inhalation:</u>	Normally does not produce symptoms.	Should there be any symptoms, transfer the person affected to the open air.																		
<u>Skin:</u>	In case of prolonged contact, the skin may become dry.	Remove contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.																		
<u>Eyes:</u>	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water, holding the eyelids apart. If irritation persists, consult a physician.																		
<u>Ingestion:</u>	If swallowed in high doses, may cause gastrointestinal disturbances.	If swallowed, seek immediate medical attention. Do not induce vomiting. Keep the patient at rest.																		
4.2	<p><b>MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:</b>            The main symptoms and effects are indicated in sections 4.1 and 11</p>																			
4.3	<p><b>INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:</b>  <u>Notes to physician:</u> Treatment should be directed at the control of symptoms and the clinical condition of the patient.  <u>Antidotes and contraindications:</u> Specific antidote not known.</p>																			
Item Numbers: 01469-1020, 01469-1021, 01469-1061, 01469-2020, 01469-2021, 01469-3010, 01469-3011, 01469-3040, 01469-3041, 01469-4010, 01469-4011, 01469-4510, 01469-4511, 01469-5810, 01469-5811, 01469-7980, 01469-7981, 01469-9010, 01469-9011, 01469-9330, 01469-9331																				

 <b>MTN PRO CHALK WATER BASED</b> Code: EX00W9011C		
<b>SECTION 5 : FIRE-FIGHTING MEASURES</b>		
5.1	<b>EXTINGUISHING MEDIA:</b> Extinguishing powder or CO2. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing; direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.	
5.2	<b>SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:</b> Decomposes when heated intensely. As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide, nitrogen oxides. Exposure to combustion or decomposition products may be a hazard to health.	 <b>ANSI/NFPA 704:</b> Health: 1 Flammability: 4 Reactivity: 1 Special key: -
5.3	<b>ADVICE FOR FIREFIGHTERS:</b> <b>Special protective equipment:</b> Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or not used, combat fire from a sheltered position or at a safe distance. The standard EN469 provides a basic level of protection for chemical incidents. <b>Other recommendations:</b> Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.	
<b>SECTION 6 : ACCIDENTAL RELEASE MEASURES</b>		
6.1	<b>PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:</b> Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.	
6.2	<b>ENVIRONMENTAL PRECAUTIONS:</b> Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.	
6.3	<b>METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:</b> Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc.). Avoid use of solvents. Keep the remains in a closed container.	
<b>SECTION 7 : HANDLING AND STORAGE</b>		
7.1	<b>PRECAUTIONS FOR SAFE HANDLING:</b> Comply with the existing legislation on health and safety at work. <b>General recommendations:</b> Avoid any type of leakage or escape. <b>Recommendations for the prevention of fire and explosion risks:</b> Pressurised container. Protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not smoke. - Flash point : -35* °C - Autoignition temperature : 296* °C - Upper/lower flammability or explosive limits : 3.3* - 23.2 % Volume 25°C <b>Recommendations for the prevention of toxicological risks:</b> Do not eat, drink or smoke in application and drying areas. After handling, wash hands with soap and water. Avoid applying the product directly to people, animals, plants or foodstuffs. For exposure controls and personal protection measures, see section 8. <b>Recommendations for the prevention of environmental contamination:</b> It is not considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6.	
7.2	<b>CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</b> Prevent unauthorized access. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. For more information, see section 10. <b>Class of store</b> : According to current legislation. <b>Maximum storage period</b> : 24. months <b>Temperature interval</b> : min: 5. °C, max: 50. °C (recommended). <b>Incompatible materials:</b> Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. <b>Type of packaging:</b> According to current legislation.	

**SAFETY DATA SHEET**

In accordance with the requirements of the OSHA Hazard Communication Standard, 29CFR 1910.1200



MTN PRO CHALK WATER BASED  
Code: EX00W9011C



**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 CONTROL PARAMETERS:**  
If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.


OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2015	Year	TLV-TWA ppm	mg/m3	TLV-STEL ppm	mg/m3	Remarks
Dimethyl ether		1000.	1920.	-	-	Recommended
Ethyl alcohol	1996	1000.	1880.	-	-	A4

TLV - Threshold Limit Value, TWA - Time Weighted Average, STEL - Short Term Exposure Limit.  
A4 - Non classified as carcinogenic in humans.

BIOLOGICAL EXPOSURE INDICES (BEI):

Not available

	<p><b>MTN PRO CHALK WATER BASED</b> Code: EX00W9011C</p>	
--	--	---

**8.2 EXPOSURE CONTROLS:**







ENGINEERING MEASURES:



Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

Protection of respiratory system: Avoid the inhalation of vapours.  
Protection of eyes and face: It is recommended to dispose of water taps or sources with clean water close to the working area.  
Protection of hands and skin: It is recommended to dispose of water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCCUPATIONAL EXPOSURE CONTROLS: Directive 89/686/EEC~96/58/EC:  
 As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding EC marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, etc.), you should consult the informative brochures provided by the manufacturers of PPE.

<p><u>Mask:</u></p> 		<p>Suitable combined filter mask for gases, vapours and particles (OSHA 29CFR 1910.134 and ANSI Z88.2). Classe 1: low capacity up to 1000 ppm, Classe 2: medium capacity up to 5000 ppm, Classe 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers.</p>
<p><u>Goggles:</u></p> 		<p>Safety goggles with suitable lateral protection (OSHA 29CFR 1910.133). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.</p>
<p><u>Face shield:</u></p>		<p>No.</p>
<p><u>Gloves:</u></p> 		<p>Gloves resistant against chemicals (OSHA 29CFR 1910.132). There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard OSHA 29CFR 1910.132. Due to the wide variety of circumstances and possibilities, we must have in mind the manual of instructions from manufacturers of gloves. The gloves should be immediately replaced when any sign of degradation is noted.</p>
<p><u>Boots:</u></p>		<p>No.</p>
<p><u>Apron:</u></p>		<p>No.</p>
<p><u>Clothing:</u></p>		<p>No.</p>

Thermal hazards:  
 Not applicable (the product is handled at room temperature).



ENVIRONMENTAL EXPOSURE CONTROLS:  
 Avoid any spillage in the environment. Avoid any release into the atmosphere.



Spills on the soil: Prevent contamination of soil.



Spills in water: Do not allow to escape into drains, sewers or water courses.

Emissions to the atmosphere: Because of volatility, emissions to the atmosphere while handling and use may result. When possible, avoid solvent release to the atmosphere; do not pulverize more than is strictly necessary.

- VOC : 603.5 g/l (-H2O-es) ASTM D-3960

 MTN PRO CHALK WATER BASED Code: EX00W9011C		
<b>SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES</b>		
9.1	<b>INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:</b> <u>Appearance</u> - Physical state : Aerosol. - Odour : Characteristic - Odour threshold : Not available (mixture). <u>pH-value</u> - pH : Not available <u>Change of state</u> - Melting point : Not applicable (mixture). - Initial boiling point : Not applicable <u>Density</u> - Vapour density : Not available - Relative density : 0.898* at 20/4°C <span style="float: right;">Relative water</span> <u>Stability</u> - Decomposition temperature : Not available (technical impossibility to obtain the data). <u>Viscosity:</u> - Viscosity (flow time) : Not applicable <u>Volatility:</u> - Evaporation rate : Not applicable - Vapour pressure : Not available <u>Solubility(ies)</u> - Liposolubility : Not applicable - Partition coefficient: n-octanol/water : Not applicable (mixture). <u>Flammability:</u> - Flash point : -35* °C - Upper/lower flammability or explosive limits : 3.3* - 23.2 % Volume 25°C - Autoignition temperature : 296* °C <u>Explosive properties:</u> Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source. <u>Oxidizing properties:</u> Not classified as oxidizing product.  *Estimated values based on the substances composing the mixture.	
9.2	<b>OTHER INFORMATION:</b> - Heat of combustion : 4549* Kcal/kg - Solids : 22.5 % Weight - VOC (supply) : 53.6 % Weight  The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the technical data sheet of the same. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.	
<b>SECTION 10 : STABILITY AND REACTIVITY</b>		
10.1	<b>REACTIVITY:</b> <u>Corrosivity to metals:</u> It is not corrosive to metals. <u>Pyrophorical properties:</u> It is not pyrophoric.	
10.2	<b>CHEMICAL STABILITY:</b> Stable under recommended storage and handling conditions.	
10.3	<b>POSSIBILITY OF HAZARDOUS REACTIONS:</b> Possible dangerous reaction with oxidizing agents, acids.	
10.4	<b>CONDITIONS TO AVOID:</b> <u>Heat:</u> Keep away from sources of heat. <u>Light:</u> Avoid direct contact with sunlight. <u>Air:</u> The product is not affected by exposure to air, but should not be left in the containers open. <u>Pressure:</u> Not relevant. <u>Shock:</u> The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.	
10.5	<b>INCOMPATIBLE MATERIALS:</b> Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.	
10.6	<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b> As consequence of thermal decomposition, hazardous products may be produced: nitrogen oxides.	
Item Numbers: 01469-1020, 01469-1021, 01469-1061, 01469-2020, 01469-2021, 01469-3010, 01469-3011, 01469-3040, 01469-3041, 01469-4010, 01469-4011, 01469-4510, 01469-4511, 01469-5810, 01469-5811, 01469-7980, 01469-7981, 01469-9010, 01469-9011, 01469-9330, 01469-9331		

 MTN PRO CHALK WATER BASED Code: EX00W9011C				
<b>SECTION 11 : TOXICOLOGICAL INFORMATION</b>				
No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008-1221/2015 (CLP).				
11.1	<b>INFORMATION ON TOXICOLOGICAL EFFECTS:</b>			
	<b>ACUTE TOXICITY:</b>			
	<b>Dose and lethal concentrations for individual ingredients:</b> Dimethyl ether Ethyl alcohol	<b>DL50 (OECD 401)</b> mg/kg oral  10470. Rat	<b>DL50 (OECD 402)</b> mg/kg cutaneous  > 20000. Rabbit	<b>CL50 (OECD 403)</b> mg/m3.4h inhalation > 100000 Rat > 20000. Rat
	<b>No observed adverse effect level</b> Not available <b>Lowest observed adverse effect level</b> Not available			
	<b>INFORMATION ON LIKELY ROUTES OF EXPOSURE : Acute toxicity:</b> <b>Inhalation:</b> Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met). <b>Skin:</b> Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met). <b>Eyes:</b> Not classified as a product with acute toxicity by eye contact (lack of data). <b>Ingestion:</b> Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).			
	<b>CORROSION / IRRITATION / SENSITISATION:</b> <b>Respiratory corrosion/irritation:</b> Not classified as a product corrosive or irritant by inhalation (based on available data, the classification criteria are not met). <b>Skin corrosion/irritation:</b> Not classified as a product corrosive or irritant in contact with skin (based on available data, the classification criteria are not met). <b>Serious eye damage/irritation:</b> Not classified as a product corrosive or irritant in contact with eyes (based on available data, the classification criteria are not met). <b>Respiratory sensitisation:</b> Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met). <b>Skin sensitisation:</b> Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).			
	<b>ASPIRATION HAZARD:</b> Not applicable.			
	<b>SPECIFIC TARGET ORGANS TOXICITY (STOT):</b> Not classified as a dangerous product for target organs (based on available data, the classification criteria are not met).			
	<b>CMR EFFECTS:</b> <b>Carcinogenic effects:</b> Is not considered as a carcinogenic product. <b>Genotoxicity:</b> Is not considered as a mutagenic product. <b>Toxicity for reproduction:</b> Do not harm fertility. Do not harm the fetus developing. <b>Effects via lactation:</b> Not classified as a hazardous product for children breast-fed.			
<b>SECTION 12 : ECOLOGICAL INFORMATION</b>				
No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008-1221/2015 (CLP).				
12.1	<b>TOXICITY:</b>			
	<b>Acute toxicity in aquatic environment for individual ingredients:</b> Dimethyl ether Ethyl alcohol	<b>CL50 (OECD 203)</b> mg/L96hours 4100. Fishes 14200. Fishes	<b>CE50 (OECD 202)</b> mg/L48hours 4400. Daphnia 5012. Daphnia	<b>CE50 (OECD 201)</b> mg/L72hours  275. Algae
	<b>No observed effect concentration</b> Not available <b>Lowest observed effect concentration</b> Not available			
12.2	<b>PERSISTENCE AND DEGRADABILITY:</b>			
	Not available.			
	<b>Aerobic biodegradation for individual ingredients:</b> Dimethyl ether Ethyl alcohol	<b>DQO</b> mgO2/g  1041. 1990.	<b>%DBO/DQO</b> 5 days 14 days 28 days ~ 1. ~ 3. ~ 5. ~ 74. ~ 95. ~ 99.	<b>Biodegradability</b>  Not easy Easy
	Note: Biodegradability data correspond to an average of data from various bibliographic sources.			
12.3	<b>BIOACCUMULATIVE POTENTIAL:</b>			
	Not available.			
	<b>Bioaccumulation for individual ingredients:</b> Dimethyl ether Ethyl alcohol	<b>logPow</b>  0.0700 -0.310	<b>BCF</b> L/kg  1.7 (calculated) 3.2 (calculated)	<b>Potential</b>  Not available Not available
12.4	<b>MOBILITY IN SOIL:</b>			
	Not available.			
Item Numbers: 01469-1020, 01469-1021, 01469-1061, 01469-2020, 01469-2021, 01469-3010, 01469-3011, 01469-3040, 01469-3041, 01469-4010, 01469-4011, 01469-4510, 01469-4511, 01469-5810, 01469-5811, 01469-7980, 01469-7981, 01469-9010, 01469-9011, 01469-9330, 01469-9331				

 <b>MTN PRO CHALK WATER BASED</b> Code: EX00W9011C		
12.6	<b>OTHER ADVERSE EFFECTS:</b> <b>Ozone depletion potential:</b> Not available. <b>Photochemical ozone creation potential:</b> Not available. <b>Earth global warming potential:</b> In case of fire or incineration liberates CO2. <b>Endocrine disrupting potential:</b> Not available.	
<b>SECTION 13 : DISPOSAL CONSIDERATIONS</b>		
13.1	<b>WASTE TREATMENT METHODS: Directive 2008/98/EC-Regulation (EU) no. 1357/2014:</b> Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose of at an authorised waste collection point. Waste should be handled and disposed of in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.  <b>Disposal of empty containers:</b> Emptied containers and packaging should be disposed of in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification. With contaminated containers and packaging, adopt the same measures as for the product in itself. Ensure the container is completely empty before throwing it away.  <b>Procedures for neutralising or destroying the product:</b> In accordance with local regulations. Do not incinerate closed containers.	
<b>SECTION 14 : TRANSPORT INFORMATION</b>		
14.1	<b>UN NUMBER:</b> 1950	
14.2	<b>UN PROPER SHIPPING NAME:</b> AEROSOLS	
14.3 14.4	<b>TRANSPORT HAZARD CLASS(ES) AND PACKING GROUP:</b>  <b>Transport by road (ADR 2017) and Transport by rail (RID 2017):</b> - Class: 2 - Packaging group: - - Classification code: 5F - Tunnel restriction code: (D) - Transport category: 2, max. ADR 1.1.3.6. 333 L - Limited quantities: 1 L (see total exemptions ADR 3.4) - Transport document: Consignment paper. - Instructions in writing: ADR 5.4.3.4  <b>Transport by sea (IMDG 37-14):</b> - Class: 2 (Division 2.1) - Packaging group: - - Emergency Sheet (EmS): F-D,S-U - First Aid Guide (MFAG): 620* - Marine pollutant: No. - Transport document: Shipping Bill of lading.  <b>Transport by air (ICAO/IATA 2016):</b> - Class: 2 (Division 2.1) - Packaging group: - - Transport document: Air Bill of lading.  <b>Transport by inland waterways (ADN):</b> Not available.	
14.5	<b>ENVIRONMENTAL HAZARDS:</b> Not applicable (not classified as hazardous for the environment).	
14.6	<b>SPECIAL PRECAUTIONS FOR USER:</b> Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.	
14.7	<b>TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:</b> Not applicable.	
<b>SECTION 15 : REGULATORY INFORMATION</b>		
15.1	<b>USA REGULATIONS:</b> <b>- Occupational Safety and Health Act (OSHA):</b> This product is not considered to be hazardous under the OSHA Hazard Communication Standard. <b>- Clean Air Act:</b> - 112(r) Hazardous air pollutants (HAP) (40CFR 68): Dimethyl ether: Threshold quantity (TQ): 10000 lbs. The TQ applies to the quantity of substance in a release process, not at the facility as a whole. <b>- Clean Water Act:</b> - 307 Hazardous water priority pollutants (HWPP): No. <b>- Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):</b> If this product is accidentally spilled, it is not subject to any special reporting under the requirements of the Comprehensive Response, Compensation and Liability Act. We recommend you contact authorities to determine if there may be other local reporting requirements.	
Item Numbers: 01469-1020, 01469-1021, 01469-1061, 01469-2020, 01469-2021, 01469-3010, 01469-3011, 01469-3040, 01469-3041, 01469-4010, 01469-4011, 01469-4510, 01469-4511, 01469-5810, 01469-5811, 01469-7980, 01469-7981, 01469-9010, 01469-9011, 01469-9330, 01469-9331		





MTN PRO CHALK WATER BASED  
Code: EX00W9011C



- Superfund Amendments and Reauthorization Act (SARA Title III):

- 302/304 Extremely Hazardous Substances (EHS) for Emergency release notification (40CFR 355): No.
- 313 Reportable Ingredients (40CFR 372): No.
- 311/312 Hazard Categories (40CFR 370): No.

- Toxic Substance Control Act (TSCA):

All chemical substances in this product comply with all applicable rules or order under TSCA.

- California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This product does not contain chemical substances known to the State of California to cause cancer or reproductive toxicity.

OTHER REGULATIONS:

Other local legislations:

The receiver should verify the possible existence of local regulations applicable to the chemical.

**SECTION 16 : OTHER INFORMATION**

TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:

Hazard statements according the Regulation (EU) No. 1272/2008-1221/2015 (CLP), Anexo III:

H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H280 Contains gas under pressure: may explode if heated. H319 Causes serious eye irritation.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of material safety data sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- European Chemicals Agency: ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (ACGIH, 2015).
- European agreement on the international carriage of dangerous goods by road, (ADR 2017).
- International Maritime Dangerous Goods Code IMDG including Amendment 37-14 (IMO, 2014).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this material safety data sheet:

- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regulation on Classification, Labelling and Packaging of substances and chemical mixtures.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials).
- VOC: Volatile Organic Compounds.
- LD50: Lethal dose, 50 percent.
- LC50: Lethal concentration, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangerous goods by road.
- RID: Regulations concerning the international transport of dangerous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.

SAFETY DATA SHEET REGULATIONS:

Safety Data Sheet in accordance with the requirements of the OSHA Hazard Communication Standard, 29CFR 1910.1200.

HISTORY:

Version: 1

Date of compilation:

24/11/2017

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Material Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.