

# SAFETY DATA SHEET

11/6/2015

## SECTION I - IDENTIFICATION

**Material Name**

UTRECHT GLOSS OIL VARNISH

**Company Information**

Utrecht Manufacturing, LLC  
33 35th Street  
Brooklyn, NY 11232  
Telephone: 800-223-9132  
[www.utrecht.com](http://www.utrecht.com)

For transportation emergencies only call 1-800-223-9132

For health emergencies call the Poison Control Center: 1-800-222-1222

## SECTION II - HAZARDS IDENTIFICATION

**Classification in accordance with paragraph (d) of 29 CFR 1910.1200.**

Aspiration Hazard - Category 1

Flammable Liquid 2

**GHS Label Elements****Symbol(s)****Signal Word(s)**

Danger

**Hazard Statement(s)**

Highly flammable liquid and vapour May be fatal if swallowed and enters airways.

**Precautionary Statement(s)****Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Keep cool. Ground and bond container and receiving equipment. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up.

**Response**

Do NOT induce vomiting. Rinse skin with water [or shower]. Take off immediately all contaminated clothing. IF SWALLOWED: Immediately call a POISON CENTER/doctor.

**SECTION III - COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS**

| <b>Hazardous Ingredients</b> | <b>CAS/EC #</b> | <b>PEL/TLV<br/>(MG/M#)</b> | <b>Max<br/>% Weight</b> | <b>NTP</b> | <b>IARC</b> |
|------------------------------|-----------------|----------------------------|-------------------------|------------|-------------|
| PETROLEUM DISTILLATES        |                 | 525.00                     | 78.34220                | N          | N           |
| STODDARD SOLVENT             | 232-489-3       | N/A                        | 51.92000                | N          | N           |
| ETHANOL                      | 64-17-5         | N/A                        | 6.14000                 | N          | N           |

**SECTION IV - FIRST AID MEASURES**

**FIRST AID MEASURES:** If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If swallowed, do not induce vomiting. Call a physician or poison control center immediately. If inhalation symptoms occur, move to fresh air. If symptoms persist, see a physician. If skin contact occurs, wash with soap and water for 5 minutes. If swallowed, get prompt medical attention.

**SECTION V - FIRE FIGHTING MEASURES**

**FLASH POINT (METHOD):** 105° F (40° C) **AUTOIGNITION TEMPERATURE:** N/A  
**EXPLOSION LIMITS IN AIR (% BY VOLUME):** LEL 0.5% - UEL 6%  
**EXTINGUISHING MEDIA:** Foam, CO<sub>2</sub>, Dry Chemical (Class B) or Halon  
**FIRE FIGHTING PROCEDURES:** NO SPECIAL FIRE FIGHTING PROCEDURES REQUIRED  
Wear self-contained breathing apparatus.  
**UNUSUAL FIRE & EXPLOSION HAZARDS:** FLAMMABLE. HIGHLY FLAMMABLE

**SECTION VI - ACCIDENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IN CASE A MATERIAL IS SPILLED:** Clean up in accordance with all applicable regulations. Absorb spillage with non-combustible, absorbent material. For waste disposal, see Section XIII

**SECTION VII - HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN DURING STORAGE AND HANDLING:** Good industrial hygiene practice requires that exposure be maintained below the TLV. This is preferably achieved through the provision of adequate ventilation. When exposure cannot be adequately controlled in this way, personal respiratory protection should be employed.

**SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS:** Use only with adequate ventilation.  
**OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC):** When using wear impermeable protective gloves.  
**WORK/HYGIENE PRACTICES:** Avoid skin contact. Wash hands immediately after use. Keep away from eyes. Avoid ingestion.  
**ENGINEERING CONTROLS:** Do not store or use near heat or flame.

**FOR HOME USE:** CHILD-PROOF PACKAGING REQUIRED IN CONFORMANCE WITH 16CFR1700.15 a), b), and c) and meet the child test protocol requirements of one of CSA-Z76.1, ISO 8317 or 16 CFR 1700.20 or a standard that is at least equivalent.

**SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

**BOILING POINT:** >300°F (>149°C) **MELTING POINT:** N/A  
**VAPOR PRESSURE:** 6mm Hg  
**SPECIFIC VAPOR DENSITY (AIR=1):** N/A **SPECIFIC GRAVITY:** 0.83  
**SOLUBILITY IN WATER:** N/A **REACTIVITY IN WATER:** NON-REACTIVE

## SECTION X - STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION PRODUCTS: N/A  
STABILITY: STABLE CONDITIONS TO AVOID: N/A  
INCOMPATIBILITY (MATERIALS TO AVOID): N/A  
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide and smoke

## SECTION XI - TOXICOLOGICAL INFORMATION

ACUTE EFFECTS ASSOCIATED WITH USE OF THIS MATERIAL: SKIN IRRITANT. EYE IRRITANT. EXPOSURE MAY RESULT IN NAUSEA, HEADACHE, CONFUSION OR INSTABILITY. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. CONTACT MAY RESULT IN IRRITATION OF THE SKIN.

The summated LD50 is >50000 mg/kg.  
The summated LC50 is 99999 mg/cubic meter.  
This product is not considered to be a known or suspected human carcinogen by NTP, IARC or OSHA (see section III)

## SECTION XII - ECOLOGICAL INFORMATION

NO HARMFUL EFFECTS KNOWN OTHER THAN THOSE ASSOCIATED WITH SUSPENDED INERT SOLIDS IN WATER.

## SECTION XIII - DISPOSAL CONSIDERATIONS

RCRA HAZARD CLASS (40 CFR 261): THIS PRODUCT IS NOT CLASSIFIED AS A HAZARDOUS WASTE.  
WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

## SECTION XIV - TRANSPORTATION INFORMATION

U.S. D.O.T. Ground Transportation: Not Regulated  
Ocean Transportation: UN 1263 Paint Related Material, Class 3, PG III, Limited Quantity  
DO NOT SHIP via air freight without special packaging and labeling. Contact your air carrier for detailed instructions.

## SECTION XV - REGULATORY INFORMATION

CONTENTS OF THIS SDS COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200  
EPA SARA TITLE III CHEMICAL LISTINGS  
NONE

SECTION 302.4 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):  
NONE

SECTION 313 TOXIC CHEMICALS (40 CFR 372):  
NONE

### INTERNATIONAL REGULATIONS

CANADIAN WHMIS: THIS PRODUCT IS A CONTROLLED PRODUCT UNDER CANADA'S WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM. IT CONTAINS THE FOLLOWING TOXIC OR HIGHLY TOXIC MATERIALS:  
ETHYL ALCOHOL  
STODDARD SOLVENT

**SUPPLEMENTAL STATE COMPLIANCE INFORMATION:**

**THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED UNDER NEW JERSEY'S RIGHT TO KNOW PROGRAM:**  
ETHYL ALCOHOL

**THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) REQUIRING NOTIFICATION TO THE STATE OF WASHINGTON UNDER THEIR CHILDREN'S SAFE PRODUCTS ACT:**  
NONE

**THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN FLORIDA'S TOXIC SUBSTANCE LIST:**  
Denatured alcohol

**THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN MAINE'S PRIORITY CHEMICAL LIST:**  
NONE

**THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS CONSIDERED BY VERMONT AS BEING OF VERY HIGH CONCERN TO CHILDREN:**  
NONE

**THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN MASSACHUSETTS HAZARDOUS SUBSTANCE LIST:**  
Ethyl alcohol

**THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED ON MICHIGAN'S CRITICAL MATERIALS REGISTER:**  
NONE

**THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED ON MINNESOTA'S HAZARDOUS SUBSTANCES LIST:**  
Ethanol

**THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN PENNSYLVANIA'S HAZARDOUS SUBSTANCES LIST:**  
Ethanol

Under CPSC's consumer product regulations (16CFR1500.3 and 150014), this product has the following required acute and chronic hazard labeling:

**DANGER:FLAMMABLE. Harmful or fatal if swallowed. VAPOR HARMFUL. SKIN IRRITANT. EYE IRRITANT.**  
**Contains: PETROLEUM DISTILLATES**

**PRECAUTIONS:**Avoid skin contact. Wash hands immediately after use. When using wear impermeable protective gloves. Keep away from eyes. Avoid ingestion. Do not store or use near heat or flame. Use only with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID TREATMENT:**If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If swallowed, do not induce vomiting. Call a physician or poison control center immediately. If inhalation symptoms occur, move to fresh air. If symptoms persist, see a physician. If skin contact occurs, wash with soap and water for 5 minutes. If swallowed, get prompt medical attention.

This adult product is certified to comply with the Consumer Product Safety Act (CPSA), the Poison Prevention Packaging Act, the Federal Hazardous Substances Act, (FHSA) and its Labeling for Hazardous Art Materials Act (LHAMA).

## SECTION XVI - OTHER INFORMATION

**Disclaimer:** We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

**LAST REVISION DATE: 11/06/2015**

**Prepared by Duke OEM Toxicology**

**BRAND NAMES**

THIS SDS APPLIES TO THE FOLLOWING BRAND NAMES

| <b>Brand Name</b>         | <b>SKU</b> | <b>SKU Description</b> |
|---------------------------|------------|------------------------|
| UTRECHT GLOSS OIL VARNISH | UT-11405   | 4 OZ, 118 ML           |
|                           | UT-11406   | 8 OZ, 236 ML           |
|                           | UT-11407   | 16 OZ, 473 ML          |