

SAFETY DATA SHEET

Section 1. Identification

GHS product identifier	: Sharpie Oil-Based Paint Markers: Extra Fine, Fine, Medium, Bold (All Colors)
Product code	: Sharpie Oil-Based Paint Markers (All Colors)
Other means of identification	: Colors: Aqua Blue, Black, Blue, Brown, Gold, Green, Lime Green, Magenta, Orange, Pink, Purple, Red, Silver, White, Yellow
Product type	: Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Material uses : Not available.

Manufacturer : Sanford, L.P.
6655 Peachtree Dunwoody Road
Atlanta, GA 30328
1-800-346-3278

Emergency telephone number (with hours of operation) : CHEMTREC (U.S. and Canada) 1-800-424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 2
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 40%

Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 40%

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Highly flammable liquid and vapor.
Causes serious eye irritation.
Causes skin irritation.
May cause drowsiness or dizziness.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling.

Section 2. Hazards identification

- Response** : IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
- Storage** : Store locked up. Store in a well-ventilated place. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Colors: Aqua Blue, Black, Blue, Brown, Gold, Green, Lime Green, Magenta, Orange, Pink, Purple, Red, Silver, White, Yellow

Ingredient name	%	CAS number
ethanol	≥25 - ≤50	64-17-5
1-methoxy-2-propanol	≥25 - ≤50	107-98-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Date of issue	Date of revision	Date of previous issue	No previous validation	Version	Page 2 of 13
2023-22100-2059, 22100-2159, 22100-3010, 22100-3011, 22100-3012, 22100-3013, 22100-3040, 22100-3041, 22100-3060, 22100-3061, 22100-3150, 22100-4010, 22100-4011, 22100-4012, 22100-4013, 22100-4510, 22100-4511, 22100-5010, 22100-5011, 22100-5012, 22100-5013, 22100-5160, 22100-5161, 22100-6000, 22100-6001, 22100-7010, 22100-7011, 22100-7012, 22100-7230, 22100-7231, 22100-8000, 22100-8001, 22100-9010, 22100-9011, 22100-9012, 22100-9330, 22100-9331, 22100-9332	2020-1001, 22100-1002, 22100-1022, 22100-1023, 22100-2020, 22100-2022, 22100-2023				

Section 4. First aid measures

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

Specific hazards arising from the chemical : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

<u>Ingredient name</u>	<u>Exposure limits</u>
ethanol	ACGIH TLV (United States, 3/2019). STEL: 1000 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 1000 ppm 8 hours. TWA: 1900 mg/m ³ 8 hours. NIOSH REL (United States, 10/2016). TWA: 1000 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 1000 ppm 8 hours. TWA: 1900 mg/m ³ 8 hours.
1-methoxy-2-propanol	ACGIH TLV (United States, 3/2019). TWA: 50 ppm 8 hours. TWA: 184 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 369 mg/m ³ 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 100 ppm 8 hours. TWA: 360 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 540 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 360 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 540 mg/m ³ 15 minutes.

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : Not available.
- Flash point** : Not available.
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : Not available.
- Solubility** : Not available.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.
- Flow time (ISO 2431)** : Not available.

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Incompatible materials** : Reactive or incompatible with the following materials:
oxidizing materials

Section 10. Stability and reactivity

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Oral	Rat	7 g/kg	-
1-methoxy-2-propanol	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	6600 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	100 UI	-
	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	400 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
1-methoxy-2-propanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
ethanol	-	1	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
1-methoxy-2-propanol	Category 3	Not applicable.	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Section 11. Toxicological information

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- General** : No known significant effects or critical hazards.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
ethanol	7000	N/A	N/A	124.7	N/A
1-methoxy-2-propanol	6600	13000	N/A	N/A	N/A

Section 11. Toxicological information**Section 12. Ecological information****Toxicity**

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 µl/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
Chronic NOEC 0.375 µl/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks	

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
ethanol	-0.35	-	low
1-methoxy-2-propanol	<1	-	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.








Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	Paint. (ethanol, 1-methoxy-2-propanol)	Paint. (ethanol, 1-methoxy-2-propanol)	Paint. (ethanol, 1-methoxy-2-propanol)	Paint. (ethanol, 1-methoxy-2-propanol)	Paint. (ethanol, 1-methoxy-2-propanol)
Transport hazard class(es)	3 	3  	3 	3  	3 
Packing group	II	II	II	II	II
Environmental hazards	No.	Yes.	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information**DOT Classification** : **Special provisions 383****TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail.**IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.**IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.**Transport in bulk according to Annex II of MARPOL and the IBC Code** : Not available.**Section 15. Regulatory information****U.S. Federal regulations** : TSCA 8(a) CDR Exempt/Partial exemption: Not determined**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Not listed**Clean Air Act Section 602 Class I Substances** : Not listed**Clean Air Act Section 602 Class II Substances** : Not listed**DEA List I Chemicals (Precursor Chemicals)** : Not listed**DEA List II Chemicals (Essential Chemicals)** : Not listed**SARA 302/304****Composition/information on ingredients**

No products were found.

Date of issue/Date of revision 22100-9342, 22100-9343, 22100-9344, 22100-9345, 22100-9346, 22100-9347, 22100-9348, 22100-9349, 22100-9350, 22100-9351, 22100-9352, 22100-9353, 22100-9354, 22100-9355, 22100-9356, 22100-9357, 22100-9358, 22100-9359, 22100-9360, 22100-9361, 22100-9362, 22100-9363, 22100-9364, 22100-9365, 22100-9366, 22100-9367, 22100-9368, 22100-9369, 22100-9370, 22100-9371, 22100-9372, 22100-9373, 22100-9374, 22100-9375, 22100-9376, 22100-9377, 22100-9378, 22100-9379, 22100-9380, 22100-9381, 22100-9382, 22100-9383, 22100-9384, 22100-9385, 22100-9386, 22100-9387, 22100-9388, 22100-9389, 22100-9390, 22100-9391, 22100-9392, 22100-9393, 22100-9394, 22100-9395, 22100-9396, 22100-9397, 22100-9398, 22100-9399, 22100-9400, 22100-9401, 22100-9402, 22100-9403, 22100-9404, 22100-9405, 22100-9406, 22100-9407, 22100-9408, 22100-9409, 22100-9410, 22100-9411, 22100-9412, 22100-9413, 22100-9414, 22100-9415, 22100-9416, 22100-9417, 22100-9418, 22100-9419, 22100-9420, 22100-9421, 22100-9422, 22100-9423, 22100-9424, 22100-9425, 22100-9426, 22100-9427, 22100-9428, 22100-9429, 22100-9430, 22100-9431, 22100-9432, 22100-9433, 22100-9434, 22100-9435, 22100-9436, 22100-9437, 22100-9438, 22100-9439, 22100-9440, 22100-9441, 22100-9442, 22100-9443, 22100-9444, 22100-9445, 22100-9446, 22100-9447, 22100-9448, 22100-9449, 22100-9450, 22100-9451, 22100-9452, 22100-9453, 22100-9454, 22100-9455, 22100-9456, 22100-9457, 22100-9458, 22100-9459, 22100-9460, 22100-9461, 22100-9462, 22100-9463, 22100-9464, 22100-9465, 22100-9466, 22100-9467, 22100-9468, 22100-9469, 22100-9470, 22100-9471, 22100-9472, 22100-9473, 22100-9474, 22100-9475, 22100-9476, 22100-9477, 22100-9478, 22100-9479, 22100-9480, 22100-9481, 22100-9482, 22100-9483, 22100-9484, 22100-9485, 22100-9486, 22100-9487, 22100-9488, 22100-9489, 22100-9490, 22100-9491, 22100-9492, 22100-9493, 22100-9494, 22100-9495, 22100-9496, 22100-9497, 22100-9498, 22100-9499, 22100-9500, 22100-9501, 22100-9502, 22100-9503, 22100-9504, 22100-9505, 22100-9506, 22100-9507, 22100-9508, 22100-9509, 22100-9510, 22100-9511, 22100-9512, 22100-9513, 22100-9514, 22100-9515, 22100-9516, 22100-9517, 22100-9518, 22100-9519, 22100-9520, 22100-9521, 22100-9522, 22100-9523, 22100-9524, 22100-9525, 22100-9526, 22100-9527, 22100-9528, 22100-9529, 22100-9530, 22100-9531, 22100-9532, 22100-9533, 22100-9534, 22100-9535, 22100-9536, 22100-9537, 22100-9538, 22100-9539, 22100-9540, 22100-9541, 22100-9542, 22100-9543, 22100-9544, 22100-9545, 22100-9546, 22100-9547, 22100-9548, 22100-9549, 22100-9550, 22100-9551, 22100-9552, 22100-9553, 22100-9554, 22100-9555, 22100-9556, 22100-9557, 22100-9558, 22100-9559, 22100-9560, 22100-9561, 22100-9562, 22100-9563, 22100-9564, 22100-9565, 22100-9566, 22100-9567, 22100-9568, 22100-9569, 22100-9570, 22100-9571, 22100-9572, 22100-9573, 22100-9574, 22100-9575, 22100-9576, 22100-9577, 22100-9578, 22100-9579, 22100-9580, 22100-9581, 22100-9582, 22100-9583, 22100-9584, 22100-9585, 22100-9586, 22100-9587, 22100-9588, 22100-9589, 22100-9590, 22100-9591, 22100-9592, 22100-9593, 22100-9594, 22100-9595, 22100-9596, 22100-9597, 22100-9598, 22100-9599, 22100-9600, 22100-9601, 22100-9602, 22100-9603, 22100-9604, 22100-9605, 22100-9606, 22100-9607, 22100-9608, 22100-9609, 22100-9610, 22100-9611, 22100-9612, 22100-9613, 22100-9614, 22100-9615, 22100-9616, 22100-9617, 22100-9618, 22100-9619, 22100-9620, 22100-9621, 22100-9622, 22100-9623, 22100-9624, 22100-9625, 22100-9626, 22100-9627, 22100-9628, 22100-9629, 22100-9630, 22100-9631, 22100-9632, 22100-9633, 22100-9634, 22100-9635, 22100-9636, 22100-9637, 22100-9638, 22100-9639, 22100-9640, 22100-9641, 22100-9642, 22100-9643, 22100-9644, 22100-9645, 22100-9646, 22100-9647, 22100-9648, 22100-9649, 22100-9650, 22100-9651, 22100-9652, 22100-9653, 22100-9654, 22100-9655, 22100-9656, 22100-9657, 22100-9658, 22100-9659, 22100-9660, 22100-9661, 22100-9662, 22100-9663, 22100-9664, 22100-9665, 22100-9666, 22100-9667, 22100-9668, 22100-9669, 22100-9670, 22100-9671, 22100-9672, 22100-9673, 22100-9674, 22100-9675, 22100-9676, 22100-9677, 22100-9678, 22100-9679, 22100-9680, 22100-9681, 22100-9682, 22100-9683, 22100-9684, 22100-9685, 22100-9686, 22100-9687, 22100-9688, 22100-9689, 22100-9690, 22100-9691, 22100-9692, 22100-9693, 22100-9694, 22100-9695, 22100-9696, 22100-9697, 22100-9698, 22100-9699, 22100-9700, 22100-9701, 22100-9702, 22100-9703, 22100-9704, 22100-9705, 22100-9706, 22100-9707, 22100-9708, 22100-9709, 22100-9710, 22100-9711, 22100-9712, 22100-9713, 22100-9714, 22100-9715, 22100-9716, 22100-9717, 22100-9718, 22100-9719, 22100-9720, 22100-9721, 22100-9722, 22100-9723, 22100-9724, 22100-9725, 22100-9726, 22100-9727, 22100-9728, 22100-9729, 22100-9730, 22100-9731, 22100-9732, 22100-9733, 22100-9734, 22100-9735, 22100-9736, 22100-9737, 22100-9738, 22100-9739, 22100-9740, 22100-9741, 22100-9742, 22100-9743, 22100-9744, 22100-9745, 22100-9746, 22100-9747, 22100-9748, 22100-9749, 22100-9750, 22100-9751, 22100-9752, 22100-9753, 22100-9754, 22100-9755, 22100-9756, 22100-9757, 22100-9758, 22100-9759, 22100-9760, 22100-9761, 22100-9762, 22100-9763, 22100-9764, 22100-9765, 22100-9766, 22100-9767, 22100-9768, 22100-9769, 22100-9770, 22100-9771, 22100-9772, 22100-9773, 22100-9774, 22100-9775, 22100-9776, 22100-9777, 22100-9778, 22100-9779, 22100-9780, 22100-9781, 22100-9782, 22100-9783, 22100-9784, 22100-9785, 22100-9786, 22100-9787, 22100-9788, 22100-9789, 22100-9790, 22100-9791, 22100-9792, 22100-9793, 22100-9794, 22100-9795, 22100-9796, 22100-9797, 22100-9798, 22100-9799, 22100-9800, 22100-9801, 22100-9802, 22100-9803, 22100-9804, 22100-9805, 22100-9806, 22100-9807, 22100-9808, 22100-9809, 22100-9810, 22100-9811, 22100-9812, 22100-9813, 22100-9814, 22100-9815, 22100-9816, 22100-9817, 22100-9818, 22100-9819, 22100-9820, 22100-9821, 22100-9822, 22100-9823, 22100-9824, 22100-9825, 22100-9826, 22100-9827, 22100-9828, 22100-9829, 22100-9830, 22100-9831, 22100-9832, 22100-9833, 22100-9834, 22100-9835, 22100-9836, 22100-9837, 22100-9838, 22100-9839, 22100-9840, 22100-9841, 22100-9842, 22100-9843, 22100-9844, 22100-9845, 22100-9846, 22100-9847, 22100-9848, 22100-9849, 22100-9850, 22100-9851, 22100-9852, 22100-9853, 22100-9854, 22100-9855, 22100-9856, 22100-9857, 22100-9858, 22100-9859, 22100-9860, 22100-9861, 22100-9862, 22100-9863, 22100-9864, 22100-9865, 22100-9866, 22100-9867, 22100-9868, 22100-9869, 22100-9870, 22100-9871, 22100-9872, 22100-9873, 22100-9874, 22100-9875, 22100-9876, 22100-9877, 22100-9878, 22100-9879, 22100-9880, 22100-9881, 22100-9882, 22100-9883, 22100-9884, 22100-9885, 22100-9886, 22100-9887, 22100-9888, 22100-9889, 22100-9890, 22100-9891, 22100-9892, 22100-9893, 22100-9894, 22100-9895, 22100-9896, 22100-9897, 22100-9898, 22100-9899, 22100-9900, 22100-9901, 22100-9902, 22100-9903, 22100-9904, 22100-9905, 22100-9906, 22100-9907, 22100-9908, 22100-9909, 22100-9910, 22100-9911, 22100-9912, 22100-9913, 22100-9914, 22100-9915, 22100-9916, 22100-9917, 22100-9918, 22100-9919, 22100-9920, 22100-9921, 22100-9922, 22100-9923, 22100-9924, 22100-9925, 22100-9926, 22100-9927, 22100-9928, 22100-9929, 22100-9930, 22100-9931, 22100-9932, 22100-9933, 22100-9934, 22100-9935, 22100-9936, 22100-9937, 22100-9938, 22100-9939, 22100-9940, 22100-9941, 22100-9942, 22100-9943, 22100-9944, 22100-9945, 22100-9946, 22100-9947, 22100-9948, 22100-9949, 22100-9950, 22100-9951, 22100-9952, 22100-9953, 22100-9954, 22100-9955, 22100-9956, 22100-9957, 22100-9958, 22100-9959, 22100-9960, 22100-9961, 22100-9962, 22100-9963, 22100-9964, 22100-9965, 22100-9966, 22100-9967, 22100-9968, 22100-9969, 22100-9970, 22100-9971, 22100-9972, 22100-9973, 22100-9974, 22100-9975, 22100-9976, 22100-9977, 22100-9978, 22100-9979, 22100-9980, 22100-9981, 22100-9982, 22100-9983, 22100-9984, 22100-9985, 22100-9986, 22100-9987, 22100-9988, 22100-9989, 22100-9990, 22100-9991, 22100-9992, 22100-9993, 22100-9994, 22100-9995, 22100-9996, 22100-9997, 22100-9998, 22100-9999, 22100-10000

No previous validation

Section 15. Regulatory information**SARA 304 RQ** : Not applicable.**SARA 311/312****Classification** : FLAMMABLE LIQUIDS - Category 2
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 1A
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3**Composition/information on ingredients**

Name	%	Classification
ethanol	≥25 - ≤50	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 1A
1-methoxy-2-propanol	≥25 - ≤50	FLAMMABLE LIQUIDS - Category 3 EYE IRRITATION - Category 2B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

State regulations**Massachusetts** : The following components are listed: ETHYL ALCOHOL; DENATURED ALCOHOL; PROPYLENE GLYCOL METHYL ETHER; PROPYLENE GLYCOL MONOMETHYL ETHER**New York** : None of the components are listed.**New Jersey** : The following components are listed: ETHYL ALCOHOL; ALCOHOL; PROPYLENE GLYCOL MONOMETHYL ETHER; 1-METHOXY-2-PROPANOL**Pennsylvania** : The following components are listed: DENATURED ALCOHOL; ETHANOL; 2-PROPANOL, 1-METHOXY-**California Prop. 65**

This product does not require a Safe Harbor warning under California Prop. 65.

International regulations**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list**Australia** : All components are listed or exempted.**Canada** : All components are listed or exempted.**China** : All components are listed or exempted.**Europe** : All components are listed or exempted.**Japan** : **Japan inventory (ENCS):** All components are listed or exempted.
Japan inventory (ISHL): All components are listed or exempted.**New Zealand** : All components are listed or exempted.**Philippines** : All components are listed or exempted.**Republic of Korea** : All components are listed or exempted.

Section 15. Regulatory information

Taiwan	: All components are listed or exempted.
Thailand	: Not determined.
Turkey	: All components are listed or exempted.
United States	: All components are listed or exempted.
Viet Nam	: All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	2
Flammability	3
Physical hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Expert judgment Calculation method Calculation method Calculation method Calculation method

History

Date of printing	: 6/30/2020
Date of issue/Date of revision	: 6/30/2020
Date of previous issue	: No previous validation
Version	: 1

Section 16. Other information

Key to abbreviations

- : ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- N/A = Not available
- SGG = Segregation Group
- UN = United Nations

References

- : Not available.

✔ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.