



DRAWING PEN

# Safety Data Sheet

According to OSHA 29 CFR 1910.1200 HCS & Canada WHMIS



Revision Date : 17. 03. 2020

**SECTION 1: Identification**

1.1. Product identifier

Product Name : Artline DRAWING SYSTEM Color : (Black)  
 EK-2305N, EK-231N, EK-232N, EK-233N, EK-234N,  
 EK-235N, EK-236N, EK-237N, EK-238N



1.2. Recommended use of the chemical and restrictions on use

Recommended use : Writing ink

1.3. Details of the supplier of the safety data sheet

Company Name : Shachihata Inc. (U.S.A.)  
 Address : 20775 S. Western Ave., Suite 105 Torrance, CA 90501 U.S.A.  
 Telephone : 1-800-541-9719  
 Fax : 1-800-541-7166  
 Contact (e-mail) : [customerservice@xstamper.com](mailto:customerservice@xstamper.com)



1.4. Emergency telephone number

CHEMTREC 1-800-424-9300  
 (For Hazardous materials or dangerous goods incident, spill, leak, fire, exposure or accident)

**SECTION 2: Hazard(s) identification**

According to OSHA 29 CFR 1910.1200 HCS & Hazardous Product Regulation (WHMIS 2015)

2.1.1 Classification of the substance or mixture

Not classified

2.1.2 Label elements

Hazard pictograms : None  
 Signal word : None  
 Hazard statement : None



Precautionary statement

**【Prevention】**

Wash hands thoroughly after handling. (P264)

**【Response】**

IF IN EYES : Rinse cautiously with water for several minutes. (P305+P351+P338)

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists : Get medical advice and attention. (P337+P313)

**【Storage】**

Store in a well-ventilated place. Keep cool. (P403+P235)

**【Disposal】**

Dispose of contents and container in accordance with local regulations. (P501)



2.1.3 Other hazards

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is not considered hazardous.

In Canada, the product mentioned above is not considered hazardous under the Workplace Hazardous Materials Information System (WHMIS2015).

MSDS for #22128 ARTLINE DRAWING PEN

2.3 Other information



**SECTION 3: Composition/information on ingredients**

Substance / Mixture : Mixture

Ingredients :

Chemical Name / Generic name	Composition weight %	CAS Registry No.	Classification (OSHA HCS 2012)	
			Hazard Class	Hazard statement
Water	50 ~ 60	7732-18-5	none	none
Ethane-1,2-diol (Ethylene Glycol)	10 ~ 20	107-21-1	Acute Tox.(oral) 4	H302
2,2'-Oxydiethanol	1 ~ 10	111-46-6	Acute Tox.(oral) 4	H302
Carbon black	5 ~ 15	1333-86-4	none	none
Synthetic resin	1 ~ 10	Confidential	none	none
Others	5 ~ 15	Confidential	none	none
total	100			

**SECTION 4: First-aid measures**

4.1. Description of first aid measures

- IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a doctor if symptoms persist.
- IF ON SKIN : Remove / Take off immediately all contaminated clothing. Wash with soap and water. If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.
- IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.
- IF SWALLOWED : After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach, and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient when not conscious. Receive the doctor's treatment (stomach pump) promptly.

Note to Physicians :

All treatments should be based on observed signs and symptoms of distress in the patient.  
Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

**SECTION 5: Fire-fighting measures**

5.1. Extinguishing media

- Suitable extinguishing media : Dry chemical powder, foam or carbon dioxide
- Unsuitable extinguishing media : None

5.2. Special hazards arising from the substance or mixture

For initial stage extinction, carbon dioxide or dry chemical powder.  
When a fire extends, fire is extinguished by a large amount of water spray.  
Do not discharge extinguishing waters into the aquatic environment.

5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn.  
Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

MSDS for #02420 ADTLINE DRAWING DEN

**SECTION 6: Accidental release measures**

- 6.1. Personal precautions, protective equipment and emergency procedures
  - Evacuate personnel to safe area. Shut off all sources of ignition.
  - No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.
- 6.2. Environmental precautions
  - Do not throw the leakage thing directly into environment
- 6.3. Methods and material for containment and cleaning up
  - In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth, etc.), and then wipe off the waste well with waste cloth, and rag.
  - In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.) and collect into empty container by scoop, suction equipment or the like.

**SECTION 7: Handling and storage**

- 7.1. Precautions for safe handling
  - Advice on safe handling : Use with adequate ventilation.
  - Avoid contact with skin, eyes and clothing.
  - Obtain special instructions before use.
  - Do not handle until all safety precautions have been read and understood.
  - Do not eat, drink or smoke when using this product.
- 7.2. Conditions for safe storage, including any incompatibilities
  - Requirements for storage : Keep containers tightly closed and store in a cool and dry place.
  - areas and containers : Keep away from heat and flame, ignition source and sunlight.
  - Keep out of the reach of children.

**SECTION 8: Exposure controls/personal protection**

- 8.1. Control parameters
  - ACGIH (2019)
    - Ethane-1,2-diol TWA 25 ppm (V) (Vapor and Aerosol)
    - Carbon black TWA 3 mg/m<sup>3</sup>
  - OSHA PEL
    - Carbon black TWA 3.5 mg/m<sup>3</sup>
  - Canada Ontario Provincial
    - Ethane-1,2-diol STEL ceiling 100mg/m<sup>3</sup>(H)
    - Carbon black TWA 3.5 mg/m<sup>3</sup>
  - Canada Quebec Provincial
    - Ethane-1,2-diol C 50ppm
    - Carbon black TWA 3.5 mg/m<sup>3</sup>
- 8.2. Exposure controls
  - Personal protective equipment
    - Respiratory Protection : Use with local exhaust ventilation, when in long use.
    - Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.
    - Hand Protection : Avoid contact with hands. Wear safety gloves, if necessary.
    - Eye Protection : Avoid contact with eyes. Wear safety glasses, if necessary.
    - Skin Protection : Avoid skin contact. Wear personal protection apron, boots, if necessary.
  - Environmental exposure controls
    - General advice : Prevent product from entering drains.
    - Prevent further leakage or spillage if safe to do so.
    - If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: Black liquid
Odor	: None
pH	: 8 ~ 11
Boiling point	: 212°F (100°C) ~ 473°F (245°C)
Flash point	: Not applicable (closed cup)
Relative Density (at 77°F, 25°C)	: 1.0 ~ 1.3 (g/cm <sup>3</sup> )
Solubility in Water	: Soluble

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

### 10.3. Chemical stability

The product is stable.

### 10.4. Conditions to Avoid

High temperature, Direct sunlight, Fire

### 10.5. Incompatible Materials

No data available

### 10.6. Hazardous decomposition products

CO, CO<sub>2</sub>

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : LD/LC50 values that are relevant for classification

[Ethane-1,2-diol]

Oral-rat LD50 >300 - <=2,000 mg/kg

Dermal-rabbit LD50 >5,000 mg/kg

[2,2'-Oxydiethanol]

Oral-rat LD50 >300 - <=2,000 mg/kg

Dermal-rabbit LD50 >5,000 mg/kg

Carcinogenicity : Carbon black has been classified by the IARC as Group 2B.

Other materials ; Not contain any component that is considered a human carcinogen by IARC, ACGIH, EPA, EU or NTP.

Regarding the carcinogenicity of carbon black, International Agency for Research on Cancer (IARC) has classified as a group 2B. However, ACGIH (American Conference of Governmental Industrial Hygienists), EPA (Environmental Protection Agency), EU (European Chemicals Agency), NTP (National Toxicology Program, USA) in the classification of suspected carcinogenic to humans has not been done. Therefore, as the ink product we could not classify the carcinogenicity of GHS from that there is no sufficient data.

## SECTION 12: Ecological information

12.1. Ecotoxicity : No data available

12.2. Persistence and degradability : No data available

12.3. Bioaccumulative potential : No data available

12.4. Mobility in soil : No data available

12.5. Other adverse effects : No known significant effects or critical hazards.

MSDS for #02420 - ARTLINE DRAWING DEN

**SECTION 13: Disposal considerations**

13.1. Waste treatment methods

Disposal must be made according to official regulations.  
 Comply with all Federal, State, and Local regulations regarding disposal.  
 Do not allow product to reach ground, any water course or sewage system.

**SECTION 14: Transport information**

- 14.1. UN number (DOT, ADR, IMDG, IATA) : None
- 14.2. UN proper shipping name (DOT, ADR, IMDG, IATA) : None
- 14.3. Transport hazard class(es) (DOT, ADR, IMDG, IATA) : None
- 14.4. Packing group (DOT, ADR, IMDG, IATA) : None
- 14.5. Environmental hazards Marine pollutant : N
- 14.6. Special precautions for user EMS Number : None

**SECTION 15: Regulatory information**

< USA Information >

OSHA STATUS : This product is not hazardous under 29 CFR 1910.1200.  
 TSCA STATUS : All components on TSCA INVENTORY.  
 TSCA Hazard Communication Program (40 CFR Part 721) (SNUR) : Not Applicable  
 CERCLA REPORTABLE QUANTITY (40 CFR 117,302) : RQ 5,000 pounds [Ethane-1,2-diol]  
 SARA TITLE III Section 313 (40 CFR 372) : Listed [Ethane-1,2-diol]  
 California Proposition 65 : Carbon black  
 (airborne, unbound particles of respirable size)  
 Ethylene glycol (ingested)

< Canada Information >

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.  
 Canada inventory : All components of this product are listed in the DSL/NDL Inventory.

**SECTION 16: Other information, including date of preparation or last revision**

Last Revision Date : 17. 03. 2020  
 Preparation Date : 27. 05. 2015



This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.

EU RoHS (Directive 2011/65/EU)  
 EU ELV (DIRECTIVE 2000/53/EC)