



Safety Data Sheet

"11/36M"

Revision date: 30.08.2019

Product code: 1060321

Page 1 of 8

1. Identification

Product identifier

"11/36M"

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

Reserved for industrial and professional use.

Sector of uses [SU]:

- Articles for printing and writing:
- Pens

Details of the supplier of the safety data sheet

Company name:	Stabilo International GmbH	
Street:	Schwanweg 1	
Place:	D-90562 Heroldsberg	
Post-office box:	Postfach 1	
	D-90560 Heroldsberg	
Telephone:	+49 (0)911567-0	Telefax: +49 (0)911567-4444
e-mail:	info@stabilo.com	
Contact person:	Tobias Fendt	Telephone: +49 (0)911-567-1260
e-mail:	tobias.fendt@stabilo.com	
Internet:	http://www.stabilo.com/	
Emergency phone number:	+49 (0)89-19240 (Germany)	

2. Hazard(s) identification

Classification of the chemical

Regulation (EC) No. 1272/2008

Hazardous to the aquatic environment: Aquatic Chronic 3

Label elements

Regulation (EC) No. 1272/2008

Hazard statements

Harmful to aquatic life with long lasting effects

Precautionary statements

Avoid release to the environment.

Dispose of contents/container to an appropriate recycling or disposal facility.

Hazards not otherwise classified

No information available.

3. Composition/information on ingredients

Mixtures

Hazardous components

CAS No	Components	Quantity
2634-33-5	1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one	0.04 %

Full text of H and EUH statements: see section 16.

4. First-aid measures



Safety Data Sheet

Stabilo International GmbH

"11/36M"

Revision date: 30.08.2019

Product code: 1060321

Page 2 of 8

Description of first aid measures**General information**

When in doubt or if symptoms are observed, get medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious place in recovery position and seek medical advice.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. If swallowed, rinse mouth with water (only if the person is conscious).
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

No information available.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures**Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

Specific hazards arising from the chemical

Non-flammable. Burning produces heavy smoke.
Hazardous decomposition products: carbon black. Danger of serious damage to health by prolonged exposure.
Use appropriate respiratory protection.

Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition - No smoking. Ventilate affected area.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Safe handling: see section 7
Personal protection equipment (PPE): see section 8



Safety Data Sheet

"11/36M"

Revision date: 30.08.2019

Product code: 1060321

Page 3 of 8

Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into surface water or drains.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Reference to other sections

Safe handling: see section 7
Personal protection equipment (PPE): see section 8
Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away.
Use explosion-proof electrical equipment. Filling and transfer: Take precautionary measures against static discharges. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink or smoke.
Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in accordance with: Betriebssicherheitsverordnung (BetrSichV).

Hints on joint storage

Do not store together with: Oxidising agent, Strong acid, Strong alkali

Further information on storage conditions

Notice the directions for use on the label.
storage temperature of °C 10 up to °C 40.
Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

8. Exposure controls/personal protection

Control parameters

Exposure limits

CAS No.	Substance	ppm	mg/m ³	f/cc	Category	Origin
7429-90-5	Aluminum (total)	-	10		TWA (8 h)	REL
7429-90-5	Aluminum Metal (as Al) Respirable fraction	-	5		TWA (8 h)	PEL



Safety Data Sheet

"11/36M"

Revision date: 30.08.2019

Product code: 1060321

Page 4 of 8

Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. Overall (Natural fibres (e.g. cotton))

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Do not allow to enter into surface water or drains.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:

Liquid

Color:

"Grünmetallic"

pH-Value:

7,4 - 9,6

Test method

Changes in the physical state

Melting point/freezing point:

not determined

Initial boiling point and boiling range:

100 °C

Flash point:

not determined DIN 53213

Flammability

Solid:

not applicable

Gas:

not applicable

Lower explosion limits:

not determined

Upper explosion limits:

not determined

Auto-ignition temperature

Solid:

not applicable

Gas:

not applicable

Decomposition temperature:

not determined



Safety Data Sheet

"11/36M"

Revision date: 30.08.2019

Product code: 1060321

Page 5 of 8

Oxidizing properties

Not oxidising.

Vapor pressure:

23 hPa

(at 20 °C)

Density (at 20 °C):

1,2 g/cm³ DIN 53217

Water solubility:

easily soluble

Solubility in other solvents

not determined

Partition coefficient:

not determined

Viscosity / dynamic:

8-10 mPa·s

(at 20 °C)

Vapor density:

not determined

Evaporation rate:

not determined

Solvent content:

0,8%

Other information

Solid content:

38,6%

10. Stability and reactivity**Reactivity**

No hazardous reaction when handled and stored according to provisions.

Chemical stability

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

Exothermic reaction with: Oxidising agent, Strong acid, Strong alkali

Conditions to avoid

In case of warming: Formation of: Hazardous decomposition products

Incompatible materials

No information available.

Hazardous decomposition products

No known hazardous decomposition products.

11. Toxicological information**Information on toxicological effects****Acute toxicity**

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
2634-33-5	1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one				
	oral	LD50 mg/kg	670	Rat	Study report (1988) OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1994) OECD Guideline 402
	inhalation vapour	ATE	0,5 mg/l		
	inhalation aerosol	ATE	0,05 mg/l		

Carcinogenicity (OSHA):

No ingredient of this mixture is listed.



Safety Data Sheet

"11/36M"

Revision date: 30.08.2019

Product code: 1060321

Page 6 of 8

Carcinogenicity (IARC): No ingredient of this mixture is listed.

Carcinogenicity (NTP): No ingredient of this mixture is listed.

Practical experience**Observations relevant to classification**

In case of inhalation:

Adverse human health effects and symptoms: May cause respiratory irritation. May cause damage to liver if inhaled. May cause damage to kidneys if inhaled. Depression of central nervous system.

Symptoms: Headache, Dizziness, Drowsiness, Unconsciousness

After eye contact:

Irritating to eyes. (reversible.)

After ingestion:

Symptoms: Nausea, Vomiting, Gastrointestinal complaints

Following skin contact:

The product is skin resorptive. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Further information

There are no data available on the mixture itself.

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Reference to other sections: 2, 3

12. Ecological information**Ecotoxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and degradability

The product has not been tested.

Bioaccumulative potential

The product has not been tested.

Mobility in soil

The product has not been tested.

Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

13. Disposal considerations**Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

14. Transport information



Safety Data Sheet

"11/36M"

Revision date: 30.08.2019

Product code: 1060321

Page 7 of 8

Marine transport (IMDG)

UN number: UN 1263
UN proper shipping name: Paint
Transport hazard class(es): 3
Packing group: II
 Hazard label: 3



Special Provisions: 163, 367
 Limited quantity: 5 L
 Excepted quantity: E2
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

UN number: UN 1263
UN proper shipping name: Paint
Transport hazard class(es): 3
Packing group: II
 Hazard label: 3



Special Provisions: A3 A72 A192
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

Special precautions for user

No information available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

15. Regulatory information**U.S. Regulations****National regulatory information**

SARA Section 311/312 Hazards:

Aluminum (fume or dust) (7429-90-5): Fire hazard

SARA Section 313 Toxic release inventory:

Aluminum (fume or dust) (7429-90-5): De minimis limit = 1.0 %, Reportable threshold = Standard

State Regulations**Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)**

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Additional information



Safety Data Sheet

"11/36M"

Revision date: 30.08.2019

Product code: 1060321

Page 8 of 8

Observe in addition any national regulations!

16. Other information

Revision date: 30.08.2019

Revision No: 1,0

Abbreviations and acronymsADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GHS

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H statements (full text)

H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H330	Fatal if inhaled
H400	Very toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
EUH208	Contains 1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

Other data

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)