

CERÁMICA COLLET S.A.	<b>SAFETY DATA SHEET</b>		
<b>PM Black Earthenware</b>	Rev. 7	Date: 15/03/16	
	Page: 1 de 6		

### 1. Identification of the substance / mixture and of the company:

#### 1.1. Product identifier

Mixture identification:  
Trade name: PM

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Ceramic clay or natural modelling clay. Designed for: pottery, artistic ceramics.

#### 1.3. Details of the supplier of the safety data sheet

CERÁMICA COLLET S.A.  
Pol. Ind. L'Olana s/n  
E-08292 Esparreguera (Barcelona) – SPAIN  
Tel. +34 93 777 23 44 Fax +34 93 770 94 11  
Web: [www.sio-2.com](http://www.sio-2.com)

Competent person responsible for the safety data sheet:  
[msds@sio-2.com](mailto:msds@sio-2.com)

#### 1.4. Emergency telephone number

CERÁMICA COLLET S.A. Telf: +34 937772344 (08:30-13:00; 14:30-18:00; GMT +01:00)

### 2. Hazards Identification

#### 2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

#### 2.2. Label elements

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Symbols:

None

Hazard statements:

None

Precautionary statements:

None

Special Provisions:

None

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

#### 2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

### 3. Composition / Information on ingredients



#### 3.1. Substances

N.A.

#### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

<b>CERAMICA COLLET S.A.</b>	<b>SAFETY DATA SHEET</b>		
<b>PM Black Earthenware</b>	Rev. 7	Date: 15/03/16	
	Page: 2 de 6		

Name	CE / EINECS	CAS	Concentration	Classification
Quartz	238-455-4	14808-60-7	< 20 % (*)	Subst. with occupational exposure limit
Manganese dioxide (Index n°: 025-001-00-3)	215-202-6	1313-13-9	>= 15% - < 20%	 3.1/4/Oral Acute Tox. 4 H302  3.1/4/Inhal Acute Tox. 4 H332

(\*) The respirable crystalline silica is less than 1%.

#### 4. First aid measures

##### **4.1. Description of first aid measures**

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

##### **4.2. Most important symptoms and effects, both acute and delayed**

None

##### **4.3. Indication of any immediate medical attention and special treatment needed**

Treatment:

Symptomatic treatment.

*Generic: In case of doubt or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.*

#### 5. Fire-fighting measures

This product is not inflammable.

##### **5.1. Extinguishing media**

Suitable extinguishing media:

Water.

Carbon dioxide (CO<sub>2</sub>).

Extinguishing media which must not be used for safety reasons:

None in particular.

##### **5.2. Special hazards arising from the substance or mixture**

Do not inhale explosion and combustion gases.

##### **5.3. Advice for firefighters**

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### 6. Accidental release measures

##### **6.1. Personal precautions, protective equipment and emergency procedures**

N.A.

##### **6.2. Environmental precautions**

N.A.

##### **6.3. Methods and material for containment and cleaning up**

Wash with plenty of water.

##### **6.4. Reference to other sections**

See also section 8 and 13.

CERAMICA COLLET S.A.	<b>SAFETY DATA SHEET</b>		
<b>PM Black Earthenware</b>	Rev. 7	Date: 15/03/16	
	Page: 3 de 6		

## 7. Handling and storage

### 7.1. Precautions for safe handling

Do not eat or drink while working.  
See also section 8 for recommended protective equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep out of frost (keep at temperature >0°C).

Incompatible materials:  
None in particular.

Instructions as regards storage premises:  
Adequately ventilated premises.

### 7.3. Specific end use(s)

None in particular

## 8. Exposure controls / personal protection

### 8.1. Parámetros de control

Name	EINECS	N° CAS	VLA-EC <sup>1</sup>		VLA-ED <sup>2</sup>	
			ppm	mg./m <sup>3</sup>	ppm	mg./m <sup>3</sup>
Crystalline silica: respirable Quartz	238-878-4	14808-60-7	-	-	-	0.05
Manganese Dioxide (Index n°: 025-001-00-3)	215-202-6	1313-13-9	-	-	-	0.5

<sup>1</sup> Exposure: 15 min.  
<sup>2</sup> Exposure: 8 h.

DNEL Exposure Limit Values  
N.A.

PNEC Exposure Limit Values  
N.A.

### 8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.  
In case of exposure to dust-state material (powder): protection glasses

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

Not needed for normal use.  
In case of exposure to dust-state material (powder): filter P2

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance and colour:	Brown plastic clay
Odour:	N.A.

CERAMICA COLLET S.A.	SAFETY DATA SHEET		
PM Black Earthenware	Rev. 7	Date: 15/03/16	
	Page: 4 de 6		

Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	N.A.
Flash point:	N.A.
Evaporation rate:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour pressure:	N.A.
Vapour density:	N.A.
Relative density:	2 g/cm <sup>3</sup>
Solubility in water:	Insoluble
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	N.A.
Decomposition temperature:	N.A.
Viscosity:	N.A.
Explosive properties:	N.A.
Oxidizing properties:	N.A.

**9.2. Other information**

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

**10. Stability and reactivity****10.1. Reactivity**

Stable under normal conditions

**10.2. Chemical stability**

Stable under normal conditions

**10.3. Possibility of hazardous reactions**

None

**10.4. Conditions to avoid**

Stable under normal conditions.

**10.5. Incompatible materials**

None in particular.

**10.6. Hazardous decomposition products**

None.

**11. Toxicological information****11.1. Information on toxicological effects**Toxicological information of the mixture:  
N.A.Toxicological information of the main substances found in the mixture:  
N.A.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;

CERAMICA COLLET S.A.	<b>SAFETY DATA SHEET</b>		
<b>PM Black Earthenware</b>	Rev. 7	Date: 15/03/16	
	Page: 5 de 6		

- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard..

## 12. Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.  
N.A.

### 12.2. Persistence and degradability

N.A.

### 12.3. Bioaccumulative potential

N.A.

### 12.4. Mobility in soil

N.A.

### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

### 12.6. Other adverse effects

None

## 13. Disposal considerations

### 13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

## 14. Transport information

### 14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

### 14.2. UN proper shipping name

N.A.

### 14.3. Transport hazard class(es)

N.A.

### 14.4. Packing group

N.A.

### 14.5. Environmental hazards

N.A.

### 14.6. Special precautions for user

N.A.

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

## 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)  
 Dir. 2000/39/EC (Occupational exposure limit values)  
 Regulation (EC) n. 1907/2006 (REACH)  
 Regulation (EC) n. 1272/2008 (CLP)  
 Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
 Regulation (EU) 2015/830  
 Regulation (EU) n. 286/2011 (ATP 2 CLP)  
 Regulation (EU) n. 618/2012 (ATP 3 CLP)  
 Regulation (EU) n. 487/2013 (ATP 4 CLP)  
 Regulation (EU) n. 944/2013 (ATP 5 CLP)  
 Regulation (EU) n. 605/2014 (ATP 6 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

CERAMICA COLLET S.A.	<b>SAFETY DATA SHEET</b>		
<b>PM Black Earthenware</b>	Rev. 7	Date: 15/03/16	
	Page: 6 de 6		

Restrictions related to the product:

No restriction.

Restrictions related to the substances contained:

No restriction.

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II):

N.A.

#### **15.2. Chemical safety assessment**

No

#### **16. Other information**

Phrases used in heading 3:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation), category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), category 4
H302	Harmful if swallowed
H332	Harmful if inhaled

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

#### **This MSDS cancels and replaces any preceding release.**

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.